



Please read this manual carefully before operating your set and retain it for future reference.

CEILING CONCEALED DUCT

Original instruction

[Representative] LG Electronics Inc. EU Representative : LG Electronics European Shared Service Center B.V. Krijgsman 1, 1186 DM Amstelveen, The Netherlands

[Manufacturer] LG Electronics Inc. Changwon 2nd factory 84, Wanam-ro, Seongsangu, Changwon-si, Gyeongsangnam-do, KOREA



P/NO · MEI 67870409

TABLE OF CONTENTS

Safety Precautions3
Prior to Operation8
Product Introduction9
Owner's instruction12
Maintenance and Service21
Before you Call for Service23



U FOR YOUR RECORDS

Write the model and serial numbers here:

Model

Serial

You can find them on a label on the side of each unit.

Dealer's Name

Date Purchased

■ Staple your receipt to this page in the event you need it to prove date of purchase or for warranty issues.



READ THIS MANUAL

Inside you will find many helpful hints on how to use and maintain your air conditioner properly. Just a little preventive care on your part can save you a great deal of time and money over the life of your air conditioner.

You'll find many answers to common problems in the chart of troubleshooting tips. If you review our chart of

Troubleshooting Tips first, you may not need to call for service at all.



PRECAUTION

- · Contact the authorized service technician for repair or maintenance of this unit.
- · Contact the installer for installation of this unit.
- · The air conditioner is not intended for use by young children or invalids without supervision.
- · Young children should be supervised to ensure that they do not play with the air conditioner.
- · When the power cord is to be replaced, replacement work shall be performed by authorized personnel only using only genuine replacement parts.
- · Installation work must be performed in accordance with the National Electric Code by qualified and authorized personnel only.



Safety Precautions

To prevent injury to the user or other people and property damage, the following instructions must be followed.

■ Incorrect operation due to ignoring instruction will cause harm or damage. The seriousness is classified by the following indications.

AWARNING This symbol indicates the possibility of death or serious injury.

ACAUTION

This symbol indicates the possibility of injury or damage to properties only.

■ Meanings of symbols used in this manual are as shown below.

	Be sure not to do.
•	Be sure to follow the instruction.

AWARNING

■ Installation

Do not use a defective or underrated circuit breaker. Use this appliance on a dedicated circuit.

 There is risk of fire or electric shock

For electrical work, contact the dealer, seller, a qualified electrician, or an Authorized Service Center.

 Do not disassemble or repair the product. There is risk of fire or electric shock.

Always ground the product.

 There is risk of fire or electric shock

Install the panel and the cover of control box securely.

 There is risk of fire or electric shock.

Always install a dedicated circuit and breaker.

 Improper wiring or installation may cause fire or electric shock

Use the correctly rated breaker or fuse.

 There is risk of fire or electric shock.

Do not modify or extend the power cable.

There is risk of fire or electric shock.

Do not install, remove, or re-install the unit by yourself (customer).

 There is risk of fire, electric shock, explosion, or injury.

Be cautious when unpacking and installing the product.

 Sharp edges could cause injury. Be especially careful of the case edges and the fins on the condenser and evaporator.

For installation, always contact the dealer or an Authorized Service Center.

 There is risk of fire, electric shock, explosion, or injury.

Do not install the product on a defective installation stand.

 It may cause injury, accident, or damage to the product.

Be sure the installation area does not deteriorate with age.

 If the base collapses, the air conditioner could fall with it, causing property damage, product failure, and personal injury.

Operation

Do not let the air conditioner run for a long time when the humidity is very high and a door or a window is left open.

 Moisture may condense and wet or damage furniture.

Take care to ensure that power cable could not be pulled out or damaged

during operation.

There is risk of fire or electric shock.

Do not place anything on the power cable.

There is risk of fire or electric shock.

Do not plug or unplug the power supply plug during operation.

There is risk of fire or electric shock.

Do not touch(operate) the product with wet hands.

There is risk of fire or electrical shock.

Do not place a heater or other appliances near the power cable.

 There is risk of fire and electric shock.

Do not allow water to run into electric parts.

Do not store or use flammable gas or combustibles near the product.

Do not use the product in a tightly closed space for a long time.

- It may cause There is risk of fire, failure of the product. or electric shock.
- · There is risk of fire or failure of product.
- Oxygen deficiency could occur.

When flammable gas leaks, turn off the gas and open a window for ventilation before turn the product on.

If strange sounds, or small or smoke comes from product. Turn the breaker off or disconnect the power supply cable.

Stop operation and close the window in storm or hurricane. If possible, remove the product from the window before the hurricane arrives.

- · Do not use the telephone or turn switches on or off. There is risk of explosion or fire.
- There is risk of electric shock or fire.
- There is risk of property damage, failure of product, or electric shock.

Do not open the inlet grill of the product during operation. (Do not touch the electrostatic filter, if the unit is so equipped.)

When the product is soaked (flooded or submerged), contact an **Authorized Service** Center

Be cautious that water could not enter the product.

- There is risk of physical injury, electric shock, or product failure.
- There is risk of fire or electric shock.
- · There is risk of fire, electric shock, or product damage.

Ventilate the product from time to time when operating it together with a stove, etc.

Turn the main power off when cleaning or maintaining the product.

- There is risk of electric shock.
- There is risk of fire or electric shock.

When the product is not be used for a long time, disconnect the power supply plug or turn off the breaker.

 There is risk of product damage or failure. or unintended operation.

Take care to ensure that nobody could step on or fall onto the outdoor unit.

• This could result in personal injury and product damage.

ACAUTION

■ Installation

Always check for gas (refrigerant) leakage after installation or repair of product.

 Low refrigerant levels may cause failure of product.

Do not install the product where the noise or hot air from the outdoor unit could damage the neighborhoods.

 It may cause a problem for your neighbors.

Install the drain hose to ensure that water is drained away properly.

· A bad connection may cause water leakage.

Use two or more people to lift and transport the product.

Avoid personal injury.

Keep level even when installing the product.

 To avoid vibration or water leakage.

Do not install the product where it will be exposed to sea wind (salt spray) directly.

 It may cause corrosion on the product. Corrosion, particularly on the condenser and evaporator fins, could cause product malfunction or inefficient operation.

■ Operation

Do not expose the skin directly to cool air for long periods of time. (Don't sit in the draft.)

· This could harm to your

Do not use the product for special purposes, such as preserving foods, works of art, etc. It is a consumer air conditioner, not a precision refrigeration system.

· There is risk of damage or loss of property.

Do not block the inlet or outlet of air flow.

 It may cause product failure.

health.

Use a soft cloth to clean. Do not use harsh detergents, solvents, etc.

· There is risk of fire, electric shock, or damage to the plastic parts of the product.

Do not touch the metal parts of the product when removing the air filter. They are very sharp!

 There is risk of personal injury.

Do not step on or put anyting on the product. (outdoor units)

· There is risk of personal injury and failure of product.

Always insert the filter securely. Clean the filter every two weeks or more often if necessary.

· A dirty filter reduces the efficiency of the air conditioner and could cause product malfunction or damage.

Do not insert hands or other objects through the air inlet or outlet while the product is operated.

 There are sharp and moving parts that could cause personal injury.

Do not drink the water drained from the product.

· It is not sanitary and could cause serious health issues.

Use a firm stool or ladder when cleaning or maintaining the product.

Replace the all batteries in the remote control with new ones of the same type. Do not mix old and new batteries or different types of batteries.

Do not recharge or disassemble the batteries. Do not dispose of batteries in a fire.

- · Be careful and avoid personal injury.
- There is risk of fire or explosion
- They may burn or explode.

If the liquid from the batteries gets onto vour skin or clothes, wash it well with clean water. Do not use the remote if the batteries have leaked.

 The chemicals in batteries could cause burns or other health hazards.

If you eat the liquid from the batteries, brush your teeth and see doctor. Do not use the remote if the batteries have leaked.

 The chemicals in batteries could cause burns or other health hazards.

Prior to Operation

Preparing for operation

- 1. Contact an installation specialist for installation.
- 2. Use a dedicated circuit.

Usage

- Being exposed to direct airflow for an extended period of time could be hazardous to your health.
 Do not expose occupants, pets, or plants to direct airflow for extended periods of time.
- Due to the possibility of oxygen deficiency, ventilate the room when used together with stoves or other heating devices.
- Do not use this air conditioner for non-specified special purposes (e.g. preserving precision devices, food, pets, plants, and art objects). Such usage could damage the items.

Cleaning and maintenance


- 1. Do not touch the metal parts of the unit when removing the filter. Injuries can occur when handling sharp metal edges.
- 2. Do not use water to clean inside the air conditioner. Exposure to water can destroy the insulation, leading to possible electric shock.
- 3. When cleaning the unit, first make sure that the power and breaker are turned off. The fan rotates at a very high speed during operation. There is a possibility of injury if the unit's power is accidentally triggered on while cleaning inner parts of the unit.

Service

For repair and maintenance, contact your authorized service dealer.


Product Introduction

Name and function of parts



- 1: Indoor unit
- 2: Outdoor unit
- 3: Remote controller
- 4: Inlet air
- 5: Discharge air
- 6: Refrigerant piping, connection electric wire
- 7: Drain pipe
- 8: Ground wire wire to ground outdoor unit to prevent electrical shocks.


Simple Wired Remote Controller



- 1. Operation Display Panel
- 2. Temperature Control Button
- 3. Fan Speed Button
- 4. On/Off Button
- 5. Operation Mode select Button

Each function will be shown on the display panel for three seconds or so when the power is applied at first.

Accessory



Wireless Remote Controller (Accessory)

This air-conditioner is equipped with wired remote controller basically. But if you want to be available with wireless remote controller, you pay for it.



PQWRHQ0FDB



CAUTION


- · Aim at the signal receiver on the wired remote controller so as to operate.
- The remote control signal can be received at a distance of up to about 7m.
- · Be sure that there are no obstructions between the remote controller and the signal recep-
- · Do not drop or throw the remote controller.
- · Do not place the remote controller in a location exposed to direct sunlight, or near the heating unit, or any other heat source.
- · Block a strong light over the signal receptor with a curtain or etc. so as to prevent the abnormal operation. (ex:electronic quick start, ELBA, inverter type fluorescent lamp)

- * For more details refer to the Wireless Remote Control Accessory manual.
- * The actual product can be different from above contents depending upon model type.
- * The wireless remote controller does not operate When using simultaneous operation system.


Owner's instruction

Standard Operation - Cooling Mode

It cools the room by comfortable and clean wind.




- Cooling operation will begin if you press the n button.
- Press the temperature button and set the desired room temperature lower than the current room temperature.



- Setting temp range: 18°C~30°C (64°F~86°F)
- If the desired temperature is set higher than the current room temperature, the cooling function will not begin and just the blowing operation will continue.
- 3 If you prees the mode button during the operation, the operation mode will be changed in the order of cooling. dry(dehumidification), heating, auto-operation and fan operation. If the product is a cooling-only model, the operation mode will be changed in the order of cooling, dry(dehumidification), auto-operation and fan operation.
- If you press the ① button, the cooling operation will stop.

Standard Operation - Heating Mode

It supplies warm wind to the indoor




What is the three-minute delay function?

It will take time for the product to blow warm air. The delay is to protect the compressor. The room will be heated with warm air after three minutes when the compressor begins operation.

■ The cooling-only model will not do heating function.


Standard Operation - Auto Operation Mode



- After operating the product by pressing the button, set up the auto operation by pressing the OPER button.
- "Auto Change Over Mode" Heat pump model only When desired the set temperature is higher than the room temperature during the auto operation
 - => Heating operation [For Heat pump models only]


When desired the set temperature is lower than the room temperature during the auto operation

- => Cooling operation
- Setting temp range: 18°C~30°C (64°F~86°F)
- "Auto Operation Mode" For the products with the exclusive purpose of cooling only, "Al" is indicated at the temperature display section.



Standard Operation - Dehumidification Modea


It removes humidity while air-cooling weakly.



- In rainy season or high humidity climate, it is possible to operate simultaneously dehumidifier and cooling mode to remove humidity effectively.
- The menu item of wind powerfulness might not be partially selected according to the product.

Standard Operation - Fan Mode

It blows the air as it is in the indoor, not the cold wind.




- After operating the product by pressing the button, set up the fan operation by pressing the MODE button.
- When the dry operation is selected, "Fn" will be shown on the display window as shown on the left side.
 - The temperature setting can not be adjusted during operation this mode.
- Press the SPEED button to select airflow rate $[SLO \rightarrow LO \rightarrow MED \rightarrow HI \rightarrow POW].$ When running ventilation, compressor of AHU doesn't work.

- · Ventilation drive does not release cool wind but general fan.
- · Because it releases the wind that has no temperature difference from the room, it functions to circulate the inside air.
- The menu item of wind powerfulness might not be partially selected according to the product.

Function Setting - Fan Speed Selection

It blows the air as it is in the indoor, not the cold wind.



- Select the proper fan speed which you want by pressing the 🛈 button on the remote controller.
 - If you press the speed button, the fan speed will change in the order of [SLO→LO→MED →HI→POW].
 - The initial fan speed is "HI".
 - If the product is not compatible with the fan speed control, it will not function as per your selection.

Fan Speed Selection in Cooling Operation



Fan Speed Selection in Heating, Dry, Fan, **Auto-Operation**



Function Setting - Room Temperature Check




When pressing the FAN button of the remote controller adjustment section for approx. 3 seconds, the room temperature will be indicated for about 5 seconds before resuming to the previous display panel.

> In the case of the room temperature display, the room temperature can be different in accordance with the setting of the remote controller's room temperature detection selection.

* As the temperature distribution of the remote controller Installation space is not uniform, slight difference can be generated between the actually felt temperature and the room temperature indication of the remote controller.


Function setting - Child Lock

It is the function to use preventing children or others from careless using.



- During the operation, when pressing the [\(\triangle \) button and [FAN] button for approx. 3 seconds, the 'Child Lock' function can be used.
 - At the time of initial setting of the 'Child Lock', the 'CL' will be indicated approx. 3 seconds at the temperature display section before resuming to the previous mode. After the setting of the 'CL', if another button is setup, the button can not be recognized as the 'CL' is indicated at the temperature display section for approx. 3 seconds.
- If the 'CL' function is wanted to be used under the operation standby state, press the button and speed button for approx. 3 seconds under the standby mode state and the system will be the 'CL' state.
- As for the releasing method, when pressing the \triangle button and $\sqrt[\text{FAN}]{\text{speed}}$ button for approx. 3 seconds, the 'CL' function can be released.

Self-diagnosis for Trouble Mode



It automatically runs a self-diagnosis when there is a trouble detected in the system.

It displays the troble mode number with maintenance CODE. <Individual control>



- <Group control>
- * When detecting an error during group control, the system will display as below.
- <In case of CH05 error, these two characters CH and 05 are alter-</p> natively displayed.>



In order to expedite a service, please remember the error number and provide it when consulting an installer.

Outage Compensation Function

If power supply fails due to outage or other reasons, the outage compensation function automatically retrieves the operating conditions previously programmed before the power failure. Thus, you don't need to press any buttons.

(Additional functions will not be retrieved automatically.)

Maintenance and Service



CAUTION: Before performing any maintenance, turn off the main power to the system.

Grille, Case, and Remote Controller


☐ Turn the system off before cleaning. To clean, wipe with a soft, dry cloth. Do not use bleach or abrasives.



Power supply must be disconnected before cleaning the indoor unit.


Air Filters

The air filters behind the front grille should be checked and cleaned once every 2 weeks or more often if neccessary.



- Never use any of the followings:
 - Water hotter than 40°C. Could cause deformation and or discoloration.
 - Volatile substances. Could damage the surfaces of the air conditioner.





- 1. Remove the Air filters.
 - Take hold of the tab and pull slightly forward to remove the filter.



CAUTION: When the air filter is to be removed, do not touch the metal parts of the indoor unit. It may cause an injury.

- 2. Clean dirt from the air filter using a vacuum cleaner or washing with water.
 - If dirt is conspicuous, wash with a neutral detergent in lukewarm water.
 - If hot water (40°C or more) is used, it may be deformed.
- 3. After washing with water, dry well in the shade.
 - Do not expose the air filter to direct sunlight or heat from a fire when drying it.
- 4. Install the air filter.

When the air conditioner is not going to be used for a long time.

When it is not going to be used for a long time.



Operate the air conditioner at the following settings for 2 to 3 hours.


- Type of operation: Fan operation mode.
- · This will dry out the internal mechanisms.



Turn off the breaker.



/!\ CAUTION -



Dirt may collect and may cause a fire.

Helpful information

The air filters and your electiric bill. If the air filters become cloqged with dust, the cooling capacity will drop, and 6% of the electricity used to operate the air conditioner will be wasted.

When the air conditioner is to be used again.



Clean the air filter and install it in the indoor unit.



Check that the air inlet and outlet of the indoor/outdoor unit are not blocked.



Check that the ground wire is connected correctly. It may be connect to the indoor unit side.

Operation Tips

Do not overcool the room.

This is not good for the health and wastes electricity.

Make sure that the doors and windows are shut tight.

Avoid opening doors and windows as much as possible to keep the cool air in the room.

Keep blinds or curtains closed.

Do not let direct sunshine enter the room when the air conditioner is in operation.

Clean the air filter regularly.

Blockages in the air filter reduce the airflow and lower cooling and dehumidifying effects. Clean at least once every two weeks.

Keep the room temperature uniform.

Adjust the vertical and horizontal airflow direction to ensure a uniform temperature in the room.

Ventilate the room occasionally.

Since windows are kept closed, it is a good idea to open them and ventilate the room now and then.

Before you call for service...



Troubleshooting Tips! Save time and money!

Check the following points before requesting repairs or service.... If the malfunction persist. please contact your dealer.

The air conditioner The room has a It seems that con-Air conditioner does not operate for about does not operate. peculiar odor. densation is leaking from the air condi-3 minutes when tioner. · Have you made a · Check that this is not Condensation occurs This is the protector mistake in timer opera damp smell exuded when the airflow from of the mechanism ation? by the walls, carpet. the air conditioner · Wait about three min-· Has the fuse blown furniture or cloth cools the warm room utes and operation or has the circuit items in the room. will begin. breaker been tripped? Does not cool or heat The air conditioner Crack sound is Remote control diseffectively. operation is noisy. heard. play is faint, or no display at all. For a noise that · Are the batteries · Is the air filter dirty? · This sound is generated See air filter cleaning sounds like water by the expansion/ condepleted? striction of the front instructions. flowina. Are the batteries · The room may have -This is the sound of panel, etc. due to inserted in the oppobeen very hot when freon flowing inside changes of temperasite (+) and (-) directhe air conditioner tions? the room air conditionture. er was first turned on. unit. Allow time for it to cool · For a noise that Filter sign lamp is sounds like the comdown pressed air releasing Has the temperature been set incorrectly? into atmosphere. · Are the indoor unit's -This is the sound of · Cleaning the filter. air inlet or outlet vents the dehumidifying press the Timer button obstructed? water being processed inside the and **◀** button of wired air conditioning unit.

NOTE

WATER RESISTANT: The outdoor side of this appliance is WATER RESISTANT. The indoor side is not water resistant and should not be exposed to excess water.

remote controller at the same time for 3 s

