

# LCD TV OWNER'S MANUAL

LCD TV MODELS 19LS4R 22LS4R

Please read this manual carefully before operating your set.

Retain it for future reference.

Record model number and serial number of the set. See the label attached on the back cover and quote this information to your dealer when you require service.

> P/NO : MFL34797012 (0710-REV01) Printed in Korea

# WARNING

# **IMPORTANT SAFETY INSTRUCTIONS**

Important safety instructions shall be provided with each apparatus. This information shall be given in a separate booklet or sheet, or be located before any operating instructions in an instruction for installation for use and supplied with the apparatus.

This information shall be given in a language acceptable to the country where the apparatus is intended to be used.

The important safety instructions shall be entitled "Important Safety Instructions". The following safety instructions shall be included where applicable, and, when used, shall be verbatim as follows. Additional safety information may be included by adding statements after the end of the following safety instruction list. At the manufacturer's option, a picture or drawing that illustrates the intent of a specific safety instruction may be placed immediately adjacent to that safety instruction :

#### WARNING

Read these instructions. Keep these instructions. Heed all warnings. Follow all instructions.



Do not place the product in direct sunlight or near heat sources such as heat registers, stove and so on.

This may cause a fire.



Do not use the product in damp place such as a bathroom or any place where it is likely to get wet.

This may cause a fire or could give an electric shock.





2

Bend antenna cable between inside and outside building to prevent rain from flowing in.

This may cause water damaged inside the product and could give an electric shock.




Earth wire should be connected.

If the earth wire is not connected, there is possible a danger of electric shock caused by the current leakage.

If grounding methods are not possible, a separate circuit breaker should be employed and installed by a qualified electrician.

Do not connect ground to telephone wires, lightning rods or gas pipe.





Do not placing anything containing liquid on top of the product.

This may cause a fire or could give an electric shock.



#### Wet Location Marking :

Apparatus shall not be exposed to dripping or splashing and no objects filled with liquids, such as vases, shall be placed on the apparatus.



8

6

Do not insert any object into the exhaust vent.

This may cause a fire or could give an electric shock.

Do not place heavy objects on the product.

This may cause serious injury to a child or adult.

# WARNING

# **IMPORTANT SAFETY INSTRUCTIONS**

#### 



Do not use water the product while cleaning.

This may cause damaged the product or could give an electric shock.



In case of smoke or strange smell from the product, switch it off ,unplug it from the wall outlet and contact your dealer or service center.

This may cause a fire or could give an electric shock.

Do not attempt to service the product yourself. Contact your dealer or service center.

This may cause damaged the product or could give an electric shock.





Never touch this apparatus or antenna during a thunder or lighting storm.

This may cause an electric shock.



## 




Never touch the power plug with a wet hand.

This may cause an electric shock.



4


Disconnect from the mains and remove all connections before moving.



Ventilation required.

When installing the product on a table, be careful not to place the edge of its stand.

This may cause the product to fall, causing serious injury to a child or adult, and serious damage to the product.



This may cause an electric shock.



There should be enough distance between an outside antenna and power lines to keep the former from touching the latter even when the antenna falls.


This may cause an electric shock.



Do not pull the cord but the plug when unplugging.

This may cause a fire.

## 



#### NOTE

▶ If the TV feels cold to the touch, there may be a small "flicker" when it is turned on. This is normal, there is nothing wrong with TV.

Some minute dot defects may be visible on the screen, appearing as tiny red, green, or blue spots. However, they have no adverse effect on the monitor's performance.

Avoid touching the LCD screen or holding your finger(s) against it for long periods of time. Doing so may produce some temporary distortion effects on the screen.

#### **On Disposal**

- a. The fluorescent lamp used in this product contains a small amount of mercury.
- b. Do not dispose of this product with general household waste.
- c. Disposal of this product must be carried out in accordance to the regulations of your local authority.

# CONTENTS

WARNING	1
Important Safety Instructions	1

#### PREPARATION

Accessories	5
Front Panel Information	6
Back Panel Information	7
Stand Installation	8
Detaching Stand	9
Back Cover for Wire Arrangement	
Positioning Your Display	
Desktop Pedestal Installation	
Kensington Security System	
Antenna or Cable Connection	

#### **EXTERNAL EQUIPMENT SETUP**

HD Receiver Setup	14
DVD Setup	
VCR Setup	
Headphone Setup	
PC Setup	
Screen Setup	25
- Auto Configure	25
- Manual Configure	
- Initializing	27

#### WATCHING TV / CHANNEL CONTROL

Remote Control Functions	3
Turning On TV	C
Channel Selection	C
Volume Adjustment	)
On-Screen Menus Selection	1
Channel Search	2
- Auto Program: Program Search	2
- Manual Program: Adding/Deleting Channels 33	3
Fine Tuning Adjustment	4
Favorite Channels Setup	5
Key Lock	5

#### PICTURE CONTROL

Picture Size (ARC- Aspect Ratio) Control37
Preset Picture Settings
- Auto Picture Control (APC) - Preset
- Color Tone - Preset
Manual Picture Adjustment
- Auto Picture Control (APC) - User Mode 40
- Color Tone - User Mode41
XD - Picture Improvement Technology42
XD Demo
Cinema 3:2 Pull down Mode
Picture Reset

#### SOUND & LANGUAGE CONTROL

47
49
50
51
52

#### TIME SETTING

Clock Setting	53
Auto On/Off Timer Setting	54
Sleep Timer Setting	55
Auto Shut-off Setting	56

#### APPENDIX


Troubleshooting	57
Maintenance	59
Product Specifications	60

#### 5

# PREPARATION

# ACCESSORIES

Ensure that the following accessories are included with your product. If an accessory is missing, please contact the dealer where you purchased the product.




# PREPARATION

# FRONT PANEL INFORMATION

Here shown may be somewhat different from your TV.

#### **Front Panel Controls**




#### NOTE

► If your product has a protection tape attached, remove the tape. And then wipe the product with a cloth (If a polishing cloth is included with your product, use it).

## **BACK PANEL INFORMATION**

Here shown may be somewhat different from your TV.

#### **Back Connection Panel**



#### HDMI/DVI IN

Connect a HDMI signal to this jack. Or DVI (Video) signal to this jack with a HDMI to DVI cable.

#### RGB (PC/DTV) IN

Connect the output from a PC or DTV. AUDIO (RGB/DVI) IN Connect the audio from a PC or DTV.

#### **3** ANTENNA IN

Connect over-the air signals to this jack.

#### HEADPHONE INPUT

Plug the headphone into the headphone socket.

#### S AV (Audio/Video) IN

Connect audio/video output from an external device to these jacks.

#### S-VIDEO

Connect S-Video out from an S-VIDEO device.

#### COMPONENT IN

Connect a component video/audio device to these jacks.

#### Power Cord Socket

For operation with AC power.

Caution: Never attempt to operate the TV on DC power.


# PREPARATION

# STAND INSTALLATION

Here shown may be somewhat different from your TV.




Carefully place the product screen side down on a cushioned surface that will protect product and screen from damage.






Hold the **HINGE BODY** and bend it upward.






Insert the STAND BODY into the product until clicking sound.





Assemble the parts of the **STAND BODY** with **COVER BASE** of the product.




# **DETACHING STAND**

Here shown may be somewhat different from your TV.




Carefully place the product screen side down on a cushioned surface that will protect product and screen from damage.






Shake the base while pulling, it will separate from stand body.






Pull stand body to separate from set while pressing the 2 latches.






Pull cover base backward while pressing button on stand body.





Hold the **HINGE BODY** and bend it upward.

#### HINGE BODY





# PREPARATION


# BACK COVER FOR WIRE ARRANGEMENT

Here shown may be somewhat different from your TV.




Connect the cables as necessary.

To connect an additional equipment, see the EXTERNAL EQUIPMENT SETUP section.






Install the CABLE MANAGEMENT as shown.



#### How to remove the cable management

First, press the cable management. Hold the **CABLE MANAGEMENT** with both hands and pull it upward.



#### NOTE


- ► Do not hold the CABLE MANAGEMENT when moving the product.
- If the product is dropped, you may be injured or the product may be broken.

# POSITIONING YOUR DISPLAY

Here shown may be somewhat different from your TV.


Adjust the position of the panel in various ways for maximum comfort.

• Tilt range



# DESKTOP PEDESTAL INSTALLATION

For proper ventilation, allow a clearance of 10.1 cm (4inches) on all four sides from the wall.



**CAUTION** > Ensure adequate ventilation by following the clearance recommendations.

# PREPARATION


# **KENSINGTON SECURITY SYSTEM**

- The TV is equipped with a Kensington Security System connector on the back panel. Connect the Kensington Security System cable as shown below.
- For the detailed installation and use of the Kensington Security System, refer to the user's guide provided with the Kensington Security System.

For further information, contact **http://www.kensington.com**, the internet homepage of the Kensington company. Kensington sells security systems for expensive electronic equipment such as note-book PCs and LCD projectors.

#### NOTE

- The Kensington Security System is an optional accessory.



# ANTENNA OR CABLE CONNECTION

#### 1. Antenna (Analog or Digital)

Wall Antenna Socket or Outdoor Antenna without a Cable Box Connections. For optimum picture quality, adjust antenna direction if needed. **Multi-family Dwellings/Apartments** Wall (Connect to wall antenna socket) Antenna Socket ANTENNA IN RF Coaxial Wire (75 ohm) Outdoor Antenna 3 (VHF, UHF) Single-family Dwellings /Houses Copper Wire (Connect to wall jack for outdoor antenna) Be careful not to bend the bronze wire when connecting the antenna. 2. Cable Cable TV ANTENNA IN Wall Jack RF Coaxial Wire (75 ohm) UHF Signal Antenna ) < ANTENNA IN 7(()) Amplifier

To improve the picture quality in a poor signal area, please purchase a signal amplifier and install properly.

If the antenna needs to be split for two TV's, install a 2-Way Signal Splitter.

VHF

If the antenna is not installed properly, contact your dealer for assistance.

**I NOTE •** The TV will let you know when the analog, cable, and digital channel scans are complete.

To prevent the equipment damage, never plug in any power cords until you have finished connecting all equipment.

# HD RECEIVER SETUP

To watch digitally broadcast programs, purchase and connect a digital set-top box.

## When connecting Component cable

#### 1. How to connect



Connect the video outputs (Y, PB, PR) of the digital set top box to the **COMPONENT IN VIDEO** jacks on the set. Match the jack colors

(Y = green, PB = blue, and PR = red).




Connect the audio output of the digital set-top box to the **COMPONENT IN AUDIO** jacks on the set.

#### 2. How to use

Turn on the digital set-top box.
 (Refer to the owner's manual for the digital set-top box. operation)

Select Component input source by using the INPUT button on the remote control.

Signal	Component
480i, 480p,	
576i, 576p,	Yes
720p, 1080i	



#### When connecting with a D-sub 15 pin cable

#### 1. How to connect



Connect the RGB output of the digital set-top box to the RGB (PC/DTV) IN jack on the set.



Connect the audio outputs of the set-top box to the AUDIO (RGB/DVI) IN jack on the set.

#### 2. How to use

- Turn on the digital set-top box.
   (Refer to the owner's manual for the digital set-top box.)
- Select RGB-DTV input source with using the INPUT button on the remote control.

#### When connecting HDMI cable

#### 1. How to connect



Connect the digital set-top box to **HDMI/DVI IN** jack on the set.


No separated audio connection is necessary. HDMI supports both audio and video.


#### 2. How to use


- Turn on the digital set-top box.
   (Refer to the owner's manual for the digital set-top box.)
- Select HDMI/DVI input source by using the INPUT button on the remote control.

#### NOTE

- When connected, the TV will tell a connected device what resolution it supports and the resolution it prefers. If the device supports this Auto HDMI function, the player output resolution will be automatically set to 720p.
- If the device does not support Auto HDMI, you need to set the output resolution appropriately.







#### When connecting HDMI to DVI cable

#### 1. How to connect

Connect the DVI output of the digital set-top box to the HDMI/DVI IN jack on the set.

Connect the audio output of the digital set-top box to the AUDIO (RGB/DVI) IN jack on the set.

#### 2. How to use

1

2

- Turn on the digital set-top box. (Refer to the owner's manual for the digital set-top box.)
- Select HDMI/DVI input source by using the INPUT button on the remote control.

# **DVD SETUP**

#### When connecting Component cable

#### 1. How to connect

1

Connect the video outputs (Y, PB, PR) of the DVD to the **COMPONENT IN VIDEO** jacks on the set. Match the jack colors (Y = green, PB = blue, and PR = red).



Connect the audio outputs of the DVD to the **COMPONENT IN AUDIO** jacks on the set.


#### 2. How to use

- Turn on the DVD player, insert a DVD.
- Select Component input source by using the INPUT button on the remote control.
- Refer to the DVD player's manual for operating instructions.

#### **Component Input ports**

To get better picture quality, connect a DVD player to the component input ports as shown below.

Component ports on the TV	Y	Рв	Pr
Video output ports on DVD player	Y Y Y Y	Рв В-Ү СЬ РЬ	P <sub>R</sub> R-Y Cr Pr



## When connecting with an S-Video cable

#### 1. How to connect



Connect the S-VIDEO output of the DVD to the S-VIDEO input on the set.



Connect the audio outputs of the DVD to the **AUDIO** input jacks on the set.

#### 2. How to use

- Turn on the DVD player, insert a DVD.
- Select AV input source by using the INPUT button on the remote control.
- Refer to the DVD player's manual for operating instructions.

## When connecting HDMI cable

#### 1. How to connect



Connect the HDMI output of the DVD to the HDMI/DVI IN jack on the set.



No separated audio connection is necessary. HDMI supports both audio and video.


#### 2. How to use


- Select HDMI/DVI input source by using the INPUT button on the remote control.
- Refer to the DVD player's manual for operating instructions.

#### NOTE

- When connected, the TV will tell a connected device what resolution it supports and the resolution it prefers. If the device supports this Auto HDMI function, the player output resolution will be automatically set to 720p.
- If the device does not support Auto HDMI, you need to set the output resolution appropriately.

To get the best picture quality, adjust the output resolution of the DVD to 720p.





# VCR SETUP

When connecting with an antenna

- To avoid picture noise (interference), leave an adequate distance between the VCR and TV.
- If the 4:3 picture format is used; the fixed images on the sides of the screen may remain visible on the screen. This phenomenon is common to all manufactures and in consequence the manufactures warranty does not cover the product bearing this phenomenon.

#### $\odot$ $\bigcirc$ $\bigcirc$ () ANT OUT õ VIDEO A S-VIDEO ۲ AUDIO HDMI/DVI IN RGB (PC/DTV) IN (RGB/DVI) IN OUTPUT ANTENNA IN Wall Jack LAUDIO R S-VIDEO 0 $\mathbf{r}$ Antenna -AUDIO-**COMPONENT IN-**

#### 1. How to connect

Connect the RF antenna out socket of the VCR to the ANTENNA IN socket on the set.

Connect the antenna cable to the RF antenna in socket of the VCR.

#### 2. How to use

2

- Set VCR output switch to 3 or 4 and then tune TV to the same channel number.
- Insert a video tape into the VCR and press PLAY on the VCR. (Refer to the VCR owner's manual.)

## When connecting with a RCA cable

#### 1. How to connect



Connect the **AUDIO/VIDEO** jacks between TV and VCR. Match the jack colors (Video = yellow, Audio Left = white, and Audio Right = red)

#### 2. How to use

- Insert a video tape into the VCR and press PLAY on the VCR. (Refer to the VCR owner's manual.)
- Select AV input source by using the INPUT button on the remote control.

#### When connecting with an S-Video cable

#### 1. How to connect



2

Connect the S-VIDEO output of the VCR to the S-VIDEO input on the set.


Connect the audio outputs of the VCR to the **AUDIO** input jacks on the set.

#### 2. How to use

- Insert a video tape into the VCR and press PLAY on the VCR. (Refer to the VCR owner's manual.)
- Select AV input source by using the INPUT button on the remote control.


#### NOTE

The picture quality is improved: compared to normal composite (RCA cable) input.



#### NOTE

If you have a mono VCR, connect the audio cable from the VCR to the AUDIO
 L/MONO jack of the set.



#### **A** CAUTION

Do not connect to both Video and S-Video at the same time. In the event that you connect both Video and the S-Video cables, only the S-Video will work.

# **HEADPHONE SETUP**

You can listen to the sound through the headphone.


#### 1. How to connect



Plug the headphone into the headphone socket.

2

To adjust the headphone volume, press the **VOL** ◀ or ▶ button. If you press the **MUTE** button, the sound from the headphone is switched off.



# PC SETUP

This TV provides Plug and Play capability, meaning that the PC adjusts automatically to the TV's settings.

## When connecting D-sub 15pin cable

#### 1. How to connect




Connect the RGB output of the PC to the **RGB** (PC/DTV) IN jack on the set.



Connect the PC audio output to the **AUDIO** (RGB/DVI) IN jack on the set.

#### 2. How to use

- Turn on the PC and the TV.
- Select RGB-PC input source by using the INPUT button on the remote control.



## When connecting HDMI to DVI cable

#### 1. How to connect




2

Connect the DVI output of the PC to the **HDMI/DVI IN** jack on the set.

Connect the PC audio output to the AUDIO (RGB/DVI) IN jack on the set.

#### 2. How to use

- Turn on the PC and the TV.
- Select HDMI/DVI input source by using the INPUT button on the remote control.



#### NOTES

- To get the the best picture quality, adjust the PC graphics card to 1440x900 (19LS4R), 1680x1050 (22LS4R).
- Depending on the graphics card, DOS mode may not work if a HDMI to DVI Cable is in use.
- Check the image on your TV. There may be noise associated with the resolution, vertical pattern, contrast or brightness in PC mode. If noise is present, change the PC output to another resolution, change the refresh rate to another rate or adjust the brightness and contrast on the VIDEO menu until the picture is clear. If the refresh rate of

the PC graphic card can not be changed, change the PC graphic card or consult the manufacturer of the PC graphic card.

- Avoid keeping a fixed image on the screen for a long period of time. The fixed image may become permanently imprinted on the screen.
- The synchronization input form for Horizontal and Vertical frequencies is separate.

#### Supported Display Specifications

#### RGB-PC, HDMI/DVI-PC mode

Resolution	Horizontal Frequency(KHz)	Vertical Frequency(Hz)
720x400	31.469	70.08
640x480	31.469	59.94
800x600	37.879	60.31
1024x768	48.363	60.00
1280x1024	63.981	60.02
1440x900 (19 inches only)	55.50	59.90
1680x1050 (22 inches only)	65.290	59.954

#### RGB-DTV, HDMI/DVI-DTV mode

Resolution	Horizontal Frequency(KHz)	Vertical Frequency(Hz)
720x480p	31.47 31.50	59.94 60.00
720x576p	31.25	50.00
1280x720p	37.50 44.96 45.00	50.00 59.94 60.00
1920x1080i	33.72 33.75 28.125	59.94 60.00 50.00

# SCREEN SETUP

## **Auto Configure**

Automatically adjusts picture position and minimizes image shaking. Although the image is still not correct, your set is functioning properly but needs further adjustment.

This function works in the following mode: RGB-PC mode.






2

Press the A.PROG button to start Auto config.

- When Auto config. has finished, Ok will be shown on screen.
- If the position of the image is still not correct, try Auto adjustment again.

If the picture needs to be adjusted more after Auto adjustment, you can adjust the **Manual config.**.

#### • You can also use the Screen menu to adjust Auto config..



#### Manual Configure

If the picture isn't clear after auto adjustment and especially if characters are still trembling, adjust the picture phase manually.

This function works in the following mode: RGB-PC mode.

# 0

Press the **MENU** button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Screen** menu.



3

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **Manual config.** 

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **H-Position**, **V-Position**, **Phase**, or **Clock**.

#### Phase

This function allows you to remove any horizontal noise and clear or sharpen the image of characters.

#### Clock

This function is to minimize any vertical bars or stripes visible on the screen background. And the horizontal screen size will also change.

#### H-Position / V-Position

This function is to adjust picture to left/right and up/down as you prefer.

Press the ◀ or ► button to make appropriate adjustments.



Press the **ENTER** button to save.








234

# APC DASP ARC/\*

▲▼ **<**► **③** MENU

EXTERNAL EQUIPMENT SETUP



Initializing (Reset to original factory settings)

This function works in the following mode: RGB-PC mode.

This function operates in current mode.

To initialize the adjusted value.

2

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **Reset**.

3

#### Press the $\blacktriangleright$ button.

• You can initialize H-Position, V-Position, Phase, Clock.


4	Screen	
	Auto config.	
	Manual config.	
Ô	ARC	
0	Reset 🕨	To set
÷	▲▼ ◀► ම MENU	

23

0

# **REMOTE CONTROL FUNCTIONS**

When using the remote control, aim it at the remote control sensor on the TV.



POWER Turns your TV or any other programmed equipment on or off, depending on the mode.


TV In AV, Component, RGB, and HDMI/DVI input sources, screen returns to the last TV channel.

INPUT Select the desired input source: TV, AV, Component, RGB, and HDMI/DVI.

#### NUMBER button

MUTE Switch the sound on or off. ▶ **p.30** 

FCR Scroll through the programmed Favorite channels. **p.35** 



#### Remote control effective range



- Use a remote control up to 7 meters distance and 30 degree (left/right) within the receiving unit scope.
- Dispose of used batteries in a recycle bin to preserve environment.

# **TURNING ON TV**

1

2

3

First, connect power cord correctly.

At this moment, the TV switches to standby mode.

- In standby mode to turn TV on, press the ७/۱, INPUT, CH (▲ or ▼) button on the TV or press the POWER, INPUT, TV, CH (▲ or ▼), Number (0~9) button on the remote control.
- Select the viewing source by using the **TV**, **INPUT** button on the remote control.
- This TV is programmed to remember which power state it was last set to, even if the power cord is out.

When finished using the TV, press the **POWER** button on the remote control. The TV reverts to standby mode.



#### 

▶ If you intend to be away on vacation, disconnect the power plug from the wall power outlet.

# CHANNEL SELECTION

Press the  $CH \blacktriangle \forall$  or NUMBER buttons to select a channel number.

# **VOLUME ADJUSTMENT**

Adjust the volume to suit your personal preference.



Press the **VOL**  $\triangleleft$  or  $\triangleright$  button to adjust the volume.



If you want to switch the sound off, press the **MUTE** button.



You can cancel the Mute function by pressing the **MUTE** or **VOL**  $\triangleleft$   $\blacktriangleright$  button.



3 6

9


8

 $\bigcirc$ 

СН 🔺

# **ON-SCREEN MENUS SELECTION**

Your TV's OSD (On Screen Display) may differ slightly from what is shown in this manual.



# **CHANNEL SEARCH**

#### Auto Program: Program Search

Auto Program should be used to memorize all the active channels in your area before you are able to use the TV.

There are two ways of storing channels in the TV's memory. You can use either.

One is called AUTO PROGRAM and the other is called MANUAL PROGRAM.

In AUTO PROGRAM mode, the TV will memorize the channels in ascending numerical order. If there are additional channels you want to add or delete, you can manually add or delete those channels with Manual Program.

- Redo Auto Program if the TV is ever moved to another location.
- Auto Program will search for channels only through the Antenna jack.

- If channels numbers for broadcast over-the air TV and cable TV are duplicated where different channels have the same number, press the same number buttons again to toggle between:

Broadcast TV Channels Cable TV Channels


(For example, press 17 to go to the channel, press 17 again to go to the duplicated channel.)



Press the **A.PROG** button. AUTO PROGRAM starts the channel search. If you want to stop auto programming, press the **MENU** button. Only the channels found up to at that time are memorized.




= You can also use the Channel menu to adjust Auto program.



TV POWER INPUT MTS APROG NEMORIEASE CAPTION 1 2 3 4 5 6 7 8 9 0 0 0 MUTE 0 CR





Manual Program: Adding/Deleting Channels

You can add or delete channels from the channel scan manually.

• You can also use the Channel menu to adjust Manual program.

N	Channel	
É	Auto program	
	Manual program	
0	Favorite channel	
0		
<u>स</u> ्		
-₽P	▲▼ ◀► ⊚ MENU	



33

# FINE TUNING ADJUSTMENT

Normally fine tuning is only necessary if reception is poor. To remove fine tuning from a channel, reprogram the finelytuned channel with Auto program or Manual Program. If a finely-tuned channel is memorized, the color of the channel number changes to yellow.

APC DASP

MUTE

hannel

Auto program

Manual program

Favorite channel

▲▼ ◀► ⊚ MENU

0

 $(\mathbf{0})$ 

СН 🔺

SI FEP



Press the **MENU** button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Channel** menu.

Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select **Manual program**.



1


2

Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select **Fine**.



Press the  $\blacktriangleleft$  or  $\blacktriangleright$  button to adjust the picture to your preference.







3 4 5

# Image: Channel Image: Chane Image: C

 $(\mathbf{0})$ 

Favorite channel

▲▼ ◀► ⊚ MENU

SLEEP

ARC/\*

MUTE



channels.

Press the **MENU** button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Channel** menu.

FAVORITE CHANNELS SETUP

Favorite Channels is a convenient feature that lets you quickly scan up to 8 channels of your choice without having to wait for the TV to scan through all the in-between

To tune to a favorite channel, press the FCR (Favorite

nels appear on the screen in numerical order.

Channel Review) button repeatedly. The 8 favorite chan-



Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select **Favorite channel**.

Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select the first favorite channel position.



3


Use the  $\blacktriangleleft$  or  $\blacktriangleright$  button to set the desired channel number for first favorite channel.



6

Press the **ENTER** button to save.

Repeat steps 3 to 5 to memorize other favorite channels.



∯

234

# WATCHING TV /CHANNEL CONTROL

## **KEY LOCK**

The TV can be set so that the remote control is needed to control it.

This feature can be used to prevent unauthorized viewing by locking out the front panel controls.

This TV is programmed to remember which option it was last set to even if you turn the set off.

Press the **MENU** button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Special** menu.



1

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\triangledown$  button to select **Key lock**.


Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **On** or **Off**.



Press the **ENTER** button to save.







# PICTURE SIZE (ARC - ASPECT RATIO) CONTROL

This feature allows an analog picture with a 4:3 aspect ratio is displayed on your TV. When you receive an analog picture with a 4:3 aspect ratio on your 16:9 TV, you need to specify how the picture is to be displayed.

PC input source use 4:3 or 16:9 aspect ratio.

#### NOTE

If a fixed image is displayed on the screen for a long time, the image may become imprinted on the screen and remain visible. This phenomenon is common to all manufactures and in consequence the manufactures warranty does not cover the product bearing this phenomenon.


Press the ARC/  $\star$  button repeatedly to select the desired picture format.

You can also adjust ARC in the Screen menu.

#### 4:3


1)

Choose 4:3 when you want to view a picture with an original 4:3 aspect ratio.



#### 16:9

Adjust the picture horizontally, in a linear proportion to fill the entire screen.




#### Horizon

The screen size is, more enlarged at both sides, to create a spectacular view.




#### Zoom 1

Choose Zoom 1 when you want to view the picture without any alteration. However, the top and bottom portions of the picture will be cropped.



#### Zoom 2

Choose Zoom 2 when you want the picture to be altered, both vertically extended and cropped. The picture taking a halfway trade off between alteration and screen coverage.





## PRESET PICTURE SETTINGS

#### Auto Picture Control (APC) - Preset

APC adjusts the TV for the best picture appearance.

Select the preset value in the APC menu based on the program category.

**Clear, Optimum, Soft** Settings are preset for optimum picture quality at the factory and are not adjustable.

In the **User** mode only, you can directly adjust the contrast, brightness, color, sharpness, tint.

APC DASP ARC/*

PICTURE CONTROL

Press the **APC** button repeatedly to select the picture appearance setup option as below : **Clear, Optimum, Soft**, and **User** (your own settings).



1

Press the **ENTER** button to save.

• You can also use the **Picture** menu to adjust **APC**.



2	Picture	
	APC 🕨	√ Clear
	ACC	Optimum
<u></u>	XD	Soft
0	Cinema	User
	Reset	
4		
-1->	▲▼ ◀► ම MENU	

0

Color Tone - Preset

Choose one of three automatic color adjustments. Set to warm to enhance hotter colors such as red, or set to cool to see less intense colors with more blue.



 $\bigcirc$ 

MUTE

(

FCR



1

Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select ACC.

Press the **MENU** button and then  $\blacktriangle$  or  $\triangledown$  button to

**3** Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select either **Cool**, **Normal**, **Warm**, or **User**.



Press the **ENTER** button to save.

select the **Picture** menu.



0

4

Cinema

▲▼ **●** MENU


Reset

#### MANUAL PICTURE ADJUSTMENT

#### Auto Picture Control (APC) - User Mode

Adjust the picture appearance to suit your preference and viewing situations.





0

	Picture	
Ē	APC	Clear
	ACC	Optimum
Ô	XD	Soft
0	Cinema	🗸 User 🕨 🕨
- A	Reset	
4		
12		▲▼ ◀► ම MENU





4

6

Contrast 85 < Contrast

PICTURE CONTROL

0



Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\checkmark$  button to select **APC**.

Press the **MENU** button and then  $\blacktriangle$  or  $\triangledown$  button to

select the **Picture** menu.



Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\checkmark$  button to select **User**.



Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\triangledown$  button to select the desired picture option (Contrast, Brightness, Color, Sharpness, and Tint).



Press the  $\blacktriangleright$  button and then  $\blacktriangleleft$  or  $\blacktriangleright$  button to make appropriate adjustments.



Press the ENTER button to save.

ONTROL

#### Color Tone - User Mode

You can also adjust the detailed settings (Red, Green, Blue) by selecting the **User** menu.



 $\bigcirc$ 

MUTE

C

FCR



Press the **MENU** button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Picture** menu.



Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\checkmark$  button to select **ACC**.



Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select **User**.



Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select **Red**, **Green**, or **Blue**.



Press the  $\blacktriangleright$  button and then  $\blacktriangleleft$  or  $\blacktriangleright$  button to make appropriate adjustments.

■ The adjustment range of **Red**, **Green**, or **Blue** is -30 ~ +30.



Press the **ENTER** button to save.







0

PICTURE CONTROL







#### **XD - PICTURE IMPROVEMENT TECHNOLOGY**

XD is LG Electronic's unique picture improving technology to display a real HD source through an advanced digital signal processing algorithm.

When selecting APC options (Clear, Optimum and Soft), XD is automatically changed to Auto.

When selecting APC options (User), you can choose the Auto / Manual.

When selecting the Manual, you can adjust the XD Contrast. XD color and XD NR.



Press the **MENU** button and then ▲ or **▼** button to select the **Picture** menu.



Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select XD.

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select Auto or Manual.

#### Selecting the Manual

- 1. Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\triangledown$  button to select XD Contrast, XD Color or **XD** Noise.
  - **XD Contrast:** Optimizing the contrast automatically according to the brightness of the reflection.
  - **XD** Color: Adjusting the colors of the reflection automatically to reproduce as closely as possible to the natural colors.
  - **XD** Noise : Removing the noise up to the point where it does not damage the original picture.
- 2. Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **On** or **Off**.











4



Press the ENTER button to save.

PICTURE CONTROL

#### **XD DEMO**

Use it to see the difference between XD Demo on and XD Demo off.

It's not available to use this function in RGB-PC, HDMI/DVI-PC mode.





PICTURE CONTROL



Press the **MENU** button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Special** menu.

2

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **XD Demo**.




Press the  $\blacktriangleright$  button to begin **XD Demo**.



To stop XD Demo, press the MENU button.







#### **CINEMA 3:2 PULL DOWN MODE**

Set up the TV for the best picture appearance for viewing movies.

When you operate Cinema 3:2 Mode (3:2 Pull-Down Mode or Cinema Correction Mode), the TV will adjust 24 fps video from movies to 30 fps video for display.





PICTURE CONTROL

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **Cinema**.

Press the **MENU** button and then  $\blacktriangle$  or  $\triangledown$  button to



2)

1

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **On** or **Off**.



Press the **ENTER** button to save.

select the **Picture** menu.

 Picture

 APC

 ACC

 XD

 O

 Cinema

 Reset

 Off

 ▲▼ ◄► ⑨ MENU

#### **PICTURE RESET**

Use to quickly reset all the Picture menu options to their original factory preset values.






Press the **MENU** button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Picture** menu.


2

3

Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select **Reset**.

Press the ► button to initialize the adjusted value.





# **SOUND & LANGUAGE CONTROL**

## DIGITAL AUTO SOUND PROCESSING (DASP)

DASP lets you enjoy the best sound without any special adjustment because the TV sets the appropriate sound options based on the program content.

Flat, Music, Movie, and Sports are preset for good sound quality at the factory and are not adjustable.





Press the **DASP** button repeatedly to select the appropriate sound setup as below :

Flat, Music, Movie, Sports, and User (your own settings).



П

Press the **ENTER** button to save.

• You can also adjust **DASP** in the **Sound** menu.



2	Sound		
$\overline{\Box}$	DASP	$\mathbf{r}$	√ Flat
	AVL		Music
õ	Balance	0	Movie
0			Sports
			User
12	▲▼ ◀► ⑨ MENU		

SOUND & LANGUAGE CONTROL

#### SOUND SETTING ADJUSTMENT - USER MODE

Adjust the sound equalizer.





Press the **MENU** button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Sound** menu.

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **DASP**.



2

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **User**.



5

Press the  $\blacktriangleright$  button.

Press the  $\blacktriangleleft$  or  $\blacktriangleright$  button to select the band you want to adjust.


Press the  $\blacktriangle$  or  $\triangledown$  button to adjust the band level.



Press the **ENTER** button to save.







SOUND & LANGUAGE CONTROL

## SOUND & LANGUAGE CONTROL

## AUTO VOLUME LEVELER (AVL)

AVL automatically keeps on an equal volume level even if you change program.



Sound DASP

Balance

▲▼ ◀► ⊚ MENU

0

4



Press the **MENU** button and then use  $\blacktriangle$  or  $\triangledown$  button to select the **Sound** menu.



Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select AVL.

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\triangledown$  button to select **On** or **Off**.



Press the **ENTER** button to save.



23

## BALANCE

Adjust the left/right sound of speaker to suit your taste and room situations.





Press the **MENU** button and then use  $\blacktriangle$  or  $\triangledown$  button to select the **Sound** menu.

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\checkmark$  button to select **Balance**.




2

Press the  $\blacktriangleright$  button and then use  $\blacktriangleleft$  or  $\blacktriangleright$  button to make appropriate adjustments.



Press the **ENTER** button to save.





SOUND & LANGUAGE CONTROL

## SOUND & LANGUAGE CONTROL

#### STEREO/SAP BROADCASTS SETUP

The TV can receive MTS stereo programs and any SAP (Secondary Audio Program) that accompanies the stereo program; if the broadcaster transmits one additional sound signal in addition to the original one.

Mono: The primary language is heard from left and right speakers. Signal mode is mono.

Stereo: The primary language is heard from left and right speakers. Signal mode is stereo.

SAP: The secondary language is heard from left and right speakers in mono sound.





Use the **MTS** button to select your desired MTS mode in analog signal. Each time you press the **MTS** button, **Mono**, **Stereo**, or **SAP** appear in turn.



2

Press the **ENTER** button to save.

#### NOTE

- Select mono sound mode if the signal is not clear or in poor signal reception areas.
- **Stereo**, **SAP** modes are available only if included on the broadcast signal.

## **ON-SCREEN MENUS LANGUAGE SELECTION**

The menus can be shown on the screen in the selected language. First select your language.





Press the **MENU** button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Special** menu.

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\checkmark$  button to select Language.



2

Press the ► button and then use ▲ or ▼ button to select your desired language. From this point on, the on-screen menus will be shown in the selected language.



Press the **ENTER** button to save.


## SOUND & ANGUAGE CONTROL

## **CAPTION / TEXT**

Closed captioning is a process which converts the audio portion of a television program into written words which then appear as subtitles on the television screen. Closed captions allow viewers to read the dialogue and narration of television programs.

#### Using Closed Captions

Captions are the subtitles of the dialogue and narration of television programs. For prerecorded programs, program dialogue can be arranged into captions in advance. Its possible to caption a live program by using a process called real-time captioning, which creates captions instantly. Real-time captioning is normally done by professional reporters using a machine shorthand system



and computer for translation into English. Captioning is an effective system for the hearingimpaired, and it can also aid in teaching language skills.

• The picture at left shows a typical caption.

#### **Caption Tips**

- Not all TV broadcasts include closed caption signals.
- Sometimes TV stations broadcast four different caption signals on the same channel. By selecting Mode1 to Mode2, you can choose which signal you view. Mode1 is usually the signal with the captions, while another mode might show demonstration or programming information.
- Your TV might not receive caption signals normally in the following situations.

1. Poor reception conditions are encountered:







#### • IGNITION:

Picture may flutter, drift, suffer from black spots, or horizontal streaking. Usually caused by interference from automobile ignition systems, neon lamps, electrical drills, and other electrical appliances.

#### • GHOSTS:

Ghosts are caused when the TV signal splits and follows two paths. One is the direct path and the other is reflected off tall buildings, hills or other objects. Changing the direction or position of the antenna may improve reception.

#### • SNOW:



If your receiver is located at the weak, fringe area of a TV signal, your picture may be marred by small dots. It may be necessary to install a special antenna to improve the picture.

- 2. An old, bad, or illegally recorded tape is being played.
- 3. Strong, random signals from a car or airplane interfere with the TV signal.
- 4. The signal from the antenna is weak.
- 5. The program wasn't captioned when it was produced, transmitted, or taped.



Use the CAPTION button repeatedly to select your caption Mode 1, Mode 2, Text1, Text2, or Off.







# TIME SETTING

## **CLOCK SETTING**

If the current time setting is wrong, reset the clock manually.







Press the **MENU** button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Timer** menu.

Press the  $\blacktriangleright$  button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select **Clock**.



2)


Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to set the Hour.



Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to set the minutes.



Press the **ENTER** button to save.



TIME SETTING

## TIME SETTING

#### AUTO ON/OFF TIMER SETTING

The timer function operates only if the current time has been set.

The Off-Timer function overrides the On-Timer function if they are both set to the same time.

The TV must be in standby mode for the On-Timer to work. If you do not press any button within 2 hours after the TV turns on with the On Timer function, the TV will automatically revert to standby mode.



Press the **MENU** button and then  $\blacktriangle$  or  $\blacktriangledown$  button to select the **Timer** menu.



Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **Off timer** or **On timer**.



TIME SETTING

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to set the hour.

4

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to set the minutes.



#### Only On timer

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  to select the channel at turn-on.

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  to set the sound level at turn-on.




Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **On**.


■ To cancel the **On/Off timer** function, select **Off**.



Press the ENTER button to save.









#### SLEEP TIMER SETTING

The Sleep Timer turns the TV off at the preset time. Note that this setting is cleared when the TV is turned off.





Press the **SLEEP** button repeatedly to select the number of minutes. First the 'C' - - - ' option appears on the screen, followed by the following sleep timer options : 10, 20, 30, 60, 90, 120, 180, and 240 minutes.



When the number of minutes you want is displayed on the screen, press the **ENTER** button. The timer begins to count down from the number of minutes selected.



To check the remaining minutes before the TV turns off, press the **SLEEP** button once.

4

To cancel the Sleep Timer, press the **SLEEP** button repeatedly to select ' $\bigcirc$  - - - '.

## TIME SETTING

#### AUTO SHUT-OFF SETTING

If set to on and there is no input signal, the TV turns off automatically after 10 minutes.





0



Press the **MENU** button and then use  $\blacktriangle$  or  $\triangledown$  button to select the **Timer** menu.



TIME SETTING

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\triangledown$  button to select **Auto off**.

3
---

Press the  $\blacktriangleright$  button and then use  $\blacktriangle$  or  $\blacktriangledown$  button to select **On** or **Off**.



Press the **ENTER** button to save.





# APPENDIX

## TROUBLESHOOTING

The operation does not work normally.	
The remote control doesn't work	<ul> <li>Check to see if there is any object between the product and the remote control causing obstruction. Ensure you are pointing the remote control directly at the TV.</li> <li>Ensure that the batteries are installed with correct polarity (+ to +, - to -).</li> <li>Ensure that the correct remote operating mode is set: TV, VCR etc.</li> <li>Install new batteries.</li> </ul>
Power is suddenly turned off	<ul> <li>Is the sleep timer set?</li> <li>Check the power control settings. Power interrupted.</li> <li>No broadcast on station tuned with Auto off activated.</li> </ul>

The video function does not work.		
No picture &No sound	<ul> <li>Check whether the product is turned on.</li> <li>Try another channel. The problem may be with the broadcast.</li> <li>Is the power cord inserted into wall power outlet?</li> <li>Check your antenna direction and/or location.</li> <li>Test the wall power outlet, plug another product's power cord into the outlet where the product's power cord was plugged in.</li> </ul>	
Picture appears slowly after switching on	This is normal, the image is muted during the product startup process. Please contact your service center, if the picture has not appeared after five minutes.	
No or poor color or poor picture	<ul> <li>Adjust Color in menu option.</li> <li>Keep a sufficient distance between the product and the VCR.</li> <li>Try another channel. The problem may be with the broadcast.</li> <li>Are the video cables installed properly?</li> <li>Activate any function to restore the brightness of the picture.</li> </ul>	
Horizontal/vertical bars or picture shaking	Check for local interference such as an electrical appliance or power tool.	
Poor reception on some channels	<ul> <li>Station or cable product experiencing problems, tune to another station.</li> <li>Station signal is weak, reorient antenna to receive weaker station.</li> <li>Check for sources of possible interference.</li> </ul>	
Lines or streaks in pictures	Check antenna (Change the direction of the antenna).	

# APPENDIX

The audio function does not work.	
Picture OK & No sound	<ul> <li>Press the VOL or VOLUME button.</li> <li>Sound muted? Press MUTE button.</li> <li>Try another channel. The problem may be with the broadcast.</li> <li>Are the audio cables installed properly?</li> </ul>
No output from one of the speakers	■ Adjust Balance in menu option.
Unusual sound from inside the product	A change in ambient humidity or temperature may result in an unusual noise when the product is turned on or off and does not indicate a fault with the product.

There is a problem in PC mode. (Only PC mode applied)		
The signal is out of range	<ul> <li>Adjust resolution, horizontal frequency, or vertical frequency.</li> <li>Check the input source.</li> </ul>	
Vertical bar or stripe on background & Horizontal Noise & Incorrect position	Work the Auto configure or adjust clock, phase, or H/V position. (Option)	
Screen color is unstable or single color	<ul> <li>Check the signal cable.</li> <li>Reinstall the PC video card.</li> </ul>	

#### MAINTENANCE

Early malfunctions can be prevented. Careful and regular cleaning can extend the amount of time you can enjoy your new TV.

Caution: Be sure to turn the power off and unplug the power cord before you begin any cleaning.

#### **Cleaning the Screen**

Here's a great way to keep the dust off your screen for a while. Wet a soft cloth in a mixture of lukewarm water and a little fabric softener or dish washing detergent. Wring the cloth until it's almost dry, and then use it to wipe the screen.

Make sure the excess water is off the screen, and then let it air-dry before you turn on your TV.

#### **Cleaning the Cabinet**

2

- To remove dirt or dust, wipe the cabinet with a soft, dry, lint-free cloth.
- Please be sure not to use a wet cloth.

#### **Extended Absence**

#### **A** CAUTION

If you expect to leave your TV dormant for a long time (such as a vacation), it's a good idea to unplug the power cord to protect against possible damage from lightning or power surges. APPENDIX

## APPENDIX

## **PRODUCT SPECIFICATIONS**

The specifications shown above may be changed without prior notice for quality improvement.

MODELS		<b>19LS4R</b> (19LS4R-MA)	<b>22LS4R</b> (22LS4R-MA)
Dimensions (Width x Height x Depth)	Including stand	18.0 x 15.6 x 6.8 inches	20.7 x 17.4 x 7.4 inches
		456.8 x 396.6 x 172.0mm	525.4 x 441.6 x 187.4 mm
	Excluding stand	18.0 x 14.5 x 2.8 inches	20.7 x 16.3 x 2.7 inches
		456.8 x 368.5 x 70.5 mm	525.4 x 413.0 x 68.6 mm
Weight	including stand	11.2 pounds / 5.1 kg	12.8 pounds / 5.8 kg
	excluding stand	10.1 pounds / 4.6 kg	11.5 pounds / 5.2 kg
Power Consumption		50 W	60 W
Power requirement		AC100-240V ~ 50/60Hz	
Television System		NTSC, PAL-M/N	
Program Coverage		VHF 2-13, UHF 14-69, CATV 1-125	
External Antenna Impedance		75 ohm	
Environment condition	Operating Temperature	32 ~ 104°F (0 ~ 40°C)	
	Operating Humidity	Less than 80%	
	Storage Temperature	-4 ~ 140°F (-20 ~ 60°C)	
	Storage Humidity	Less than 85%	

**LG Electronics Inc.**