



Prior to installation, this airconditioning unit must be submitted

LG Multi Type Air Conditioner **OWNER'S MANUAL**

MODELS:




TABLE OF CONTENTS

Safety Precautions3	
Prior to Operation9	
Introduction10	
Electrical Safety11	
Operating Instructions12	
Maintenance and Service23	

FOR YOUR RECORDS

Write the model and serial numbers here:

Model

Serial #

You can find them on a label on the side of each unit.

Dealer's Name

Date Purchased

Staple your receipt to this page in the event you need it to prove date of purchase or for warranty issues.

CREAD THIS MANUAL

Inside you will find many helpful hints on how to use and maintain your air conditioner properly. Just a little preventive care on your part can save you a great deal of time and money over the life of your air conditioner.

You'll find many answers to common problems in the chart of troubleshooting tips. If you review our chart of

Troubleshooting Tips first, you may not need to call for service at all.

PRECAUTION


- Contact the authorized service technician for repair or maintenance of this unit.
- Contact the installer for installation of this unit.
- The air conditioner is not intended for use by young children or invalids without supervision.
- Young children should be supervised to ensure that they do not play with the air conditioner.
- When the power cord is to be replaced, replacement work shall be performed by authorized personnel only using only genuine replacement parts.
- Installation work must be performed in accordance with the National Electric Code by qualified and authorized personnel only.



Safety Precautions


To prevent the injury of the user or other people and property damage, the following instructions must be followed.

■ Incorrect operation due to ignoring instruction will cause harm or damage. The seriousness is classified by the following indications.



Be cautious when unpacking and installing the product.

• Sharp edges could cause injury. Be especially careful of the case edges and the fins on the condenser and evaporator.



Be sure the installation area does not deteriorate with age.

 If the base collapses, the air conditioner could fall with it, causing property damage, product failure, and personal injury.

For installation, always contact the dealer or an Authorized Service Center.

• There is risk of fire, electric shock, explosion, or injury.





Do not let the air conditioner run for a long time when the humidity is very high and a door or a window is left open.

• Moisture may condense and wet or damage furnishings.

Do not install the product on a defective installation stand.

• It may cause injury, accident, or damage to the product.





Operation

Take care to ensure that power cable could not be pulled out or damaged during operation.

• There is risk of fire or electrical shock.



Do not place anything on the power cable.

• There is risk of fire or electric shock.



Do not turn the breaker on/off or connect/disconnect the power supply cable during operation.

• There is risk of fire or electrical shock.



Do not allow water to run

• It may cause There is risk of

fire, failure of the product, or

into electric parts.

electric shock.

Do not touch product with wet hands.


• There is risk of fire or electrical shock.



Do not store or use flammable gas or combustibles near the air conditioner.

Do not place a heater or other appliances near the power cable.

• There is risk of fire and electric shock.



Do not use the product in a tightly closed space for a long time.

a When flammable gas leaks, turn off the gas and open a window for ventilation before turn the product on. DO NOT use the telephone or turn switches on or off.

There is risk of fire or failure of product.



Oxygen deficiency could occur.

Unplug the unit if strange sounds, odors, or smoke comes from it.

There is risk of electrical shock
 or fire



Stop operation and close the window in storm or hurricane. If possible, remove the air conditioner from the window before the hurricane arrives.

• There is risk of property damage, failure of product, or electric shock.



• There is risk of explosion or fire.



Do not open the inlet grill of the product during operation. (Do not touch the electrostatic filter, if the unit is so equipped.)

• There is risk of physical injury, electric shock, or product failure.




When the product is soaked (flooded or submerged), contact an Authorized Service Center.

• There is risk of fire or eletric shock.



Ventilate the product from time to time when operating it together with a stove, etc.

• There is risk of fire or electrical shock.



There is risk of electrical shock.



When the product is not be used for a long time, disconnect the power supply cable or turn off the breaker.

• There is risk of product damage or failure, or unintended operation.

Take care to ensure that nobody could step on or fall onto the outdoor unit.

• This could result in personal injury and product damage.





ACAUTION

Installation


Always check for gas (refrigerant) leakage after installation or repair of product.

• Low refrigerant levels may cause failure of product.



Install the drain hose to ensure that water is drained away properly.

• A bad connection may cause water leakage.



Keep level even when installing the product.

To avoid vibration or water leakage.



Do not install the product where the noise or hot air from the outdoor unit could damage the neighborhoods.


• It may cause a problem for your neighbors.

Use two or more people to lift and transport the air conditioner.

Avoid personal injury.

Do not install the product where it will be exposed to sea wind (salt spray) directly.

 It may cause corrosion on the product. Corrosion, particularly on the condenser and evaporator fins, could cause product malfunction or inefficient operation.







■Operation -

Do not direct airflow at room occupants. (Don't sit in the draft.)

This could damage your health.




Use a soft cloth to clean. Do not use harsh detergents, solvents, etc.

• There is risk of fire, electric shock, or damage to the plastic parts of the product.



Do not use the product for special purposes, such as preserving foods, works of art, etc. It is a consumer air conditioner, not a precision refrigeration system.

• There is risk of damage or loss of property.



Do not touch the metal parts of the product when removing the air filter. They are very sharp!

There is risk of personal injury.



• It may cause product failure.

Do not block the inlet or

outlet of air flow.



Do not step on or put anyting on the product. (outdoor units)

• There is risk of personal injury and failure of product.



ay cause product failure.

Always insert the filter securely. Clean the filter every two weeks or more often if necessary.

 A dirty filter reduces the efficiency of the air conditioner and could cause product malfunction or damage.



Do not insert hands or other objects through the air inlet or outlet while the air conditioner is plugged in.

• There are sharp and moving parts that could cause personal injury.

Do not drink the water drained from the unit.

• It is not sanitary and could cause serious health issues.



Use a firm stool or ladder when cleaning or maintaining the air conditioner.

· Be careful and avoid personal injury.



Replace the all batteries in the remote control with new ones of the same type. Do not mix old and new batteries or different types of batteries.

There is risk of fire or explosion



Disuse -

Do not recharge or disassemble the batteries. Do not dispose of batteries in a fire.

• They may burn or explode.

If the liquid from the batteries gets onto your skin or clothes, wash it well with clean water. Do not use the remote if the batteries have leaked.

• The chemicals in batteries could cause burns or other health hazards.





Prior to Operation

- Preparing for Operation
 - 1. Contact an installation specialist for installation.
 - 2. Plug in the power plug properly.
 - 3. Use a dedicated circuit.
 - 4. Do not use an extension cord.
 - 5. Do not start/stop operation by plugging/unplugging the power cord.
 - 6. If the cord/plug is damaged, replace it with only an authorized replacement part.



- 1. Being exposed to direct airflow for a long time may be hazardous to your health. Do not expose occupants, pets, or plants to direct airflow for a long time.
- 2. Due to the possibility of oxygen deficiency, ventilate the room when using the appliance together with stoves or other heating devices.
- 3. Do not use this air conditioner for non-specified special purpose (e.g. preserving precision devices, food, pets, plants, or art objects). Such use may damage your properties.



- 1. Do not touch the metal parts of the unit when removing the filter. Injury can occur.
- 2. Do not use water to clean inside the air conditioner. Exposure to water can destroy the insulation, leading to electric shock.
- 3. When cleaning the unit, first make sure that the power and breaker are turned off. The fan rotates at a very high speed during operation. There is a possibility of injury if the unit's power is triggered while cleaning inner parts of the unit.



For repair and maintenance, contact your authorized service dealer.

Introduction


Symbols used in this Manual



This symbol alerts you to the risk of electric shock.




This symbol alerts you to hazards that may cause harm to the air conditioner.



Features

AWARNING

This appliance should be installed in accordance with national wiring regulations. This guide acts as a guide to help to explain product features.



Electrical Safety

A WARNING

- This appliance must be properly grounded.
 To minimize the risk of electric shock, you must alway plug into a grounded outlet.
- Do not cut or remove the grounding prong from the power plug.
- Attaching the adapter ground terminal to the wall receptacle cover screw does not ground the appliance unless the cover screw is metal and not insulated, and the wall receptacle is grounded through the house wiring.
- If you have any doubt whether the air conditioner is properly grounded, have the wall receptacle and circuit checked by a qualified electrician.

Temporary Use of an Adapter

We strongly discourage the use of an adapter due to potential safety hazards. For temporary connections, use only a UL-listed adapter, available from most local hardware stores. Ensure that the large slot in the adapter is aligned with the large slot in the receptacle for a proper polarity connection.

To disconnect the power cord from the adapter, use one hand on each to avoid damaging the ground terminal. Avoid frequently unplugging the power cord as this can lead to eventual ground terminal damage.

A WARNING

• Never use the appliance with a broken adapter.

Temporary Use of an Extension Cord

We strongly discourage the use of an extension cord due to potential safety hazards. For temporary situations, use only CSA certified and UL listed 3-wire grounded extension cords, rated 15 A, 125 V.


Operating Instructions

How to insert the Batteries

- 1. Remove the battery cover by pulling it according to the arrow direction.
- 2. Insert new batteries making sure that the (+) and (-) of battery are installed correctly.
- 3. Reattach the cover by sliding it back into position.


NOTICE

Use 2 AAA(1.5volt) batteries. Do not use rechargeable batteries.




Storage and Tips for using the Remote Controller

• The remote controller may be stored by mounting it on a wall.



• To operate the room air conditioner, aim the remote controller at the signal receptor.




Signal Receptor

Receives the signals from the remote control.(Signal receiving sound: two short beeps or one long beep.)


Operation Indication Lamps

\bigcirc	On/Off	: Lights up during the system operation.
ふ	Sleep Mode	: Lights up during Sleep Mode Auto operation.
	Timer	: Lights up during Timer operation.
8	Defrost Mode	: Lights up during Defrost Mode or Hot Start operation (Heat pump model only)




Remote Control Operation


The Remote Controller transmits the signals to the system.



Cooling Model(√), Heat Pump Model(♥)




buttons.




Natural wind by the CHAOS logic

□ For more fresh feeling, press the Indoor Fan Speed Selector and set CHAOS mode. In this mode, the wind blows like natural breeze by automatically changing fan speed according to the CHAOS logic.




□You cannot switch the indoor fan speed. It has already been set by the Fuzzy rule.

- □ If the system is not operating as desired, manually switch to another mode. The system will not automatically switch from the cooling mode to the heating mode, or from heating to cooling, then you must set the mode and the desired temperature again.
- During Auto Operation, pressing the chaos swing button makes the horizontal louvers swing up and down automatically. If you want to stop auto-swing, press the chaos swing button again.




DURING HEALTHY DEHUMIDIFICATION OPERATION:

- □ If you select the dehumidification mode on the operation selection button, the A/C starts to run the dehumidification function, automatically setting the room temp. and air volume to the best condition for dehumidification based on the sensed room temp. In this case, the setting temp. is not displayed on the Remote Controller and you are not able to control the room temp. either.
- □ During the healthy dehumidification function, the airflow volume is automatically set according to the optimization algorithm responding to the current room temp. So that room condition is kept healthy and comfortable even in the very humid season.




Natural wind by the CHAOS logic

□ For more fresh feeling, press the Indoor Fan Speed Selector and set CHAOS mode. In this mode, the wind blows like natural breeze by automatically changing fan speed according to the CHAOS logic.



NOTICE

- □ During the JET COOL function at any moment, the A/C starts to blow the cool air at extremely high speed for 30 minutes setting the room temp. automatically to 18°C. It is especially used to cool the room temperature quickly in a hot summer.
- □ In order to return to the normal cooling mode from the Jet Cool mode, you just press either the operation mode selection button, air volume selection or temp. setting button or the JET COOL button again.



Additional Features

😭 Sleep mode

- 1. Press the Sleep Mode Auto button to set the time you want the unit to stop automatically
- 2. The Timer is programmed in one-hour increments by pressing the Sleep Mode Auto button 1 to 7 times. The sleep mode is available for 1 to 7 times. To alter the time period in steps of 1 hour, press the Sleep Mode Button while aiming at air conditioner.
- 3. Make sure the Sleep Mode Auto LED lights up. To cancel the Sleep Mode, press the sleep Mode Auto button several times until the star $(\sum_{i=1}^{N})$ disappears from the operation display.
- NOTICE The Sleep Mode will be operated at slow fan speed (cooling) or medium fan speed (heat pump only) for a comfortable sleep.

In sleep mode: Chaos Swing function does not operate.

In cooling mode or healthydehumidification mode:

The temperature will automatically rise by 1°C over the next 30 minutes and by 2°C in 1 hour for a comfortable sleep.

Setting the time

- 1. Time can be set only when you press the Reset button. Having replacing the batteries, you should press the reset buttons to reset the time. Press the Start/Stop button.
- 2. Press 2nd F button and check if 2nd F icon is on.
- 3. Press the Time Setting buttons until the desired time is set.
- 4. Press the Timer SET button.

NOTICE Check the indicator for A.M. and P.M.

Delay start/Pre-set stop

- 1. Make sure the time is set correctly on the display of the remote controller.
- 2 Press 2nd E button
- 3. Press the ON/OFF Timer buttons to turn Timer on or off.
- 4. Press the Time Setting buttons until the desired time is set.
- 5. To set the selected time, press the Timer setting button aiming the remote controller at the signal receptor.

To cancel the timer setting

Check if 2nd F icon is off.

Press the Timer Cancel button aiming the remote controller at the signal receptor.

(The timer lamp on the air conditioner and the display will go out.)

NOTICE Select one of the following four types of operation.

with the unit running

013	a.m. 6:00	ON OFF	ON OFF
a.m. 12:00		a.m. 3:30 a.m. 3:00	a.m. 3:00 a.m. 3:30
Delay OFF Timer	Delay ON Timer	Delay OFF and ON Timer	Delay ON and OFF Timer





🕒 Vertical Airflow Direction Control

The up/down airflow (Vertical Airflow) can be adjusted by using the remote control.



- 1. Press the Start/Stop button to start the unit.
- 2. Press Chaos Swing button and the louvers will swing up and down. Press the Chaos Swing button

again to set the vertical louver at the desired airflow direction.




NOTICE

- ☐ If you press the CHAOS swing button, the horizontal airflow direction is changed automatically based on the CHAOS algorithm to distribute the air in the room evenly and at the same time to make the human body feel most comfortable, as if enjoying a natural breeze.
- □Always use the remote control to adjust the up/down airflow direction. Manually moving the vertical airflow direction louver by hand, could damage the air conditioner.
- □When the unit is shut off, the up/down airflow direction louver will close the air outlet vent of the system.

Forced operation

Operation procedures when the remote control can't be used. The operation will be started if the ON/OFF button is pressed. If you want to stop operation, re-press the button.



	Cooling Model		Heat pump Model	
		Room Temp. <i>≥</i> 24°C	21°C ≪Room Temp. < 24°C	Room Temp. < 21°C
Operating mode	Cooling	Cooling	Healthy Dehumidification	Heating
Indoor FAN Speed	High	High	High	High
Setting Temperature	22°C	22°C	23°C	24°C

Test operation

During the TEST OPERATION, the unit operates in cooling mode at high speed fan, regardless of room temperature and resets in 18 minutes.

During test operation, if remote controller signal is received, the unit operates as remote controller sets.

If you want to use this operation, Press and hold the ON/OFF button for 3~5 seconds, then the buzzer sound 1 "beep".

If you want to stop the operation, re-press the button.

Auto restart

In case the power comes on again after a power failure, Auto Restarting Operation is the function to operate procedures automatically to the previous operating conditions.

So there is no need of activating this function by pressing any key or button.

In the initial mode, the fan operates at a low speed and the compressor starts 2.5~3 minutes later.


As the compressor starts, the fan speed also resumes its previous setting mode.

Helpful information

Fan speed and cooling capacity.

The cooling capacity indicated in the specification is the value when the fan speed is set to high, and the capacity will be lower at low or medium fan speed.


High fan speed is recommended when you wish to cool the room quickly.



Air Circulation Mode

Circulates the room air without cooling or heating.

- 1. Press the Start/Stop button. The unit will respond with beep sound.
- Open the door on the Remote Controller. Press the Air Circulation button. Now each time that you press the Indoor Fan Speed Selector, the fan speed is shifted from low to CHAOS and back to low again.



NOTICE

□ CHAOS Air economizes power consumption and prevents overcooling. The fan speed is automatically changed from high to low or vice versa, depending on the ambient temperature.


Maintenance and Service

ACAUTION

Before performing any maintenance, turn off the main power to the system.



Turn the system off before cleaning. To clean, wipe with a soft, dry cloth. Do not use bleach or abrasives.



NOTICE

Supply power must be disconnected before cleaning the indoor unit.

Air filters

The air filters behind the front grille should be checked and cleaned once in every 2 weeks or more often if neccessary.

- 1. Pull the both sides and remove front panel.
- 2. Pull the filter tab slightly forward to remove the filter.
- 3. Clean the filter with a vacuum cleaner or warm, soapy water,
 - · If dirt is conspicuous, wash with a solution of detergent in lukewarm water.
 - If hot water (40°C or more) is used, it may be deformed.
- 4. After washing with water, dry well in the shade.
- 5. Re-install the air filter.

TRIPLE DEODORIZER filter (Optional)

- 1. After removing the air filters, pull slightly forward to remove the TRIPLE DEODORIZER filter.
- 2. Dry in the sunlight for two hours.
- 3. Re-install the TRIPLE DEODORIZER filter to the original position.

ACAUTION

Never use any of the followings:

- Water hotter than 40°C
- Could cause deformation and/or discoloration. Volatile substances
- Could damage the surfaces of the air conditioner.










Replacement of purifying filter (Optional)

Recomended use period : About 2 years

- 1. Remove front panel and air filters.
- 2. Remove air purifying filters.
- 3. Insert new air purifying filters.
- 4. Reinsert air filters and close front panel.
 - Type 1: Open the front panel as shown.

Then pull the filter tab slightly forward to remove the air filter. After removing the air filter remove the plasma and deodorizer filter by slightly pulling forward.



Type 2: Pull the front panel from both sides as shown.

Then pull the filter tab slightly forward to remove the filter. After removing the air filter remove the plasma and triple deodorizer filter by slightly pulling forward.





The heat exchanger coils and panel vents of the outdoor unit should be checked regularly. If clogged with dirt or soot, the heat exchanger and panel vents may be professionally steam cleaned. (Rear)

NOTICE

(Side Piping Air intake vents Drain Hose Dirty or clogged coils will reduce the operating efficiency of the system and Air outlet vents cause higher operating costs. (Rear) (Side) Air intake 0 vents Drain hose Air outlet vents Q

Common Problems and Solutions

Before calling for service

If you have problems with your air conditioner, read the following information and try to solve the problem. If you cannot find a solution, turn off the air conditioner and contact your dealer.

Air conditioner does not operate

- 1. Ensure that the air conditioner is plugged into a proper outlet.
- 2. Check the fuse or circuit breaker.
- 3. Check whether the voltage is unusually high or low.

Air does not feel cold enough on the cooling setting

- 1. Ensure that the temperature settings are correct.
- 2. Check to see if the air filter is clogged with dust. If so, replace the filter.
- 3. Ensure that the air flow from the outside is not obstructed and that there is a clearance of over 20" between the back of the air conditioner and the wall or fence behind it.
- 4. Close all doors and windows and check for any source of heat in the room.



Before calling for service, please review the following list of common problems and solutions.

The air conditioner is operating normally when:

- You hear a pinging noise. This is caused by water being picked up by the fan on rainy days or in highly humid conditions. This feature is designed to help remove moisture in the air and improve cooling efficiency.
- You see water dripping from the rear of the unit. Water may be collected in the base pan in highly humid conditions or on rainy days. This water overflows and drips from the rear of the unit.
- You hear the fan running while the compressor is silent. This is a normal operational feature.

Troubleshooting

Check the following points before requesting repairs or service.... If the fault persists, please contact your dealer or service center.

Case	Explanation	See page
The air conditioner does not operate.	Check room temperature setting? Check if circuit breaker is on?	20 -
The room has a peculiar odor.	 Check that this is not a damp smell exuded by the walls, carpet, furniture, or cloth items in the room. 	-
It seems that condensation is leaking from the air conditioner.	 Check the drain hose is connected tight or if indoor unit is installed even. 	-
Air conditioner does not operate for about 3 minutes after turning on.	 This is the protector of the mechanism. Wait about 3 minutes and operation will begin. About 3 minutes delay is applied to protect compressor from frequenty on/off. 	-
Does not cool or heat effectively.	 Is the air filter dirty? See air filter cleaning instructions. 	23, 24
	Has the temperature been set correctly?	14, 17
	Are the indoor unit's air inlet or outlet vents obstructed?	-
The air conditioner operation is noisy.	 For a noise that sounds like water flowing. This is the sound of refrigerant flowing inside the air conditioner unit. For a noise that sounds like the compressed air releasing into atmosphere. This is the sound of the dehumidifying water being processed inside the air conditioning unit. 	-
Remote Controller display is faint, or no display at all.	 Are the batteries depleted? Are the batteries inserted in the opposite (+) and (-) directions? 	12
Crack sound is heard.	This sound is generated by the expansion/constriction of the front panel, etc. due to changes of temperature.	-

