

OWNER'S MANUAL

Please read this manual carefully before operating your set and retain it for future reference.

LT36**

www.lg.com

3 LICENSES

- 3 OPEN SOURCE SOFTWARE NOTICE
- 4 INSTALLATION PROCEDURE

4 ASSEMBLING AND PREPARING

- 4 Unpacking
- 7 Parts and buttons
- 8 Lifting and moving the TV
- 9 Setting up the TV
- 9 Attaching the stand
- 11 Mounting on a table
- 12 Mounting on a wall
- 14 Tidying cables

14 MAKING CONNECTIONS

- 15 Adapter connection
- 15 External speaker out
- 15 Antenna connection
- 16 HDMI connection
- 16 DVI to HDMI connection
- 17 Composite connection
- 17 RGB-PC connection
- 17 USB connection

18 REMOTE CONTROL

19 MAINTENANCE

- 19 Cleaning your TV
- 19 Screen, frame, cabinet and stand
- 19 Power cord

19 TROUBLESHOOTING

20 SPECIFICATIONS

23 IR CODES

24 EXTERNAL CONTROL DEVICE SETUP

- 24 RS-232C Setup
- 24 Type of connector; D-Sub 9-Pin Male
- 24 RS-232C Configurations
- 25 Communication Parameters
- 25 Command reference list
- 26 Transmission / Receiving Protocol

🛕 WARNING

• If you ignore the warning message, you may be seriously injured or there is a possibility of accident or death.

• If you ignore the caution message, you may be slightly injured or the product may be damaged.

• The note helps you understand and use the product safely. Please read the note carefully before using the product.

LICENSES

Supported licenses may differ by model. For more information about licenses, visit www.lg.com.



Manufactured under license from Dolby Laboratories. "Dolby" and the double-D symbol are trademarks of Dolby Laboratories.



The terms HDMI and HDMI High-Definition Multimedia interface, and the HDMI logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.



ABOUT DIVX VIDEO: DivX® is a digital video format created by DivX, LLC, a subsidiary of Rovi Corporation. This is an official DivX Certified® device that plays DivX video. Visit divx.com for more information and software tools to convert your files into DivX video.

ABOUT DIVX VIDEO-ON-DEMAND: This DivX Certified® device must be registered in order to play purchased DivX Video-on-Demand (VOD) movies. To obtain your registration code, locate the DivX VOD section in your device setup menu. Go to vod. divx.com for more information on how to complete your registration.

"DivX Certified® to play DivX® video up to HD 1080p, including premium content."

"DivX®, DivX Certified® and associated logos are trademarks of Rovi Corporation or its subsidiaries and are used under license."

Covered by one or more of the following U.S. patents : 7,295,673; 7,460,668; 7,515,710; 7,519,274

OPEN SOURCE SOFTWARE NOTICE

To obtain the source code under GPL, LGPL, MPL and other open source licenses, that is contained in this product, please visit *http://opensource.lge.com*.

In addition to the source code, all referred license terms, warranty disclaimers and copyright notices are available for download.

LG Electronics will also provide open source code to you on CD-ROM for a charge covering the cost of performing such distribution (such as the cost of media, shipping and handling) upon email request to opensource@lge.com. This offer is valid for three (3) years from the date on which you purchased the product.

- Image shown may differ from your TV.
- Your TV's OSD (On Screen Display) may differ slightly from that shown in this manual.
- The available menus and options may differ from the input source or product model that you are using.
- New features may be added to this TV in the future.
- The TV can be placed in standby mode in order to reduce the power consumption. And the TV should be turned off if it will not be watched for some time, as this will reduce energy consumption.
- The energy consumed during use can be significantly reduced if the level of brightness of the picture is reduced, and this will reduce the overall running cost.

INSTALLATION PROCEDURE

- 1 Open the package and make sure all the accessories are included.
- 2 Attach the stand to the TV set.
- 3 Connect an external device to the TV set.


ASSEMBLING AND PREPARING

Unpacking

Check your product box for the following items. If there are any missing accessories, contact the local dealer where you purchased your product. The illustrations in this manual may differ from the actual product and item.

- Do not use any unapproved items to ensure the safety and product life span.
- Any damages or injuries by using unapproved items are not covered by the manufacturer's warranty.
- Some models have a thin film attached on to the screen and this must not be removed.

- The items supplied with your product may vary depending on the model.
- Product specifications or contents of this manual may be changed without prior notice due to upgrade of product functions.
- For an optimal connection, HDMI cables and USB devices should have bezels less than 10 mm thick and 18 mm width. Use an extension cable that supports USB 2.0 if the USB cable or USB memory stick does not fit into your TV's USB port.







Power Cord holder (Only 32/37/42/47LT36**) (See p. 14)




Isolator (Depending on model) (See p. 6)



DC Adapter (Only 22/26LT36**) (See p. 15)

- Antenna Isolator Installation Guide
 - Use this to install TV in a place where there is a voltage difference between TV Set and GND of antenna signal.
 - » If there is a voltage difference between TV Set and GND of antenna signal, the antenna contact might be heated and excessive heat might cause an accident.
 - You can improve the safety when watching TV by efficiently removing power voltage from TV antenna. It is recommended to mount the isolator to the wall. If it cannot be mounted to the wall, mount it on the TV. Avoid disconnecting the antenna Isolator after installation.
 - Before starting, be sure that the TV antenna is connected.




Connect one end of the isolator to cable/antenna jack and the other to TV set or set-top box.

"Equipment connected to the protective earthing of the building installation through the mains connection or through other equipment with a connection to protective earthing - and to a cable distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a cable distribution system has therefore to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11)"

When applying the RF Isolator, a slight loss of signal sensitivity can occur.

Parts and buttons



Button	Description	
ν ^	Scrolls through the saved programmes.	
- +	Adjusts the volume level.	
<u>ዓ</u>	Turns the power on or off.	


Lifting and moving the TV

When moving or lifting the TV, read the following to prevent the TV from being scratched or damaged and for safe transportation regardless of its type and size.

- Avoid touching the screen at all times, as this may result in damage to the screen.
- It is recommended to move the TV in the box or packing material that the TV originally came in.
- Before moving or lifting the TV, disconnect the power cord and all cables.
- When holding the TV, the screen should face away from you to avoid damage.



• Hold the top and bottom of the TV frame firmly. Make sure not to hold the transparent part, speaker, or speaker grill area.



- When transporting a large TV, there should be at least 2 people.
- When transporting the TV by hand, hold the TV as shown in the following illustration.




- When transporting the TV, do not expose the TV to jolts or excessive vibration.
- When transporting the TV, keep the TV upright, never turn the TV on its side or tilt towards the left or right.
- Do not apply excessive pressure to cause flexing/ bending of frame chassis as it may damage screen.


Setting up the TV


Image shown may differ from your TV.

Attaching the stand

(Only 22/26LT360C, 22LT361C, 22/26LT365H)









M4 x 16

2 EA

(Only 32/37/42/47LT360C)






- When attaching the stand to the TV set, place the screen facing down on a cushioned table or flat surface to protect the screen from scratches.
- Make sure that the screws are fastened completely. (If they are not fastened securely enough, the TV may tilt forward after being installed.)


Do not fasten the screws with excessive force otherwise they may be worn out and become loose.

• Remove the stand before installing the TV on a wall mount by performing the stand attachment in reverse.



Mounting on a table

- 1 Lift and tilt the TV into its upright position on a table.
 - Leave a 10 cm (minimum) space from the wall for proper ventilation.




2 Connect the power cord to a wall outlet.

 Do not place the TV near or on sources of heat, as this may result in fire or other damage.

Attaching the TV to a table

Image shown may differ from your TV. The TV must be attached to desk so it cannot be pulled in a forward/backward direction, potentially causing injury or damaging the product. (Only 32/37/42/47LT360C)




Screws: M5 x L (*L: Table depth + 8-10 mm) ex) Table depth: 15 mm, Screw: M5 x 25

Securing the TV to a table

Fix the TV to a table to prevent from tilting forward, damage, and potential injury.


To secure the TV to a table, insert and tighten the supplied screw on the rear of the stand. (Only 32/37/42/47LT360C)



• To prevent TV from falling over, the TV should be securely attached to the floor/wall per installation instructions. Tipping, shaking, or rocking the TV may cause injury.

Adjusting the angle of the TV to suit view


Swivel 90 degrees to the left or right and adjust the angle of the TV to suit your view. (Only LT360C, LT361C, LT365H)



- When adjusting the angle of the product, watch out for your fingers.
- » Personal injury may occur if hands or fingers are pinched. If the product is tilted too much, it may fall, causing damage or injury.

Securing the TV to a wall

(This feature is not available for all models.)



- 1 Insert and tighten the eye-bolts, or TV brackets and bolts on the back of the TV.
 - If there are bolts inserted at the eye-bolts position, remove the bolts first.
- 2 Mount the wall brackets with the bolts to the wall.

Match the location of the wall bracket and the eye-bolts on the rear of the TV.

3 Connect the eye-bolts and wall brackets tightly with a sturdy rope.

Make sure to keep the rope horizontal with the flat surface.

 Make sure that children do not climb on or hang on the TV.


- Use a platform or cabinet that is strong and large enough to support the TV securely.
- Brackets, bolts and ropes are not provided. You can obtain additional accessories from your local dealer.

- If a television is not positioned in a sufficiently stable location, it can be potentially hazardous due to falling. Many injuries, particularly to children, can be avoided by taking simple precautions such as:
 - » Using cabinets or stands recommended by the manufacturer of the television.
 - » Only using furniture that can safely support the television.
 - » Ensuring the television is not overhanging the edge of the supporting furniture.
 - » Not placing the television on tall furniture (for example, cupboards or bookcases) without anchoring both the furniture and the television to a suitable support.
 - » Not standing the televisions on cloth or other materials placed between the television and supporting furniture.
 - » Educating children about the dangers of climbing on furniture to reach the television or its controls.

Mounting on a wall

Attach an optional wall mount bracket at the rear of the TV carefully and install the wall mount bracket on a solid wall perpendicular to the floor. When you attach the TV to other building materials, please contact qualified personnel.


LG recommends that wall mounting be performed by a qualified professional installer.



Make sure to use screws and wall mount bracket that meet the VESA standard. Standard dimensions for the wall mount kits are described in the following table.

Separate purchase (Wall Mounting Bracket)

Model	22LT36**	32LT36**
	26LT36**	
VESA	100 x 100	200 x 100
Standard screw	M4	M4
Number of	4	4
screws		
Wall mount	LSW100B(G)	
bracket		
Model	37/42LT36**	
VESA	200 x 200	
Standard screw	M6	
Number of	4	
screws		
Wall mount	LSW200B(G)	LSW220BX
bracket		
Model	47LT36**	
VESA	400 x 400	
Standard screw	M6	
Number of screws	4	
Wall mount	LSW420BX	
bracket	- 190: : : : : : : : : : : : : : : : : : :	



- Disconnect the power first, and then move or install the TV. Otherwise electric shock may occur.
- If you install the TV on a ceiling or slanted wall, it may fall and result in severe injury. Use an authorized LG wall mount and contact the local dealer or qualified personnel.
- Do not over tighten the screws as this may cause damage to the TV and void your warranty.
- Use the screws and wall mount that meet the VESA standard. Any damages or injuries by misuse or using an improper accessory are not covered by the manufacturer's warranty.
- On the 47LT**** models, use M6 x 51 screws.
- If you use the wall mounting bracket, do not fix screw into holes for assembling the stand.


- Use the screws that are listed on the VESA standard screw specifications.
- The wall mount kit includes an installation manual and necessary parts.
- The wall mount bracket is not provided. You can obtain additional accessories from your local dealer.
- The length of screws may differ depending on the wall mount. Make sure to use the proper length.
- For more information, refer to the manual supplied with the wall mount.

Not using the desk-type stand

Image shown may differ from your TV. When installing the wall-mounted unit, use the protection cover.

Insert the **Protection cover** into the TV until clicking sound.


(Only 32/37/42/47LT36**)



Tidying cables


(Only 32/37/42/47LT36**)

 Install the Power Cord Holder and Power Cord. It will help prevent the power cable from being removed by accident.




Power Cord Holder

2 Gather and bind the cables with the cable holder.



(Only 22/26LT36**)

1 Gather and bind the cables with the cable holder.



• Do not move the TV by holding the Cable Holder and Power Cord Holder, as the Cable holders may break, and injuries and damage to the TV may occur.

MAKING CONNECTIONS

This section on **MAKING CONNECTIONS** mainly uses diagrams for the LT36** models.


Connect various external devices to the TV and switch input modes to select an external device. For more information of external device's connection, refer to the manual provided with each device.

Available external devices are: HD receivers, DVD players, VCRs, audio systems, USB storage devices, PC, gaming devices, and other external devices.

- The external device connection may differ from the model.
- Connect external devices to the TV regardless of the order of the TV port.
- If you record a TV program on a DVD recorder or VCR, make sure to connect the TV signal input cable to the TV through a DVD recorder or VCR. For more information of recording, refer to the manual provided with the connected device.
- Refer to the external equipment's manual for operating instructions.
- If you connect a gaming device to the TV, use the cable supplied with the gaming device.
- In PC mode, there may be noise associated with the resolution, vertical pattern, contrast or brightness. If noise is present, change the PC output to another resolution, change the refresh rate to another rate or adjust the brightness and contrast on the PICTURE menu until the picture is clear.
- In PC mode, some resolution settings may not work properly depending on the graphics card.

Adapter connection

(Only 22/26LT36**)




DC Adapter

- 1 Connect the antenna cable to the antenna input port on the TV.
- 2 Connect the DC adapter plug to the power input jack on the TV.
- 3 Connect the power cord to the DC adapter first, then plug the power cord into the wall power outlet.


External speaker out

Connecting External Speaker.



Antenna connection


Connect the TV to a wall antenna socket with an RF cable (75 Ω).



- Use a signal splitter to use more than 2 TVs.
- If the image quality is poor, install a signal amplifier properly to improve the image quality.
- If the image quality is poor with an antenna connected, try to realign the antenna in the correct direction.
- An antenna cable and converter are not supplied.
- Supported DTV Audio: MPEG, Dolby Digital, Dolby Digital Plus, HE-AAC

HDMI connection

Transmits the digital video and audio signals from your PC to the TV. Connect the PC and the TV with the HDMI cable as shown. Choose any HDMI input port to connect. It does not matter which port you use.




DVD/ Blu-Ray / HD Cable Box / HD STB / PC

- It is recommended to use the TV with the HDMI connection for the best image quality.
- Use the latest High Speed HDMI[™] Cable with CEC (Customer Electronics Control) function.
- High Speed HDMI[™] Cables are tested to carry an HD signal up to 1080p and higher.
- Supported HDMI Audio format : Dolby Digital, PCM (Up to 192 KHz, 32 KHz/44.1 KHz/48 KHz/88 KHz/96 KHz/176 KHz/192 KHz, DTS Not supported.)

DVI to HDMI connection

Transmits the digital video signal from an external device to the TV. Connect the external device and the TV with the DVI-HDMI cable as shown. To transmit an audio signal, connect an audio cable. Choose any HDMI input port to connect. It does not matter which port you use.




DVD/ Blu-Ray / HD Cable Box / PC

• Depending on the graphics card, DOS mo

 Depending on the graphics card, DOS mode may not work if a HDMI to DVI Cable is in use.

Composite connection


Transmits analog video and audio signals from an external device to the TV. Connect the external device and the TV with the composite cable as shown.



VCR / DVD / Blu-Ray / HD Cable Box


RGB-PC connection

Transmits the video signal from PC to the TV. To transmit an audio signal, connect an audio cable.



USB connection

Connect a USB storage device such as s USB flash memory, external hard drive or a USB memory card reader to the TV and access the My media menu to use various multimedia files.



REMOTE CONTROL

The descriptions in this manual are based on the buttons on the remote control. Please read this manual carefully and use the TV correctly.

To replace batteries, open the battery cover, replace batteries (1.5 V AAA) matching the \oplus and \bigcirc ends to the label inside the compartment, and close the battery cover. To remove the batteries, perform the installation actions in reverse.



- Do not mix old and new batteries, as this may damage the remote control.
- In Analogue TV and some countries, some remote control buttons may not work.

Make sure to point the remote control toward the remote control sensor on the TV.

ウ POWER Turns the TV on or off.	ENERGY POWER	
ENERGY SAVING Adjusts the brightness of the screen to reduce energy consumption.		EXIT Clears on-screen displays and return to TV viewing.
► TV/RAD Selects Radio, TV and DTV programme.		$+ \bigtriangleup -$ Adjusts the volume level.
GUIDE Shows programme guide.		FAV Accesses your favourite programme list.
INFOO Views the information of the current programme and screen.	7 8 9 UST 0 0/EN	SIMPLINK Accesses the AV devices connected with the HDMI cable through HDMI-CEC. Opens the SIMPLINK menu.
RATIO Resizes an image. INPUT	SETTINGS A QMENU	MUTE ≰ Mutes all sounds.
Changes the input source.		+ P – Scrolls through the saved programmes.
Number buttons Enters numbers.	EXIT	
LIST Accesses the saved programme list.		Moves to the previous or next screen.
Q.VIEW Returns to the previously viewed programme.		These access special functions in some menus. (: Red, : Green, : Yellow, : Blue)
SETTINGS Accesses the main menus.		Control buttons (■, ▶, Ⅱ, ◀, ▶) Controls the MY MEDIA menus, or
Q. MENU Accesses the quick menus.		the SIMPLINK compatible devices (USB,SIMPLINK).
Navigation buttons (up/down/left/right) Scrolls through menus or options.	1	SUBTITLE Recalls your preferred subtitle in digital
OK Selects menus or options and confirms your input.		mode. TELETEXT BUTTONS These buttons are used for teletext.

MAINTENANCE

Cleaning your TV

Clean your TV regularly to keep the best performance and to extend the product lifespan.



- · Make sure to turn the power off and disconnect the power cord and all other cables first.
- When the TV is left unattended and unused for a long time, disconnect the power cord from the wall outlet to prevent possible damage from lightning or power surges.

Screen, frame, cabinet and stand

- To remove dust or light dirt, wipe the surface with a dry, clean, and soft cloth.
- To remove major dirt, wipe the surface with a soft cloth dampened in clean water or a diluted mild detergent. Then wipe immediately with a dry cloth.

- Avoid touching the screen at all times, as this may result in damage to the screen.
- Do not push, rub, or hit the screen surface with your fingernail or a sharp object, as this may result in scratches and image distortions.
- Do not use any chemicals as this may damage the product.
- Do not spray liquid onto the surface. If water enters the TV, it may result in fire, electric shock, or malfunction.

Power cord

Remove the accumulated dust or dirt on the power cord regularly.

TROUBLESHOOTING

Problem	Solution
Cannot control the TV with the remote control.	 Check the remote control sensor on the product and try again. Check if there is any obstacle between the product and the remote control. Check if the batteries are still working and properly installed (⊕ to ⊕, ⊝ to ⊝).
No image display and no sound is produced.	 Check if the product is turned on. Check if the power cord is connected to a wall outlet. Check if there is a problem in the wall outlet by connecting other products.
The TV turns off suddenly.	 Check the power control settings. The power supply may be interrupted. Check if the Auto sleep feature is activated in the Time settings.
When connecting to the PC (RGB/ HDMI DVI), 'No signal' or 'Invalid Format' is displayed.	 Turn the TV off/on using the remote control. Reconnect the RGB/HDMI cable. Restart the PC with the TV on.

SPECIFICATIONS

Product specifications may be changed without prior notice due to upgrade of product functions. For the power supply and power consumption, refer to the label attached to the product.

		22LT360C 22LT361C 22LT365H	26LT360C 26LT365H	32LT360C
K	IODELS	22LT360C-TA 22LT361C-TA 22LT365H-TA	26LT360C-TA 26LT365H-TA	32LT360C-TA
Dimensions	With stand (mm)	516.6 x 385.7 x 192.0	625.9 x 453.5 x 192.0	765.6 x 535.6 x 231.9
(W x H x D)	Without stand (mm)	516.6 x 332.2 x 41.6	625.9 x 393.2 x 46.6	765.6 x 475.8 x 68.5
Weight	With stand (kg)	3.7	4.7	9.2
	Without stand (kg)	3.1	4.1	8.0
Dowo	r roquiromont	DC 24 V, 1.4 A	DC 24 V, 1.8 A	AC 100-240 V~ 50 / 60
Powe	r requirement	AC-DC adaptor : 24 V , 2.	5 A / AC 100-240 V~ 50 / 60 Hz	Hz
	IODELS	37LT360C	42LT360C	47LT360C
I. I.	IODELS	37LT360C-TA	42LT360C-TA	47LT360C-TA
Dimensions	With stand (mm)	867.3 x 592.8 x 231.9	991.7 x 666.5 x 273.1	1101.0 x 728.5 x 273.1
(W x H x D)	Without stand (mm)	867.3 x 532.8 x 68.6	991.7 x 604.0 x 55.0	1101.0 x 665.4 x 54.5
Weight	With stand (kg)	11.2	15.5	17.3
	Without stand (kg)	10.0	13.5	15.3
Powe	r requirement	AC 100-240 V~ 50 / 60 Hz	AC 100-240 V~ 50 / 60 Hz	AC 100-240 V~ 50 / 60 Hz
		26LT36WC	32LT36WC	
N	IODELS	26LT36WC-TA	32LT36WC-TA	
Dimensions Without stand (mm) (W x H x D)		625.9 x 393.2 x 46.6	765.6 x 475.8 x 68.5	
Weight Without stand (kg)		4.1	8.0	
Power requirement		DC 24 V, 1.8 A		
		AC-DC adaptor : 24 V, 2.5 A / AC 100-240 V~ 50 / 60 Hz	AC 100-240 V~ 50 / 60 Hz	

	Operation Temperature	0 °C to 40 °C
	Operation Humidity	Less than 80 %
Environment condition	Storage Temperature	-20 °C to 60 °C
	Storage Humidity	Less than 85 %

		Digital TV	Analogue TV
New Zealand,	Television System	DVB-T	PAL/SECAM-B/G/D/K, PAL-I
Singapore	Programme Coverage	UHF 21 to 69	BG : VHF/UHF 1 to 69, CATV 01 to 47 I : VHF/UHF 1 to 69, CATV 01 to 47 DK : VHF/UHF 1 to 69, CATV 01 to 47
Australia	Television System	DVB-T	PAL B/B
	Programme Coverage	VHF 06 to 12, UHF 27 to 69	B/B : VHF/UHF 0 to 75, CATV : 2 to 44
Indonesia,	Television System	DVB-T	PAL/SECAM-B/G/D/K, PAL-I, NTSC-M
Israel, Myanmar, Sri Lanka	Programme Coverage	UHF 21 to 69	BG : VHF/UHF 1 to 69, CATV 01 to 47 I : VHF/UHF 1 to 69, CATV 01 to 47 DK : VHF/UHF 1 to 69, CATV 01 to 47 M : VHF/UHF 2 to 78, CATV 01 to 71
Vietnam,	Television System	DVB-T	PAL/SECAM-B/G/D/K, PAL-I, NTSC-M
Malaysia	Programme Coverage	VHF 6 to 12, UHF 21 to 69	BG : VHF/UHF 1 to 69, CATV 01 to 47 I : VHF/UHF 1 to 69, CATV 01 to 47 DK : VHF/UHF 1 to 69, CATV 01 to 47 M : VHF/UHF 2 to 78, CATV 01 to 71
Iran, Algeria,	Television System	DVB-T	PAL/SECAM-B/G/D/K, PAL-I, NTSC-M
Tunisia, Digital model	Programme Coverage	VHF 5 to 12, UHF 21 to 69	BG : VHF/UHF 1 to 69, CATV 01 to 47 I : VHF/UHF 1 to 69, CATV 01 to 47 DK : VHF/UHF 1 to 69, CATV 01 to 47 M : VHF/UHF 2 to 78, CATV 01 to 71
Analogue model,	Television System	-	PAL/SECAM-B/G/D/K, PAL-I, NTSC-M
India, Thailand, South Africa	Programme Coverage	-	BG : VHF/UHF 1 to 69, CATV 01 to 47 I : VHF/UHF 1 to 69, CATV 01 to 47 DK : VHF/UHF 1 to 69, CATV 01 to 47 M : VHF/UHF 2 to 78, CATV 01 to 71
	External Antenna Impedance	75 Ω	75 Ω

HDMI/DVI-DTV supported mode

Resolution	Horizontal Frequency (kHz)	Vertical Frequency (Hz)
720x480	31.469 31.5	59.94 60
720x576	31.25	50
1280x720	37.5 44.96 45	50 59.94 60
1920x1080	$\begin{array}{c} 33.72\\ 33.75\\ 28.125\\ 26.97\\ 27\\ 33.716\\ 33.75\\ 56.25\\ 67.43\\ 67.5\\ \end{array}$	59.94 60 50 23.97 24 29.976 30.00 50 59.94 60

RGB-PC, HDMI/DVI-PC supported mode

Resolution Horizonta Frequency (k		Vertical Frequency (Hz)
720x400	31.468	70.08
640x480	31.469	59.94
800x600	37.879	60.31
1024x768	48.363	60.00
1280x720	45	60
1280x768	47.78	59.87
1360x768	47.72	59.80
1280x1024	63.981	60.02
1920x1080 (RGB-PC)	66.587	59.93
1920x1080 (HDMI-PC)	67.5	60.00

-(Only 37/42/47LT36**)

IR CODES

• This feature is not available for all models.

Code (Hexa)	Function	Note
08	凸 (POWER)	Remote control Button (Power On/Off)
95	ENERGY SAVING	Remote control Button
0B	INPUT	Remote control Button
F0	TV/RAD	Remote control Button
10-19	Number Key 0-9	Remote control Button
53	LIST	Remote control Button
1A	Q.VIEW	Remote control Button
02	⊿ +	Remote control Button
03	⊿ -	Remote control Button
1E	FAV	Remote control Button
09	MUTE	Remote control Button
00	P+	Remote control Button
01	P-	Remote control Button
43	SETTINGS	Remote control Button
AB	GUIDE	Remote control Button
45	Q.MENU	Remote control Button
28	う (BACK)	Remote control Button
AA	INFO	Remote control Button
5B	EXIT	Remote control Button
44	ОК	Remote control Button
40	^	Remote control Button
41	V	Remote control Button
07	<	Remote control Button
06	>	Remote control Button
72	RED	Remote control Button
71	GREEN	Remote control Button
63	YELLOW	Remote control Button
61	BLUE	Remote control Button
20	TEXT	Remote control Button
21	T.OPT(T.Option)	Remote control Button
39	SUBTITLE	Remote control Button
B1		Remote control Button
B0	•	Remote control Button
BA	11	Remote control Button
8E		Remote control Button
8F	44	Remote control Button
7E	SIMPLINK	Remote control Button
79	RATIO	Remote control Button


EXTERNAL CONTROL DEVICE SETUP

RS-232C Setup


Connect the RS-232C (serial port) input jack to an external control device (such as a computer or an A/V control system) to control the product's functions externally.

Connect the serial port of the control device to the RS-232C jack on the product back panel.

Note: RS-232C connection cables are not supplied with the product.




Type of connector; D-Sub 9-Pin Male



No.	Pin name		
1	3.5V		
2	RXD (Receive data)		
3	TXD (Transmit data)		
4	IR OUT from TV		
5	GND		
6	No Connection		
7	No Connection		
8	No Connection		
9	No Connection (12V available in some models)		

RS-232C Configurations



	PC	TV	
RXD TXD GND DTR DSR RTS CTS	2 •	 3 2 5 6 4 7 8 	TXD RXD GND DTR DSR RTS CTS
	D-Sub 9	D-Sub 9	

Set ID

Set ID number. "Real Data Mapping" on See p.30

- 1 Press **SETTINGS** to access the main menus.
- 2 Press the Navigation buttons to scroll to OPTION and press OK.
- 3 Press the Navigation buttons to scroll to SET ID and press OK.
- 4 Scroll left or right to select a set ID number and select **CLOSE**. The adjustment range is 1-99.
- 5 When you are finished, press EXIT.

ENGLISH

- **Communication Parameters**
 - Baud rate: 9600 bps (UART)
 - Data length: 8 bits
 - Parity : None

- Stop bit: 1 bit
- Communication code: ASCII code
- Use a crossed (reverse) cable.

Command reference list

(Depending on model)

	COMMAND1	COMMAND2	DATA (Hexadeci- mal)		COMMAND1	COMMAND2	DATA (Hexadeci- mal)
01. Power	k	а	00 to 01	13. Treble	k	r	00 to 64
02. Aspect Ratio	k	с	(See p.27)	14. Bass	k	s	00 to 64
03. Screen Mute	k	d	(See p.27)	15. Balance	k	t	00 to 64
04. Volume Mute	k	е	00 to 01	16. Colour Temperature	x	u	00 to 64
05. Volume Control	k	f	00 to 64	17. Energy Saving	j	q	00 to 05
06. Contrast	k	g	00 to 64	18. Auto Configuration	j	u	01
07. Brightness	k	h	00 to 64	19. Tune Command	m	а	(See p.29)
08. Colour	k	i	00 to 64	20. Proramme Add/Skip	m	b	00 to 01
09. Tint	k	j	00 to 64	21. Key	m	с	Key Code
10. Sharpness	k	k	00 to 64	22. Control Back Light	m	g	00 to 64
11. OSD Select	k	I	00 to 01	23. Input select (Main)	х	b	(See p.30)
12. Remote Control Lock Mode	k	m	00 to 01				

• * Note : During USB operations such as DivX or EMF, all commands except Power(ka) and Key(mc) are not executed and treated as NG.

Transmission / Receiving Protocol

Transmission

[Command1][Command2][][Set ID][][Data][Cr]

[Command 1]	: First command to control the TV.(j, k, m or x)
[Command 2]	: Second command to control the TV.
[Set ID]	 You can adjust the set ID to choose desired monitor ID number in option menu. Adjustment range is 1 to 99. When selecting Set ID '0', every connected set is controlled. Set ID is indicated as decimal (1 to 99) on menu and as Hexa decimal (0x0 to 0x63) on transmission/receiving protocol.
[DATA]	: To transmit command data. Transmit 'FF' data to read status of command.
[Cr]	: Carriage Return ASCII code '0x0D'
[]	: ASCII code 'space (0x20)'

OK Acknowledgement

[Command2][][Set ID][][OK][Data][x]

* The set transmits ACK (acknowledgement) based on this format when receiving normal data. At this time, if the data is data read mode, it indicates present status data. If the data is data write mode, it returns the data of the PC computer.

Error Acknowledgement

[Command2][][Set ID][][NG][Data][x]

* The set transmits ACK (acknowledgement) based on this format when receiving abnormal data from non-viable functions or communication errors.

Data 00: Illegal Code

01. Power (Command: k a)

► To control Power On/Off of the set.

	Transmission[k][a][][Set ID][][Data][Cr]
Data	00 : Power Off	01 : Power On

Ack [a][][Set ID][][OK/NG][Data][x]

► To show Power On/Off.

Transmission [k][a][][Set ID][][FF][Cr]

Ack [a][][Set ID][][OK/NG][Data][x]

- * Similarly, if other functions transmit '0xFF' data based on this format, Acknowledgement data feed back presents status about each function.
- * OK Ack., Error Ack. and other message may display on the screen when TV is power On.

02. Aspect Ratio (Command: k c) (Main Picture Size)

► To adjust the screen format. (Main picture format) You can also adjust the screen format using the Aspect Ratio in the Q.MENU. or PICTURE menu.

Transmission [k][c][][Set ID][][Data][Cr]

Data	01	: Normal screen (4:3)	07 : 14:9 09 : Just Scan
	02	: Wide screen (16:9)	0B : Full Wide 10 to 1F:Cinema Zoom 1 to 16
	04	: Zoom	
	06	: Original	

Ack [c][][Set ID][][OK/NG][Data][x]

- * Using the PC input, you select either 16:9 or 4:3 screen aspect ratio.
- * In DTV/HDMI (1080i 50 Hz / 60 Hz, 720p 50Hz / 60 Hz, 1080p 24 Hz / 30 Hz / 50 Hz / 60 Hz), Component(720p, 1080i, 1080p 50 Hz / 60 Hz) mode, Just Scan is available.
- * Full Wide is supported only for DTV.

03. Screen Mute (Command: k d)

► To select screen mute on/off.

Transmission [k][d][][Set ID][][Data][Cr]

- Data 00: Screen mute off (Picture on)
 - Video mute off
 - 01: Screen mute on (Picture off)
 - 10: Video mute on

Ack [d][][Set ID][][OK/NG][Data][x]

* In case of video mute on only, TV will display On Screen Display(OSD). But, in case of Screen mute on, TV will not display OSD.

- 04. Volume Mute (Command: k e)
- To control volume mute on/off. You can also adjust mute using the MUTE button on remote control.

Transmission [k][e][][Set ID][][Data][Cr]

Data 00 : Volume mute on (Volume off) 01 : Volume mute off (Volume on)

Ack [e][][Set ID][][OK/NG][Data][x]

05. Volume Control (Command: k f)

To adjust volume. You can also adjust volume with the volume buttons on remote control.

Transmission [k][f][][Set ID][][Data][Cr]

Data Min : 00 to Max : 64 * Refer to 'Real data mapping'. See p.30.

Ack [f][][Set ID][][OK/NG][Data][x]

06. Contrast (Command: k g)

To adjust screen contrast.
 You can also adjust contrast in the PICTURE menu.

Transmission [k][g][][Set ID][][Data][Cr]

- Data Min : 00 to Max : 64
 - * Refer to 'Real data mapping'. See p.30.

Ack [g][][Set ID][][OK/NG][Data][x]

07. Brightness (Command: k h)

To adjust screen brightness. You can also adjust brightness in the PICTURE menu.

Transmission [k][h][][Set ID][][Data][Cr]

Data Min : 00 to Max : 64 * Refer to 'Real data mapping'. See p.30.

Ack [h][][Set ID][][OK/NG][Data][x]

08. Colour (Command: k i)

To adjust the screen colour.
 You can also adjust colour in the PICTURE menu.

Transmission [k][i][][Set ID][][Data][Cr]

- Data Min: 00 to Max: 64
 - * Refer to 'Real data mapping'. See p.30.

Ack [i][][Set ID][][OK/NG][Data][x]

- 09. Tint (Command: k j) 13. Treble (Command: k r) To adjust the screen tint. ► To adjust treble. You can also adjust tint in the PICTURE menu. You can also adjust treble in the AUDIO menu. Transmission [k][j][][Set ID][][Data][Cr] Data Red : 00 to Green : 64 Transmission [k][r][][Set ID][][Data][Cr] * Refer to 'Real data mapping'. See p.30. Data Min: 00 to Max: 64 * Refer to 'Real data mapping'. See p.30. Ack [j][][Set ID][][OK/NG][Data][x] Ack [r][][Set ID][][OK/NG][Data][x] 10. Sharpness (Command: k k) 14. Bass (Command: k s) To adjust the screen sharpness. You can also adjust sharpness in the PICTURE menu. To adjust bass. You can also adjust bass in the AUDIO menu. Transmission [k][k][][Set ID][][Data][Cr] Data Min: 00 to Max: 64 Transmission [k][s][][Set ID][][Data][Cr] * Refer to 'Real data mapping'. See p.30. Data Min: 00 to Max: 64 * Refer to 'Real data mapping'. See p.30. Ack [k][][Set ID][][OK/NG][Data][x] Ack [s][][Set ID][][OK/NG][Data][x] 15. Balance (Command: k t) 11. OSD Select (Command: k I) To select OSD (On Screen Display) on/off when controlling To adjust balance. remotely. You can also adjust balance in the AUDIO menu. Transmission [k][I][][Set ID][][Data][Cr] Transmission [k][t][][Set ID][][Data][Cr] Data 00 : OSD off 01 : OSD on
 - Data Min : 00 to Max : 64 * Refer to 'Real data mapping'. See p.30.

Ack [t][][Set ID][][OK/NG][Data][x]

- 12. Remote control lock mode (Command: k m)
- To lock the front panel controls on the monitor and remote control.

Transmission [k][m][][Set ID][][Data][Cr]

Ack [I][][Set ID][][OK/NG][Data][x]

Data 00 : Lock off

01 : Lock on

Ack [m][][Set ID][][OK/NG][Data][x]

- * If you are not using the remote control, use this mode. When main power is on/off, external control lock is released.
- * In the standby mode, if key lock is on, TV will not turn on by power on key of IR & Local Key.

- 16. Colour Temperature (Command: x u)
- To adjust colour temperature. You can also adjust Colour Temperature in the PICTURE menu.

Transmission [x][u][][Set ID][][Data][Cr]

Data Min : 00 to Max : 64 * Refer to 'Real data mapping'. See p.30.

Ack [u][][Set ID][][OK/NG][Data][x]

- 17. Energy Saving (Command: j q)
- ► To reduce the power consumption of the TV. You can also adjust Energy Saving in PICTURE menu.

Transmission [j][q][][Set ID][][Data][Cr]

Power Saving				Level					
Function							Description		
7	6	5	4		3	2	1	0	
0	0	0	0	Low Power	0	0	0	0	Off
0	0	0	0	Low Power	0	0	0	1	Minimum
0	0	0	0	Low Power	0	0	1	0	Medium
0	0	0	0	Low Power	0	0	1	1	Maximum
0	0	0	0	Low Power	0	1	0	1	Screen Off
0	0	0	0	Low Power	0	1	0	0	Auto

'Auto' is available in TV that supports 'Intelligent Sensor'

Ack [q][][Set ID][][OK/NG][Data][x]

- 18. Auto Configure(Command: j u)
- To adjust picture position and minimize image shaking automatically. It works only in RGB (PC) mode.

Transmission [j][u][][Set ID][][Data][Cr]

Data 01: To set

Ack [u][][Set ID][][OK/NG][Data][x]

- 19. Tune Command (Command: m a)
- Select channel to following physical number.

Transmission [m][a][][Set ID][][Data0][][Data1][][Data2][Cr]

Data00 : High channel data					
Data01 : Low channel data					
ex. No. 47 -> 00 2F (2FH)					
No. 394 -> 01 8A (18AH),					
DTV No. 0 -> Don't care					
Data02 : 0x00 : Analogue Main					
0x10 : DTV Main					
0x20 : Radio					

Channel data range Analogue - Min: 00 to Max: 63 (0 to 99) Digital - Min: 00 to Max: 3E7 (0 to 999)

Ack [a][][Set ID][][OK/NG][Data][x]

Data Min: 00 to Max: 7DH

20. Programme Add/Skip(Command: m b)

► To set skip status for the current Programme.

Transmission [m][b][][Set ID][][Data][Cr]

Data 00 : Skip 01 : Add

Ack [b][][Set ID][][OK/NG][Data][x]

- 21. Key(Command: m c)
- To send IR remote key code.

Transmission [m][c][][Set ID][][Data][Cr]

Data Key code - See p.23.

Ack [c][][Set ID][][OK/NG][Data][x]

22. Control Back Light(Command: m g)

► To control the back light.

Transmission [m][g][][Set ID][][Data][Cr] Data Min : 00 to Max : 64

Ack [g][][Set ID][][OK/NG][Data][x]


23. Input select (Command: x b)

(Main Picture Input)

► To select input source for main picture.

Transmission [x][b][][Set ID][][Data][Cr] Data Structure

Duid Olidot



	Externa	al Inpu	t	Data
0	0	0	0	DTV
0	0	0	1	Analogue
0	0	1	0	AV
0	1	0	0	Component
0	1	1	0	RGB
0	1	1	1	
1	0	0	0	HDMI
1	0	0	1	
1	0	1	0	

	Input N	lumbei	r	Data
0	0	0	0	Input1
0	0	0	1	Input2
0	0	1	0	Input3
0	0	1	1	Input4

Ack [b][][Set ID][][OK/NG][Data][x]

* Real data mapping					
00 :	Step 0				
:					
A :	Step 10 (Set ID 10)				
:					
F :	Step 15 (Set ID 15)				
10 :	Step 16 (Set ID 16)				
:					
64 :	Step 100				
:					
6E :	Step 110				
:					
73 :	Step 115				
74 :	Step 116				
:					
CF :	Step 199				
:					
FE :	Step 254				
FF :	Step 255				



Record the model number and serial number of the TV. Refer to the label on the back cover and quote this information to your dealer when requiring any service.

Model :_____

Serial No. : _____

(Only DTV)