

OWNER'S MANUAL

AIR **CONDITIONER**

Read this owner's manual thoroughly before operating the appliance and keep it handy for reference at all times.

Ελληνικά

()

TYPE: WALL MOUNTED

Original instruction

۲

EN	English
HU	Magyar
МТ	Malti
LT	Lietuvių
BS	Bosanski

BG Български RO Română GA Gaeilge Italiano

FR Français

IT

HR Hrvatski Slovenčina SK SR srpski ES Español

EL

	NL	Nederlands	PL	Polski
	cz	Čeština	ET	Eesti
а	SL	Slovenščina	LV	Latviešu
	MK	Македонски	SQ	Shqip
	DE	Deutsch	PT	Português
		_		



www.lg.com

(�)

MFL69780811 Rev.01 040819

Copyright © 2019 LG Electronics Inc. All Rights Reserved.

TABLE OF CONTENTS

()

This manual may contain images or content different from the model you purchased.

This manual is subject to revision by the manufacturer.

۲

SAFETY INSTRUCTIONS	
IMPORTANT SAFETY INSTRUCTIONS	4
OPERATION	11
Notes for Operation	11
Parts and Function	11
Wireless Remote Control	12
Restarting the Air Conditioner Automatically	16
Using the Mode Function	16
Using the Jet Mode Function	19
Using the Fan Speed Function	20
Using the Air Flow Direction Function	20
Setting the On/Off Timer	21
Using the Sleep Function	22
Using the Energy Saving Function	22
Using the Light Function	23
Using the Auto Clean Function	23
SMART FUNCTIONS	24
Using LG SmartThinQ Application (Optional)	24
MAINTENANCE	25
Clean the air filter	27
TROUBLESHOOTING	

SAFETY INSTRUCTIONS

The following safety guidelines are intended to prevent unforeseen risks or damage from unsafe or incorrect operation of the appliance.

The guidelines are separated into 'WARNING' and 'CAUTION' as described below.

۲

This symbol is displayed to indicate matters and operations that can cause risk. Read the part with this symbol carefully and follow the instructions in order to avoid risk.

WARNING

This indicates that the failure to follow the instructions can cause serious injury or death.

This indicates that the failure to follow the instructions can cause the minor injury or damage to the product.

The following symbols are displayed on indoor and outdoor units.

This symbol indicates that this appliance uses a flammable refrigerant. If the refrigerant is leaked and exposure to an external ignition source, there is a risk of fire.

This symbol indicates that the Operation Manual should be read carefully.

This symbol indicates that a service personnel should be handling this equipment with reference to the Installation Manual.

This symbol indicates that information is available such as the Operating Manual or Installation Manual.

 $(\mathbf{0})$

IMPORTANT SAFETY INSTRUCTIONS

To reduce the risk of explosion, fire, death, electric shock, injury or scalding to persons when using this product, follow basic precautions, including the following:

۲

Children in the Household

This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety. Children should be supervised to ensure that they do not play with the appliance.

For use in Europe:

This appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved. Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children without supervision.

Installation

4

- •Do not install the air conditioner on an unstable surface or in a place where there is danger of it falling.
- •Contact an authorized service center when installing or relocating the air conditioner.
- Install the panel and the cover of the control box safely.

EN

- •Do not install the air conditioner in a place where flammable liquids or gases such as gasoline, propane, paint thinner, etc., are stored.
- •Make sure that the pipe and the power cable connecting the indoor and outdoor units are not pulled too tight when installing the air conditioner.
- •Use standard circuit breaker and fuse that conform to the rating of the air conditioner.
- •Do not input air or gas into the system except with the specific refrigerant.
- •Use non-flammable gas (nitrogen) to check for leak and to purge air; using compressed air or flammable gas may cause fire or explosion.
- •The indoor/outdoor wiring connections must be secured tightly, and the cable should be routed properly so that there is no force pulling the cable from the connection terminals. Improper or loose connections can cause heat generation or fire.
- •Install dedicated electric outlet and circuit breaker before using the air conditioner.
- •Do not connect the ground wire to a gas pipe, a lightning rod, or a telephone ground wire.
- •Keep any required ventilation openings clear of obstruction.

Operation

- •Be sure to use only those parts listed in the service parts list. Never attempt to modify the equipment.
- •Make sure that children do not climb on or hit the outdoor unit.
- •Dispose of the batteries in a place where there is no danger of fire.
- •Use only the refrigerant specified on the air conditioner label.

•Cut off the power supply if there is any noise, smell, or smoke coming from the air conditioner. •Do not leave flammable substances such as gasoline, benzene, or thinner near the air conditioner •Contact an authorized service center when the air conditioner is submerged by flood waters. •Do not use the air conditioner for an extended period of time in a small place without proper ventilation. •In the event of a gas leak (such as Freon, propane gas, LP gas, etc.) ventilate sufficiently before using the air conditioner again. To clean the interior, contact an authorized service center or dealer. Using harsh detergents may cause corrosion or damage to the unit. •Be sure to ventilate sufficiently when the air conditioner and a heating appliance such as a heater are used simultaneously. •Do not block the inlet or outlet of air flow. •Do not insert hands or other objects through the air inlet or outlet while the air conditioner is operating. •Make sure that the power cable is neither dirty, loose, nor broken. •Never touch, operate, or repair the air conditioner with wet hands. •Do not place any objects on the power cable. •Do not place a heater or other heating appliances near the power cable •Do not modify or extend the power cable. Scratches or peeling insulation on the power cables may result in fire or electric shock, and should be replaced. •Cut off the power supply immediately in the event of a blackout or a thunderstorm.

۲

EN

- $igodoldsymbol{\Theta}$
- Take care to ensure that power cable could not be pulled out or damaged during operation.
- •Do not touch refrigerant pipe, water pipe and any internal parts while the unit is operating or immediately after operation.

Maintenance

- •Do not clean the appliance by spraying water directly onto the product.
- •Before cleaning or performing maintenance, disconnect the power supply and wait until the fan stops.

Technical Safety

- •Installation or repairs made by unauthorized persons can pose hazards to you and others.
- •Any person who is involved with working on or breaking into a refrigerant circuit should hold a current valid certificate from an industry-accredited assessment authority, which authorizes their competence to handle refrigerants safely in accordance with an industry recognized assessment specification.
- •Servicing shall only be performed as recommended by the equipment manufacturer. Maintenance and repair requiring the assistance of other skilled personnel shall be carried out under the supervision of the person competent in the use of flammable refrigerants.
- •The information contained in the manual is intended for use by a qualified service technician who is familiar with the safety procedures and equipped with the proper tools and test instruments.
- •Failure to read and follow all instructions in this manual can result in equipment malfunction, property damage, personal injury and/or death.

•The appliance shall be installed in accordance with national wiring regulations •When the power cord is to be replaced, the replacement work shall be performed by authorized personnel using only genuine replacement parts. This appliance must be properly grounded to minimize risk of electric shock. •Do not cut or remove the grounding prong from the power plug. •Attaching the earth wire to the power outlet cover screw does not ground the appliance unless the cover screw is metal, uninsulated, and the power outlet is grounded through house wiring. • If you have any doubt whether the air conditioner is properly grounded, have the power outlet and circuit checked by a qualified electrician. •The refrigerant and insulation blowing gas used in the appliance require special disposal procedures. Consult a service agent or a similarly qualified person before disposing of them. •If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly gualified person in order to avoid a hazard The appliance shall be stored in a well-ventilated area where the room size corresponds to the room area as specified for operation.

۲

- •The appliance shall be stored in a room without continuously operating open flames (for example an operating gas appliance) and ignition sources (for example an operating electric heater).
- •The appliance shall be stored so as to prevent mechanical damage from occurring.

EN

To reduce the risk of minor injury to persons, malfunction, or damage to the product or property when using this product, follow basic precautions, including the following:

۲

Installation

- •Do not install the air conditioner in an area where it is directly exposed to sea wind (salt spray).
- •Install the drain hose properly for the smooth drainage of water condensation.
- •Exercise caution when unpacking or installing the air conditioner.
- •Do not touch the leaking refrigerant during installation or repair.
- •Transport the air conditioner with two or more people or use a forklift.
- •Install the outdoor unit such that it is protected from direct sunlight. Do not place the indoor unit in a place where it is directly exposed to sunlight via the windows.
- •Safely dispose of packing materials such as screws, nails or batteries using proper packaging after installation or repair.
- •Install the air conditioner in a place where the noise from the outdoor unit or the exhaust fumes will not inconvenience the neighbors. Failure to do so may result in conflict with the neighbors.

Operation

•Remove the batteries if the remote control is not to be used for an extended period of time.

- EN
- •Make sure that the filter is installed before operating the air conditioner.
- •Be sure to check if there is a refrigerant leak after installing or repairing the air conditioner.
- •Do not place any object on the air conditioner.
- •Never mix different types of batteries, or old and new batteries for the remote control.

- •Do not let the air conditioner run for a long time when humidity is very high or when a door or a window has been left open.
- •Stop using the remote control if there is a fluid leak in the battery. If your clothes or skin are exposed to the leaking battery fluid, wash off with clean water.
- •Do not expose people, animals, or plants to the cold or hot wind from the air conditioner for extended periods of time.
- •If the leaking battery fluid has been swallowed, rinse the inside of the mouth thoroughly and consult a doctor.
- •Do not drink the water drained from the air conditioner.
- •Do not use the product for special purposes, such as preserving foods, works of art, and etc. It is an air conditioner for consumer purposes, not a precision refrigeration system. There is risk of damage or loss of property.
- •Do not recharge or disassemble the batteries.

Maintenance

- •Never touch the metal parts of the air conditioner when removing the air filter.
- •Use a sturdy stool or ladder when cleaning, maintaining, or repairing the air conditioner at a height.
- •Never use strong cleaning agents or solvents when cleaning the air conditioner or spray water. Use a smooth cloth.

OPERATION

Notes for Operation


Suggestion for Energy Saving

- Do not over-cool the space. This may be harmful for your health and may consume more electricity.
- Block sunlight with blinds or curtains while you are operating the air conditioner.
- · Keep doors or windows closed tightly while you are operating the air conditioner.
- · Adjust the direction of the air flow vertically or horizontally to circulate indoor air.
- Speed up the fan to cool or warm indoor air quickly, within a short period of time.
- Open windows regularly for ventilation. The indoor air quality may deteriorate if the air conditioner is used for long durations.
- Clean the air filter once every 2 weeks. Dust and impurities collected in the air filter may block the air flow or reduce the unit performance.

Parts and Function

Indoor Unit

Outdoor Unit



- The number and location of operation lamps may vary according to the model of the air conditioner.
- The feature may be changed according to the type of model.



EN

(�)

Wireless Remote Control

Inserting Batteries

If the display screen of the remote control begins to fade, replace the batteries. Insert AAA (1.5 V) batteries before using the remote control.

1 Remove the battery cover.



2 Insert the new batteries and make sure that the + and - terminals of the batteries are installed correctly.



Installing the Remote Control Holder

To protect the remote control, install the holder where there is no direct sunlight.

- 1 Choose a safe and easily accessible location.
- **2** Fix the holder by fastening 2 screws firmly with a screwdriver.



Operating Method

Point the remote control towards the signal receiver at the right side of the air conditioner to operate it.




- The remote control may operate other electronic devices if it is directed towards them. Make sure to point the remote control towards the air conditioner signal receiver.
- For proper operation, use a soft cloth to clean the signal transmitter and receiver.



(

Setting the Current Time

- 1 Press SEL TWEEP button and hold it about 3 seconds.
 - The icon below blinks at the bottom of the display screen.



- 2 Press vee or button to select the minutes.
- 3 Press SET/CLEAR button to finish.

NOTE

• The On/Off Timer is available after setting the current time.


Using the °C/°F Conversion Function (Optional)

This function changes unit between °C and °F

• Press and hold with button about 5 seconds.

Operating the Air Conditioner without the Remote Control

You can use the **ON/OFF** button of the indoor unit to operate the air conditioner when the remote control is unavailable.



ON/OFF button

- The stepping motor may be broken, if the horizontal vane opens rapidly.
- The fan speed is set to high.
- The feature may be changed according to the type of model.
- The temperature cannot be altered when using this emergency **ON/OFF** button.
- \bullet For cooling & heating models, the temperature is set from 22 °C to 24 °C

Using Wireless Remote Control


You can operate the air conditioner more conveniently with the remote control.

	Control panel	2 Display screen	Description
<u>````````````````````````````````````</u>	FAN	労	To select the fan mode.
<u> </u>	SLEEP ON OFF	ⓒ ON OFF	To turn on/off air conditioner automatically at desired time.
	TEMP	° 00 %	To adjust the desired room temperature in cooling, heating or auto changeover mode.
		-	To turn on/off the air conditioner.
I SLEEP ON OFF	FAN SPEED	۲۶۰۱	To adjust the fan speed.
		₩	To select the cooling mode.
		-ờ:-	To select the heating mode.
RESET	MODE	0	To select the dehumidification mode.
		(Al)	To select the auto changeover/auto operation mode.
	JET MODE	Po	To change room temperature quickly.
	SWING	渤 ///	To adjust the air flow direction vertically or horizontally.
	ROOM TEMP	①	To display the room temperature.
	°C / °F (5 s)	°C °F	To change unit between °C and °F
	A/CLEAN	[]	To remove moisture generated inside the indoor unit.
	E/SAVING	Ċ	To minimize power consumption.

۲

()

EN



 (\bullet)

Control panel	2 Display screen	Description
LIGHT	-	To set the brightness of the display on the indoor unit.
	-	To set/cancel the function and timer.
	-	To adjust time.
TIME (3 s)	-	To set the current time.
0	-	To initialize the remote control settings.

NOTE

• Some functions may not be supported, depending on the model.

۲

EN




Restarting the Air Conditioner Automatically

When the air conditioner is turned on again after a power failure, this function restores the previous settings.

Disabling Auto Restart

- Press the ON/OFF button and hold it for 6 seconds, then the unit will beep twice and the lamp will blink twice 4 times.
 - To re-enable the function, press the **ON**/ **OFF** button and hold it for 6 seconds. The unit will beep twice and the lamp will blink 4times.



ON/OFF button

NOTE


- The feature may be changed according to the type of model.
- If you press and hold the ON/OFF button for 3

 5 seconds, instead of 6 seconds, the unit will switch to the test operation. In the test operation, the unit blows out strong cooling air for 18 minutes and then returns to factory default settings.

Using the Mode Function

۲

This function allows you to select the desired function.



Cooling Mode

 $(\mathbf{0})$

- 1 Turn the appliance on.
- 2 Press MODE button repeatedly to select the Cooling Mode.
 - 🕌 is displayed on the display screen.



3 Press () or () button to set the desired temperature.

Auto Operation (Artificial Intelligence)

Cooling-only models

In this operation mode, the system is automatically operated by the electronic controls.

- 1 Turn the appliance on.
- 2 Press **MODE** button repeatedly to select the Auto Operation.
 - (AI) is displayed on the display screen.

	Code	Description
<u> </u>	2	Cold
C C	1	A little cold
AM [2:00	0	Maintain room temperature
	-1	A little hot
	-2	Hot

NOTE

 In this mode, you cannot adjust the fan speed, but you can set the air deflector to rotate automatically.

Auto Changeover Mode

Cooling & Heating Model

 \bigcirc

 (\mathbf{O})

This mode changes the mode automatically to maintain the set temperature at ± 2 °C

- 1 Turn the appliance on.
- 2 Press **MODE** button repeatedly to select the Auto Changeover Mode.
 - (AI) is displayed on the display screen.



- 3 Press () or () button to set the desired temperature.
- Press FAN SPEED button to adjust the fan speed.

(



 $(\mathbf{0})$

Dehumidification Mode

This mode removes excess moisture from a highly humid environment or during the rainy season, in order to prevent mildew from setting in. This mode adjusts the room temperature and the fan speed automatically to maintain the optimal level of humidity.

- **1** Turn the appliance on.
- 2 Press **MODE** button repeatedly to select the Dehumidification Mode.
 - 🛆 is displayed on the display screen.



NOTE

- In this mode you cannot adjust the room temperature, it is adjusted automatically.
- The room temperature is not displayed on the display screen.

Heating Mode

- 1 Turn the appliance on.
- 2 Press MODE button repeatedly to select the Heating Mode.

EN

(�)

• 🔆 is displayed on the display screen.



3 Press () or () button to set the desired temperature.



Fan Mode

This mode only circulates the indoor air without changing the room temperature.

- 1 Turn the appliance on.
- 2 Press FAN button.
 - 🖇 is displayed on the display screen.



3 Press FAN SPEED button to adjust the fan speed.

Using the Jet Mode Function

Changing Room Temperature Quickly

This function allows you to cool indoor air quickly during the summer or warm it quickly during winter.

- The Jet Mode function is available with Cooling, Heating and Dehumidification Mode.
- 1 Turn the appliance on.
- 2 Press **MODE** button repeatedly to select the desired mode.
- 3 Press JET MODE button.
 - **P** is displayed on the display screen.



NOTE

 $(\mathbf{0})$

- Jet Heating Mode is not available on some models.
- In Jet Cooling Mode, strong air blows out for 30 minutes.
- After 30 minutes later, setting temperature is maintaining 18 °C If you want to change the temperature, Press

 (\bullet) or (\bullet) button to set the desired temperature.

- In Jet Heating Mode, strong air blows out for 30 minutes.
- After 30 minutes later, setting temperature is maintaining 30 °C
 If you want to change the temperature, Press

 \bigcirc or \bigcirc button to set the desired temperature.

• This function may operate differently from the remote control display.

EN



(�)

Using the Fan Speed Function

Adjusting the Fan Speed

• Press FAN SPEED button repeatedly to adjust the fan speed.

Display Screen	Speed
به ا ا	High
ふ〓	Medium
क्ष	Low
ا لايا الاي	Natural Wind

Using the Air Flow Direction Function

This function adjusts the direction of the air flow vertically (horizontally).

- Press **SWING** button repeatedly and select the desired direction.
- Select in to adjust the direction of the air flow automatically.

NOTE

 $(\mathbf{\Phi})$

- Adjusting the air deflector arbitrarily may cause product failure.
- If you restart the air conditioner, it starts to operate with the previously set direction of air flow, so the air deflector may not match the icon displayed on the remote control.
 When this occurs, press SWING button to adjust the direction of the air flow again.
- This function may operate differently from the remote control display.



Setting the On/Off Timer

This function sets the air conditioner to turn on/ off automatically at desired time.

On/Off Timer can be set together.

Setting the ON Timer

- 1 Press ON button.
 - The icon below blinks at the bottom of the display screen.



- 2 Press v or button to select the minutes.
- 3 Press SET/CLEAR button to finish.
 - After setting the timer, current time and **ON** icon are displayed on the display screen indicating that the desired time is set.

Setting the OFF Timer

- 1 Press OFF button.
 - The icon below blinks at the bottom of the display screen.



- 3 Press SET/CLEAR button to finish.
 - After setting the timer, current time and OFF icon are displayed on the display screen indicating that the desired time is set.

Canceling the Timer Setting

- 1 Press ON(OFF) button.
 - ON (OFF) icon blinks at the bottom of the display screen.
- Press SET/CLEAR button to cancel the setting.

NOTE

• To cancel all timer settings, press SET/ CLEAR button. ΕN



Using the Sleep Function

This function turns off the air conditioner automatically when you go to sleep.

- 1 Turn the appliance on.
- 2 Press SLEEP button.
 - 😰 icon blinks at the bottom of the display screen.
- 3 Press or button to select the hour (up to 7 hours).
- 4 Press SET/CLEAR button to finish.

• 😭 is displayed on the display screen.

NOTE

- In the Cooling and Dehumidification Mode, the temperature increases by 1 °C after 30 minutes and additional 1 °C after another 30 minutes for a more comfortable sleep.
- The temperature increases up to 2 °C from the preset temperature.
- Although the remark for fan speed on the display screen may be changed, the fan speed is adjusted automatically.

Using the Energy Saving Function

This function minimizes power consumption during Cooling and increases the set temperature to the optimal level for a more comfortable environment. The temperature automatically settles at 22 °C if desired temperature is below 22 °C The temperature remains constant if it is above 22 °C

1 Turn the appliance on.

- 2 Press **MODE** button repeatedly to select the Cooling Mode.
- 3 Press E/SAVING button.
 - e is displayed on the display screen.

Using the Light Function

Display Screen Brightness

You can set the brightness of the indoor unit display screen.

۲

 (\mathbf{O})

• Press LIGHT button.

NOTE

• Turn on/off the Display screen.

Using the Auto Clean Function

In the Cooling and Dehumidification Mode, moisture is generated inside the indoor unit. This function removes such moisture.

- 1 Turn the appliance on.
- 2 Press Auto Clean button.
 □ s displayed on the display screen.

NOTE

- Some functions cannot be used while the Auto Clean function is in operation.
- If you turn off the unit, the fan continues to run for 30 minutes and cleans the inside of the indoor unit.

(4)

EN

SMART FUNCTIONS

()

 (\mathbf{O})

Using LG SmartThinQ Application (Optional)

Wi-Fi Function

Communicate with the appliance from a smart phone using the convenient smart features.

Smart Diagnosis™

If you use the Smart Diagnosis function, you will be provided with the useful information such as a correct way of using the appliance based on the pattern of use.

Settings

Allows you to set various options on the appliance and in the application.

NOTE

- If you change your wireless router, Internet service provider, or password, delete the registered appliance from the LG SmartThinQ application and register it again.
- The application is subject to change for appliance improvement purposes without notice to users.
- Functions may vary by model.

EN

(�)

MAINTENANCE


MARNING

• Before cleaning or performing maintenance, disconnect the power supply and wait until the fan stops.

۲

If the air conditioner will not be used for an extended period of time, dry the air conditioner to maintain it in best condition. Clean the product regularly to maintain optimal performance and to prevent possible breakdown.

- Dry the air conditioner in Fan mode for 3 to 4 hours and disconnect the power. There may be internal damage if moisture is left in its components.
- Before using the air conditioner again, dry the inner components of the air conditioner in Fan mode for 3 to 4 hours. This will help to remove the odor generated from moisture.



• The feature may be changed according to the type of model.

Туре	Description	Interval
Air filter	Clean with a vacuum or hand wash.	2 weeks
	Clean the Indoor unit surface by using a soft, dry cloth.	Regularly
Indoor unit	Have a professional clean the condensate drain pan.	Once a year
indoor unit	Have a professional clean the condensate drain pipe.	Every 4 months
	Replace the remote control batteries.	Once a year
	Have a professional clean the heat exchanger coils and the panel vents. (Consult with technician.)	Once a year
	Have a professional clean the fan.	Once a year
Outdoor unit	Have a professional clean the condensate drain pan.	Once a year
	Have a professional verify that all the fan assembly is firmly tightened.	Once a year
	Clean the electric components with air.	Once a year

NOTE

()

1

• Never use water that is higher than 40 °C when you clean the filters. It may cause deformation or discoloration.

۲

• Never use volatile substances when you clean the filters. They may damage the surface of the product.


EN



Clean the air filter

Clean the air filter once every 2 weeks or more if necessary.


- 1 Turn Off the power to the unit.
- 2 Pull out the upper section of front panel and lift it up.




3 Take out a filter with front panel held.



- 4 Clean the filter with a vacuum cleaner or with warm water. If dirt is difficult to remove, wash the filter in lukewarm water with neutral detergent.
- **5** Dry it completely in the shade after cleaning.
- 6 Then set a filter orderly.



7 Put the hook of front panel onto the hanger, in order to close the front panel.



- The air filter can be broken when it is bent.
- When the air filter is not assembled correctly, dust and other substances can enter into the indoor unit.
- If you do not hang the front cover correctly, it may result in having a gap between the front panel and the inner cover. If so, remove the front cover and refit it correctly.
- The feature can be changed according a type of model.

TROUBLESHOOTING

Self-diagnosis Function

This product has a built-in self-diagnosis function. If an error occurs, the lamp of the indoor unit will blink in 2 second intervals. If this occurs, contact your local dealer or service center.

۲

Before Calling for Service

Please check the following before you contact the service center. If the problem persists, contact your local service center.

Problem	Possible Causes	Corrective Action
The air conditioner does not work normally.	Burning smell and strange sounds are coming from the unit.	
	Water leaks from the indoor unit even when the humidity level is low.	 Turn off the air conditioner, switch OFF, or disconnect the power supply, and contact the service center.
	The power cable is damaged or it is generating excessive heat.	
	A switch, a circuit breaker (safety, ground), or a fuse is not operated properly.	
	The unit generates an error code from its self-diagnosis.	
The air conditioner does not work.	The air conditioner is unplugged.	• Check whether the power cord is plugged into the outlet or the power isolators are switched on.
	A fuse exploded, or the power supply is blocked.	 Replace the fuse or check if the circuit breaker has tripped.
	A power failure has occurred.	 Turn off the air conditioner when a power failure occurs. When the power is restored, wait 3 minutes, and then turn on the air conditioner.
	The voltage is too high or too low.	 Check if the circuit breaker has tripped.
	The air conditioner was turned off automatically at a preset time.	• Turn the air conditioner on.
	The battery setting in the remote controller is incorrect.	 Make sure that the batteries are inserted correctly in your remote controller. If the batteries are placed correctly, but the air conditioner still does not operate, replace the batteries and try again.

۲

۲

(4



Problem	Possible Causes	Corrective Action
	Air is not circulating properly.	Make sure that there are no curtains, blinds, or pieces of furniture blocking the front of the air conditioner.
	The air filter is dirty.	 Clean the air filter once every 2 weeks. See "Clean the Air Filter" for more information.
	The room temperature is too high.	 In summer, cooling the indoor air fully may take some time. In this case, select the Jet Mode to cool the indoor air quickly.
The air conditioner does not emit cool	Cold air is escaping from the room.	 Make sure that no cold air is escaping through the ventilation points in the room.
air.	The desired temperature is higher than the current temperature.	• Set the desired temperature to a level lower than the current temperature.
	There is a heating source nearby.	 Avoid using heat generators like electric ovens or gas burners while the air conditioner is in operation.
	Fan Mode is selected.	 During Fan Mode, air blows from the air conditioner without cooling or heating the indoor air. Switch the operation mode to cooling operation.
	Outside temperature is too high.	 The cooling effect may not be sufficient.
The fan speed cannot be adjusted.	The Jet Mode, or Auto Operation Mode is selected.	 In some operation modes, you cannot adjust the fan speed. Select an operation mode in which you can adjust the fan speed.
The temperature cannot be adjusted.	The Fan Mode or Jet Mode is selected.	 In some operation modes, you cannot adjust the temperature. Select an operation mode in which you can adjust the temperature.
The air conditioner stops during operation.	The air conditioner is suddenly turned off.	• The Timer Function may have timed out, which turns the unit off. Check the timer settings.
	A power failure has occurred during operation.	Wait for the power to come back. If you have the Auto Restart function enabled, your unit will resume its last operation several minutes after power is restored.

EN

Problem	Possible Causes	Corrective Action
The indoor unit is still operating even when the unit has been turned off.	The Auto Clean function is being operated.	• Allow the Auto Clean function to continue since it removes any remaining moisture inside the indoor unit. If you do not want this feature, you can turn the unit off.
The air outlet on the indoor unit is discharging mist.	The cooled air from the air conditioner makes mist.	When the room temperature decreases, this phenomenon will disappear.
Water leaks from the outdoor unit.	In the heating operations, condensed water drops from the heat exchanger.	• This symptom requires installing a drain hose under the base pan. Contact the installer.
There is noise or vibration.	A clicking sound can be heard when the unit starts or stops due to movement of the reversing valve. Creaking sound: The plastic parts of the indoor unit creak when they shrink or expand due to sudden temperature changes. Flowing or Blowing sound: This is the flow of refrigerant through the air conditioner.	• These are normal symptoms. The noise will stop.
The indoor unit gives off an odor.	Odors (such as cigarette smoke) may be absorbed into the indoor unit and discharged with airflow.	 If the smell does not disappear, you need to wash the filter. If this does not work, contact the service center to clean your heat exchanger.
	When Heating Mode starts, the vane is almost closed, and no air comes out, even though the outdoor unit is operating.	• This symptom is normal. Please wait until the unit has generated enough warm air to blow through the indoor unit.
The air conditioner does not emit warm air.	The outdoor unit is in Defrosting Mode.	 In Heating Mode, ice/frost is built up on the coils when the outside temperature falls. This function removes a layer of frost on the coil, and it should finish in approximately 15 minutes.
	Outside temperature is too low.	 The heating effect may not be sufficient.

EN

Problem	Possible Causes	Corrective Action
	The password for the Wi-Fi that you are trying to connect to is incorrect.	 Find the Wi-Fi network connected to your smartphone and remove it, then register your appliance on LG SmartThinQ.
	Mobile data for your smartphone is turned on.	• Turn off the Mobile data of your smartphone and register the appliance using the Wi-Fi network.
Your home appliance and smartphone is not connected to the Wi-Fi network.	The wireless network name (SSID) is set incorrectly.	• The wireless network name (SSID) should be a combination of English letters and numbers. (Do not use special characters.)
	The router frequency is not 2.4 GHz.	• Only a 2.4 GHz router frequency is supported. Set the wireless router to 2.4 GHz and connect the appliance to the wireless router. To check the router frequency, check with your Internet service provider or the router manufacturer.
	The distance between the appliance and the router is too far.	 If the distance between the appliance and the router is too far, the signal may be weak and the connection may not be configured correctly. Move the location of the router so that it is closer to the appliance.


۲



NOTE

• Some functions may not be supported, depending on the model.

EN





_____| |