



OWNER'S MANUAL

Please read this manual carefully before operating your set and retain it for future reference.

EC93**

FC97**

FG97**

3

LICENSES

TABLE OF CONTENTS

3	OPEN SOURCE SOFTWARE NOTICE
	INFORMATION

3 EXTERNAL CONTROL DEVICE SETUP

4	SAFFTY	INSTRII	CTIONS

9 - Viewing 3D Imaging

10 INSTALLATION PROCEDURE

10 ASSEMBLING AND PREPARING

- 10 Unpacking
- 12 Separate purchase
- 13 Parts and buttons
- 15 Using the joystick button
- 16 Lifting and moving the TV
- 17 Setting up the TV
- 17 Detaching the stand
- 18 Attaching the AV cover
- 18 Mounting on a table
- 19 Mounting on a wall
- 20 Wall Type Set-up Guide
- How to detach the stand
- 22 Tidying cables
- 24 Using Built-in Camera
- 24 Preparing Built-in Camera
- 25 Name of Parts of Built-in camera
- 25 Checking the Camera's Shooting Range

26 MAKING CONNECTIONS

- 26 Antenna connection
- 27 HDMI connection
- 29 DVI to HDMI connection
- 30 Component connection
- 31 Composite connection
- 31 Audio connection
- 31 Digital optical audio connection
- 32 Headphone connection
- 32 MHL connection
- 34 USB connection

35 MAGIC REMOTE FUNCTIONS

- 36 Registering Magic Remote
- 36 How to use magic remote
- 36 Precautions to Take when Using the Magic Remote

37 USING THE USER GUIDE

38 MAINTENANCE

- 38 Cleaning Your TV
 - Screen, frame, cabinet and stand
- 38 Power cord

38

38 TROUBLESHOOTING

39 SPECIFICATIONS



WARNING

 If you ignore the warning message, you may be seriously injured or there is a possibility of accident or death.



CAUTION

 If you ignore the caution message, you may be slightly injured or the product may be damaged.



NOTE

 The note helps you understand and use the product safely. Please read the note carefully before using the product.

LICENSES

Supported licenses may differ by model. For more information about licenses, visit www.lg.com.









OPEN SOURCE SOFTWARE NOTICE INFORMATION

To obtain the source code under GPL, LGPL, MPL, and other open source licenses, that is contained in this product, please visit http://opensource.lge.com.

In addition to the source code, all referred license terms, warranty disclaimers and copyright notices are available for download.

LG Electronics will also provide open source code to you on CD-ROM for a charge covering the cost of performing such distribution (such as the cost of media, shipping, and handling) upon email request to opensource@lge.com. This offer is valid for three (3) years from the date on which you purchased the product.

EXTERNAL CONTROL DEVICE SETUP

To obtain the external control device setup information, please visit www.lg.com.

SAFETY INSTRUCTIONS

Please read these safety precautions carefully before using the product.



WARNING

- Do not place the TV and/or remote control in the following environments:
 - A location exposed to direct sunlight
 - An area with high humidity such as a bathroom
 - Near any heat source such as stoves and other devices that produce heat
 - Near kitchen counters or humidifiers where they can easily be exposed to steam or oil
 - An area exposed to rain or wind
 - Near containers of water such as vases

Otherwise, this may result in fire, electric shock, malfunction or product deformation.



 Do not place the product where it might be exposed to dust.

This may cause a fire hazard.



 Mains Plug is the TV connecting/disconnecting device to AC mains electric supply. This plug must remain readily attached and operable when TV is in use.



Do not touch the power plug with wet hands. Additionally, if the cord pin is wet or covered with dust, dry the power plug completely or wipe dust off.
 You may be electrocuted due to excess moisture.



 Make sure to connect Mains cable to compliant AC mains socket with Grounded earth pin. (Except for devices which are not grounded on earth.) Otherwise possibility you may be electrocuted or injured.



 Insert power cable plug completely into wall socket otherwise if not secured completely into socket, fire ignition may break out.



 Ensure the power cord does not come into contact with hot objects such as a heater.
 This may cause a fire or an electric shock hazard.



 Do not place a heavy object, or the product itself, on power cables.

Otherwise, this may result in fire or electric shock.



 Bend antenna cable between inside and outside building to prevent rain from flowing in.
 This may cause water damaged inside the Product and could give an electric shock.



 When mounting TV onto wall make sure to neatly install and isolate cabling from rear of TV as to not create possibility of electric shock /fire hazard.



 Do not plug too many electrical devices into a single multiple electrical outlet.

Otherwise, this may result in fire due to overheating.

heating.



Do not drop the product or let it fall over when connecting external devices.

Otherwise, this may result in injury or damage to the product.

uct.

Keep the anti-moisture packing material or vinyl packing out of the reach of children.
 Anti-moisture material is harmful if swallowed. If swallowed by mistake, force the patient to vomit and visit the nearest hospital. Additionally, vinyl packing can cause suffocation. Keep it out of the reach of children.



Do not let your children climb or cling onto the TV.
 Otherwise, the TV may fall over, which may cause serious injury.



 Dispose of used batteries carefully to ensure that a small child does not consume them. Please seek Doctor- Medical Attention immediately if child consumes batteries.




 Do not insert any metal objects/conductors (like a metal chopstick/cutlery/screwdriver) between power cable plug and input Wall Socket while it is connected to the input terminal on the wall. Additionally, do not touch the power cable right after plugging into the wall input terminal. You may be electrocuted. (Depending on model)



 Do not put or store inflammable substances near the product. There is a danger of combustion/explosion or fire due to careless handling of the inflammable substances.



 Do not drop metallic objects such as coins, hair pins, chopsticks or wire into the product, or inflammable objects such as paper and matches. Children must pay particular attention. Electrical shock, fire or injury can occur. If a foreign object is dropped into the product, unplug the power cord and contact the service centre.





 Do not allow any impact, shock or any objects to fall into the unit, and do not drop anything onto the screen.

You may be injured or the product can be damaged.



 Never touch this product or antenna during a thunder or lighting storm.

You may be electrocuted.



 Never touch the wall outlet when there is leakage of gas, open the windows and ventilate.
 It may cause a fire or a burn by a spark.



 Do not disassemble, repair or modify the product at your own discretion.

Fire or electric shock accident can occur. Contact the service centre for check, calibration or repair.



- If any of the following occur, unplug the product immediately and contact your local service centre.
 - The product has been impacted by shock
 - The product has been damaged
 - Foreign objects have entered the product
 - The product produced smoke or a strange smell

This may result in fire or electric shock.



 Unplug the TV from AC mains wall socket if you do not intend to use the TV for a long period of time.
 Accumulated dust can cause fire hazard and insulation deterioration can cause electric leakage/shock/ fire



 Apparatus shall not be exposed to dripping or splashing and no objects filled with liquids, such as vases, shall be placed on the apparatus.





CAUTION

· Install the product where no radio wave occurs.



 There should be enough distance between an outside antenna and power lines to keep the former from touching the latter even when the antenna falls

This may cause an electric shock.



Do not install the product on places such as unstable shelves or inclined surfaces. Also avoid places where there is vibration or where the product cannot be fully supported. Otherwise, the product may fall or flip over, which may cause injury or damage to the product.

 If you install the TV on a stand, you need to take actions to prevent the product from overturning. Otherwise, the product may fall over, which may cause injury.



- If you intend to mount the product to a wall, attach VESA standard mounting interface (optional parts) to the back of the product. When you install the set to use the wall mounting bracket (optional parts), fix it carefully so as not to drop.
- Only use the attachments / accessories specified by the manufacturer.
- When installing the antenna, consult with a qualified service technician. If not installed by a qualified technician, this may create a fire hazard or an electric shock hazard.



 We recommend that you maintain a distance of at least 2 to 7 times the diagonal screen size when watching TV.

If you watch TV for a long period of time, this may cause blurred vision.



Only use the specified type of battery.
 This could cause damage to the remote control.



Do not mix new batteries with old batteries. This
may cause the batteries to overheat and leak.



Batteries should not be exposed to excessive heat.
 For example, keep away from direct Sunlight, open fireplace and electric heaters.

- Do not place non-rechargeable batteries in charging device.
- Make sure there are no objects between the remote control and its sensor.



 Signal from Remote Control can be interrupted due to external/internal lighting eg Sunlight, fluorescent lighting. If this occurs turn off lighting or darken viewing area.



 When connecting external devices such as video game consoles, make sure the connecting cables are long enough.

Otherwise, the product may fall over, which may cause injury or damage the product.



 Do not turn the product On/Off by plugging-in or unplugging the power plug to the wall outlet. (Do not use the power plug for switch.)

It may cause mechanical failure or could give an electric shock.



- Please follow the installation instructions below to prevent the product from overheating.
 - The distance between the product and the wall should be more than 10 cm.
 - Do not install the product in a place with no ventilation (e.g., on a bookshelf or in a cupboard).
 - Do not install the product on a carpet or cushion.
 - Make sure the air vent is not blocked by a tablecloth or curtain.

Otherwise, this may result in fire.



 Take care not to touch the ventilation openings when watching the TV for long periods as the ventilation openings may become hot. This does not affect the operation or performance of the product.



- Periodically examine the cord of your appliance, and if its appearance indicates damage or deterioration, unplug it, discontinue use of the appliance, and have the cord replaced with an exact replacement part by an authorized servicer.
- Prevent dust collecting on the power plug pins or outlet.

This may cause a fire hazard.



Protect the power cord from physical or mechanical abuse, such as being twisted, kinked, pinched, closed in a door, or walked upon. Pay particular attention to plugs, wall outlets, and the point where the cord exits the appliance.



 Do not press strongly upon the panel with a hand or sharp object such as nail, pencil or pen, or make a scratch on it, as it may cause damage to screen.



 Avoid touching the screen or holding your finger(s) against it for long periods of time. Doing so may produce some temporary or permanent distortion/ damage to screen.



When cleaning the product and its components, unplug the power first and wipe it with a soft cloth. Applying excessive force may cause scratches or discolouration. Do not spray with water or wipe with a wet cloth. Never use glass cleaner, car or industrial shiner, abrasives or wax, benzene, alcohol etc., which can damage the product and its panel. Otherwise, this may result in fire, electric shock or product damage (deformation, corrosion or breakage).

000

As long as this unit is connected to the AC wall outlet, it is not disconnected from the AC power source even if you turn off this unit by SWITCH.

When unplugging the cable, grab the plug and unplug it, by pulling at the plug. Don't pull at the cord to unplug the power cord from the power board, as this could be hazardous.



 When moving the product, make sure you turn the power off first. Then, unplug the power cables, antenna cables and all connecting cables.
 The TV set or power cord may be damaged, which may create a fire hazard or cause electric shock.



 When moving or unpacking the product, work in pairs because the product is heavy.
 Otherwise, this may result in injury.



 Contact the service centre once a year to clean the internal parts of the product.
 Accumulated dust can cause mechanical failure.



 Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.



 If the product feels cold to the touch, there may be a small "flicker" when it is turned on. This is normal, there is nothing wrong with product.



 The panel is a high technology display product with resolution of two million to six million pixels. You may see tiny black dots and/or brightly coloured dots (red, blue or green) at a size of 1 ppm on the panel. This does not indicate a malfunction and does not affect the performance and reliability of the product.

This phenomenon also occurs in third-party products and is not subject to exchange or refund.



 You may find different brightness and colour of the panel depending on your viewing position(left/right/ top/down).

This phenomenon occurs due to the characteristic of the panel. It is not related with the product performance, and it is not malfunction.



 Displaying a still image (e.g., broadcasting channel logo, on-screen menu, scene from a video game or computer screen) for a prolonged time may cause damage to the screen, resulting in retention of the image, which is known as image sticking. It can remain for long time or never disappear. The warranty does not cover the product for image sticking. Avoid displaying a fixed image on your television's screen for a prolonged period (1 or more hours for OLED).

Also, if you watch the TV at a ratio of 4:3 for a long time, image sticking may occur on the borders of the panel.

This phenomenon also occurs in third-party products and is not subject to exchange or refund.







Generated Sound

"Cracking" noise: A cracking noise that occurs when watching or turning off the TV is generated by plastic thermal contraction due to tempera-ture and humidity. This noise is common for products where thermal deformation is required. Electrical circuit humming/panel buzzing: A low level noise is generated from a high-speed switching circuit, which supplies a large amount of current to operate a product. It varies depend-ing on the product.

This generated sound does not affect the performance and reliability of the product.

 Do not use high voltage electrical goods near the TV(e.g. electric mosquito-swatter). This may result in product malfunction.

Viewing 3D Imaging



Viewing Environment

- Viewing Time
 - When watching 3D contents, take 5 15 minute breaks every hour. Viewing 3D contents for a long period of time may cause headache, dizziness, fatigue or eye strain.

Those that have a photosensitive seizure or chronic illness

- Some users may experience a seizure or other abnormal symptoms when they are exposed to a flashing light or particular pattern from 3D contents.
- Do not watch 3D videos if you feel nausea, are pregnant and/ or have a chronic illness such as epilepsy, cardiac disorder, or blood pressure disease, etc.
- 3D Contents are not recommended to those who suffer from stereo blindness or stereo anomaly.
 Double images or discomfort in viewing may be experienced.
- If you have strabismus (cross-eyed), amblyopia (weak eyesight) or astigmatism, you may have trouble sensing depth and easily feel fatigue due to double images. It is advised to take frequent breaks than the average adult.
- If your eyesight varies between your right and left eye, revise your eyesight prior to watching 3D contents.

Symptoms which require discontinuation or refraining from watching 3D contents

- Do not watch 3D contents when you feel fatigue from lack of sleep, overwork or drinking.
- When these symptoms are experienced, stop using/ watching 3D contents and get enough rest until the symptom subsides.
 - Consult your doctor when the symptoms persist.
 Symptoms may include headache, eyeball pain, dizziness, nausea, palpitation, blurriness, discomfort, double image, visual inconvenience or fatigue.



Viewing Environment

- · Viewing Distance
 - Maintain a distance of at least twice the screen diagonal length when watching 3D contents.
 If you feel discomfort in viewing 3D contents, move further away from the TV.

Viewing Age

- · Infants/Children
 - Usage/ Viewing 3D contents for children under the age of 5 are prohibited.
 - Children under the age of 10 may overreact and become overly excited because their vision is in development (for example: trying to touch the screen or trying to jump into it. Special monitoring and extra attention is required for children watching 3D contents.
 - Children have greater binocular disparity of 3D presentations than adults because the distance between the eyes is shorter than that of adults. Therefore they will perceive more stereoscopic depth compared to adults for the same 3D image.
- · Teenagers
 - Teenagers under the age of 19 may react with sensitivity due to stimulation from light in 3D contents. Advise them to refrain from watching 3D contens for a long time when they are tired.
- Elderly
 - The elderly may perceive less 3D effect compared to the young. Do not sit closer to the TV than the recommended distance.

Cautions when using the 3D glasses

- Make sure to use LG 3D glasses. Otherwise, you may not be able to view 3D videos properly.
- Do not use 3D glasses instead of your normal glasses, sunglasses or protective goggles.
- Using modified 3D glasses may cause eye strain or image distortion.
- Do not keep your 3D glasses in extremely high or low temperatures. It will cause deformation.
- The 3D glasses are fragile and are easily scratched.
 Always use a soft, clean piece of cloth when wiping the lenses.
 - Do not scratch the lenses of the 3D glasses with sharp objects or clean/wipe them with chemicals.



- · Image shown may differ from your TV.
- · Your TV's OSD (On Screen Display) may differ slightly from that shown in this manual.
- · The available menus and options may differ from the input source or product model that you are using.
- · New features may be added to this TV in the future.
- The TV can be placed in standby mode in order to reduce the power consumption. And the TV should be turned off if it
 will not be watched for some time, as this will reduce energy consumption.
- The energy consumed during use can be significantly reduced if the level of brightness of the picture is reduced, and this will reduce the overall running cost.

INSTALLATION PROCEDURE

- 1 Open the package and make sure all the accessories are included.
- 2 Connect an external device to the TV set.
- 3 Make sure the network connection is available.
 You can use the TV network functions only when the network connection is made.
- * If the TV is turned on for the first time after it was shipped from the factory, initialization of the TV may take a few minutes.

ASSEMBLING AND PREPARING

Unpacking

Check your product box for the following items. If there are any missing accessories, contact the local dealer where you purchased your product.

The illustrations in this manual may differ from the actual product and item.



CAUTION

- Do not use any unapproved items to ensure the safety and product life span.
- Any damages or injuries by using unapproved items are not covered by the warranty.
- Some models have a thin film attached on to the screen and this must not be removed.



NOTE

- The items supplied with your product may vary depending on the model.
- Product specifications or contents of this manual may be changed without prior notice due to upgrade of product functions
- For an optimal connection, HDMI cables and USB devices should have bezels less than 10 mm thick and 18 mm width.
 Use an extension cable that supports USB 2.0 if the USB cable or USB memory stick does not fit into your TV's USB port.






*A ≤ 10 mm

*B ≤ 18 mm

- · Use a certified cable with the HDMI logo attached.
- If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- Recommended HDMI Cable Types
 - High-Speed HDMI[®]/[™] Cable
 - High-Speed HDMI[®]/TM Cable with Ethernet



Owner's manual



Magic remote, Batteries (AA) (See p.35)



Cinema 3D glassesThe number of 3D glasses may differ depending on the model or country.



Tag on (Depending on model)



Cable Holder (See p.22, 23)



Component gender cable (See p.30)



Composite gender cable (See p.30,31)



HDMI Cable (Depending on model) (See p.27, 28)



AV Cover (Only EC93**) (See p.18)



AV Cover (Only EC97**) (See p.18)




AV Cover (Only EG97**) (See p.18)



Cable Managements 2 EA (Only EC97**) (See p.22, 23)



Cable Management Screws 2 EA, M4 x L10 (Only EC97**) (See p.23)



Cleaning Cloth (Depending on model)

Separate purchase

Separate purchase items can be changed or modified for quality improvement without any notification. Contact your dealer to buy these items.

These devices only work with certain models.


AG-F***	AN-MR500	AN-VC5**	AG-F***DP Dual Play Glasses	
Cinema 3D Glasses	Magic Remote	Video call camera		
LG Audio Device	Tag On			

Compatibility	EC93**	EC97**	EG97**	
AG-F*** Cinema 3D Glasses	•	•	•	
AN-MR500 Magic Remote	•	•		
AN-VC5** Video call camera				
AG-F***DP Dual Play Glasses				
LG Audio Device	•		•	
Tag On	•	•	•	


The model name or design may be changed depending on the upgrade of product functions, manufacturer's circumstances or policies.

Parts and buttons


A type : EC93**



B type : EC97**



C type : EG97**



- 1 Intelligent sensor Adjusts the image quality and brightness based on the surrounding environment.
- 2 Joystick Button This button is located behind the TV screen.
- 3 Joystick Button This button is located below the TV screen.



NOTE

• You can set the LG Logo Light to on or off by selecting **GENERAL** in the main menus.

Using the joystick button

You can operate the TV by pressing the button or moving the joystick left, right, up, or down.

Basic Functions

Power On	When the TV is turned off, place your finger on the joystick button and press it once and release it.
Power Off	When the TV is turned on, place your finger on the joystick button and press it once for a few seconds and release it.
Volume Control	If you place your finger over the joystick button and move it left or right, you can adjust the volume level you want.
Programmes Control	If you place your finger over the joystick button and move it up or down, you can scrolls through the saved programmes you want.



NOTE

When your finger over the joystick button and push it to the up, down, left or right, be careful not to press the
joystick button. If you press the joystick button first, you may not be able to adjust the volume level and saved
programmes.

Adjusting the Menu

When the TV is turned on, press the joystick button one time.

You can adjust the Menu items ($0, \times, \bigcirc$) moving the joystick button left or right.

	ტ	TV OFF	Turns the power off.
(b × •	×	CLOSE	Clears on-screen displays and returns to TV viewing.
	•	INPUT	Changes the input source.

Lifting and moving the TV

Please note the following advice to prevent the TV from being scratched or damaged and for safe transportation regardless of its type and size.




CAUTION -


- Avoid touching the screen at all times, as this may result in damage to the screen.
- It is recommended to move the TV in the box or packing material that the TV originally came in.
- Before moving or lifting the TV, disconnect the power cord and all cables.
- When holding the TV, the screen should face away from you to avoid damage.



 Hold the top and bottom of the TV frame firmly.
 Make sure not to hold the transparent part, speaker, or speaker grill area.



- When transporting a large TV, there should be at least 2 people.
- When transporting the TV by hand, hold the TV as shown in the following illustration.




- When transporting the TV, do not expose the TV to jolts or excessive vibration.
- When transporting the TV, keep the TV upright, never turn the TV on its side or tilt towards the left or right.
- Do not apply excessive pressure to cause flexing / bending of frame chassis as it may damage screen.
- Be sure to keep your TV upright instead of laying or tilting it while moving the TV.
- When handling the TV, be careful not to damage the protruding joystick button.


Setting up the TV

(Image shown may differ from your TV.)

Detaching the stand


(Only EC93**, EG97**)





- When you assemble the stand, have the arrows on the bottom of the stand base looking towards the same direction as the screen.
- When detaching the stand, make sure to hold it firmly while removing the screws to stop it from falling.

(Only EC97**)





CAUTION

- When detaching the stand to the TV set, place the screen(or back) facing down on a cushioned table or flat surface to protect the screen(or back) from scratches.
- Make sure that the screws are inserted correctly and fastened securely. (If they are not fastened securely enough, the TV may tilt forward after being installed.)

Do not use too much force and over tighten the screws; otherwise screw may be damaged and not tighten correctly.




NOTE

 When you assemble the stand again, performing the stand detaching in reverse.


Attaching the AV cover

Assemble the AV Cover as shown.


(Only EC93**)



(Only EC97**)





(Only EG97**)



Mounting on a table

- 1 Lift and tilt the TV into its upright position on a table.
 - Leave a 10 cm (minimum) space from the wall for proper ventilation.





2 Connect the power cord to a wall outlet.




CAUTION -


• Do not place the TV near or on sources of heat, as this may result in fire or other damage.

Securing the TV to a wall

(This feature is not available for all models.)

To use the desk-type stand safely, make sure to securely attach it to a wall.





- 1 Insert and tighten the eye-bolts, or TV brackets and bolts on the back of the TV.
 - If there are bolts inserted at the eye-bolts position, remove the bolts first.
- 2 Mount the wall brackets with the bolts to the wall. Match the location of the wall bracket and the eyebolts on the rear of the TV.
- 3 Connect the eye-bolts and wall brackets tightly with a sturdy rope.
 - Make sure to keep the rope horizontal with the flat surface.



CAUTION

 Make sure that children do not climb on or hang on the TV.




NOTE

- Use a platform or cabinet that is strong and large enough to support the TV securely.
- Brackets, bolts and ropes are not provided. You can obtain additional accessories from your local dealer.

Mounting on a wall

Attach an optional wall mount bracket at the rear of the TV carefully and install the wall mount bracket on a solid wall perpendicular to the floor. When you attach the TV to other building materials, please contact qualified personnel.

LG recommends that wall mounting be performed by a qualified professional installer.



Make sure to use screws and wall mount bracket that meet the VESA standard. Standard dimensions for the wall mount kits are described in the following table.

Separate purchase(Wall Mounting Bracket)

Model	55EC93**	65EC97**	
(A)	210	210	
Standard screw	M6	M6	
Number of screws	2	2	
	OSW100	OSW200	
Wall mount bracket			

Model	77EG97** 400 x 400		
VESA (A x B)			
Standard screw	M6		
Number of screws	4		
	LSW420BX		
Wall mount bracket			



CAUTION

- · Disconnect the power first, and then move or install the TV. Otherwise electric shock may occur.
- · If you install the TV on a ceiling or slanted wall, it may fall and result in severe injury. Use an authorized LG wall mount and contact the local dealer or qualified personnel.
- Do not over tighten the screws as this may cause damage to the TV and void your warranty.
- · Use the screws and wall mounts that meet the VESA standard. Any damages or injuries by misuse or using an improper accessory are not covered by the warranty.



NOTE


- · Use the screws that are listed on the VESA standard screw specifications.
- · The wall mount kit includes an installation manual and necessary parts.
- The wall mount bracket is not provided. You can obtain additional accessories from your local
- · The length of screws may differ depending on the wall mount. Make sure to use the proper length.
- · For more information, refer to the manual supplied with the wall mount.

Wall Type Set-up Guide


(Only EG97** - Separate purchase)

Guide spacer assembly

1 Remove the VESA screws (4 EA).




2 Assemble Guide spacer (4 EA) and Guide spacer screws (4 EA).



Wall mount bracket installation


After installation, move the bracket forward.



How to detach the stand

Type 1. Hanging the TV on the wall before removing a stand.






2




3



4



5



Type 2. Hanging the TV on the wall after removing a stand.

1







CAUTION

 When laying the TV on its back on a padded table or surface, be careful to prevent the TV from being damaged.




3





5



6




Tidying cables

(Image shown may differ from your TV.)

Stand Type


(Only EC93**)

Gather and bind the cables with the cable holder.




(Only EC97**)


1 Put the cable management in the hole of TV back cover.



2 Fix the cable management with cable management screw.




- NOTE
- When attaching the cable management, use a magnetic screwdriver.
- If you don't have a magnetic screwdriver, insert the screws into the cable management and then attach it to the TV.
- 3 Gather and bind the cables with the cable holder.
 Arrange the cables in the cable mangement.




(Only EG97**)

Gather and bind the cables with the cable holder.



Wall Mount Type

(Only EC93**)





 Do not move the TV by holding the cable holder, as the cable holder may break, and injuries and damage to the TV may occur.

Using Built-in Camera

(Only EC97**, EG97**)


This TV does not support the use of an external camera.



- Before using the built-in camera, you must recognize the fact that you are legally responsible for the use or misuse of the camera by the relevant national laws including the criminal law.
- The relevant laws include the Personal Information Protection law which regulates the processing and transferring of personal information and the law which regulates the monitoring by camera in a workplace and other places.
- · When using the built-in camera, avoid questionable, illegal, or immoral situations. Other than at public places or events, consent to be photographed may be required. We suggest avoiding the following situations:
 - (1) Using the camera in areas where the use of camera is generally prohibited such as restroom, locker room, fitting room and security area.
 - (2) Using the camera while causing the infringement of
- (3) Using the camera while causing the violation of the relevant regulations or laws.


Preparing Built-in Camera

1 Pull up the built-in camera at the back of the TV.







- Remove the protective film before using the built-in camera.
- You can adjust the angle of the camera with the angle adjustment lever on the back on the back of the built-in camera.



3 Push down the built-in camera when you are not using it.



Name of Parts of Built-in camera



Checking the Camera's Shooting Range

- 1 Press the (Home) button on the remote control to display the **HOME** menu.
- Select CAMERA and then press the Wheel(OK) button.



 The optimal distance from the camera to use the motion recgnition function is between 1.5 m and 4.5 m.

MAKING CONNECTIONS

This section on MAKING CONNECTIONS mainly uses diagrams for the EC97** models.

Connect various external devices to the TV and switch input modes to select an external device. For more information on external device's connection, refer to the manual provided with each device.

Available external devices are: HD receivers, DVD players, VCRs, audio systems, USB storage devices, PC, gaming devices, and other external devices.





NOTE

- · The external device connection may differ from the model.
- · Connect external devices to the TV regardless of the order of the TV port.
- If you record a TV program on a DVD recorder or VCR, make sure to connect the TV signal input cable to the TV through a DVD recorder or VCR. For more information of recording, refer to the manual provided with the connected device.
- · Refer to the external equipment's manual for operating instructions.
- If you connect a gaming device to the TV, use the cable supplied with the gaming device.
- In PC mode, there may be noise associated with the resolution, vertical pattern, contrast or brightness. If noise is present, change the PC output to another resolution, change the refresh rate to another rate or adjust the brightness and contrast on the PICTURE menu until the picture is clear.
- In PC mode, some resolution settings may not work properly depending on the graphics card.
- If Ultra HD content is played via PC, the video or audio may have disruptions intermittently depending on your PC's performance.

Antenna connection

Connect the TV to a wall antenna socket with an RF cable $(75 \Omega).$








- Use a signal splitter to use more than 2 TVs.
- · If the image quality is poor, install a signal amplifier properly to improve the image quality.
- · If the image quality is poor with an antenna connected, try to realign the antenna in the correct direction.
- An antenna cable and converter are not provided.
- · Supported DTV Audio: MPEG, Dolby Digital, Dolby Digital Plus, HE-AAC
- This TV cannot receive UHD (3840 x 2160 pixels) broadcasts directly because the related standards have not been confirmed.


HDMI connection

Transmits the digital video and audio signals from an external device to the TV. Connect the external device and the TV with the HDMI cable as shown.


(Only EC93**)



(Only EC97**)



(Only EG97**)



ARC (Audio Return Channel)

- An external audio device that supports SIMPLINK and ARC must be connected using HDMI/DVI IN 1 (ARC) or HDMI(4K @ 60 Hz)/DVI IN 2 (ARC) port.
- When connected with a high-speed HDMI cable, the external audio device that supports ARC outputs optical SPDIF without additional optical audio cable and supports the SIMPLINK function.

(Only EC97**, EG97**)

- 1) HDMI specifications may be different for each input port, so make sure to check the device specifications before connecting.
- 2) The HDMI IN 3 port is especially suitable for the specifications to enjoy UHD Video (4:4:4, 4:2:2) of 4K @ 50/60 Hz.
 - However, video or audio may not be supported depending on the specifications of the external equipment. In that case, use any other HDMI port.
- 3) Contact customer service for more information on the HDMI specifications of each input port.

4K @ 50/60 Hz Support Format

Resolution	Frame rate (Hz)	Colour Depth / Chroma Sampling		
		8 bit	10 bit	12 bit
	50.00 59.94 60.00	YCbCr 4:2:0	YCbCr	4:2:0 ¹
2040 × 21605		Y	CbCr 4:2:2	1
3840 x 2160p 4096 x 2160p		YCbCr 4:4:4 ¹	-	-
		RGB 4:4:4 ¹	-	-

1: Only Supported at **HDMI IN 3** Port




- · It is recommended to use the TV with the HDMI connection for the best image quality.
- Use the latest High Speed HDMI™ Cable with CEC (Customer Electronics Control) function.
- High Speed HDMI™ Cables are tested to carry an HD signal up to 1080p and higher.
- Supported HDMI Audio format : Dolby Digital (32 KHz, 44.1 KHz, 48 KHz), DTS (44.1 KHz, 48 KHz), PCM (32 KHz, 44.1 KHz, 48 KHz, 96 KHz, 192 KHz)
- When you use HDMI IN 3 port, it is recommended that you use the cable provided (Depending on model). If you want to use a regular HDMI cable. use one that is a highspeed HDMI cable (3m or

DVI to HDMI connection


Transmits the digital video signal from an external device to the TV. Connect the external device and the TV with the DVI-HDMI cable as shown. To transmit an audio signal, connect an audio cable.

(Only EC93**)




DVD / Blu-Ray / PC / HD Cable Box / HD STB

(Only EC97**)



(Only EG97**)






- · Depending on the graphics card, DOS mode may not work if a HDMI to DVI Cable is in use.
- When using the HDMI / DVI cable, Single link is only supported.

Component connection

Transmits analogue video and audio signals from an external device to the TV. Connect the external device and the TV with a component gender cable as shown.




DVD / Blu-Ray / HD Cable Box



· If cables are not installed correctly, it could cause this image to display in black and white or with distorted colours.

Composite connection

Transmits analogue video and audio signals from an external device to the TV. Connect the external device and the TV with a composite gender cable as shown.




DVD / Blu-Ray / HD Cable Box / VCR

Audio connection

You may use an external audio system instead of the built-in speaker.

Digital optical audio connection

Transmits a digital audio signal from the TV to an external device. Connect the external device and the TV with the optical audio cable as shown.






CAUTION

- Do not look into the optical output port. Looking at the laser beam may damage your vision.
- Audio with ACP (Audio Copy Protection) function may block digital audio output.

Headphone connection


Transmits the headphone signal from the TV to an external device. Connect the external device and the TV with the headphone as shown.



MHL connection


Mobile High-definition Link (MHL) is an interface for transmitting digital audiovisual signals from mobile phones to television sets.

(Only EC93**)




- · AUDIO menu items are disabled when connecting a headphone.
- Optical Digital Audio Out is not available when connecting a headphone.
- Headphone impedance: 16 Ω
- Max audio output of headphone: 0.627 mW to
- Headphone jack size: 0.35 cm

(Only EC97**)



(Only EG97**)






- · Connect the mobile phone to the HDMI/DVI IN 4(MHL) or HDMI(4K @ 60 Hz)/DVI IN 4(MHL) port to view the phone screen on the TV.
- The MHL passive cable is needed to connect the TV and a mobile phone.
- · This only works for the MHL-enabled phone.
- Some applications can be operated by the remote
- For some mobile phones supporting MHL, you can control with the magic remote control.
- · Remove the MHL passive cable from the TV when:
 - » the MHL function is disabled
 - » your mobile device is fully charged in standby mode


USB connection

Connect a USB storage device such as a USB flash memory, external hard drive or a USB memory card reader to the TV and access the Smart Share menu to use various multimedia files.

(Only EC93**)



(Only EC97**, EG97**)






- · Some USB Hubs may not work. If a USB device connected using a USB Hub is not detected, connect it to the USB IN port on the TV directly.
- Connect the external power source if your USB is needed.
- Connecting via USB 3.0 : Some USB device may not work if it dose not meet USB 3.0 standard. In case, connect it to USB IN 2 or USB IN 3 port. (Only EC97**, EG97**)

MAGIC REMOTE FUNCTIONS

When the message "Magic remote battery is low. Change the battery." is displayed, replace the


To replace batteries, open the battery cover, replace batteries (1.5 V AA) matching \oplus and \bigcirc ends to the label inside the compartment, and close the battery cover. Be sure to point the magic remote toward the remote control sensor on the TV.

To remove the batteries, perform the installation actions in reverse.





- Do not mix old and new batteries, as this may damage the remote control.
- In Analogue TV and some countries, some remote control buttons may not work.





(Voice recognition)

Network connection is required to use the voice recognition function.

- 1. Press the voice recognition button.
- 2. Speak when the voice display window appears on the left of the TV screen.
 - · Use the Magic Remote no further than 10 cm from your face.
 - · The voice recognition may fail when you speak too fast or too slowly.
 - · The recognition rate may vary depending on the user's characteristics (voice, pronunciation, intonation, and speed) and the environment (noise and TV volume).

Registering Magic Remote

How to register the Magic Remote



To use the Magic Remote, first pair it with your TV.

- 1 Put batteries into the Magic Remote and turn the TV on.
- 2 Point the Magic Remote at your TV and press the **Wheel (OK)**
- on the remote control.

 * If the TV fails to register the Magic Remote, try again after turning the TV off and back on.

How to deregister the Magic Remote



Press the (BACK) and (Home) buttons at the same time, for five seconds, to unpair the Magic Remote with your TV.

* Pressing and holding the (EXIT to LIVE) button will let you cancel and re-register Magic Remote at once.

Precautions to Take when Using the Magic Remote

- Use the Magic Remote within the maximum communication distance (10 m). Using the Magic Remote beyond this distance, or with an object obstructing it, may cause a communication failure.
- A communication failure may occur due to nearby devices. Electrical devices such as a microwave oven or wireless LAN product may cause interference, as these use the same bandwidth (2.4 GHz) as the Magic Remote.
- The Magic Remote may be damaged or may malfunction if it is dropped or receives a heavy impact.
- Take care not to bump into nearby furniture or other people when using the Magic Remote.
- Manufacturer and installer cannot provide service related to human safety as the applicable wireless device has possibility of electric wave interference.
- It is recommended that an Access Point (AP) be located more than 1 m away from the TV. If the AP is installed closer than 1 m, the Magic Remote may not perform as expected due to frequency interference.

How to use magic remote



- Shake the Magic Remote slightly to the right and left or press (Home),
 Solution 30 buttons to make the pointer appear on the screen. (In some TV models, the pointer will appear when you turn the Wheel button.)
- If the pointer has not been used for a certain period of time or Magic Remote is placed on a flat surface, then the pointer will disappear.
- If the pointer is not responding smoothly, you can reset the pointer by moving it to the edge of the screen
- The Magic Remote depletes batteries faster than a normal remote due to the additional features.

USING THE USER GUIDE

User Guide allows you to more easily access the detailed TV information.

- 1 Press the $\mathbf{\hat{\omega}(Home)}$ button to access the Home menu.
- 2 Select User Guide and press the (1) Wheel(OK) button.







MAINTENANCE

Cleaning Your TV

Clean your TV regularly to keep the best performance and to extend the product lifespan.



CAUTION

- · Make sure to turn the power off and disconnect the power cord and all other cables first.
- · When the TV is left unattended and unused for a long time, disconnect the power cord from the wall outlet to prevent possible damage from lightning or power surges.

Screen, frame, cabinet and stand

- To remove dust or light dirt, wipe the surface with a dry, clean, and soft cloth.
- · To remove major dirt, wipe the surface with a soft cloth dampened in clean water or a diluted mild detergent. Then wipe immediately with a dry cloth.



CAUTION

- Avoid touching the screen at all times, as this may result in damage to the screen.
- · Do not push, rub, or hit the surface with your fingernail or a sharp object, as this may result in scratches on the screen and image distortions.
- · Do not use any chemicals as this may damage the product.
- Do not spray liquid onto the surface. If water enters the TV, it may result in fire, electric shock, or malfunction.

Power cord

Remove the accumulated dust or dirt on the power cord regularly.

TROUBLESHOOTING

Problem	Solution
Cannot control the TV with the remote control.	 Check the remote control sensor on the product and try again. Check if there is any obstacle between the product and the remote control. Check if the batteries are still working and properly installed (⊕ to ⊕, ⊝ to ⊝).
No image display and no sound is produced.	 Check if the product is turned on. Check if the power cord is connected to a wall outlet. Check if there is a problem in the wall outlet by connecting other products.
The TV turns off suddenly.	Check the power control settings. The power supply may be interrupted. Check if the Sleep Timer or Timer Power Off feature is activated in the TIMERS settings. If there is no signal while the TV is on, the TV will turn off automatically after 15 minutes of inactivity.
When connecting to the PC (HDMI/DVI), 'No signal' or 'Invalid Format' is displayed.	Turn the TV off/on using the remote control. Reconnect the HDMI/DVI cable. Restart the PC with the TV on.

SPECIFICATIONS

(Only EC93**)

Wireless module(LGSBW41)Specification					
	Wireless LAN		Bluetooth		
Standard	IEEE 802.11a/b/g/n	Standard	Bluetooth Version 3.0		
Frequency Range	2400 to 2483.5 MHz 5150 to 5250 MHz 5725 to 5850 MHz (for Non EU)	Frequency Range	2400 to 2483.5 MHz		
Output Power (Max.)	802.11a: 13 dBm 802.11b: 15 dBm 802.11g: 14 dBm 802.11n - 2.4 GHz: 16 dBm 802.11n - 5 GHz: 16 dBm	Output Power (Max.)	10 dBm or Lower		

- Because band channel used by the country could be different, the user can not change or adjust the operating frequency and this product is set for the regional frequency table.
- This device should be installed and operated with minimum distance 20 cm between the device and your body. And this phrase is for the general statement for consideration of user environment.

(Only EC97**, EG97**)

Wireless module(LGSWF41)Specification			
Standard	IEEE 802.11a/b/g/n/ac		
Frequency Range	2400 to 2483.5 MHz 5150 to 5250 MHz 5725 to 5850 MHz (for Non EU)		
Output Power (Max.)	802.11a: 14.5 dBm 802.11b: 16 dBm 802.11g: 13.5 dBm 802.11n - 2.4 GHz: 14 dBm 802.11n - 5 GHz: 15.5 dBm 802.11ac - 5 GHz: 16 dBm		

- Because band channel used by the country could be different, the user can not change or adjust the operating frequency and this product is set for the regional frequency table.
- This device should be installed and operated with minimum distance 20 cm between the device and your body. And this phrase is for the general statement for consideration of user environment.

Bluetooth module (BM-LDS401) specification			
Standard	Bluetooth Version 3.0		
Frequency Range 2400 to 2483.5 MHz			
Output Power (Max.)	10 dBm or Lower		

Product specifications may be changed without prior notice due to upgrade of product functions. For the power supply and power consumption, refer to the label attached to the product.

Thickness

MODEL		55EC93**	
MO	DEL	55EC9300-CA	
Dimensions	With stand (mm)	1225 x 753 x 204	
(W x H x T(D))	Without stand (mm)	1225 x 715 x 44 (81)	
Weight	With stand (kg)	16.7	
vveigni	Without stand (kg)	14.7	
Power re-	quirement	AC 100-240 V~ 50 / 60 Hz	
MO	DEL	65EC97**	
INIO	DEL	65EC9700-CA	
Dimensions	With stand (mm)	1447 x 880 x 256.6	
(W x H x T(D))	Without stand (mm)	1447 x 844 x 56.3 (108.7)	
\\/oight	With stand (kg)	25.5	
Weight	Without stand (kg)	24.1	
Power re	quirement	AC 100-240 V~ 50 / 60 Hz	
	DE!	77EG97**	
MO	DEL	77EG9700-CA	
Dimensions	With stand (mm)	1718 x 1110 x 322	
(W x H x T(D))	Without stand (mm)	1718 x 1064 x 34.7 (108.2)	
Moight	With stand (kg)	43.3	
Weight	Without stand (kg)	39.9	
Power requirement		AC 100-240 V~ 50 / 60 Hz	

Depth

	Operating Temperature	0 °C to 40 °C
Environment condition	Operating Humidity	Less than 80 %
	Storage Temperature	-20 °C to 60 °C
	Storage Humidity	Less than 85 %

	Digital TV	Analogue TV	
Television System	DTMB	PAL D/K, PAL I, NTSC M	
Programme Coverage	DTMB : 1~62	PAL D/K : VHF/UHF 1~62, CATV 1~41 PAL I : VHF/UHF 1~69, CATV 1~47 NTSC M : VHF/UHF 2~78, CATV 1~71	
External Antenna Impedance	75 Ω		



Record the model number and serial number of the TV.

Refer to the label on the back cover and quote this information to your dealer when requiring any service.

MODEL			
CEDIAL			



WNER'S MANUAL

EXTERNAL CONTROL DEVICE SETUP

lease read this manual carefully before operating the set and retain it for iture reference.

KEY CODES

· This feature is not available for all models.

Code (Hexa)	Function	Note	Code (Hexa)	Function	Note
00	CH +, PR +	R/C Button	53	List	R/C Button
01	CH -, PR -	R/C Button	5B	Exit	R/C Button
02	Volume +	R/C Button	60	PIP(AD)	R/C Button
03	Volume -	R/C Button	61	Blue	R/C Button
06	> (Arrow Key / Right Key)	R/C Button	63	Yellow	R/C Button
07	< (Arrow Key / Left Key)	R/C Button	71	Green	R/C Button
08	Power	R/C Button	72	Red	R/C Button
09	Mute	R/C Button	79	Ratio / Aspect Ratio	R/C Button
0B	Input	R/C Button	91	AD (Audio Description)	R/C Button
0E	SLEEP	R/C Button	7A	User Guide	R/C Button
0F	TV, TV/RAD	R/C Button	7C	Smart / Home	R/C Button
10 - 19	* Number Key 0 - 9	R/C Button	7E	SIMPLINK	R/C Button
1A	Q.View / Flashback	R/C Button	8E	▶▶ (Forward)	R/C Button
1E	FAV (Favorite Channel)	R/C Button	8F	◀ (Rewind)	R/C Button
20	Text (Teletext)	R/C Button	AA	Info	R/C Button
21	T. Opt (Teletext Option)	R/C Button	AB	Program Guide	R/C Button
28	Return (BACK)	R/C Button	B0	► (Play)	R/C Button
30	AV (Audio / Video) Mode	R/C Button	B1	■ (Stop / File List)	R/C Button
39	Caption/Subtitle	R/C Button	ВА	II (Freeze / Slow Play / Pause)	R/C Button
40	Λ (Arrow Key / Cursor Up)	R/C Button	BB	Soccer	R/C Button
41	V (Arrow Key / Cursor Down)	R/C Button	BD	• (REC)	R/C Button
42	My Apps	R/C Button	DC	3D	R/C Button
43	Menu / Settings	R/C Button	99	AutoConfig	R/C Button
44	OK / Enter	R/C Button	9F	App / *	R/C Button
45	Q.Menu	R/C Button			
4C	List, - (ATSC Only)	R/C Button			

^{*} Key code 4C (0x4C) is available on ATSC/ISDB models which use major/minor channel. (For South Korea, Japan, North America, Latin America except Colombia models)

EXTERNAL CONTROL DEVICE SETUP

Image shown may differ from your TV.


onnect the USB to Serial converter/RS-232C input jack to an external control device (such as a computer r an A/V control system) to control the product's functions externally.

ote: The type of control port on the TV can be different between model series.

Please be advised that not all models support this type of connectivity. Cable is not provided.

ISB to Serial converter with USB Cable

SB Type



LGTV supports PL2303 chip-based (Vendor ID : 0x0557, Product ID : 0x2008) USB to serial converter which is not made nor provided by LG.

It can be purchased from computer stores that carry accessories for IT support professionals.

RS-232C With RS232C Cable

E9 (D-Sub 9pin) Type


You need to purchase the RS-232C (DE9, D-Sub 9pin female-to-female type) to RS-232C cable required for the connection between the PC and the TV, which is specified in the manual.




he connection interface may differ from your TV.

Phone jack Type


- You need to purchase the phone-jack to RS-232 cable required for the connection between the PC and the TV, which is specified in the manual.
- * For other models, connect to the USB port.
- * The connection interface may differ from your TV.



- or




Customer Computer



RS-232C configurations

3-Wire Configurations(Not standard)



Set ID

For Set ID number, see "Real Data Mapping" on p.6

- 1. Press **SETTINGS** to access the main menus.
- Press the Navigation buttons to scroll to (*General → About this TV or OPTION) and press OK.
- 3. Press the Navigation buttons to scroll to SET ID and press OK.
- 4. Scroll left or right to select a set ID number and select CLOSE. The adjustment range is 1-99.
- 5. When you are finished, press **EXIT**.
 - * (Depending on model)

Communication Parameters

Baud rate : 9600 bps (UART)

Data length: 8 bits

Parity : None

Stop bit : 1 bit

Communication code : ASCII code

DATA

Use a crossed (reverse) cable.

command reference list

Depending on model)

	COMMAND1	COMMAND2	(Hexadecimal)		COMMAND1	COMMAND2	(Hexadecimal)
1. Power*	k	а	00 to 01	15. Balance	k	t	00 to 64
)2. Aspect Ratio	k	С	(p.7)	16. Color (Colour) Temperature	х	u	00 to 64
03. Screen Mute	k	d	(p.7)	17. ISM Method (Only Plasma TV)	j	р	(p.8)
)4. Volume Vute	k	е	00 to 01	18. Equalizer	j	v	(p.8)
05. Volume Control	k	f	00 to 64	19. Energy Saving	j	q	00 to 05
06. Contrast	k	g	00 to 64	20. Tune Command	m	а	(p.9)
)7. Brightness	k	h	00 to 64	21. Channel (Programme) Add/Del(Skip)	m	b	00 to 01
)8. Color/ Colour	k	i	00 to 64	22. Key	m	С	Key Codes
09. Tint	k	j	00 to 64	23. Control Backlight, Control Panel Light	m	g	00 to 64
I0. Sharpness	k	k	00 to 32	24. Input select (Main)	х	b	(p.11)
I1. OSD Select	k	I	00 to 01	25. 3D (Only 3D models)	х	t	(p.11)
I2. Remote Control Lock Mode	k	m	00 to 01	26. Extended 3D (Only 3D models)	х	V	(p.11)
I3. Treble	k	r	00 to 64	27. Auto Configure	j	u	(p.12)
I4. Bass	k	s	00 to 64				

DATA

Note: During playing or recording media, all commands except Power (ka) and Key (mc) are not executed and treated as NG.

With RS232C cable, TV can communicate "ka command" in power-on or power-off status. but with USB-to-Serial converter cable, the command works only if TV is on.

Transmission / Receiving Protocol

Transmission

[Command1][Command2][][Set ID][][Data][Cr]

[Command 1]: First command to control the TV. (j, k, m or x)

[Command 2]: Second command to control the TV.

: You can adjust the [Set ID] to choose desired monitor ID number in option menu. [Set ID]

> Adjustment range in TV is 1 to 99. If [Set ID] value is selected to '0', every connected set can be controlled.

* [Set ID] is indicated as decimal (1 to 99) on menu and as Hexadecimal (0x00 to 0x63) or

transmission/receiving protocol.

[DATA] : To transmit command data (hexadecimal). Transmit 'FF' data to read status of command.

[Cr] : Carriage Return - ASCII code '0x0D' : Space - ASCII code '0x20' []

OK Acknowledgement

[Command2][][Set ID][][OK][Data][x]

* The set transmits ACK (acknowledgement) based on this format when receiving normal data. At this time if the data is data read mode, it indicates present status data. If the data is data write mode, it returns the data of the PC computer.

Error Acknowledgement

[Command2][][Set ID][][NG][Data][x]

* The set transmits ACK (acknowledgement) based on this format when receiving abnormal data from non-viable functions or communication errors.

Data 00: Illegal Code

00: Step 0

Real data mapping (Hexadecimal → Decimal)

- * When you enter the [data] in hexadecimal, refer to following conversion table.
- * Channel Tune (ma) Command uses two-byte hexadecimal value([data]) to select channel number.

FE: Step 254

32 : Step 50 (Set ID 50)

01 : Step 1 (Set ID 1)	33 : Step 51 (Set ID 51)	FF : Step 255
0A : Step 10 (Set ID 10)	63 : Step 99 (Set ID 99)	01 00 : Step 256
0F : Step 15 (Set ID 15)	C7 : Step 199	27 0E : Step 9998
10 : Step 16 (Set ID 16)	C8 : Step 200	27 0F : Step 9999

Commands may work differently depending on model and signal.

 Power (Command: k a) To control Power *On or Off of the set.

Transmission[k][a][][Set ID][][Data][Cr]

ata 00 : Power Off 01: *Power On

Ack [a][][Set ID][][OK/NG][Data][x]

To Show TV is Power On or *Off

Transmission [k][a][][Set ID][][FF][Cr]

Ack [a][][Set ID][][OK][Data][x]

Similarly, if other functions transmit 'FF' data

based on this format, Acknowledgement feedback presents status about each function.

Aspect Ratio (Command: k c)

(Main Picture Size)

To adjust the screen format. (Main picture format) You can also adjust the screen format using the

Aspect Ratio in the Q.MENU. or PICTURE menu.

Transmission [k][c][][Set ID][][Data][Cr]

ata 01 : Normal screen 07 : 14:9

(4:3)(Europe, Colombia, Mid-East, 02 : Wide screen Asia except South Korea and (16:9)Japan) 04 : Zoom 09: * Just Scan

05 : Zoom 2 0B: Full Wide (Latin America (Europe, Colombia, Mid-

except Colombia East, Asia except South Only) Korea and Japan) 06: Set by Program/ 10 to 1F: Cinema Zoom 1

Original Ack [c][][Set ID][][OK/NG][Data][x]

Using the PC input, you select either 16:9 or 4:3 screen aspect ratio. In DTV/HDMI/Component mode (high-definition), Just Scan is available.

Full wide mode may work differently based on

model and is supported for DTV fully, and ATV,

AV partially.

3. Screen Mute (Command: k d)

To select screen mute on/off.

10: Video mute on

Transmission [k][d][][Set ID][][Data][Cr]

01: Screen mute on (Picture off)

ata 00 : Screen mute off (Picture on) Video mute off

Ack [d][][Set ID][][OK/NG][Data][x]

* In case of video mute on only, TV will display On Screen Display(OSD). But, in case of Screen mute on, TV will not display OSD.

04. Volume Mute (Command: k e) ► To control volume mute on/off.

You can also adjust mute using the MUTE button on remote control. Transmission [k][e][][Set ID][][Data][Cr]

Data 00: Volume mute on (Volume off) 01: Volume mute off (Volume on)

Ack [e][][Set ID][][OK/NG][Data][x]

05. Volume Control (Command: k f) ▶ To adjust volume. You can also adjust volume with the volume

buttons on remote control. Transmission [k][f][][Set ID][][Data][Cr]

Data Min: 00 to Max: 64

Ack [f][][Set ID][][OK/NG][Data][x]

▶ To adjust screen contrast. You can also adjust contrast in the PICTURE

06. Contrast (Command: k g)

Transmission [k][g][][Set ID][][Data][Cr]

Data Min: 00 to Max: 64

07. Brightness (Command: k h)

Ack [g][][Set ID][][OK/NG][Data][x]

▶ To adjust screen brightness. You can also adjust brightness in the PICTURE

menu.

Transmission [k][h][][Set ID][][Data][Cr]

Data Min: 00 to Max: 64

Ack [h][][Set ID][][OK/NG][Data][x]

08. Color/Colour (Command: k i)

➤ To adjust the screen Color(Colour). You can also adjust colour in the PICTURE menu.

Transmission [k][i][][Set ID][][Data][Cr]

Data Min: 00 to Max: 64 * (Depending on model) Ack [i][][Set ID][][OK/NG][Data][x] 14. Bass (Command: k s) 09. Tint (Command: k j) ▶ To adjust Bass. ▶ To adjust the screen tint. You can also adjust in the AUDIO menu. You can also adjust tint in the PICTURE menu. Transmission [k][s][][Set ID][][Data][Cr] Transmission [k][j][][Set ID][][Data][Cr] Data Min: 00 to Max: 64 Data Red: 00 to Green: 64 Ack [s][][Set ID][][OK/NG][Data][x] Ack [j][][Set ID][][OK/NG][Data][x] * (Depending on model) 15. Balance (Command: k t) 10. Sharpness (Command: k k) ► To adjust balance. ▶ To adjust the screen sharpness. You can also adjust balance in the AUDIO menu. You can also adjust sharpness in the PICTURE Transmission [k][t][][Set ID][][Data][Cr] Data Min: 00 to Max: 64 Transmission [k][k][][Set ID][][Data][Cr] Ack [t][][Set ID][][OK/NG][Data][x] Data Min: 00 to Max: 32 Ack [k][][Set ID][][OK/NG][Data][x] 16. Color(Colour) Temperature (Command: x u) ► To adjust colour temperature. You can also adjust 11. OSD Select (Command: k l) Color(Colour) Temperature in the PICTURE menu ► To select OSD (On Screen Display) on/off when Transmission [x][u][][Set ID][][Data][Cr] controlling remotely. Data Min: 00 to Max: 64 Transmission [k][I][][Set ID][][Data][Cr] Ack [u][][Set ID][][OK/NG][Data][x] Data 00: OSD off 01: OSD on Ack [l][][Set ID][][OK/NG][Data][x] 17. ISM Method (Command: j p) (Only Plasma TV ► To control the ISM method. You can also adjust 12. Remote control lock mode (Command: k m) ISM Method in OPTION menu. ▶ To lock the front panel controls on the monitor and Transmission [j][p][][Set ID][][Data][Cr] remote control. Data Min: 02: Orbiter Transmission [k][m][][Set ID][][Data][Cr] 08: Normal 20: Color(Colour) Wash Data 00: Lock off 01: Lock on Ack [p][][Set ID][][OK/NG][Data][x] Ack [m][][Set ID][][OK/NG][Data][x] * If you are not using the remote control, use this 18. Equalizer (Command : j v) When main power is off & on (plug-off and plug-in, ► Adjust EQ of the set. after 20 - 30 seconds), external control lock is Transmission [j][v][][Set ID][][Data][Cr] released. **MSB** LSB * In the standby mode (DC off by off timer or 'ka', 0 0 0 0 0 0 0 0 'mc' command), and if key lock is on, TV will not turn on by power on key of IR & Local Key. Frequency Data 13. Treble (Command: k r) ▶ To adjust treble. 5 2 You can also adjust in the AUDIO menu. 6 Frequency 4 3 1 0 Step 0 0 0 0 0(decimal) 0 0 1st Band 0 0 Transmission [k][r][][Set ID][][Data][Cr] 0 0 1 2nd Band 0 0 0 0 1 1(decimal) Data Min: 00 to Max: 64

	Data 02 - Analog Antenna TV - 00		
It depends on model, and can adjust when sound	Result = ma 00 00 0a 00		
ode is EQ adjustable value.	2. Tune to the digital antenna (DVB-T) Channel 01.		
0.5	Set ID = All = 00		
9. Energy Saving (Command: j q)	Data 00 & 01 = Channel Data is 1 = 00 01		
To reduce the power consumption of the TV. You	Data 02 = Digital Antenna TV = 10		
can also adjust Energy Saving in PICTURE menu.	Result = ma 00 00 01 10		
Transmission [j][q][][Set ID][][Data][Cr]	3 Tune to the catallite (DVP S) Channel 1000		
ata	3. Tune to the satellite (DVB-S) Channel 1000. Set ID = All = 00		
00 : Off	Data 00 & 01 = Channel Data is 1000 = 03 E8		
01 : Minimum	Data 02 = Digital Satellite TV = 40		
02 : Medium	Result = ma 00 03 E8 40		
03 : Maximum	Ack [a][][Set ID][][OK][Data 00][Data 01]		
04 : Auto (For LCD TV / LED TV) /			
Intelligent sensor (For PDP TV) 05 : Screen off	[Data 02][x][a][][Set ID][][NG][Data 00][x]		
(Depending on model)	 For South Korea, North/Latin America except 		
, , , , ,	Colombia Model		
Ack [q][][Set ID][][OK/NG][Data][x]	To tune channel to following physical/major/minor number.		
	Transmission [m][a][][0][][Data00][][Data01]		
0. Tune Command (Command: m a)	[][Data02][][Data03][][Data04][][Data05][Cr]		
This command may work differently depending on	Digital channels have a Physical, Major, and Minor		
nis command may work differently depending on model and signal.	channel number. The Physical number is the actual		
For Europe, Mid-East, Colombia, Asia except	digital channel number, the Major is the number that		
South Korea and Japan Model	the channel should be mapped to, and the Minor is		
Select channel to following physical number.	the sub-channel. Since the ATSC tuner automatically		
Transmission [m][a][][Set ID][][Data 00][]	maps the channel from the Major / Minor number, the Physical number is not required when sending a		
[Data 01][][Data 02][Cr]	command in Digital.		
	* Analog Antenna/Cable		
Analog Antenna/Cable	<u> </u>		
Data 00][Data 01] Channel Data	Data 00 : Physical Channel Number		
ata 00 : High byte channel data	- Antenna (ATV) : 02~45 (Decimal: 2 ~ 69)		
ata 01 : Low byte channel data	- Cable (CATV) : 01, 0E~7D (Decimal : 1, 14~125)		
- 00 00 ~ 00 C7 (Decimal : 0 ~ 199)	[Data 01 ~ 04]: Major/Minor Channel Number		
ata 02 : Input Source (Anales)	Data 01 & 02: xx (Don't care)		
ata 02 : Input Source (Analog) - 00 : Antenna TV (ATV)	Data 03 & 04: xx (Don't care)		
- 80 : Cable TV (CATV)	Data 05: Input Source (Analog)		
Digital Antenna/Cable/Satellite	- 00 : Antenna TV (ATV)		
Digital / tritorilla/Cable/Gatellite	- 01 : Cable TV (CATV)		
Data 00][Data 01]: Channel Data	* Digital Antenna/Cable		
ata 00 : High Channel data	Data 00 : vv (Don't caro)		
ata 01 : Low Channel data	Data 00 : xx (Don't care)		
- 00 00 ~ 27 0F (Decimal: 0 ~ 9999)	[Data 01][Data 02]: Major Channel Number		
ata 02 : Input Source (Digital)	Data 01 : High byte Channel Data		
- 10 : Antenna TV (DTV)	Data 02 : Low byte Channel Data		
- 20 : Antenna Radio (Radio)	- 00 01 ~ 27 0F (Decimal: 1 ~ 9999)		
- 40 : Satellite TV (SDTV)	[Data 03][Data 04]: Minor Channel Number		
- 50 : Satellite Radio (S-Radio)	Data 03 : High byte Channel Data Data 04 : Low byte Channel Data		
- 90 : Cable TV (CADTV)	Data 51. 2011 Sylo Orialinoi Data		
- a0 : Cable Radio (CA-Radio)	Data 05 : Input Source (Digital)		
	- 02 : Antenna TV (DTV) - Use Physical Channel		

Set ID = AII = 00

Data 00 & 01 = Channel Data is 10 = 00 0a

Data 02 = Analog Antenna TV = 00

0 0

5th Band

0 0

Acknowledgement [v][][Set ID][][OK/NG][Data][x]

0 | 1

20(decimal)

* Tune Command Examples: * This feature is varied based on the model. 1. Tune to the Analog cable (NTSC) channel 35. Ack [a][][Set ID][][OK][Data 00][Data 01] Set ID = AII = 00 [Data 02][Data 03][Data 04][Data 05] Data 00 = Channel Data is 35 = 23 Data 01 & 02 = No Major = 00 00 [x][a][][Set ID][][NG][Data 00][x] Data 03 & 04 = No Minor = 00 00 Data 05 = Analog Cable TV = 01 Total = ma 00 23 00 00 00 00 01 21. Channel(Programme) Add/Del(Skip) Tune to the digital antenna (ATSC) channel 30-3. (Command: m b) Set ID = All = 00 ► To skip current channel(programme) for next time Data 00 = Don't know Physical = 00 Data 01 & 02 = Major is 30 = 00 1E Transmission [m][b][][Set ID][][Data][Cr] Data 03 & 04 = Minor is 3 = 00 03 Data 05 = Digital Antenna TV = 22 Data 00 : Del(ATSC,ISDB)/Skip(DVB) 01 : Add Total = ma 00 00 00 1E 00 03 22 Ack [b][][Set ID][][OK/NG][Data][x] Ack [a][][Set ID][][OK][Data 00][Data 01] * Set the saved channel status to del(ATSC, ISDB)/ [Data 02][Data 03][Data 04][Data 05] skip(DVB) or add. [x][a][][Set ID][][NG][Data 00][x] For Japan Model ► To tune channel to following physical/major/minor 22. Key (Command: m c) number. ► To send IR remote key code. Transmission [m][a][][0][][Data00][][Data01] Transmission [m][c][][Set ID][][Data][Cr] [][Data02][][Data03][][Data04][][Data05][Cr] Data Key code - p.2. * Digital Antenna/Satellite Data 00: xx (Don't care) Ack [c][][Set ID][][OK/NG][Data][x] 23. Control Backlight (Command: mg) [Data 01][Data 02]: Major Channel Number Data 01: High byte Channel Data For LCD TV / LED TV Data 02: Low byte Channel Data ► To control the backlight. - 00 01 ~ 27 0F (Decimal: 1 ~ 9999) Transmission [m][g][][Set ID][][Data][Cr] [Data 03][Data 04]: Minor/Branch Channel Number Data Min: 00 to Max: 64 (Don't care in Satellite) Data 03: High byte Channel Data Ack [g][][Set ID][][OK/NG][Data][x] Data 04: Low byte Channel Data Control Panel Light (Command: mg) Data 05: Input Source (Digital/Satellite for Japan) For Plasma TV - 02 : Antenna TV (DTV) ► To control the panel light. - 07 : BS (Broadcasting Satellite) - 08 : CS1 (Communication Satellite 1) Transmission [m][g][][Set ID][][Data][Cr] - 09 : CS2 (Communication Satellite 2) Data Min: 00 to Max: 64 * Tune Command Examples: Ack [g][][Set ID][][OK/NG][Data][x] 1 Tune to the digital antenna (ISDB-T) channel 17-1. Set ID = AII = 00 Data 00 = Don't know Physical = 00

Data 05 = Digital Antenna TV = 02 Total = **ma 00 00 00 11 00 01 02**

2. Tune to the BS (ISDB-BS) channel 30.

Data 00 = Don't know Physical = 00

Data 01 & 02 = Major is 30 = 00 1E

Data 03 & 04 = Don't Care = 00 00

Total = ma 00 00 00 1E 00 00 07

Data 05 = Digital BS TV = 07

Set ID = AII = 00

Number

(high byte is 0).

Channel Number

Channel Number

- 22 : Antenna TV (DTV) - Don't Use Physical

- 26 : Cable TV (CADTV) - Don't Use Physical

- 46 : Cable TV (CADTV) - Use Major Channel

Number Only (One Part Channel)

channel data, but usually the low byte is used alone

Two bytes are available for each major and minor

4. Input select (Command: x b)		00	0	0	0		
(Main Picture Input)		01	Х	Х	Х		
To select input source for main picture. Transmission [x][b][][Set ID][][Data][Cr]		02	Х	Х	Х		
		03	Х	0	0		
ata 00 : DTV 02 : Satellite DTV ISDB-BS (Japan) 03 : ISDB-CS1 (Japan) 04 : ISDB-CS2 (Japan) 11 : CATV	•	Ack [t][][S [Data03][X : don't care Ack [t][][Set ID][][OK][Data00][Data01][Data02] [Data03][x] [t][][Set ID][][NG][Data00][x]				
20 : AV or AV1	21 : AV2						
40 : Component1 60 : RGB	41 : Component2	(Dependi	26. Extended 3D(Command: x v) (only 3D models) (Depending on model)				
90 : HDMI1 92 : HDMI3	91 : HDMI2 93 : HDMI4		► To change 3D option for TV. Transmission [x][v][][Set ID][][Data 00][]				
Ack [b][][Set ID][][OI	K/NG][Data][x]	[Data 01][Cr]					
This function depends on model and signal. 5. 3D(Command: x t) (only 3D models) (Depending on model)		00 01 02 06 07	[Data 00] 3D option 00 : 3D Picture Correction 01 : 3D Depth (3D Mode is Manual Only) 02 : 3D Viewpoint 06 : 3D Color Correction 07 : 3D Sound Zooming				
To change 3D mode for TV. Transmission [x][t][][Set ID][][Data 00][][Data 01]		08 : Normal Image View 09 : 3D Mode (Genre)					
[][Data 02][][Data 03 (Depending on model) ata Structure Data 00] 00 : 3D On 01 : 3D Off 02 : 3D to 2D	de 1) When [Dat 00 : 01 :	 [Data 01] It has own range for each 3D option determined by [Data 00]. 1) When [Data 00] is 00 00: Right to Left 01: Left to Right 					
03 : 2D to 3D lata 01] 00 : Top and Bottom 01 : Side by Side 02 : Check Board 03 : Frame Sequential 04 : Column interleaving 05 : Row interleaving		 2) When [Data 00] is 01, 02 Data Min: 0 - Max: 14 (*transmit by Hexadecimal code) Data value range(0 - 20) converts Viewpoint range (-10 - +10) automatically (Depending on model) * This option works when 3D Mode (Genre) is manual only. 					
		00 :	3) When [Data 00] is 06, 07 00 : Off 01 : On				
[Data 02], [Data 03] functions depend on model and signal. If [Data 00] is 00 (3D On), [Data 03] has no		00 :	4) When [Data 00] is 08 00 : Revert to 3D video from 3D-to-2D converted 2D video				

meaning.

If [Data 00] is 01 (3D off) or 02 (3D to 2D), [Data

If [Data 00] is 00 (3D On) or 03 (2D to 3D), [Data

03] works when 3D Mode (Genre) is manual only.

available according to broadcasting/video signal.

All 3D pattern options ([Data 01]) may not be

01], [Data 02] and [Data 03] have no meaning.

If [Data 00] is 03 (2D to 3D), [Data 01] and

[Data 02] have no meaning.

5) When [Data 00] is 09

treated as NG.

00 : Standard 02 : Cinema

04 : Manual

03: Extreme 05 : Auto

2D-to-3D video

* If conversion condition doesn't meet, command is

01: Change 3D video to 2D video, except

01: Sport

27. Auto Configure (Command: j u) (Depending on model)

➤ To adjust picture position and minimize image shaking automatically. It works only in RGB (PC) mode.

Transmission [j][u][][Set ID][][Data][Cr]

Data 01: To set

Ack [u][][Set ID][][OK/NG][Data][x]