

FRIDGE-FREEZER

User's Guide

Please read this User's Guide carefully before operating and keep it handy for reference at all times.




Table of Contents

Introduction	Registration —	4
	Important Safety Instruction —	4
	Identification of Parts	
	Tuentineation of Farts	
locata Hadi a o	Installation —	
Installation		
	Starting —	7
_		
Operation	Temperature Control	
	Quick Freeze	
	Vacation —	
	Self Test	9
	Door Alarm	9
	Ice Making ————————————————————————————————————	9
	Defrosting —	
	Water Dispenser —	
	water Dispenser	
	G E. I	•
Suggestion On	Storing Food —	12
Food storage		
Care and	General Information	13
Maintenance	Lamp Replacement ————————————————————————————————————	13
	Cleaning —	14
Trouble Shooting	Trouble Shooting	16
3		
To Reverse the	Precaution	18
Doors	How to Reverse the Doors	18
שטטע	THUM TO INCIDENCE THE DUULS ———————————————————————————————————	

Introduction

Registration

Introduction

The model and serial number are found on the rear of this unit. This number is unique to this unit and not available to others. You should record requested information here and retain this guide as a permanent record of your purchase. Staple your receipt here.

Date of Purcha	ise : _			
Dealer Purchas	:			
Dealer Address				
Dealer Phone No.				
Model No. :				
Serial No. :				

Important Safety Instruction

Precaution

This fridge-freezer must be properly installed and located in accordance with the Installation Instruction before it is used.

Never unplug your fridge-freezer by pulling on the power cord. Always grip plug firmly and pull straight out from the outlet.

When moving your appliance away from the wall, be careful not to roll over or damage the power cord.

After your fridge-freezer is in operation, do not touch the cold surfaces in the freezer compartment, particularly when hands are damp or wet. Skin may adhere to these extremely cold surfaces.

Important Safety Instruction

Precaution

Pull out the power plug prior to cleaning the fridge-freezer. Never damage, serverely bend, pull out, or twist the power cord because power cord damage may cause a fire or electronic shock. Never place glass products in the freezer because they may be broken when their inner contents are frozen.

Don't Use an Extension Cord

If possible, connect the fridge-freezer to its own individual electrical outlet to prevent it and other appliances or household lights from causing an overload.

Accessibility of Supply Plug Supply Cord Replacement

The supply plug of the refrigerator-freezer should be placed in easy accessible position for quick disconnection in emergency.

If the supply cord is damaged, it must be replaced by the manufacturer or its service agent or a similarly qualified person in order to avoid a hazard.

Danger

Risk of child entrapment.

Before you throw away your old refrigerator or freezer: Take off the doors.

Leave the shelves in place so that children may not easily climb inside.

Don't store

Don't store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.


Grounding (Earthing)

In the event of an electric short circuit, grounding (earthing) reduces the risk of electric shock by providing an escape wire for the electric current. In order to prevent possible electric shock, this appliance must be grounded. Improper use of the grounding plug can result in an electric shock. Consult a qualified electrician or service person if the grounding instructions are not completely understood, or if you have doubts on whether the appliance is properly grounded.

▲Warning

- ▲ Keep ventilation openings, in the appliance enclosure or in the built-in structure, clear of obstruction.
- ▲ Do not use mechanical devices or other means to accelerate the defrosting process, other than those recommended by the manufacturer.
- Do not damage the refrigerant circuit.
- ▲ Do not use electrical appliances inside the food storage compartments of the appliance, unless they are of the type recommended by the manufacturer.
- ▲ The refrigerant and insulation blowing gas used in the appliance require special disposal procedures. When disposal, please consult with service agent or a similarly qualified person.

Identification of Parts



If you found some parts missing from your unit, they may be parts only used in other models.

Installation

Installation

- **1.** Select a good location.

 Place your fridge-freezer where it is easy to use.
- **2.** Avoid placing the unit near heat sources, direct sunlight or moisture.
- **3.** There must be proper air circulation around your fridge-freezer to keep it operating efficiently. If your fridge-freezer is placed in a recessed area in the wall, allow at least 2 inches(5 cm) above.
- 4. To avoid vibration, the unit must be leveled. If required, adjust the leveling screws to compensate for the uneven floor. The front should be slightly higher than the rear to aid in door closing. Leveling screws can be turned easily by tipping the cabinet slightly. Turn the leveling screws counterclockwise() to
- **5.** Clean your fridge-freezer thoroughly and wipe off all dust accumulated during shipping.

raise the unit, clockwise() to lower it.

- **6.** Install accessories such as ice cube box, etc., in their proper places. They are packed together to prevent possible damage during shipment.
- **7.** Connect the power supply cord (or plug) to the outlet. Don't double up with other appliances on the same outlet.

Starting

When your fridge-freezer is installed, allow it 2-3 hours to stabilize at normal operating temperature prior to filling it with fresh or frozen foods.

If power plug is disconnected, allow 5 minutes delay before restarting.

Your fridge-freezer is now ready for use.

Operation

Temperature Control

Your fridge-freezer has two controls that let you regulate the temperature in the fridge and freezer compartments.

Fridge

- Initially set the TEMP. CONTROL at "4". Then adjust the compartment temperature according to your desire.
- 7 MAX 7 6 MIN 1
- If you want an inside temperature slightly less cold or colder, turn the knob towards MIN or MAX, respectively.

 When the surrounding temperature is low, adjust the TEMP. CONTROL 'MIN'.

Freezer

- Freezer temperature control is on the top of the fridgefreezer. Initially set the Freeze Temp at mid-point. By pressing the Freezer Temp button, you can adjust the temperature of the Freezer as indicated by the numbers of lamps lit.(the setting is composed of five steps, 5 lamps lit indicates coldest.)
- When you starting the Fridge-Freezer or connecting the power plug to the outlet, temperature setting is automatically set to the mid-point.



Quick Freeze

 This function is used when you want to freeze the foods quickly. Press the 'QUICK FREEZE' button once, and then the quick freeze operation starts with the lamp lit.

The quick freeze operation takes about 3 hours.

When its operation ends,

it automatically returns to the normal state. If you want to stop the quick freeze operation, press the 'QUICK FREEZE' button once more, the lamp goes out, and the quick freeze operation stops and the refrigerator returns to the normal state.



Vacation

This function makes the fridge-freezer work in a power saving mode which is useful for when you are away on holiday, by reducing energey consumption as much as possible. Pressing 'VACATION' starts operation with lamp ON and pressing it again stops the operation.

VACATION

For better functioning, you should set the TEMP. CONTROL to "MIN".

Self Test

This function allows you to check for operational problems. If you think you have a problem with your fridge-freezer, then press the temperature control button:

- If the indicate lights move up or down, then there is no problem with your fridge-freezer.
- If the indicate lights do not move up or down, then please leave the power connected and call your nearest service agent.

Door Alarm

When the door of the fridge is left opened for a while, the alarm sounds.

Ice Making

- To make ice cubes, fill the ice tray to the water level and place it in the freezer.
- If ice cubes are required fast, press the 'QUICK FREEZE' button.
- To remove ice cubes, hold the tray at its ends and twist gently.



To remove ice cubes easily, run water on the tray before twisting.

Defrosting


Defrosting takes place automatically.


The defrosting water flows down to the evaporating tray and is evaporated automatically.

Operation

Water Dispenser (optional)

Features





Install

Please assemble the VALVE ASSEMBLY after correctly adjusting it with a DOOR HOLE.

Filling of WATER TANK

- 1. After turning the HANDLE Tank backward with the WATER TANK installed at the DOOR, Open the CAP TANK (SMALL) and then fill water using a kettle etc.
 - * Fill water while watching a sight glass on the front of the WATER TANK.
 - * Water up to 4.5¢ can be filled.
- 2. Press and fix the CAP TANK(SMALL).
- **3.** After filling spring water, fix the HANDLE TANK at a proper position.

Drinking

- 1. Press the Dispenser Pad with a cup.
- **2.** If pressing the Pad, water inside of the Dispenser is supplied.
- **3.** If slowly removing a cup from the Pad, water will not fall down.

Do not use other beverage (milk, juice, carbonated beverage etc) than spring water. Especially beverage including grain must not be used (may result in failure).

Storing Food

- Do not store food which goes bad easily at low temperature, such as banana, and melon.
- Allow hot food to cool prior to storing. Placing hot food in the fridge-freezer could spoil other food, and lead to higher electric bills.
- When storing the food, use a container with a lid. This prevents moisture from evaporating, and helps food to keep its taste and nutrients.
- Do not block air vents with food. Smooth circulation of cold air keeps fridge-freezer temperature even.
- Do not open the door frequently. Opening the door lets warm air enter the fridge-freezer, and cause temperature to rise.
- To adjust the temperature control easily, do not store food near the temperature control dial.
- Never keep too many foods in door rack, as this may stop the door from fully closing.
- Do not store bottles in the freezer compartment they may break when frozen.
- Do not refreeze food that has been thawed. This causes loss of taste and nutrition.

If you keep the fridge-freezer in a hot, and humid place, frequently open its door or put a lot of vegetables in it, dew may form in it, which has no effect on its performance.

Remove the dew with dust cloth free from care.

Care and Maintenance

General Information

Power Failure


• 1~2 hour power failure does no harm to the foods stores. Try to avoid opening and closing the door too frequently.

If You Move

- Take out foods from the fridge-freezer and firmly fix the loose items with tape.
- Turn the leveling screws until they stop before moving the fridge-freezer. Otherwise the screw may scratch the floor or the fridge-freezer cannot move.

Anti Condensation Pipe

The Anti-Condensation pipe is installed around the front side of fridge-freezer as well as on the partition between fridge compartment and freezer compartment to prevent dewing.




Anti-Condensation

• Especially after installation or when ambient temperature is high, the fridge-freezer may feel hot, which is quite normal.

Lamp Replacement

- 1. Unplug the power cord from the outlet.
- 2. Remove fridge shelves.
- **3.** To remove the lamp cover, insert ⊖ type driver in the underside of the lamp cover and pull it out forwards.
- **4.** Turn the lamp counterclockwise.
- Assemble in reverse order of disassembly.
 Replacement lamp must be the same specification as original.
 - You must check the O-RING, which is made by rubber and prevent electric spark.



Cleaning

Before Cleaning

Be sure to unplug the power.

Exterior

Clean the outside of the fridge-freezer with a soft cloth soaked with hot water or liquid detergent. If you use a detergent, be sure to wipe it with a clean wet cloth.

Interior

As above.

After Cleaning

Check that the power cord is not damaged, power plug has not overheated, and that the power plug is tightly inserted into the outlet.

A Warning

Be sure to dry the appliance with a cloth after washing it with water.

Do not use abrasive, petroleum, benzene, thinner, hydrochloride acid, boiling water, rough brush, etc, as they may damage parts of the fridge-freezer.

Care and Maintenance

GRILLE and DRIP TRAY

- **1.** After removing the HOLE part of the GRILLE with the finger, slowly pull the DRIP TRAY out.
- **2.** fter discharging Drip Water inside of the DRIP TRAY, clean and fully rinse the GRILLE and the DRIP TRAY.
- **3.** Wipe moisture out around the DOOR part and the DRIP TRAY using a clean cloth.

Exterior Dispenser

Wipe moisture etc out outside of Dispenser and on the Dispenser Pad using a cloth.

Water Tank

- **1.** Lift the WATER TANK up by pressing the fixing LEVER on the bottom of WATER TANK and then remove it.
- **2.** After removing the CAP TANK (BIG), clean and fully rinse the inside/outside part of the WATER TANK by using neutral cleansing agent.

Cap Tank(Big & Small)

Clean and fully rinse the Cap Tank (Big & Small) by using neutral cleansing agent.

Especially for the groove part of the CAP TANK, it is convenient to cleanse it by using a small brush.

Valve Assembly

Clean and fully rinse the VALVE ASSEMBLY by using a small brush. Rinse it while operating the bottom part of the valve assembly. Always fix the Sealing Rubber separated for cleansing at the existing position (may result in water leakage).

Trouble Shooting

Before calling for service, check this list. It may save you both time and expense. This list includes common occurrences that are not the result of defective workmanship or materials in this appliance.

Problem

Possible Causes

Fridge-Freezer does not operate

 Power plug may be unplugged from the electric outlet.

Plug it in securely.

• House fuse has blown or circuit breaker has tripped.

Check and/or replace fuse and reset circuit breaker.

Power cut.
 Check house lights.

Fridge or Freezer Compartment Temperature too warm

- Temperature control not set on proper position. Refer to Temperature Control section.
- Appliance is placed close to heat source.
- Warm weather-frequent door openings.
- Door left open for a long time.
- Package holding door open or blocking air duct in freezer compartment.

Vibration or Rattling or Abnormal Noise

• The floor on which the fridge-freezer is installed may be uneven or the fridge-freezer may be unstable.

Make it even by rotating the leveling screw.

• Unnecessary objects placed in the back side of the fridge-freezer.

Frost or Ice Crystals on frozen Food

- Door may have been left ajar or package holding door open.
- Too frequent or too long door openings.
- Frost within package is normal.

Moisture forms on Cabinet Surface

• This phenomenon is likely to occur in a wet space. Wipe it with a dry towel.

Trouble Shooting

Problem

Possible Causes

Moisture collects inside

- Too frequent or too long door openings.
- In humid weather, air carries moisture into fridge when doors are opened.

Fridge has odor

- Foods with strong odors should be tightly covered or wrapped.
- Check for spoiled food.
- Interior needs cleaning.

 Refer to CLEANING section

Door not closing properly

- Food package is keeping door open.
 Move packages that keep door from closing.
- Fridge-freezer is not level.
 Adjust the leveling screws.
- The floor on which the fridge-freezer is installed may be uneven or the fridge-freezer may be unstable.

Slightly raise the front side with the leveling screw.

Interior light does not work

- No power at outlet.
- Light lamp needs replacing.

 Refer to the Lamp Replacement section

To Reverse the Doors


Your fridge-freezer is designed with reversible doors, so that they may open from either the left of right hand side to suit your kitchen design.

Precaution


- 1. Before reversing the door, first of all, you should take out food and accessories like shelves or trays which are not fixed in the fridge-freezer.
- 2. Use Torque Wrench or Spanner to fix or remove the bolt.
- **3.** Do not lay the fridge-freezer down. This will cause problems.
- **4.** Be careful not to drop the doors in disassembling or assembling.

How to Reverse the Doors


Remove SCREWS 3 after removing a
 CAP 2 from the right part of the
 refrigerator room HANDLE 1. Remove 2
 SCREWS 3 on the bottom part of the
 refrigerator room HANDLE 1. The freezer
 room HANDLE 5 may be also separated in
 the same sequence as in the refrigerator
 room HANDLE 1.




2. Remove screw 7 and remove Cover 6 and move Cap Cover 8. And, remove screw 9, Hinge-L 10, and remove pin 11. Remove the Freezer Door 23, and move the position of the cap 12. Move the position of bracket door 13 and screw 14.



3. Remove bolt **(5)** and remove the Hinge-C **(6)** and the Fridge Door **(7)**. Move the position of the cap **(8)**. Move the position of bracket door **(2)** and screw **(2)**.



- 4. Move the position of Hinge-U pin (9), and Cap, Top cover (10) Assemble the Fridge Door (17) Assemble Hinge-C (16) and bolt (15) Assemble F-Door (10). Assemble the Hinge-L (10) and bolt (9). Assemble Low Cover (6) and screw (7).
- 5. Install HANDLES (5) installed at the existing freezer room, at the refrigerator room. Adjust the bottom part of HANDLES to the groove and then fasten 2 screws (3) after removing the CAP (1). After bolting SCREWS in the side of the refrigerator room DOOR, press and insert the CAP (2). Insert the CAP (4) to hole which the HANDLE (1) was installed previous. The freezer room HANDLES (1) are assembled in the same manner as above using the existing.
- 6. Stop the groom where the existing HANDLE 1, 5 was installed at by using the CAP removed in the initial installation.



Reversing the doors is not covered by the warranty.

Memo





LG Twin Tower, 20, Yoido-Dong, Youngdungpo-Gu, Seoul, 150-721, Korea. http://www.lge.co.kr

P/No. 3828JD8441X

Printed in Korea