

User's Guide

M198WA
M208WA
M228WA

Make sure to read the **Safety Precautions** before using the product.

Keep the User's Guide(CD) in an accessible place for future reference.

See the label attached on the product and give the information to your dealer when you ask for service.



Safety Precautions

Please read these safety precautions carefully before using the product.



Warning

If you ignore the warning message, you may be seriously injured or there is a possibility of accident or death.



Caution

If you ignore the caution message, you may be slightly injured or the product may be damaged



Precautions in installing the Product



Warning

- **Keep away from heat sources like electrical heaters.**
 - Electrical shock, fire, malfunction or deformation may occur.
- **Keep the packing anti-moisture material or vinyl packing out of the reach of children.**
 - Anti-moisture material is harmful if swallowed. If swallowed by mistake, force the patient to vomit and visit the nearest hospital. Additionally, vinyl packing can cause suffocation. Keep it out of the reach of children.
- **Do not put heavy objects on the product or sit upon it.**
 - If the product collapses or is dropped, you may be injured. Children must pay particular attention.
- **Do not leave the power or signal cable unattended on the pathway.**
 - The passerby can falter, which can cause electrical shock, fire, product breakdown or injury.
- **Install the product in a neat and dry place.**
 - Dust or moisture can cause electrical shock, fire or product damage.
- **If you can smell smoke or other odors or hear a strange sound unplug the power cord and contact the service center.**
 - If you continue to use without taking proper measures, electrical shock or fire can occur.
- **If you dropped the product or the case is broken, turn off the product and unplug the power cord.**
 - If you continue to use without taking proper measures, electrical shock or fire can occur. Contact the service center.
- **Do not drop an object on or apply impact to the product. Do not throw any toys or objects on the product screen.**
 - It can cause injury to human, problem to product and damage the display.



Caution

- **Make sure the product ventilation hole is not blocked. Install the product in a suitably wide place (more than 10cm from the wall)**
 - If you install the product too close to the wall, it may be deformed or fire can break out due to internal heat.
- **Do not block the ventilation hole of the product by a tablecloth or curtain.**
 - The product can be deformed or fire can break out due to overheating inside the product.
- **Install the product on a flat and stable place that has no risk of dropping the product.**
 - If the product is dropped, you may be injured or the product may be broken.
- **Install the product where no EMI occurs.**
- **Keep the product away from direct sunlight.**
 - The product can be damaged.

Safety Precautions

Electrical Power Related Precautions

Warning

- **Make sure to connect the power cable to the grounded current.**
 - You may be electrocuted or injured.
- **Use the rated voltage only.**
 - The product can be damaged, or you may be electrocuted.
- **In the presence of thunder and lightning, never touch the power cord and signal cable because it can be very dangerous.**
 - It can cause electric shock.
- **Do not connect several extension cords, electrical appliances or electrical heaters to a single outlet. Use a power bar with a grounding terminal designed for exclusive use with the computer.**
 - A fire can break out due to overheating.
- **Do not touch the power plug with wet hands. Additionally, if the cord pin is wet or covered with dust, dry the power plug completely or wipe dust off.**
 - You may be electrocuted due to excess moisture.
- **If you don't intend to use the product for a long time, unplug the power cable from the product.**
 - Covering dust can cause a fire, or insulation deterioration can cause electric leakage, electric shock or fire.
- **Fix the power cable completely.**
 - If the power cable is not fixed completely, a fire can break out.
- **Hold the plug when pulling out the power cable. Do not bend the power cord with excessive force or put heavy objects on the power cord.**
 - The power line can be damaged, which may cause electric shock or fire.
- **Do not insert a conductor (like a metal chopstick) into one end of the power cable while the other end is connected to the input terminal on the wall. Additionally, do not touch the power cable right after plugging into the wall input terminal.**
 - You may be electrocuted.
- **The power supply cord is used as the main disconnection device. Ensure that the socket-outlet is easily accessible after installation.**
- **Main power breaker is the power cord and this breaking device must be located at a location where it is easy to operate.**

Caution

- **Do not unplug the power cord while the product is in use.**
 - Electrical shock can damage the product.

Precautions in Moving the Product

Warning

- **Make sure to turn off the product.**
 - You may be electrocuted or the product can be damaged.
- **Make sure to remove all cables before moving the product.**
 - You may be electrocuted or the product can be damaged.

Safety Precautions

Caution

- **Do not shock the product when moving it.**
 - You may be electrocuted or the product can be damaged.
 - **Do not dispose the product-packing box. Use it when you move.**
 - **Make the panel face forward and hold it with both hands to move.**
 - If you drop the product, the damaged product can cause electric shock or fire. Contact with the service center for repair.
-

Precautions in Using the Product

Warning

- **Do not disassemble, repair or modify the product at your own discretion.**
 - Fire or electric shock accident can occur.
 - Contact the service center for check, calibration or repair.
- **When cleaning the brown tube surface, unplug the power cord and scrub with soft cloth to prevent scratching. Do not clean with a wet cloth.**
- **Keep the product away from water.**
 - Fire or electric shock accident can occur.

Caution

- **Do not put or store inflammable substances near the product.**
 - There is a danger of explosion or fire due to careless handling of the inflammable substances.
 - **When cleaning the brown tube surface, unplug the power cord and scrub with soft cloth to prevent scratching. Do not clean with a wet cloth.**
 - The water can sink into the product, which can cause electric shock or serious malfunction.
 - **Take a rest from time to time to protect your vision.**
 - **Keep the product clean at all times.**
 - **Take a comfortable and natural position when working with a product to relax the muscles.**
 - **Take a regular break when working with a product for a long time.**
 - **Do not press strongly upon the panel with a hand or sharp object such as nail, pencil or pen, or make a scratch on it.**
 - **Keep the proper distance from the product.**
 - Your vision may be impaired if you look at the product too closely.
 - **Set the appropriate resolution and clock by referring to the User's Guide.**
 - Your vision can be impaired.
 - **Use authorized detergent only when cleaning the product. (Do not use benzene, thinner or alcohol.)**
 - Product can be deformed.
-

On Disposal


- **The fluorescent lamp used in this product contains a small amount of mercury.**
- **Do not dispose of this product with general household waste.**
Disposal of this product must be carried out in accordance to the regulations of your local authority.

Before Connecting to the PC

Connecting the stand

- Before setting up the product, ensure that the power supply, the computer system, and other attached devices is turned off.

1. Place the monitor with its front facing downward on a soft cloth.
2. Connect the Stand Base to the Stand Body and press latches at the button toward each end.
3. Connect the Stand, assembled in step 2, to the Monitor Panel until you hear a "Click".
4. Once assembled take the monitor up carefully and face the front side



Important

- Once you connect the stand base, try not to disconnect it.
- Do not carry the product upside down holding only the stand base. The product may fall and get damaged or injure your foot.

Before Connecting to the PC




- Before setting up the product, ensure that the power supply, the computer system, and other attached devices is turned off.

Positioning your display

1. Adjust the position of the panel in various ways for maximum comfort.

■ Tilt Range : $-3^{\circ} \sim 10^{\circ}$


■ Swivel : 350°



Warning:

When adjusting the angle of the screen, do not put your finger(s) in between the head of the monitor and the stand body. You can hurt your finger(s).

Theft prevention locking device




Locking Device


Use this locking cable (This has to be purchased separately if required.) to prevent theft.

Name and Function of the Parts

● Name of the Remote Control Buttons



TV : TV button
POWER
INPUT



Each time you press the Input button it will change to
 TV → AV → Component → RGB → DVI.
 If nothing is inputted for several seconds the screen will automatically move to the selected menu.

MTS

Press repeatedly to select **Mono**, **Stereo**, **SAP** sound tone.
 But **Stereo**, **SAP** mode are available only if included on the broadcast signal.

A.PROG

Auto Channel Button
 PC: Automatic adjustment function (Operational for the analog signal only)

MEMORY/ERASE

User can do manual channel selection and store or erase individual channels.


CAPTION

Select a closed caption
 Off → Mode1 → Mode2 → Text1 → Text2

Number buttons

Able to directly select and change channel.


● Inserting batteries into remote control.



1. Take out the battery cap.
2. Insert the batteries with correct polarity (+/-).
3. Close the battery cap.
 - Dispose of used batteries in the recycle bin to prevent environmental pollution.

Name and Function of the Parts

Name of the Remote Control Buttons



MUTE

Switches the sound on or off.

FCR

Favorite channel button.

CH (▲ ▼) Buttons

Up and Down Button.
Able to change channel.

VOL (◀ ▶) Buttons

Volume Button

ENTER Button

Use when functional adjustment is completed.

MENU

Use this button to enter the On Screen Display menu.

REVIEW


Turn to the last channel viewed.

SLEEP : SLEEP Timer

You can set a time period after which the all modes should switch itself to standby.

Press the key repeatedly to select the number of minutes.

Press the key repeatedly to select the number of minutes.



APC Button(Auto Picture Control)

Press repeatedly to select **Clear**, **Optimum**, **Soft**, **User** picture mode.

DASP Button (Digital Auto Sound Processing)

Use this button to select the sound tone.

Press repeatedly to select **Flat**, **Music**, **Movie**, **Sports**, **User** sound tone.



ARC/*

To select the image size of the screen.

- When TV, AV mode: 16:9, Horizon, Zoom1, Zoom2, 4:3
- When RGB/DVI /Component mode: 16:9, 4:3

Name and Function of the Parts


● Rear View



- ❶ **Power Connector** : Connect the power cord.
- ❷ **DVI Digital Signal Connector**
- ❸ **D-Sub Analog Signal Connector**
- ❹ **RGB, DVI Sound Jack** : Connect to the jack in the PC sound card or D-TV sound Output Jack.
- ❺ **TV Tuner Jack** : Connect the antenna.
- ❻ **AV Input Terminal**
- ❼ **Headphone/Earphone Connection Terminal**
- ❽ **Component Input Terminal**

Name and Function of the Parts

● AV Input Terminal



① Video Input Terminal

② Audio Input Terminal


③ S-Video Input Terminal

Connecting to External Devices


■ ■ ■ Connecting to your PC

1. First of all, see if the computer, product and the peripherals are turned off.
Then, connect the signal input cable.

Rear side of the product.



- (A)** Connecting with the D-Sub signal input cable.



Rear side of the product.

Macintosh Adapter (Not included)

Use the standard Macintosh adapter since an incompatible adapter is available in the market.
(Different signaling system)

- (B)** Connecting with the DVI signal input cable.



Rear side of the product.

2. Connect the audio cable.




Rear side of the product.


- Make sure to check the sound card connection terminal in the PC before connecting to the product.
If the PC sound card supports both Speaker Out and Line Out, change it to Line Out by setting the jumper or the PC application. (For more details, refer to the sound card user's guide.)
 - **Speaker Out** : The terminal connected to the speaker that is not equipped with an amplifier.
 - **Line Out** : The terminal connected to the speaker equipped with an amplifier.
If Audio Out in the PC sound card has only Speaker Out, reduce the PC volume. This product is integrated with an amplifier.

Connecting to External Devices

3. Connect the power cord.



4. ① Turn on power by pressing the power button on the product.




Power button

② Turn on the PC.


5. Select an input signal. Press the INPUT button on the remote control to select the input signal. Or, press the INPUT button at the top side of the product.

INPUT → ENTER

A • Select RGB



B • Select DVI



Each time you press the Input button it will change to TV → AV → Component → RGB → DVI
If nothing is inputted for several seconds the screen will automatically move to the selected menu.



Note

- Directly connect to a grounded power outlet on the wall or a power bar with a ground wire.


Connecting to External Devices

■ ■ ■ Connecting to VCR/DVD

1. Connect the video/audio cable as shown in the figure below and then connect the power cord (See page 11).


(A) When using the RCA cable.

- Connect the input terminal with a proper colour match.



(B) When using the S-Video cable.

- Connect to the S-Video input terminal to watch high image quality movies.




2. Select an input signal.

Press the **INPUT** button on the remote control to select the input signal.
Or, press the **INPUT** button at the top side of the product.

INPUT → ENTER

- (A)** When connecting with a RCA cable.
- Select **AV**
- (B)** When connecting with a S-Video cable.
- Select **AV**



Each time you press the Input button it will change to TV → AV → Component → RGB → DVI
If nothing is inputted for several seconds the screen will automatically move to the selected menu.



Note


- In case the RCA cable is connected simultaneously as S-Video cable is connected, S-Video cable is first.

Connecting to External Devices

■ ■ ■ Connecting to Set-top Box /DVD (480i/576i/480p/576p/720p/1080i)

1. Connect the video/audio cable as shown in the figure below and then connect the power cord (See page 11).


- Connect the input terminal with a proper color match.



2. Select an input signal.
Press the INPUT button on the remote control to select the input signal.
Or, press the INPUT button at the top side of the product.

INPUT → ENTER

- Select **Component**




Each time you press the Input button it will change to TV → AV → Component → RGB → DVI
If nothing is inputted for several seconds the screen will automatically move to the selected menu.

Connecting to External Devices



■ ■ ■ When watching RGB/DVI from the Set-top Box /DVD

1. Connect the D-sub cable, RCA/PC cable as shown in the below figure and then connect the power cord. (see page 11)



2. Select an input signal.
Press the INPUT button on the remote control to select the input signal.
Or, press the INPUT button at the top side of the product.

INPUT → ENTER




Each time you press the Input button it will change to TV → AV → Component → RGB → DVI
If nothing is inputted for several seconds the screen will automatically move to the selected menu.

Connecting to External Devices

■ ■ ■ When Watching TV


1. Check if the antenna cable is connected at the rear side of the product and then, connect the power cord.



2. Select an input signal.
Press the INPUT button on the remote control to select the input signal.
Or, press the INPUT button at the Top of the product.

INPUT → ENTER


- Select TV





Each time you press the Input button it will change to TV → AV → Component → RGB → DVI
If nothing is inputted for several seconds the screen will automatically move to the selected menu.

To arrange cables using cable management


1. Arrange the cables in the center as shown in the following picture.




2. Fit the cable management to the Holder Groove downward.



* When you want remove it.



Push down slightly.




Push up slightly to remove it.

Warning

- Do not use the cable management as a handle for the Monitor.
- Do not press the cable management.

Adjusting the Screen

● Name of the Buttons in the Screen Adjustment Unit



- 1 Power Indicator**
 - This Indicator lights up blue when the display operates normally (On Mode). If the display is in Sleep (Energy Saving) Mode, this indicator colour changes to amber.
- 2 Power Button**
 - Use this button to turn the product on and off.
- 3 MENU Button**
 - Use this button to show/hide the OSD (On Screen Display) menu screen.
- 4 OSD Select/Adjust Button**
 - Use this button to select an icon or adjust the setting in the OSD screen.
- ▼ ▲**
 - Use this button to control the channel for the TV signal.
- ◀ ▶**
 - Adjust the volume.



Adjusting the Screen

● Name of the Buttons in the Screen Adjustment Unit

5


ENTER Button

- ENTER button is usually used in choosing the MENU.
When there is no MENU on the screen pushing the ENTER button will give the information about the current input source.

6

INPUT Button

TV	Television
AV	CVBS, S-Video
Component	HDTV, DVD
RGB	D-Sub analog signal
DVI	DVI Digital signal



Each time you press the Input button it will change to TV → AV → Component → RGB → DVI
If nothing is inputted for several seconds the screen will automatically move to the selected menu.

7

IR Receiver

- The unit that receives the signal from the remote control.

Adjusting the Screen

OSD (On Screen Display) Menu

Icon	Function Description
 Channel	Set/Select the channel when using the TV
 Picture	Adjusting the picture function.
 Sound	Adjusting the sound function.
 Timer	Adjusting the time function.
 Special	Selecting the special function.
 Screen	Adjusting the screen function.

Note




OSD(On Screen Display)

The OSD function enables you to adjust the screen status conveniently since it provides graphical presentation.

Adjusting the Screen

● OSD (On Screen Display) Screen Tracking Order




- 1 Press the **MENU** Button, then the main menu of the OSD will appear.
- 2 To access a control, use the ▼ ▲ Buttons.
- 3 When the icon you want becomes highlighted, press the **ENTER** Button.
- 4 Use the ▼ ▲ ◀ ▶ Buttons to adjust the item to the desired level.
- 5 Accept the changes by pressing the **ENTER** Button.
- 6 Exit the OSD by pressing the **MENU** Button repeatedly .

Adjusting the Screen



Channel ID set/Select the channel when using the TV



Auto Program Press ► button to start automatic programming. All available TV channels are searched and stored automatically. To stop Auto Program progress, press the **MENU** button.
• Wait for Auto Program progress to complete the channel search cycle before choosing a channel.
The TV scans for over-the-air channels and then channels are provided by a cable service.

Manual program **TV/CATV** Press ► button and then use ◀ ► button to select the channel.

Erase/Memory User can do manual channel selection and store or erase individual channels.
Press ► button and then use ◀ ► button to select a channel you want to add to memory or erase.

Fine In case of poor reception, you can improve the reception by fine tuning. Use the ◀ ► buttons to fine tune for the best picture and sound.

Favorite channel This function lets you select your favorite channels directly. Press the ▼ ▲ ◀ ► buttons to select a channel number.


* **FCR Button (remote control)** : Rotate Favorite channel.

Adjusting the Screen




PICTURE ID adjust the picture function(RGB-PC/DVI-PC)

APC (Auto Picture Control)



The **APC** function automatically adjusts the screen image quality.


- **Clear**
Select this option to display with a sharp image.
- **Optimum**
The most general and natural screen display status.
- **Soft**
Select this option to display with a mild image.
- **User**
Select this option to use the user-defined settings.



Contrast : To adjust the contrast of the screen.


Brightness : To adjust the brightness of the screen.

ACC (Auto Color Control)



The **ACC** function automatically adjusts the screen colour set.

- **9300K**
Slightly purplish white.
- **6500K**
Slightly bluish white.
- **sRGB**
Slightly lower brightness.
- **User**
Select this option to use the user-defined settings.



Red / Green / Blue

Set your own colour levels.

Adjusting the Screen



PICTURE ID adjust the picture function(RGB-PC/DVI-PC)


- XD** **XD** is LG Electronics unique picture improving technology to display a real **HD** source through an advanced digital signal processing algorithm.
It's not available to use this function in **RGB-PC** or **DVI-PC** modes.
- Cinema** When you watch the movie, this function adjusts the set to the best picture appearance.
It's not available to use this function in **RGB-PC** or **DVI-PC** modes.
- Reset** Return to the default settings **APC**, **ACC** at the factory.

Adjusting the Screen




PICTURE ID adjust the picture function (TV/AV/Component/RGB-DTV/DVI-DTV)

APC (Auto Picture Control)



The **APC** function automatically adjusts the screen image quality.

- **Clear**
Select this option to display with a sharp image.
- **Optimum**
The most general and natural screen display status.
- **Soft**
Select this option to display with a mild image.
- **User**
Select this option to use the user-defined settings.



Contrast : To adjust the contrast of the screen.


Brightness : To adjust the brightness of the screen.

Color : To adjust the colour to desired level.

Sharpness : To adjust the clearness of the screen.


Tint : To adjust the tint to desired level.

ACC (Auto Color Control)



The **ACC** function automatically adjusts the screen color set.

- **Cool**
Slightly purplish white.
- **Normal**
Slightly bluish white.
- **Warm**
Slightly reddish white.
- **User**
Select this option to use the user-defined settings.



Red / Green / Blue


Set your own colour levels.

Adjusting the Screen



PICTURE ID adjust the picture function (TV/AV/Component/RGB-DTV/DVI-DTV)

XD



XD is LG Electronics unique picture improving technology to display a real **HD** source through an advanced digital signal processing algorithm.
Manual is activated after selecting the user of **APC**.

Cinema (Function works in the following mode - TV, AV, Component 480i/576i)


When you watch the movie, this function adjusts the set to the best picture appearance.

Reset Return to the default settings **APC**, **ACC**, **XD**, **Cinema** at the factory.

Adjusting the Screen




SOUND ID to adjust the sound function



DASP (Digital Auto Sound Processing)

The best sound tone quality will be selected automatically depending on the video type that you're currently watching.

- **Flat** : The most commanding and natural audio.
- **Music** : Select this option to enjoy the original sound when listening to the music.
- **Movie** : Select this option to enjoy sublime sound.
- **Sports** : Select this option to watch sports broadcasting.
- **User** : Select this option to use the user-defined audio settings.



AVL

To adjust uneven sound volumes across all channels or signals automatically to the most appropriate level. To use this feature, select **On**.


Balance

Use this function to balance sound from the left and right speakers.

Adjusting the Screen



TIMER ID to adjust the time function



Clock

This function is used to set up of current time.

You must set the time correctly before using **On/Off timer** function.

- 1) Press the **MENU** button and then use **▼▲** button to select the **Timer** menu.
- 2) Press the **▶** button and then use **▼▲** button to select the **Clock** menu.
- 3) Press **▶** button and then use **▼▲** button to set the hour(00~12 AM/PM).
- 4) Press **▶** button and then use **▼▲** button to set the minutes(00~59).
The default value is -- : --.
- 5) Press the **ENTER/MENU** button to save.

Off/On timer

The **Off timer** automatically switches the set to off mode at the pre-set time.

- 1) Press the **MENU** button and then use **▼▲** button to select the **Timer** menu.
- 2) Press the **▶** button and then use **▼▲** button to select **Off timer** or **On timer**.
- 3) Press the **▶** button and then use **▼▲** button to set the hour(00~12 AM/PM).
- 4) Press the **▶** button and then use **▼▲** button to set the minutes(00~59).
- 5) Press the **▶** button and then use **▼▲** button to select **On** or **Off**.
- 6) Only **On timer** function; Press the **▶** button and then **▼▲** button to adjust volume level and programme number.
- 7) Press the **ENTER/MENU** button to save.

Auto off

If **Auto off** is active and there is no input signal, the set switches to off mode automatically after 10 minutes. (It is not working in PC)

- 1) Press the **MENU** button and then use **▼▲** button to select the **Auto off** menu.
- 2) Press the **▶** button and then use **▼▲** button to select **On** or **Off**.
- 3) Press the **ENTER/MENU** button to save .




Note

- In the event of power interruption (disconnection or power failure), the **Clock** must be reset.
- Two hours after the set is switched on by the **On timer** function it will automatically switch back to off mode unless a button has been pressed.
- Once the **On** or **Off timer** is set, these functions operate daily at the preset time.
- **Off timer** function overrides **On timer** function if they are set to the same time.
- The set must be in off mode for the **On timer** to work.
- **On timer** will move on to auto off if no activity is received in 2hours after setting the **On timer**.
- If the monitor switches to sleep mode when using the PC, "Clock" menu dose not operate.

Adjusting the Screen



SPECIAL ID to Select the special function



Language

To choose the language in which the control names are displayed.

Key lock

Use the ▼▲ buttons to select **On** or **Off**. It can be set up so that it can only be used with the remote control. This feature can prevent unauthorized viewing.

In order to lock the OSD screen adjustment, set the **Key lock** tab to the 'On' position.

In order to unlock it, do the following :

Push the **menu** button on the remote control and set **Key lock** to the 'Off' position.

Caption/Text

Use the ▼▲ buttons to select caption mode.

Text services give a wide variety of information on all kind of subjects(ex. captioned program lists, weather forecasts, stock exchange topics, news for hearing-impaired....) on up to half of the screen. But not all stations offer text services, even though they might offer captioning.

In the event you are receiving a poor signal, an empty black box may appear and disappear, even when the text mode is selected. This is a normal when receiving a poor signal.

This set is programmed to remember the **Caption/Text** mode it was last set to, when you turn the power off.

DDC-CI

DDC/CI(Display Data Channel Command Interface) is communication protocol for communications between PC and monitor.

DDC/CI makes it possible to adjust and setup detailed functions on PC instead of the monitor OSD.

Monitor can be adjusted with PC by connecting communication between PC and monitor when DDC/CI is ON, and monitor cannot be adjusted with PC because communication between PC and monitor is disconnected when DDC/CI is OFF.

XD Demo


Use it to see the difference between XD demo on and XD Demo off.

(XD Demo function is not available in RGB PC/ DVI PC mode.)

Adjusting the Screen



SCREEN ID to adjust the screen function



Auto config.

This button is for the automatic adjustment of the screen **Position**, **Clock** and **Phase**. (It is working in RGB-PC.)

Manual config.

This button is for the manual adjustment of the screen **Position**, **Clock** and **Phase**.

- **H-Position** (It is working In RGB-PC, RGB-DTV, DVI-DTV, Component mode.)
To move the displayed image left or right.
- **V-Position** (It is working In RGB-PC, RGB-DTV, DVI-DTV, Component mode.)
To move the displayed image up or down.
- **Phase** (It is working in RGB-PC.)
To adjust the focus of the display. This item allows you to remove any horizontal noise and clear or sharpen the image of characters.
- **Clock** (It is working in RGB-PC.)
To minimize any vertical bars or stripes visible on the screen background.
The horizontal screen size will also change.

ARC

To select the image size of the screen.

- **When TV, AV mode:** 16:9, Horizon, Zoom1, Zoom2, 4:3
- **When RGB/DVI/Component mode:** 16:9, 4:3

Reset

Use this function to reset the product to the factory default. However, language selection will not be initialized.

Troubleshooting

No image is displayed

- Is the product's power cord connected?
 - Is the power indicator turning on?
 - Power is on, power indicator is blue but the screen appears extremely dark.
 - Does the power indicator look amber?
 - Does the 'Out of range' message appear?
 - Does the 'Check signal cable' message appear?
- Check if the power cord is properly connected to the outlet.
 - See if the power switch is turned on.
 - Adjust brightness and contrast again.
 - If the product is in power saving mode, move the mouse or press any key.
 - In DVD Player or Set-top Box, check the power status of connected device.
 - The signal from the PC (video card) is out of the vertical or horizontal frequency range of the product. Adjust the frequency range by referring to the Specifications in this user's guide.
 - * **Maximum resolution**
 - 19 inch : **RGB** : 1440 X 900 @75 Hz
 - DVI** : 1440 X 900 @60 Hz
 - 20.1 inch : 1680 X 1050 @60 Hz
 - 22 inch : 1680 X 1050 @60 Hz
 - The signal cable between PC and product is not connected. Check the signal cable.
 - Press the 'INPUT' button in the remote control to check the input signal.

'Unknown Product' message appears when the product is connected.

- Did you install the driver?
- Install the product driver, which is provided with the product, or download it from the web site. (<http://www.lge.com>)
 - See if the plug&play function is supported by referring to the video card user's guide.



Note

* **Vertical frequency:** To enable the user to watch the product display, screen image should be changed tens of times every second like a fluorescent lamp. The vertical frequency or refresh rate is the times of image display per second. The unit is Hz.

* **Horizontal frequency:** The horizontal interval is the time to display one vertical line. When the 1 is divided by horizontal interval, the number of horizontal lines displayed every second can be tabulated as the horizontal frequency. The unit is kHz.

Troubleshooting

The screen image looks abnormal.

- Is the screen position wrong?
 - Adjust the Position menu in OSD.
 - See if the video card resolution and frequency are supported by the product. If the frequency is out of range, set to the recommended resolution in the Control Panel – Display – Setting menu.
- Do thin lines appear on the background screen?
 - Adjust the Clock menu in OSD.
- Horizontal noise appears or the characters look blurred.
 - Adjust the Phase menu in OSD.

After-image appears on the product.

- After-image appears when the product is turned off.
 - If you use a fixed image for a long time, the pixels may be damaged quickly. Use the screen saver function.

The TV function does not work.

- The TV signal is not being received.
 - See if you have selected the proper channel mode.
 - Use the automatic channel setup function.
 - Check if the TV antenna is properly connected.

Troubleshooting

The audio function does not work.

- | | |
|---|---|
| <ul style="list-style-type: none">● No sound?● Sound is too low. | <ul style="list-style-type: none">• Check if the audio cable is connected properly.• Adjust the volume.• Check if the sound is set properly.• Adjust the volume. |
|---|---|

Screen color is abnormal.

- | | |
|---|---|
| <ul style="list-style-type: none">● Screen has poor color resolution (16 colors).● Screen color is unstable or mono-colour.● Do black spots appear on the screen? | <ul style="list-style-type: none">• Set the color resolution to more than 24 bits (true colour)
Select Control Panel – Display – Settings
– color Table menu in Windows.• Check the connection status of the signal cable.
Or, re-insert the PC video card.• Several pixels (red, green, white or black colour) may appear on the screen, which can be attributable to the unique characteristics of the LCD panel. It is not a malfunction of the LCD. |
|---|---|

Specifications

The product specifications can change without prior notice for product improvement.

[19 inch]

LCD Panel	Screen Type	19 inches Wide (48.14 cm) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel Visible diagonal size: 48.14 cm
	Pixel Pitch	0.285 mm
Video Signal	Max. Resolution	RGB : 1440 X 900 @75 Hz DVI : 1440 X 900 @60 Hz
	Recommended Resolution	1440 X 900 @60 Hz
	Horizontal Frequency	28 - 83 kHz
	Vertical Frequency	56 - 75 Hz
	Synchronization Type	Separate Sync, Digital
Input Connector		S-Video, Composite video, TV, D-Sub Analog, DVI-D PC Audio In, Headphone/Earphone, component
Power	Rated Voltage	AC 100-240V~ 50/60Hz 1.0A
	Power Consumption	On Mode : 50 W (Typ.) Sleep Mode ≤ 1 W Off Mode ≤ 1 W
Tilt	Tilt Range	-3° ~ 10°
	Swivel	350°
Dimension/Weight	Size (WxLxH)	456.8 mm x 230.0 mm x 395.0 mm
	Weight (excl. package)	4.9 kg (10.8 lbs)
Environmental Conditions	Operational Condition	Temperature: 10°C ~ 35°C , Humidity: 20% ~ 80%
	Storage Condition	Temperature: -10°C ~ 60°C , Humidity: 5% ~ 90%

Specifications

The product specifications can change without prior notice for product improvement.

[20.1 inch]

LCD Panel	Screen Type	20.1 inches Wide (51.113 cm) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel Visible diagonal size: 51.113 cm
	Pixel Pitch	0.258 mm
Video Signal	Max. Resolution	RGB : 1680 X 1050 @60 Hz DVI : 1680 X 1050 @60 Hz
	Recommended Resolution	1680 X 1050 @60 Hz
	Horizontal Frequency	28 - 83 kHz
	Vertical Frequency	56 - 75 Hz
	Synchronization Type	Separate Sync, Digital
Input Connector	S-Video, Composite video, TV, D-Sub Analog, DVI-D PC Audio In, Headphone/Earphone, component	
Power	Rated Voltage	AC 100-240V~ 50/60Hz 1.0A
	Power Consumption	On Mode : 50 W (Typ.) Sleep Mode ≤ 1 W Off Mode ≤ 1 W
Tilt	Tilt Range	-3° ~ 10°
	Swivel	350°
Dimension/Weight	Size (WxLxH)	484.3 mm x 230.0 mm x 414.3 mm
	Weight (excl. package)	4.8 kg (10.58 lbs)
Environmental Conditions	Operational Condition	Temperature: 10°C ~ 35°C , Humidity: 20% ~ 80%
	Storage Condition	Temperature: -10°C ~ 60°C , Humidity: 5% ~ 90%

Specifications

The product specifications can change without prior notice for product improvement.

[22 inch]

LCD Panel	Screen Type	22 inches Wide (55.868 cm) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel Visible diagonal size: 55.868 cm
	Pixel Pitch	0.282 mm
Video Signal	Max. Resolution	RGB : 1680 X1050 @60 Hz DVI : 1680 X1050 @60 Hz
	Recommended Resolution	1680 X1050 @60 Hz
	Horizontal Frequency	28 - 83 kHz
	Vertical Frequency	56 - 75 Hz
	Synchronization Type	Separate Sync, Digital
Input Connector		S-Video, Composite video, TV, D-Sub Analog, DVI-D, PC Audio In, Headphone/Earphone, component
Power	Rated Voltage	AC 100-240V~ 50/60Hz 1.0A
	Power Consumption	On Mode : 50 W (Typ.) Sleep Mode ≤ 1 W Off Mode ≤ 1 W
Tilt	Tilt Range	-3° ~ 10°
	Swivel	350°
Dimension/Weight	Size (WxLxH)	525.4 mm x 230.0 mm x 439.0 mm
	Weight (excl. package)	5.82 kg (13 lbs)
Environmental Conditions	Operational Condition	Temperature: 10°C ~ 35°C , Humidity: 20% ~ 80%
	Storage Condition	Temperature: -10°C ~ 60°C , Humidity: 5% ~ 90%

Specifications

● PC Mode – Preset Mode

[19 inch]

Preset mode		Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Preset mode		Horizontal Frequency (kHz)	Vertical Frequency (Hz)
1	720 x 400	31.468	70	11	1440 x 900	55.5	60
2	640 x 480	31.469	60	12	1440 x 900	55.935	60
3	640 x 480	37.500	75	13	1440 x 900	70.635	75
4	800 x 600	37.879	60				
5	800 x 600	46.875	75				
6	1024 x 768	48.363	60				
7	1024 x 768	60.123	75				
8	1152 x 864	67.500	75				
9	1280 x 1024	63.981	60				
10	1280 x 1024	79.976	75				

* 1~13 : RGB mode * 1~12 : DVI mode

[20.1 inch] [22 inch]

Preset mode		Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Preset mode		Horizontal Frequency (kHz)	Vertical Frequency (Hz)
1	720 x 400	31.468	70	11	1680 x 1050	64.674	60
2	640 x 480	31.469	60	12	1680 x 1050	65.290	60
3	640 x 480	37.500	75				
4	800 x 600	37.879	60				
5	800 x 600	46.875	75				
6	1024 x 768	48.363	60				
7	1024 x 768	60.123	75				
8	1152 x 864	67.500	75				
9	1280 x 1024	63.981	60				
10	1280 x 1024	79.976	75				

● DTV -Timing

Preset mode		Horizontal Frequency (kHz)	Vertical Frequency (Hz)
*1	720 x 480/60p	31.47	60
*2	720 x 480/60p	31.5	60
3	720 x 576/50p	31.25	50
*4	1280 x 720/50p	37.5	50
*5	1280 x 720/60p	44.96	60
*6	1280 x 720/60p	45	60
7	1920 x 1080/60i	33.72	60
8	1920 x 1080/60i	33.75	60
9	1920 x 1080/50i	28.125	50

● Power Indicator

Mode	Product
On Mode	Blue
Sleep Mode	Amber
Off Mode	Off

* : User have to select directness PC or DTV when using the PC or the Set-top box this resolution.


Specifications

● VESA wall mounting


This product meets VESA-compliant mounting interface pad specifications.

1. Put the product on a piece of cloth or other soft surface with the front side facing downward.

2. Please pull and remove the stand base while pressing the button on the stand body in the direction of the arrows.




3. Please put the stand body up.




Specifications


4. Please pull and remove the stand body while sliding and holding the latches down.



5. Fasten the screw on the backside of the product and the other one in the joint of the stand.



6. Install the VESA standard wall mounting.



VESA wall mounting

Connected to another object (stand type and wall-mounted type).


This product accepts a VESA-compliant mounting interfacepad.

(This has to be purchased separately if required.)

For further information, refer to the VESA Wall Mounting Instruction Guide.

Specifications

Signal Connector Pin Assignment



- DVI-D Connector

Pin	Signal(DVI-D)	Pin	Signal(DVI-D)
1	T. M. D. S. Data2-	16	Hot Plug Detect
2	T. M. D. S. Data2+	17	T. M. D. S. Data0-
3	T. M. D. S. Data2/4 Shield	18	T. M. D. S. Data0+
4	T. M. D. S. Data4-	19	T. M. D. S. Data0/5 Shield
5	T. M. D. S. Data4+	20	T. M. D. S. Data5-
6	DDC Clock	21	T. M. D. S. Data5+
7	DDC Data	22	T. M. D. S. Clock Shield
8	Analog Vertical Sync.	23	T. M. D. S. Clock+
9	T. M. D. S. Data1-	24	T. M. D. S. Clock-
10	T. M. D. S. Data1+		
11	T. M. D. S. Data1/3 Shield		
12	T. M. D. S. Data3-		
13	T. M. D. S. Data3+		
14	+5V Power		
15	Ground (return for +5V, H. Sync. and V. Sync.)		

T. M. D. S. (Transition Minimized Differential Signaling)