LG
Life's Good

ENGLISH

OWNER'S MANUAL
MONITOR SIGNAGE

Please read this manual carefully before operating the your set and retain it for future reference.

MONITOR SIGNAGE MODELS

42WS10
47WS10
55WS10

www.lg.com

ENGLISH

CONTENTS

4 LICENSES

5 ASSEMBLING AND PREPARING

5 Accessories
6 Optional Accessories
7 Parts and buttons
8 Using the Mounting Cable Tie
8 Connecting the Speakers
9 Connecting the stand
9 Using the Kensington security system
10 Portrait Layout
11 Mounting on a wall

12 REMOTE CONTROL

14 USING THE MONITOR

14 Connecting to a PC
15 - RGB connection
15 - DVI-D connection
16 - HDMI connection
16 - Display Port connection
17 Adjusting the screen
17 - Selecting an image mode
17 - Customizing image options
18 - Customizing PC display options
18 Adjusting the sound
18 - Selecting an sound mode
19 - Customizing sound options
19 Using additional options
19 - Adjusting aspect ratio
21 - Using the input list

22 ENTERTAINMENT

22 - Connecting to a wired network
23 - Network Status
24 - Connecting USB storage devices
25 - Browsing files
26 - Viewing movies
30 - Viewing photos
33 - Listening to music
35 - Viewing the Contents List
36 - DivX® VOD Guide
37 - Using PIP/PBP

39 CUSTOMIZING SETTINGS

39 Accessing main menus
40 - PICTURE settings
43 - AUDIO settings
44 - TIME settings
45 - OPTION settings
50 - NETWORK settings

51 MAKING CONNECTIONS

52 Connecting to a HD receiver, DVD, Camcorder, Camera, Gaming Device or VCR player
52 - HDMI connection
52 - Component connection
53 - AV(CVBS) connection
53 Connecting to a USB
54 Connecting to the LAN
54 - LAN connection
55 Daisy Chain Monitors

ENGLISH

56 TROUBLESHOOTING

59 SPECIFICATIONS

67 IR CODES

68 CONTROLLING THE MULTIPLE PRODUCT

68 Connecting the cable
68 RS-232C Configurations
68 Communication Parameter
69 Command reference list
71 Transmission / Receiving protocol

ENGLISH

LICENSES

Supported licenses may differ by model. For more information of the licenses, visit www.lg.com.

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

ABOUT DIVX VIDEO: DivX® is a digital video format created by DivX, LLC, a subsidiary of Rovi Corporation. This is an official DivX Certified® device that plays DivX video. Visit divx.com for more information and software tools to convert your files into DivX videos.
ABOUT DIVX VIDEO-ON-DEMAND: This DivX Certified® device must be registered in order to play purchased DivX Video-on-Demand (VOD) movies. To obtain your registration code, locate the DivX VOD section in your device setup menu. Go to vod.divx.com for more information on how to complete your registration.
DivX Certified® to play DivX® video up to HD 1080p, including premium content.
DivX®, DivX Certified® and associated logos are trademarks of Rovi Corporation or its subsidiaries and are used under license.
Covered by one or more of the following U.S. patents: 7,295,673; 7,460,668; 7,515,710; 7,519,274

Manufactured under license from Dolby Laboratories. Dolby and the double-D symbol are trademarks of Dolby Laboratories.

ENGLISH

ASSEMBLING AND PREPARING

Accessories

Check your product box for the following items. If there are any missing accessories, contact the local dealer where you purchased your product. The illustrations in this manual may differ from the actual product and accessories.



Remote control and Batteries



Power Cord



CD (Owner's Manual) / Card



D-sub 15 pin signal cable



Mounting Cable Tie (Provided for 42WS10 and 47WS10 models only)

CAUTION

- Do not use any pirated items to ensure the safety and product life span.
- Any damages or injuries by using pirated items are not covered by the warranty.

NOTE

- The accessories supplied with your product may vary depending on the model.
- Product specifications or contents in this manual may be changed without prior notice due to upgrade of product functions.

Optional Accessories

Without prior notice, optional accessories are subject to change to improve the performance of the product, and new accessories may be added. The illustrations in this manual may differ from the actual product and accessories.



ST-200T
Stand



Screws
: Diameter 4.0 mm x Pitch 0.7 mm x
Length 10mm(Included Spring Washer)

Stand kit



SP-2000
Speaker



Cable holder
/Cable Tie



Screws
Diameter 4.0 mm x Pitch 0.7 mm x
Length 8 mm(Included Spring Washer)

Speaker kit

NOTE

- Cable holder/Cable tie may not be available in some areas or for some models.
- Optional accessories are not included for all models.

Parts and buttons



Screen Marks	Description
INPUT	Changes the input source.
MENU	Accesses the main menus, or saves your input and exits the menus.
▼▲	Adjust the up and down.
◄ ►	Adjusts the volume level.
AUTO/SET	Displays the current signal and mode. Press this button to adjust the screen automatically (available only in RGB mode)
⏻ / I	Turns the power on or off.
IR Receiver	This is where the unit receives signals from the remote control.
Power Indicator	This Indicator lights up blue when the display operates normally(on mode). If the display In sleep mode (In Power Saving mode), this indicator color changes to amber.

NOTE

- You can set the Power indicator to on or off by selecting **OPTION** in the main menu.

Using the Mounting Cable Tie

- Applicable only to 42WS10 and 47WS10 models.

First, connect the input signal cable to be used. Insert the cable tie into the bottom hole on the back as shown in the figure to organize cables.



NOTE

- The Mounting cable tie is provided for 42WS10 and 47WS10 models only.

Connecting the Speakers

- Only on some models.

1 Connect an input signal cable to use before installing the speakers.



2 Mount the speaker by using a screw as shown in the following. Then connect the speaker cable.



3 After installing your speakers, use holders and cable ties to organize the speaker cables.



Connecting the stand

- Only on some models.

1 Place a soft cloth on the table and put the product with the screen facing downward. Connect the stand as shown in the following picture.



2 Use the screws to secure the stand on the rear side of the product as shown in the diagram.



Using the Kensington security system

The Kensington security system connector is located at the back of the Monitor. For more information of installation and using, refer to the manual supplied with the Kensington security system or visit *http://www.kensington.com*.

Connect the Kensington security system cable between the Monitor and a table.



NOTE

- The Kensington security system is optional. You can obtain additional accessories from most electronics stores.

Portrait Layout

- Only on some models.

When installing in a Portrait Layout, rotate the monitor clockwise 90 degrees (when facing the screen).



Mounting on a wall

For proper ventilation, allow a clearance of 10 cm on each side and from the wall. Detailed installation instructions are available from your dealer, see the optional Tilt Wall Mounting Bracket Installation and Setup Guide.



If you intend to mount the Monitor to a wall, attach Wall mounting interface (optional parts) to the back of the set.
When you install the Monitor using the wall mounting interface (optional parts), attach it carefully so it will not fall.

1 Please, Use the screw and wall mount interface in accordance with VESA Standards.

2 If you use screw longer than standard, the monitor might be damaged internally.

3 If you use improper screw, the product might be damaged and drop from mounted position. In this case, LG Electronics is not responsible for it.

4 VESA compatible.

5 Please use VESA standard as below.

- 785mm(31 inch) or greater
  * Fastening screw: Diameter 6.0 mm x Pitch 1.0 mm x Length 10 mm

CAUTION

- Disconnect the power before installing or moving the monitor. Otherwise electric shock may occur.
- If you install the Monitor on a ceiling or slanted wall, it may fall and result in severe injury. Use an authorized LG wall mount and contact the local dealer or qualified personnel.
- Do not over tighten the screws as this may cause damage to the Monitor and void your warranty.
- Use screws and wall mounts that meet the VESA standard. Any damages or injuries by misuse or using an improper accessory are not covered by the warranty.

NOTE

- Use screws that are listed on the VESA standard screw specifications.
- The wall mount kit includes an installation manual and necessary parts.
- The wall mount bracket is optional. You can obtain additional accessories from your local dealer.
- The length of screws may differ depending on the wall mount. Be sure to use the proper length.
- For more information, refer to the instructions supplied with the wall mount.

ENGLISH

REMOTE CONTROL

The descriptions in this manual are based on the buttons of the remote control. Please read this manual carefully and use the Monitor correctly.
To replace batteries, open the battery cover, replace batteries (1.5 V AAA) matching ⊕ and ⊖ ends to the label inside the compartment, and close the battery cover.
To remove the batteries, perform the installation actions in reverse.

CAUTION

- Do not mix old and new batteries, as this may damage the remote control.
- Make sure to point the remote control at the remote control sensor on the Monitor.







⏻ / I (POWER)
Turns the Monitor on or off.

MONITOR ON / OFF
Turn off the monitor and then turn it back on.

1/a/A Button
This button selection is not applicable.

ARC
Selects the Aspect Ratio Mode.

Volume Up / Down
Adjusts the volume level.

PSM
Selects the Picture Status Mode.

MUTE
Mutes all sounds.

ENERGY SAVING
Adjusts the brightness of the screen to reduce energy consumption.

INPUT
Selects the input mode.

Number and Alphabet buttons
Enters numbers.
The alphabet selection is not applicable.

CLEAR
This button selection is not applicable.

BRIGHTNESS Key
Adjust the brightness by pressing the Up and Down buttons on the remote control. In USB mode, the OSD menu has the Page function to move to the next file list.

ENGLISH



MENU (See p.39)
Accesses the main menus or saves your input and exit menus.

Navigation buttons
Scrolls through menus or options.

OK
Selects menus or options and confirms your input.

BACK
Allows the user to move back one step.

ID ON/OFF
When more than one monitor is present in the same room, this allows you to control them individually.



AUTO
Automatically adjusts picture position and minimizes image instability.(RGB input only)

S.MENU
(SuperSign Menu Key)
This button selection is not applicable.

EXIT
Clears all on-screen displays and returns to Monitor viewing from any menu.

TILE
Selects the TILE Mode.

USB Menu control buttons
Controls media playback.

USING THE MONITOR

Connecting to a PC

Your Monitor supports the Plug & Play* feature.

* Plug & Play: This is the function that allows a PC to use the monitor without installing a driver.

CAUTION



- Connect the signal input cable and tighten it by turning the screws clockwise.
- Do not press the screen with your finger for a long time as this may result in temporary distortion on the screen.
- Avoid displaying a fixed image on the screen for a long period of time to prevent image burn. Use a screensaver if possible.

NOTE

- It is recommended to use the Monitor with the HDMI connection for the best image quality.
- Use a shielded signal interface cable, such as D-sub 15 pin signal cable and DVI cable, with a ferrite core to maintain standard compliance for the product.
- If you turn the Monitor on when the set becomes cold, the screen may flicker. This is normal.
- Some red, green, or blue spots may appear on the screen. This is normal.

RGB connection

Transmits the analog video signal from your PC to the Monitor. Connect the PC and the Monitor set with the 15 pin signal cable as shown the following illustrations.
Select RGB input source on the monitor.



DVI-D connection

Transmits the digital video signal from your PC to the Monitor. Connect the PC and the Monitor set with the DVI cable as shown the following illustrations.
Select DVI-D input source on the monitor.



NOTE



- Use the standard Macintosh adapter since an incompatible adapter is available in the market. (Different signaling system)
- Apple computers may require an adapter to connect to this monitor. Call or visit their web site for more information.

HDMI connection

Transmits the digital video and audio signals from your PC to the Monitor. Connect the PC and the Monitor with the HDMI cable as shown in the following illustrations.
Select HDMI input source.



Display Port connection

Transmits the digital video and audio signals from your PC to the Monitor. Connect the PC and the Monitor with the Display Port cable as shown in the following illustrations.
Select Display Port input source.



NOTE

- Use a High Speed HDMI™ Cable.
- Please check the PC environment if you cannot hear the sound in HDMI mode. Some PCs require you to manually change the default audio output to HDMI.
- If you want to use HDMI PC mode, you must set PC/DTV to PC mode.
- When HDMI PC is used, a compatiblity problem might occur.

Adjusting the screen

Selecting an image mode

Display images in its optimized settings by selecting one of the preset image modes.

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **PICTURE** and press **OK**.

3 Press the Navigation buttons to scroll to **Picture Mode** and press **OK**.

4 Press the Navigation buttons to scroll to an image mode you want and press **OK**.

Mode	Description
Vivid	Adjusts the video image for the retail environment by enhancing the contrast, brightness, color, and sharpness.
Standard	Adjusts the image for a normal environment.
Cinema	Optimizes the video image for a cinematic look to enjoy movies as if you are in a movie theater.
Sport	Optimizes the video image for high and dynamic actions by emphasizing primary colors such as white, grass, or sky blue.
Game	Optimizes the video image for a fast gaming screen such as PCs or games.

5 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

Customizing image options

Customize basic and advanced options of each image mode for the best screen performance.

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **PICTURE** and press **OK**.

3 Press the Navigation buttons to scroll to **Picture Mode** and press **OK**.

4 Press the Navigation buttons to scroll to an image mode you want and press **OK**.

5 Select and adjust the following options, and then press **OK**.

Option	Description
Backlight	Adjusts the brightness of the screen by controlling the LCD backlight. If you decrease the brightness level, the screen becomes darker and the power consumption will be reduced without any video signal loss.
Contrast	Increases or decreases the gradient of the video signal. You may use Contrast when the bright parts of the picture are saturated.
Brightness	Adjusts the base level of the signal in the picture. You may use Brightness when the dark areas of the picture are saturated.
Sharpness	Adjusts the level of crispness in the edges between the light and dark areas of the picture. The lower the level, the softer the image.
Color	Adjusts intensity of all colors.
Tint	Adjusts the balance between red and green levels.
Color Temp.	Set to warm to enhance hotter Colors such as red, or set to cool to make picture bluish.
Advanced Control	Customizes the advanced options. Refer to the Advanced image options. (See p.42)
Picture Reset	Restores the options to the default setting.

6 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

Customizing PC display options

Customize options of each image mode for the best image quality.

- This function works in the following mode: RGB[PC] mode.

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **PICTURE** and press **OK**.

3 Press the Navigation buttons to scroll to **Screen** and press **OK**.

4 Select and adjust following options, and then press **OK**.

Option	Description
Resolution	Selects a proper resolution. See “Customizing PC display options”.
Auto Config.	Adjusts the screen position, clock, and phase automatically. The displayed image may be unstable for a few seconds while the configuration is in progress.
Position/ Size/Phase	Adjusts the options when the picture is not clear, especially when characters are shaky. Run Auto Config. before adjusting these.
Reset	Restores the options to the default setting.

5 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

Adjusting the sound

Selecting an sound mode

This Monitor has 5 preset sound modes to compliment different types of video content.

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **AUDIO** and press **OK**.

3 Press the Navigation buttons to scroll to **Sound Mode** and press **OK**.

4 Press the Navigation buttons to scroll to a sound mode you want and press **OK**.

Mode	Description
Standard	Select when you want standard-quality sound.
Music	Select when you listen to music.
Cinema	Select when you watch movies.
Sport	Select when you watch sport events.
Game	Selects when you play games.

5 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

Customizing sound options

You may customize options of each sound mode for the best sound quality.

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **AUDIO** and press **OK**.

3 Press the Navigation buttons to scroll to **Sound Mode** and press **OK**.

4 Press the Navigation buttons to scroll to a sound mode you want and press **OK**.

5 Select and adjust following options, and then press **OK**.

Option	Description
Infinite Sound	LG's Infinity Sound option provides 5.1 channel stereo quality sound from two speakers.
Treble	Controls the dominant sounds in the output. When you turn up the treble, it will increase the output of the higher frequency range.
Bass	Controls the softer sounds in the output. When you turn up the bass, it will increase the output of the lower frequency range.
Reset	Resets the sound mode to the default setting.

6 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

Using additional options

Adjusting aspect ratio

Resize the image to view the image at its optimal size by pressing **ARC** while you are watching content.

CAUTION

- If a fixed image displays on the screen for a long period of time, it will be imprinted and become a permanent disfigurement on the screen. This is “image burn” or “burn-in” and not covered by the warranty.
- If the aspect ratio is set to 4:3 for a long period of time, image burn may occur on the letterboxed area of the screen.

NOTE

- You can also change the image size by accessing the main menus.

MODE / ARC	AV	Component	RGB	Display Port		DVI-D		HDMI	
			PC	DTV	PC	DTV	PC	DTV	PC
16:9	o	o	o	o	o	o	o	o	o
Just Scan	x	o	x	o	x	o	x	o	x
1:1	x	x	o	x	o	x	o	x	o
4:3	o	o	o	o	o	o	o	o	o
Zoom	o	o	x	o	x	o	x	o	x
Cinema Zoom 1	o	o	x	o	x	o	x	o	x

- **16:9** : This selection will allow you to adjust the picture horizontally, in linear proportion, to fill the entire screen(useful for viewing 4:3 formatted DVDs).



- **4:3** : This selection will allow you to view a picture with an original 4:3 aspect ratio, black bars will appear on both the left and right of the screen.



- **Just Scan** : This Selection will allow you view the picture of best quality without loss of original picture in high resolution image. Note: If there is noise in original Picture, You can see the noise at the edge.



- **Zoom** : This selection will allow you to view the picture without any alteration, while filling the entire screen. However, the top and bottom of the picture will be cropped.



- **1:1** : The aspect ratio is not adjusted from the original. (Only Display Port PC, HDMI PC, DVI-D PC, RGB PC)



- **Cinema Zoom 1** : Choose Cinema Zoom when you want to enlarge the picture in correct proportion. Note: When enlarging or reducing the picture, the image may become distorted.



Using the input list

Selecting an input source

1 Press **INPUT** to access the input source list.
- The connected device displays on each input source.

2 Press the Navigation buttons to scroll to one of the input sources and press **OK**.

Input source	Description
AV(CVBS)	Watch video from a VCR or other external devices.
Component	Watch content from a DVD or other external devices, or through a digital set-top box
RGB	View a PC display on the screen
Display Port	Watch content from a PC, DVD of Digital set-top box other high definition devices
DVI-D	View a PC display on the screen
HDMI	Watch content from a PC, DVD of Digital set-top box other high definition devices

ENTERTAINMENT

Connecting to a wired network

(Depending on model)

Connect the display to a local area network (LAN) via the LAN port as shown on the following illustration and set up the network settings.
This monitor only supports a wired network connection.
After making a physical connection, a small number of home networks may require the display network settings to be adjusted. For most home networks, the display will connect to automatically without any adjustments.
For detail information, contact your internet provider or router manual.



CAUTION

- Do not connect a modular phone cable to the LAN port.
- Since there are various connection methods, please follow the specifications of your telecommunication carrier or internet service provider.

To set up the network seetings: (Even if your display has already connected automatically, running setup again will not harm anything),

1. Press **MENU** to access the main menus.
2. Press the Navigation buttons to scroll to **NETWORK** and press **OK**.
3. Press the Navigation buttons to select **Network Setting** and press **OK**.
4. If you already set Network Setting, select **Resetting**. The new connection settings resets the current network settings.
5. Select **IP Auto Setting** or **IP Manual Setting**.
   - If selecting **IP Manual Setting**, press the Navigation and Number buttons. IP addresses will need to be input manually.
   - **IP Auto Setting**: Select this if there is a DHCP server (Router) on the local area network (LAN) via wired connection, the display will automatically be allocated an IP address. If you're using a broadband router or broadband modem that has a DHCP (Dynamic Host Configuration Protocol) server function. The IP address will automatically be determined.
6. When you are finished, press **EXIT**.

CAUTION

- Network setting menu will not be available until the display is connected to physical network.
- Since there are various connection methods, please follow the specifications of your telecommunication carrier or internet service provider.

NOTE

- If you want to access the Internet directly on your display, the internet connection should always be on.
- If you cannot access the Internet, check the network conditions from a PC on your network.
- When you use **Network Setting**, check the LAN cable or check if DHCP in the router is turned on.
- If you do not complete the network settings, the network may not work properly.

Tips for Network setting

- Use a standard LAN cable with this display. Cat5 or better with a RJ45 connector.
- Many network connection problems during set up can often be fixed by re-setting the router or modem. After connecting the display to the home network, quickly power off and/or disconnect the power cable of the home network router or cable modem. Then power on and/or connect the power cable again.
- Depending on the internet service provider (ISP), the number of devices that can receive internet service may be limited by the applicable terms of service. For details, contact your ISP.
- LG is not responsible for any malfunction of the display and/or the internet connection feature due to communication errors/malfunctions associated with your internet connection, or other connected equipment.
- LG is not responsible for problems within your internet connection.
- You may experience undesired results if the network connection speed does not meet the requirements of the content being accessed.
- Some internet connection operations may not be possible due to certain restrictions set by the Internet service provider (ISP) supplying your Internet connection.
- Any fees charged by an ISP including, without limitation, connection charges are your responsibility.
- A 10 Base-T or 100 Base-TX LAN port is required when using a wired connection to this display. If your internet service does not allow for such a connection, you will not be able to connect the display.
- A DSL modem is required to use DSL service and a cable modem is required to use cable modem service. Depending on the access method of and subscriber agreement with your ISP, you may not be able to use the internet connection feature contained in this display or you may be limited to the number of devices you can connect at the same time. (If your ISP limits sub-scription to one device, this display may not be allowed to connect when a PC is already connected.)
- The use of a “Router” may not be allowed or its usage may be limited depending on the policies and restrictions of your ISP. For details, contact your ISP directly.

Network Status

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **NETWORK** and press **OK**.

3 Press the Navigation buttons to select **Network Status**.

4 Press **OK** to check the network status.

5 When you are finished, press **EXIT.**

Option	Description
Setting	Return to the network setting menu.
Test	Test the current network status after setting the network.
Close	Return to the previous menu.

Connecting USB storage devices

You can connect USB storage devices such as a USB flash memory, external hard drive to the display and use multimedia features .
Connect a USB flash memory or USB memory card reader to the Display as shown on the following illustration. The My media screen appears.



CAUTION

- Do not turn the display off or remove a USB storage device while the EMF(my media) Menu is activated, as this could result in loss of files or damage to the USB storage device.
- Back up your files saved on a USB storage device frequently, as you may lose or damage the files and this may be not covered by the warranty.

Tips for using USB storage devices

- Only a USB storage device is recognizable.
- If the USB storage device is connected through a USB hub, the device is not recognizable.
- A USB storage device using an automatic recognition programme may not be recognized.
- A USB storage device which uses its own driver may not be recognized.
- The recognition speed of a USB storage device may depend on each device.
- Please do not turn off the display or unplug the USB device when the connected USB storage device is working. When such device is suddenly separated or unplugged, the stored files or the USB storage device may be damaged.
- Please do not connect the USB storage device which was artificially maneuvered on the PC. The device may cause the product to malfunction or fail to be played. Never forget to use only a USB storage device which has normal music files, image files or movie files.
- Please use only a USB storage device which was formatted as a FAT32 file system or NTFS file system provided with the Windows operating system. In case of a storage device formatted as a different utility program which is not supported by Windows, it may not be recognized.
- Please connect power to a USB storage device(over 0.5 A) which requires an external power supply. If not, the device may not be recognized.
- Please connect a USB storage device with the cable offered by the device maker.
- Some USB storage devices may not be supported or operated smoothly.
- File alignment method of USB storage device is similar to Window XP and filename can recognize up to 100 English characters.
- Be sure to back up important files since data stored in a USB memory device may be damaged. We will not be responsible for any data loss.

- If the USB HDD does not have an external power source, the USB device may not be detected. So be sure to connect the external power source.
  - Please use a power adaptor for an external power source. We do not guarantee an USB cable for an external power source.
- If your USB memory device has multiple partitions, or if you use a USB multi-card reader, you can use up to 4 partitions or USB memory devices.
- If a USB memory device is connected to a USB multi-card reader, its volume data may not be detected.
- If the USB memory device does not work properly, disconnect and reconnect it.
- How fast a USB memory device is detected differs from device to device.
- If the USB is connected in Standby Mode, specific hard disk will automatically be loaded when the display is turned on.
- The recommended capacity is 1 TB or less for a USB external hard disk and 32 GB or less for USB memory.
- Any device with more than the recommended capacity may not work properly.
- If a USB external hard disk with a “Energy Saving” function does not work, turn the hard disk off and on again to make it work properly.
- USB storage devices below USB 2.0 are supported as well. But they may not work properly in the movie list.
- Maximum of 999 folders or files can be recognized under one folder.
- It is recommended to use a certified USB storage device and cable. Otherwise, a USB storage device may not be detected or a playback error may occur.
- Only a USB memory stick can be used to play back the files distributed and stored by SuperSign Manager. A USB hard disk or multi-card reader will not work.
- Only an FAT 32 file formatted storage device can play back the files distributed and stored by SuperSign manager.
- A USB 3.0 storage device may not work.

Browsing files

Access the photo, music, or movie lists and browse files.

1 Connect a USB storage device.

2 Press **MENU** to access the main menus.

3 Press the Navigation buttons to scroll to **My Media** and press **OK**.

4 Press the Navigation buttons to choose from **Movie List, Photo List**, **Music List** or **Contents List** and press **OK**.





No.	Description
1	Moves to upper level folder
2	Current page/Total pages
3	Corresponding buttons on the remote control
4	Current page/ total pages of contents under the folder focused on 1
5	Contents under the folder focused on 1
Buttom	**Description**
Green button	Repeatedly, press the GREEN button to converted to **Movie List**->**Photo List, Photo List**->**Music List**, **Music List**->**Contents List** or **Contents List**->**Movie List**.
Yellow button	**A method to view in 5 large thumbnail or simple list.**
Blue button	Convert to Mark Mode.

Supported File Formats

Type	Supported file format
Movie	**DAT,MPG,MPEG,VOB,AVI,DIVX,MP4,MKV,TS,TRP,TP,ASF,WMV,FLV)** **Movie**(*.mpg/*.mpeg/*dat/*.ts/*.trp/*.tp/*.vob/*.mp4/*.mov/*.mkv/*.divx/*.avi/*.asf/*.wmv/*.flv/*.avi(motion-jpeg)/*. mp4(motion-jpeg)/*.mkv(motion-jpeg))supporting file **Video format** : DivX3.11, DivX4.12, DivX5.x, DivX6, Xvid1.00, Xvid1.01, Xvid1.02, Xvid1.03, Xvid1.10 beta-1/beta-2, Mpeg-1, Mpeg-2, Mpeg-4, H.264/AVC, VC1, JPEG, Sorenson H.263 **Audio format** : Dolby Digital, AAC, Mpeg, MP3, LPCM, HE-AAC, ADPCM, WMA **Bit rate** : within 32 kbps to 320 kbps(MP3) **External Subtitle format** : *.smi/*.srt/*.sub (MicroDVD,Subviewer1.0/2.0)/*.ass/*.ssa/*.txt(TMPlayer)/*.psb(PowerDivX) **Internal Subtitle format** : only, XSUB (It is the subtitle format used in DivX6 files)
Photo	JPEG Baseline : 64 x 64 to 15360 x 8640 Progressive : 64 x 64 to 1920 x 1440 • You can play JPEG files only. • Non-supported files are displayed in the form of predefined icon.
Music	MP3 Bit rate 32 to 320 • Sampling rate MPEG1 Layer3 : 32 kHz, 44.1 kHz, 48 kHz • Sampling rate MPEG2 Layer3 : 16 kHz, 22.05 kHz, 24 kHz • Sampling rate MPEG2.5 Layer3 : 8 kHz, 11.025 kHz, 12 kHz
Content (when using SuperSign Manager)	File Extensions : *.cts/ *.cse Movie **File Extensions**: *.mpg/*.mpeg/*.dat/*.ts/*.trp/*.tp/*.vob/*.mp4/*.mov/*.mkv/*.avi/*.asf/*.wmv/*.avi(motion JPEG)/*.mp4(motion JPEG)/*.mkv(motion JPEG) **Video format**: MPEG1, MPEG2, MPEG4,H.264/AVC, DivX 3.11, DivX 4.12, DivX 5.x, DivX 6, Xvid 1.00,Xvid 1.01, Xvid 1.02, Xvid 1.03,Xwvid 1.10-beta1/2, JPEG, VC1(WVC1/WMV3) **Audio format**: MP2,MP3,Dolby Digital, LPCM, AAC, HE-AAC,LPCM, ADPCM, WMA, MP3

		File Extensions	Item	Profile
	Photo	JPEG JPG PNG BMP	supported file format	• SOF0: baseline • SOF1: Extend Sequential • SOF2: Progressive
			Photo size	• Min: 64 x 64 • Max Type: 1366 x 768
	Music	MP3	Bit rate	32 kbps to 320 kbps
			Sampling rate	32 kHz, 44.1 kHz, 48 kHz (MPEG1 L3) 16 kHz, 22.05 kHz, 24 kHz (MPEG2 L3) 8kHz, 11.025 kHz, 12 kHz (MPEG2.5 L3)

Viewing movies

Play video files on display. Your display shows all of the video files saved in a USB storage device or shared folder on a PC.

1 Press the Navigation buttons to scroll to **My Media** and press **OK**.

2 Press the Navigation buttons to scroll to **Movie List** and press **OK**.

3 Press the Navigation buttons to scroll to a folder you want and press **OK**.

4 Press the Navigation buttons to scroll to a file you want and press **OK**.





Menu	Description
Play Marked	Play the selected movie file. Once a movie file finishes playing, the next selected one will be played automatically.
Mark All	Mark all movie files on the screen.
Unmark All	Deselect all marked movie files.
Exit Mark Mode	Exit the Mark Mode.

5 Play a movie.

NOTE

- Non-supported files are displayed the preview image by icon only .
- Abnormal files are displayed in the form of bitmap .

6 Control playback by using the following buttons.



Button	Description
■	Stops the playback
▶	Plays a video
II	Pauses or resumes the playback
◀◀	Scans backward in a file
▶▶	Scans forward in a file
MENU	Show the **Option** menu.
↩	Hide the menu on the full-sized screen.
⏏	Return to **Movie List**.
"<" or ">"	Skips to specific points in a file during playback. The time of a specific point will appear on the status bar. In some files, this function may not work properly.
ENERGY SAVING	Press the **ENERGY SAVING** button repeatedly to increase the brightness of your screen.

Tips for using playing video files

- Some user-created subtitles may not work properly.
- Some special characters are not supported in subtitles.
- HTML tags are not supported in subtitles.
- Subtitles in languages other than the supported languages are not available.
- The screen may suffer temporary interruptions (image stoppage, faster playback, etc.) when the audio language is changed.
- A damaged movie file may not be played correctly, or some player functions may not be usable.
- Movie files produced with some encoders may not be played correctly.
- If the video and audio structure of recorded file is not interleaved, either video or audio is outputted.
- HD videos with a maximum of 1920x1080@25/30P or 1280x720@50/60P are supported, depending on the frame.
- Videos with resolutions higher than 1920X1080@25/30P or 1280x720@50/60P may not work properly depending on the frame.
- Movie files other than the specified types and formats may not work properly.
- Max bitrate of playable movie file is 20 Mbps. (only, Motion JPEG : 10 Mbps)
- We do not guarantee smooth playback of profiles encoded level 4.1 or higher in H.264/AVC.
- DTS Audio codec is not supported.
- A movie file more than 30 GB in file size is not supported for playback.
- A DivX movie file and its subtitle file must be located in the same folder.
- A video file name and its subtitle file name must be identical for it to be displayed.
- Playing a video via a USB connection that doesn't support high speed may not work properly.
- Files encoded with GMC(Global Motion Compensation) may not be played.
- When you are watching the movie by Movie List function, you can adjust an image by Energy Saving key on the remote control. User setup for each image mode does not operate.

Video options

1 Press **MENU** to access the **Pop-Up** menus.

2 Press the Navigation buttons to scroll to **Set Video Play., Set Video.** or **Set Audio.** and press **OK**.

NOTE

- Option values changed in **Movie List** does not affect **Photo List** and **Music List**.
- Option value changed in **Photo List** and **Music List** are changed likewise in **Photo List** and **Music List** excluding **Movie List**.
- When replaying the video file after stopping, you can play from where it stopped previously.

When you select the **Set Video Play,**,

1 Press the Navigation buttons to scroll to show the **Picture Size, Audio Language, Subtitle Language** or **Repeat**.

2 Press the Navigation buttons to scroll to make appropriate adjustments.

Menu	Description
Picture Size	Selects your desired picture format during movie play.
Audio Language	Changes the Language Group of the audio during movie play. Files with a single audio track cannot be selected.
Subtitle Language	Turn on/off the subtitle.
Language	Activated for SMI subtitle and can select the language within the subtitle.
Code Page	Can select the font for subtitle. When set to default, same font as general menu will be used.
Sync	Adjusts the time synchronisation of the subtitle from -10 secs to +10 secs by steps of 0.5 secs during movie play.
Position	Changes the position of the subtitle either up or down during movie play.
Size	Selects your desired Subtitle size during movie play.
Repeat	Turn on/off repeat function of movie playback. When turned on, the file within the folder will be played back repeatedly. Even when the repeated playback is turned off, it can run the playback if the file name is similar to the previous file.

Code Page	Support Language
Latin1	English, Spanish, French, German, Italian, Swedish, Finnish, Dutch, Portuguese, Danish, Romanian, Norwegian, Albanian, Gaelic, Welsh, Irish, Catalan,Valencian
Latin2	Bosnian, Polish, Croatian, Czech, Slovak, Slovenian, Serbian, Hungarian
Latin4	Estonian, Latvian, Lithuanian
Cyrillic	Bulgarian, Macedonian, Russian, Ukrainian, Kazakh
Greek	Greek
Korean	Korean

NOTE

- Only 10,000 of sync blocks can be supported within the subtitle file.
- When playing a video, you can adjust the Picture Size by pressing the RATIO button.
- Subtitles in your language are only supported when the OSD menu is also in this language.
- The code page options may be disabled depending on the language of the subtitle files.
- Select the appropriate code page for the subtitle files.

When you select the **Set Video,**,

1 Press the Navigation buttons to scroll to make appropriate adjustments.

When you select the **Set Audio,**,

1 Press the Navigation buttons to scroll to show the **Sound Mode, Clear Voice II** or **Balance**.

2 Press the Navigation buttons to scroll to make appropriate adjustments.

Viewing photos

View image files saved in a USB storage device. The displays on the screen may differ from the model.

1 Press the Navigation buttons to scroll to **My Media** and press **OK**.

2 Press the Navigation buttons to scroll to **Photo List** and press **OK**.

3 Press the Navigation buttons to scroll to a folder you want and press **OK**.

4 Press the Navigation buttons to scroll to a file you want and press **OK**.





Menu	Description
View Marked	Display the selected photo file.
Mark All	Mark all photo files on the screen.
Unmark All	Deselect all marked photo files.
Exit Mark Mode	Exit the Mark Mode.

5 View photos.

NOTE

- Non-supported files are displayed the pre-view image by icon only .
- Abnormal files are displayed in the form of bitmap .

Using photo options

Use the following options while viewing photos.



Options Number of selected photos

Option	Description
Slideshow	Starts or stops a slideshow with selected photos. If there are no selected photos, all photos saved in the current folder display during a slideshow. Select **Option** to set the speed and view mode of the slideshow.
BGM	Turns the background music on or off. To set the background music folder, select **Option**. You can adjust Option by MENU button on the remote control.
Rotate	Rotates photos clockwise (90°, 180°, 270°, 360°). **NOTE** • The supported photo size is limited. You cannot rotate a photo if the resolution of the rotated width is larger than the supported resolution size.
Zoom	Enlarges the image to 200% or 400%. **NOTE** • Zoom to 200% or 400% only work for image of 1372×772 pixel size or larger. • For image of 960×540 pixel size or larger, only zoom to 400% works properly.
ENERGY SAVING	Press the **ENERGY SAVING** button repeatedly to change the brightness of your screen.
Option	• **Slide Speed**: Selects a slideshow speed (**Fast**, **Medium**, **Slow**). • **TransitionEffect:** Set the view mode of the slideshow. • **BGM**: Selects a music folder for the background music. **NOTE** • You cannot change the music folder while the background music is playing. • You can only select the MP3 folder saved on the device that currently displays the photo.
Hide	Hides the option window. To display the options, press **OK**.
EXIT	Return to **Photo List**.

Photo options

1 Press **MENU** to show the **Option** menus.

2 Press the Navigation buttons to scroll to **Set Photo View.**, **Set Video.** or **Set Audio.** and press **OK**.

NOTE

- Option values changed in **Movie List** does not affect **Photo List** and **Music List.**
- Option value changed in **Photo List** and **Music List** are changed likewise in **Photo List** and **Music List** excluding **Movie List**.

When you select the **Set Photo View**,

1 Press the Navigation buttons to scroll to select **Slide Speed,Transition Effect** or **BGM.**

2 Press the Navigation buttons to scroll to make appropriate adjustments.

Transition Effect Option

Option	Description
Sliding	Pushes the current slide out of view as it plays to the next slide. 
Stairs	Pushes the current slide in a staircase shape as it plays to the next slide. 
Door Open /Close	Pushes the current slide like opening or closing the door as it plays to the next slide. 
Shutter	Pushes the current slide like drawing or pulling down the blind as it plays to the next slide 
Fade In	Fades the slide out slowly before playing to the next slide. 

When you select the **Set Video**,

1 Press the Navigation buttons to scroll to make appropriate adjustments.

When you select the **Set Audio,**

1 Press the Navigation buttons to scroll to show the **Sound Mode, Clear Voice II** or **Balance**.

2 Press the Navigation buttons to scroll to make appropriate adjustments.

Listening to music

1 Press the Navigation buttons to scroll to **My Media** and press **OK**.

2 Press the Navigation buttons to scroll to **Music List** and press **OK**.

3 Press the Navigation buttons to scroll to a folder you want and press **OK**.

4 Press the Navigation buttons to scroll to a file you want and press **OK**.





Menu	Description
Play Marked	Display the selected music file.
Mark All	Mark all music files on the screen.
Unmark All	Deselect all marked music files.
Exit Mark Mode	Exit the Mark Mode.

5 Play music.

6 Control playback by using the following buttons.



Button	Description
■	Stops playback
▶	Plays a music file
⏸	Pauses or resumes playback
⏭	Skips to the next file
⏮	Skips to the previous file
⏮ or ⏭	When playing, When you press the ⏮ button, the previous music file will be played. When you press the ⏭ button, the next music file will be played.
Green button	Start playing the selected music files and then move to the **Photo List**.
ENERGY SAVING	Press the **ENERGY SAVING** button repeatedly to change the brightness of your screen.
MENU **Option**	Show the Option menu.
Hide	Hides the option window. To display the options, press **OK**.
EXIT	When you press the **EXIT** button while the Music player is displayed, only the music will be stopped and the player will not return to normal viewing. When you press the **EXIT** button while the music is stopped or while the music player is hidden, the player will return to normal viewing.
"<" or ">"	When using the **<** or **>** button during playback a cursor indicating the position can be played.

Tips for playing music files

- This unit doesn't support the ID3 Tag embedded MP3 files.

NOTE

- Non-supported files are displayed the preview image by icon only .
- Abnormal files are displayed in the form of bitmap .
- A damaged or corrupted music does not play but displays 00:00 in playtime.
- A music downloaded from a paid service with copyright protection does not start but displays inappropriate information in playtime.
- If you press OK, ■ buttons, screen saver is stopped.
- The PLAY(▶), Pause(⏸), ■, ⏭, ⏮ buttons on the remote control are also available in this mode.
- You can use the ⏭ button to select the next music and the ⏮ button to select the previous music.



Music options

1 Press **MENU** to access the **Pop-Up** menus.

2 Press the Navigation buttons to scroll to **Set Audio Play.** or **Set Audio.** and press **OK**.

NOTE

- Option values changed in **Movie List** does not affect **Photo List** and **Music List**.
- Option value changed in **Photo List** and **Music List** are changed likewise in **Photo List** and **Music List** excluding **Movie List.**

When you select the **Set Audio Play.**,

1 Press the Navigation buttons to scroll to select the **Repeat** or **Random**.

2 Press the Navigation buttons to scroll to make appropriate adjustments.

When you select the **Set Audio,**,

1 Press the Navigation buttons to scroll to select the **Sound Mode, Clear Voice II** or **Balance**.

2 Press the Navigation buttons to scroll to make appropriate adjustments.

Viewing the Contents List

Plays back the stored files using the Export option in SuperSign Manager.

1 Press the Navigation buttons to scroll to **My Media** and press **OK**.

2 Press the Navigation buttons to scroll to **Contents List** and press **OK**.

3 Press the Navigation buttons to scroll to a folder you want and press **OK**.

4 Press the Navigation buttons to scroll to a file you want and press **OK**.



NOTE

- While playing media files from Contents List, only the BACK, EXIT or Volume button are available. Selecting the BACK or EXIT button stops playing media files and returns to the screen view mode.
- If there is the AutoPlay folder in the USB device and its files are in supported formats, they can be played back automatically when the USB device is connected to the monitor.

DivX® VOD Guide

DivX® VOD Registration

In order to play purchased or rented DivX® VOD contents, you should register your device with 10 digit DivX registration code from your device at **www.divx.com/vod.**

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **MY MEDIA** and press **OK**.

3 Press the Blue button.

4 Press the Navigation buttons to scroll to **DivX Reg. Code** and press **OK**.

5 View the registration code of your display.

6 When you are finished, press **EXIT.**
When you return to the previous menu, press **BACK**.



NOTE

- While you are checking the registration code, some buttons may not work.
- If you use the DivX registration code of another device, you cannot play the rented or purchased DivX file. Make sure to use the DivX registration code assigned to your TV.
- The video or audio files that are not converted by the standard DivX codec may be corrupted or not be played.
- The DivX VOD code allows you to activate up to 6 devices under one account.

DivX® VOD Deregistration

You should deregister your device with 8 digit DivX deregistration code from your device at www.divx.com/vod.

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **MY MEDIA** and press **OK**.

3 Press the Blue button.

4 Press the Navigation buttons to scroll to **Deactivation** and press **OK**.

5 Press the Navigation buttons to select **Yes** to confirm.



6 When you are finished, press **EXIT.**
When you return to the previous menu, press **BACK**.

NOTE

- Once the deregistration is executed, you must register your device again to see DivX® VOD contents.

Using PIP/PBP

Videos or pictures stored on the USB device can be displayed on a single monitor by dividing them into the main and subscreens. (See p.49)

1 Press the **MENU** button to move to **OPTION** and press **OK**.

2 Press **PIP/PBP** to select **PIP** or **PBP** and then press **OK**.



3 Select **Movie List** or **Photo List** from **My Media**.



4 Select a file you want and then press **OK**.



5 Select the **PIP** or **PBP** icon from the play list.



< MOVIE LIST >



< PHOTO LIST >

6 For sound select either Main or Sub. You must to select the output sound before running the **PIP** or **PBP** function.



7 The sub screen is displayed on the main screen.



ENGLISH

CUSTOMIZING SETTINGS

Accessing main menus

1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to one of the following menus and press **OK**.

3 Press the Navigation buttons to scroll to the setting or option you want and press **OK**.

4 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.





PICTURE settings



1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **PICTURE** and press **OK**.

3 Press the Navigation buttons to scroll to the setting or option you want and press **OK**.

- To return to the previous level, press **BACK**.

4 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

The available picture settings are described in the following:

Setting	Description	
Aspect Ratio	Changes the image size to view images at its optimal size (See p.19).	
Energy Saving	Sets to automatically adjust the screen brightness corresponding to the surroundings.	
	Level	
	Auto	Adjust automatically
	Off	Disables Energy Saving function
	Minimum/ Medium/ Maximum	Selects the brightness level of the backlight.
	Screen off	The screen turns off in 3 seconds.
Smart Energy Saving	Adjusts the backlight and contrast depending on the screen brightness.	
	Level	
	Off	Disables the Smart Energy Saving function.
	On	Enables the Smart Energy Saving function to save power consumption as much as the value set in the smart energy saving rate.
Picture Mode	Selects one of the preset image or customizes options in each mode for the best Monitor screen performance. You are also able to customize advanced options of each mode. The available preset picture modes vary depending on the Monitor .	
	Mode	
	Vivid	Adjusts the video image for the retail environment by enhancing the contrast, brightness, Colour, and sharpness.
	Standard	Adjusts the image for the normal environment.
	Cinema	Optimizes the video image for a cinematic look to enjoy movies as if you are in a movie theater.
	Sport	Optimizes the video image for high and dynamic actions by emphasizing primary Colours such as white, grass, or sky blue.
	Game	Optimizes the video image for a fast gaming screen such as PCs or games.

Setting	Description	
SCREEN (In RGB Mode Only)	Customizes the PC display options in RGB mode.	
	Option	
	Resolution	Selects a proper resolution. See “Customizing PC display options”.
	Auto Config.	Adjusts the screen position, clock, and phase automatically. The displayed image may be unstable for a few seconds while the configuration is in progress.
	Position/Size/ Phase	Adjusts the options when the picture is not clear, especially when characters are shaky. Run Auto Config. before adjusting these.
	Reset	Restores all options to the default setting.

Picture Mode options

Setting	Description
Backlight	Adjusts the brightness of the screen by controlling the LCD backlight. If you decrease the brightness level, the screen becomes darker and the power consumption will be reduced without any video signal loss.
Contrast	Increases or decreases the gradient of the video signal. You may use Contrast when the bright part of the picture is saturated.
Brightness	Adjusts the base level of the signal in the picture. You may use Brightness when the dark part of the picture is saturated.
Sharpness	Adjusts the level of crispness in the edges between the light and dark areas of the picture. The lower the level, the softer the image.
Color	Adjusts intensity of all colors.
Tint	Adjusts the balance between red and green levels.
Color Temp.	Set to warm to enhance hotter Colors such as red, or set to cool to make picture bluish.
Advanced Control	Customizes the advanced options. Refer to the Advanced image options. (See p.42).
Picture Reset	Restores the options to the default setting.

NOTE

- When using the Smart Energy Saving function, the screen may look saturated in the white area of a still image.
- If Energy Saving is set to Minimum, Medium, or Maximum, the Smart Energy Saving function is disabled.

Advanced Control

Setting	Description
Dynamic Contrast (Off/High/Medium/Low)	Adjusts the contrast to keep it at the best level according to the brightness of the screen. The picture is improved by making bright parts brighter and dark parts darker. (Function works in the following mode - AV(CVBS), Component, HDMI-DTV, Display Port-DTV)
Dynamic Color (Off/High/Low)	Adjusts screen Colors so that they look livelier, richer and clearer. This feature enhances hue, saturation and luminance so that red, blue, green and white look more vivid. (Function works in the following mode - AV(CVBS), Component, HDMI-DTV, Display Port-DTV)
Clear White (Off/High/Low)	Make the white area of screen brighter and more white.
Skin Color (-5 to 5)	It detects the skin area of video and adjusts it to express a natural skin color.
Noise Reduction (Off/High/Medium/Low)	Reduces screen noise without compromising video quality. (Function works in the following mode - AV(CVBS), Component, HDMI-DTV, Display Port-DTV)
Digital Noise Reduction (Off/High/Medium/Low)	This option reduces the noise produced while creating digital video signals.
Gamma (High/Medium/Low)	Set your own gamma value. On the monitor, high gamma values display whitish images and low gamma values display high contrast images.
Black Level (High/Low)	● Low: The picture of the screen gets darker. ● High: The picture of the screen gets brighter. Set black level of the screen to proper level. (Function works in the following mode - AV(CVBS), Component, HDMI-DTV, Display Port-DTV)

AUDIO settings



1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **AUDIO** and press **OK**.

3 Press the Navigation buttons to scroll to the setting or option you want and press **OK**.
- To return to the previous level, press **BACK**.

4 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

The available audio options are described in the following:

Setting	Description	
Clear Voice II	By differentiating the human sound range from others,it helps users makes dialog easier to understand.	
Balance	Adjusts balance between the left and right speakers according to your room environment.	
Sound Mode	Mode	
	Standard	Select when you want standard-quality sound.
	Music	Select when you listen to music.
	Cinema	Select when you watch movies.
	Sport	Select when you watch sport events.
	Game	Selects when you play games.
Digital Audio Input	**HDMI/Display Port:** Outputs the sound of digital signal from HDMI and display ports through the monitor speaker. **Audio In:** Outputs the sound through the monitor speaker by connecting HDMI and display ports to the Audio In port.	
Speaker	**ON**: Enables sound to the monitor speaker. (* The monitor speaker is sold separately.) **OFF**: Disables sound to the monitor speaker. Use this option when using an external sound device.	

Sound Mode options

Setting	Description
Infinite Sound	LG's Infinity Sound option provides 5.1 channel stereo sound from two speakers.
Treble	Controls the dominant sounds in the output. When you turn up the treble, it will increase the output to the higher frequency range.
Bass	Controls the softer sounds in the output. When you turn up the bass, it will increase the output to the lower frequency range.
Reset	Resets the sound mode to the default setting.

TIME settings



1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **TIME** and press **OK**.

3 Press the Navigation buttons to scroll to the setting or option you want and press **OK**.
- To return to the previous level, press **BACK**.

4 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

The available time settings are described in the following:

Setting	Description
Clock	Sets the time feature.
Off/On Time	Sets the time to turn on or off the Monitor.
Sleep Timer	Sets the length of time until the Monitor to turns off. When you turn the Monitor off and turn it on again, the Sleep Timer will be set to off.
Power on delay	When connecting multiple monitors and turning the power on, the monitors are turned on individually to prevent overload.
Auto off	If Auto off is active and there is no input signal, the set switches to off mode automatically after 15 minutes.
Automatic Standby	If you do not use the monitor for more than 4 hours, it will be in off mode automatically.

NOTE

- Off/On Time can be saved for up to seven schedules; the Monitor is turned on or off at the preset time in the schedule list. If multiple preset times are stored in the schedule list, this function works at the nearest time from the current time.
- The scheduled power-off function works properly only when the device time is set correctly.
- When the scheduled power-on and power-off times are the same, the power-off time has priority over the power-on time if the set is turned on, and vice versa if the set is turned off.
- "The ""Automatic Standby"" and ""Auto off"" functions may not be available in some countries."

OPTION settings



1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **OPTION** and press **OK**.

3 Press the Navigation buttons to scroll to the setting or option you want and press **OK**.
- To return to the previous level, press **BACK**.

4 When you are finished, press **EXIT**.
When you return to the previous menu, press **BACK**.

The available option settings are described in the following:

Setting	Description	
Language	To choose the language in which the control names are displayed.	
Power Indicator	Use this function to set the power indicator on the front side of the product to On or Off.	
ISM Method	A frozen or still picture from a PC/Video game displayed on the screen for prolonged periods could result in a ghost image remaining even when you change the image. Avoid allowing a fixed image to remain on the screen for a long period of time.	
	Setting	
	Normal	Leave on normal if you don't foresee image burn in being a problem.
	Orbiter	May help prevent ghost images. However, it is best not to allow any fixed image to remain on the screen. To avoid a permanent image on the screen, the screen will move every 2 minutes.
	Inversion	This function inverts the panel color of the screen. The panel color is automatically inverted every 30 minutes.
	White Wash	White wash fills the screen with solid white. This helps removes permanent images burned into the screen. A permanent image may be impossible to clear entirely with white wash.
DPM Select	A user can choose to turn the power saving mode on / off.	
Fail Over	If there is no input signal, it automatically switches to another input with signal.	
	Setting	
	Off	Stops auto switch of the input source.
	Auto	Switches to another input source with video signal if no video signal comes from the current input source.
	Manual	Selects the priority of input source for auto switch. When several input sources are found, the input source with a higher priority will be selected.
Factory Reset	Select this option to return to the default factory settings.	
Set ID	You can assign a unique Set ID NO (name assignment) to each product when several products are connected for display. Specify the number (1 to 99) using the button and exit. Use the assigned Set ID to individually control each product using the Product Control Program.	

Setting	Description	
Tile Mode	**Tile Mode**	To use this function - Must be displayed with various other products. - Must be in a function that can be connected to RGB Cable by distributor and RS-232C. Tile mode and choose Tile alignment and set the ID of the current product to set location. * Only after pressing the SET button the adjustments made to the settings will be saved. - Tile mode : column x row (c = 1, 2, 3, 4, 5 r = 1, 2, 3, 4, 5) - 5 x 5 available. - Configuration of an integration screen is also available as well as configuration of One by one Display.
	Auto Config.	Adjusts the screen position automatically. The displayed image may be unstable for a few seconds while the configuration is in progress.
	PC Position	Moving the screen position horizontally and vertically.
	PC Size	Adjust the horizontal and vertical size of the screen taking into account the size of the bezel.
	Natural	The image is omitted by the distance between the screens to be naturally shown.
	Reset	Function to initialize and release Tile. All Tile setting are released when selecting Tile recall and the screen returns to Full screen.
	NOTE • If Tile Mode is enabled, Smart Energy Saving and the Auto option in Energy Saving will be disabled to provide the same picture quality as other displays.	
PIP/PBP	Videos or photos stored on the USB device can be displayed on a single monitor by dividing them into the main and subscreens.	
	Option	
	Mode	Sets the type of secondary screen. *OFF: Disables the secondary screen. *PIP (Picture In Picture): Displays the secondary screen in the main screen. *PBP (Picture By Picture): Displays the secondary screen next to the main screen.
	Position	Adjusts the position of the subscreen (top left, bottom left, top right, bottom right) The default value is inthe bottom right.
	Size	Adjusts the size of the subscreen (Size 0-10). The default size of the PIP (Size: 0) is 480x240; the maximum size (Size: 10) is 960x540.
	NOTE • The Position and Size options are enabled only in PIP mode.	

Setting	Description	
Key Lock	Key input does not work. This prevents invalid key input.	
Product/Service Info.	Displays the model name, software version, serial number, IP address, MAC address and home page.	
Portrait mode	Rotate OSD clockwise (90°,270°)	
	Option	
	90°	Rotate OSD clockwise 90°.
	270°	Rotate OSD clockwise 270°.
	 **90˚**	 **270˚**

Tile Mode

This monitor can be tiled with additional monitors to create a large tiled display.

Off

When the Tile Mode option is disabled

2X1

When using 2 monitors



2X2

When using 4 monitors



3X3

When using 9 monitors



4X4

When using 16 monitors



5X5

When using 25 monitors



Tile Mode - Natural mode

When active, the part of the image that would normally be displayed in the gap between the monitors is omitted.

Before



After



PIP/PBP

Displays videos or photos stored in the USB device on a single monitor by dividing it into the main and sub screens. (See p.37)

Mode

***PIP(Picture In Picture)**: Displays the Sub screen in the main screen.
***PBP(Picture By Picture)**: Displays the Sub screen next to the main screen.



Position

Adjusts the position of the subscreen (top left, bottom left, top right, bottom right)



Size

Adjusts the size of the subscreen (Size 0-10).



< 1920x1080 >

NOTE

- The subscreen is only supported when using the USB device.

		Sub
		USB
Main	Component	O
	RGB	O
	HDMI/DVI-D/Display Port	O
	AV	X

- You can only change the size and position in PIP mode.
- With PBP selected, the Aspect Ratio option in the PICTURE menu is disabled (Fixed as 16:9).
- While running the PBP function, the Tile Mode function does not work.
- You must select the output sound before running the PIP or PBP functions. (Select either Main or Sub.)
- If you fail to select Main or Sub from the sound selection box, and if the OSD disappears after either a period of time or when the Exit or Back key is pressed, the PIP/PBP subscreen is not activated.
- You cannot change the sound while running the PIP or PBP functions. If you want to change the sound, please restart PIP/PBP.
- The picture quality of the subscreen is set according to the values selected in the main menu, not the USB device.
- Even when the power is turned off or on, if the USB device is connected, the PIP/PBP mode plays again from where it left off.
- If you play videos you selected in PIP/PBP mode, the videos will play back repeatedly in succession.
- The buttons below work in PIP mode.

Button	Photo	Movie
"<"	O	X
">"	O	X
▶	X	O
■	X	X
▶▶	X	O
◀◀	X	O
II	X	O

NETWORK settings



1 Press **MENU** to access the main menus.

2 Press the Navigation buttons to scroll to **NETWORK** and press **OK**.

3 Press the Navigation buttons to scroll to the setting or option you want and press **OK**.

- To return to the previous level, press **BACK**.

4 When you are finished, press **EXIT**.

When you return to the previous menu, press **BACK**.

The available option settings are described in the following:

Setting	Description
Player Name	Sets the player name used in SuperSign Manager.(Up to 20 characters)
Network Setting	Configure the network settings.
Network Status	Display the network status. - Internet is connected : Extermally connected - Home network is connected : Only internally connected - Not connected : When there is no network connection
Server IP Setting	Sets the IP address of the computer (server) on which SuperSign Manager is installed.
Server IP Status	Displays the connection status with the server. - Not connected : When there is no network connection with SuperSign server - Waiting for approval : When network connection with SuperSign server has been made, but access to server has not been approved by the server - Rejected : When network connection with SuperSign server has been made, but access to server has been rejected by the server - Internet is connected : When network connection with SuperSign server has been made and access to server has also been approved by the server

CAUTION

- When setting the Player Name, input delay may occur if you press the buttons on the remote control continuously.

ENGLISH

MAKING CONNECTIONS

Connect various external devices to the ports on the Monitor's back panel.

1 Find an external device you want to connect to your Monitor shown on the following illustration.

2 Check the connection type of the external device.

3 Go to the appropriate illustration and check the connection details.



NOTE

- If you connect a gaming device to the Monitor, use the cable supplied with the gaming device.

Connecting to a HD receiver, DVD, Camcorder, Camera, Gaming Device or VCR player

Connect a HD receiver, DVD, or VCR player to the Monitor and select an appropriate input mode.

HDMI connection

Transmits the digital video and audio signals from an external device to the Monitor. Connect the external device and the Monitor with the HDMI cable as shown on the following illustration.



Component connection

Transmits the analog video and audio signals from an external device to the Monitor. Connect the external device and the Monitor with the 15 pin signal to RCA cable as shown on the following illustration. To display images by using progressive scan, make sure to use the component cable.



NOTE

- Use a High Speed HDMI™ Cable.
- High Speed HDMI™ Cables are tested to carry an HD signal up to 1080p and higher.

AV(CVBS) connection

Transmits the analog video and audio signals from an external device to the Monitor. Connect the external device and the Monitor with the 15 pin signal to RCA cable as shown on the following illustration.



Connecting to a USB

Connect a USB storage device such as s USB flash memory, external hard drive, MP3 player or a USB memory card reader to the Monitor and access the USB menu to use various multimedia files.



Connecting to the LAN

LAN connection

A Connect PC to Monitor directly.



B Using a router(Switch)



C Using the Internet.



NOTE

- Using LAN establishes communication between your PC and the monitor and enables to use the OSD menus on the PC as well as on the monitor.

Daisy Chain Monitors

Use this function to share the RGB video signal with other monitors without having to use a separate signal splitter box.
To use different products connected to each other Connect one end of the signal input cable (15-pin D-Sub Signal Cable) to the RGB OUT connector of product 1 and connect the other end to the RGB IN connector of other products



NOTE

- The number of monitors that can be connected to one output may vary depending on signal status and cable loss. If the signal status is good, and there is no cable loss, it is possible to connect up to 9 monitors. If you want to connect more than this number of monitors, it is recommended to use a distributor.
- When multi-connecting in/out cascade format, no loss cables are recommended.

TROUBLESHOOTING

No image is displayed

Problem	Resolution
Is the product power cord connected?	• See if the power cord is properly connected to the outlet.
Is the power indicator light on?	• See if the power switch is turned on. • May need service.
Power is on, power indicator is blue but the screen appears extremely dark.	• Adjust brightness and contrast again. • Backlight may need repair.
The power indicator amber?	• If the product is in power saving mode, move the mouse or press any key. • Turn both devices off and then back on.
Does the 'Out of range' message appear?	• The signal from the PC (video card) is out of the vertical or horizontal frequency range of the product. Adjust the frequency range by referring to the Specifications in this manual. * Maximum resolution RGB, HDMI, DVI-D, Display Port : 1920 x 1080 @ 60 Hz
Does the 'Check signal cable' message appear?	• The signal cable between PC and product is not connected. Check the signal cable. • Press the 'INPUT' menu in the remote Control to check the input signal.

'Unknown Product' message appears when the product is connected.

Problem	Resolution
Did you install the driver?	• Install the product driver, which is provided with the product, or download it from the web site. (http://www.lg.com) • See if the plug&play function is supported by referring to the video card user manual.

'Key Lock On' message appears.

Problem	Resolution
The 'Key Lock On' message appears when pressing the Menu button.	The Lock function prevents the OSD settings from being changed inadvertently. To release the lock, go to Menu and Option and disable the Key Lock option.

The screen image looks abnormal.

Problem	Resolution
Is the screen position wrong?	• D-Sub analog signal - Press the "AUTO" button in the remote control to automatically select the optimal screen status that fits into the current mode. If adjustment is not satisfactory, use the Position OSD menu. • See if the video card resolution and frequency are supported by the product. If the frequency is out of range, set to the recommended resolution in the Control Panel "Display" Setting menu.
Do thin lines appear on the background screen?	• D-Sub analog signal - Press the "AUTO" button in the remote control to automatically select an optimal screen status that fits into the current mode. If adjustment is not satisfactory, use the Clock OSD menu.
Horizontal noise appears or the characters look blurred.	• D-Sub analog signal - Press the "AUTO" button in the remote control to automatically select an optimal screen status that fits into the current mode. If adjustment is not satisfactory, use the Phase OSD menu.
The screen is displayed abnormally.	• The proper input signal is not connected to the signal port. Connect the signal cable that matches with the source input signal.

After-image appears on the product.

Problem	Resolution
After-image appears when the product is turned off.	• If you use a fixed image for a long time, the pixels may be damaged quickly. Use the screen-saver function.

The audio function does not work.

Problem	Resolution
No sound?	• See if the audio cable is connected properly. • Adjust the volume. • See if the sound is set properly.
Sound is too dull.	• Adjust the Clear Voice II, Treble and Bass appropriately.
Sound is too low.	• Adjust the volume.

Screen color is abnormal.

Problem	Resolution
Screen has poor color resolution (16 colors).	• Set the number of colors to more than 24 bits (true color) Select Control Panel - Display - Settings - Color Table menu in Windows.
Screen color is unstable or mono-colored.	• Check the connection status of the signal cable. Or, re-insert the PC video card.
Do black spots appear on the screen?	• Several pixels (red, green, white or black color) may appear on the screen, which can be attributable to the unique characteristics of the LCD panel. It is not a malfunction of the LCD.

The operation does not work normally.

Problem	Resolution
The power suddenly turned off.	• Is the sleep timer set? • Check the power control settings. Power interrupted

SPECIFICATIONS

42WS10

LCD Panel	Screen Type	1067.31 mm Wide (42 inch) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel. Visible diagonal size : 1067.31 mm
	Pixel Pitch	0.4845 mm (H) x 0.4845 mm (V)
Video Signal	Max. Resolution	RGB : 1920 X 1080 @60 Hz HDMI,DVI-D, Display Port : 1920 X 1080 @60 Hz - It may not be supported depending on the OS or video card type.
	Recommended Resolution	RGB : 1920 X 1080 @60 Hz HDMI,DVI-D, Display Port : 1920 X 1080 @60 Hz - It may not be supported depending on the OS or video card type.
	Horizontal Frequency	RGB : 30 kHz to 83 kHz HDMI,DVI-D, Display Port : 30 kHz to 83 kHz
	Vertical Frequency	RGB : 56 Hz to 75 Hz HDMI,DVI-D, Display Port : 56 Hz to 60 Hz
	Synchronization Type	Separate Sync, Composite Sync, Digital
Input Connector		15-pin D-Sub, HDMI, DVI-D, Display Port, RS-232C, LAN, USB, Audio
Power	Rated Voltage	100-240 V~ 50/60 Hz 1.6 A
	Power Consumption	On Mode : 115 W Typ. Sleep Mode (RGB) : ≤ 1 W Sleep Mode (HDMI, DVI-D, Display Port) : ≤ 1 W (Set Only) / ≤ 2 W (With External Device) Off Mode : ≤ 0.5 W
Environmental conditions	Operating Temperature Operating Humidity	0 °C to 40 °C 10 % to 80 %
	Storage Temperature Storage Humidity	-20 °C to 60 °C 5 % to 95 %

Product specifications shown above may be changed without prior notice due to upgrade of product functions.

Dimensions (Width x Height x Depth) / Weight	
	991.7 mm x 584.3 mm x 37.5 mm / 12.6 kg
	
	991.7 mm x 659.2 mm x 298.3 mm / 14 kg
	
	991.7 mm x 584.3 mm x 75.7 mm / 13.4 kg
	
	991.7 mm x 659.2 mm x 298.3 mm / 14.8 kg

*** Applicable only for models that support the speakers**

Audio	RMS Audio Output	10 W + 10 W (R + L)
	Input Sensitivity	0.7 Vrms
	Speaker Impedance	8 Ω

Product specifications shown above may be changed without prior notice due to upgrade of product functions.

47WS10

LCD Panel	Screen Type	1192.78 mm Wide (47 inch) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel. Visible diagonal size : 1192.78 mm
	Pixel Pitch	0.5414 mm (H) x 0.5414 mm (V)
Video Signal	Max. Resolution	RGB : 1920 X 1080 @60 Hz HDMI,DVI-D, Display Port : 1920 X 1080 @60 Hz - It may not be supported depending on the OS or video card type.
	Recommended Resolution	RGB : 1920 X 1080 @60 Hz HDMI,DVI-D, Display Port : 1920 X 1080 @60 Hz - It may not be supported depending on the OS or video card type.
	Horizontal Frequency	RGB : 30 kHz to 83 kHz HDMI,DVI-D, Display Port : 30 kHz to 83 kHz
	Vertical Frequency	RGB : 56 Hz to 75 Hz HDMI,DVI-D, Display Port : 56 Hz to 60 Hz
	Synchronization Type	Separate Sync, Composite Sync, Digital
Input Connector		15-pin D-Sub, HDMI, DVI-D, Display Port, RS-232C, LAN, USB, Audio
Power	Rated Voltage	100-240 V~ 50/60 Hz 1.8 A
	Power Consumption	On Mode : 120 W Typ. Sleep Mode (RGB) : ≤ 1 W Sleep Mode (HDMI, DVI-D, Display Port) : ≤ 1 W (Set Only) / ≤ 2 W (With External Device) Off Mode : ≤ 0.5 W
Environmental conditions	Operating Temperature Operating Humidity	0 °C to 40 °C 10 % to 80 %
	Storage Temperature Storage Humidity	-20 °C to 60 °C 5 % to 95 %

Product specifications shown above may be changed without prior notice due to upgrade of product functions.

Dimensions (Width x Height x Depth) / Weight	
	1102.0 mm x 646.4 mm x 37.4 mm / 17.5 kg
	
	1102.0 mm x 720.9 mm x 298.3 mm / 18.9 kg
	
	1102.0 mm x 646.4 mm x 74.1 mm / 18.3 kg
	
	1102.0 mm x 720.9 mm x 298.3 mm / 19.7 kg

*** Applicable only for models that support the speakers**

Audio	RMS Audio Output	10 W + 10 W (R + L)
	Input Sensitivity	0.7 Vrms
	Speaker Impedance	8 Ω

Product specifications shown above may be changed without prior notice due to upgrade of product functions.

55WS10

LCD Panel	Screen Type	1387.80 mm Wide (55 inch) TFT (Thin Film Transistor) LCD (Liquid Crystal Display) Panel. Visible diagonal size : 1387.80 mm
	Pixel Pitch	0.630 mm(H) x 0.630 mm(V)
Video Signal	Max. Resolution	RGB : 1920 X 1080 @60 Hz HDMI,DVI-D, Display Port : 1920 X 1080 @60 Hz - It may not be supported depending on the OS or video card type.
	Recommended Resolution	RGB : 1920 X 1080 @60 Hz HDMI,DVI-D, Display Port : 1920 X 1080 @60 Hz - It may not be supported depending on the OS or video card type.
	Horizontal Frequency	RGB : 30 kHz to 83 kHz HDMI,DVI-D, Display Port : 30 kHz to 83 kHz
	Vertical Frequency	RGB : 56 Hz to 75 Hz HDMI,DVI-D, Display Port : 56 Hz to 60 Hz
	Synchronization Type	Separate Sync, Composite Sync, Digital
Input Connector		15-pin D-Sub, HDMI, DVI-D, Display Port, RS-232C, LAN, USB, Audio
Power	Rated Voltage	100-240 V~ 50/60 Hz 2.0 A
	Power Consumption	On Mode : 140 W Typ. Sleep Mode (RGB) : ≤ 1 W Sleep Mode (HDMI, DVI-D, Display Port) : ≤ 1 W (Set Only) / ≤ 2 W (With External Device) Off Mode : ≤ 0.5 W
Environmental conditions	Operating Temperature Operating Humidity	0 °C to 40 °C 10 % to 80 %
	Storage Temperature Storage Humidity	-20 °C to 60 °C 5 % to 95 %

Product specifications shown above may be changed without prior notice due to upgrade of product functions.

Dimensions (Width x Height x Depth) / Weight	
	1281.6 mm x 752.4 mm x 37.8 mm / 21.8 kg
	
	1281.6 mm x 825.7 mm x 298.3 mm /23.2 kg
	
	1281.6 mm x 752.4 mm x 79.1 mm / 22.5 kg
	
	1281.6 mm x 825.7 mm x 298.3 mm / 23.9 kg

*** Applicable only for models that support the speakers**

Audio	RMS Audio Output	10 W + 10 W (R + L)
	Input Sensitivity	0.7 Vrms
	Speaker Impedance	8 Ω

Product specifications shown above may be changed without prior notice due to upgrade of product functions.

Dimensions

The illustrations in this manual may differ from the actual product and accessories.
Please see the "Mounting on a wall" section for sizes of screws. (See p.11)







(Unit : mm)

	42 inch	47 inch	55 inch
A	991.7	1102.0	1281.6
B	298.3	298.3	298.3
C	37.5	37.5	37.8
D	76.1	76.1	80.0
E	584.3	646.4	752.4
F	659.2	720.9	825.7
G	726.0	824.2	950.0
H	27.6	28.0	33.5
I	27.6	28.0	33.5
J	27.6	28.0	33.5
K	102.4	102.5	106.8
L	140.3	140.3	136.4
M	295.9	351.0	440.8
N	92.2	123.2	176.2
O	400.0	400.0	400.0
P	400.0	400.0	400.0

Product specifications shown above may be changed without prior notice due to upgrade of product functions.

RGB (PC) supported mode

Resolution	Horizontal Frequency(kHz)	Vertical Frequency(Hz)
640 x 350	31.469	70.8
720 x 400	31.468	70.8
640 x 480	31.469	59.94
640 x 480	37.5	75
800 x 600	37.879	60.317
800 x 600	46.875	75
832 x 624	49.725	74.55
1024 x 768	48.363	60
1024 x 768	60.123	75.029
1280 x 720	44.772	59.855
1366 x 768	47.7	60
1280 x 1024	63.981	60.02
1280 x 1024	79.98	75.02
1680 x 1050	65.290	59.954
1920 x 1080	67.5	60

HDMI,DVI-D,Display Port (PC) supported mode

Resolution	Horizontal Frequency(kHz)	Vertical Frequency(Hz)
640 x 480	31.469	59.94
800 x 600	37.879	60.317
1024 x 768	48.363	60
1280 x 720	44.772	59.855
1366 x 768	47.7	60
1280 x 1024	63.981	60.02
1680 x 1050	65.290	59.954
1920 x 1080	67.5	60

DTV Mode

Resolution	Component	HDMI,Display Port (DTV)
480i	o	x
576i	o	x
480p	o	o
576p	o	o
720p	o	o
1080i	o	o
1080p	o	o

Power Indicator

Mode	Product
On Mode	blue
Sleep Mode	Amber
Off Mode	-

NOTE

- When the cable is connected to the HDMI or the display port, you can select the PC/DTV mode optionally. It is recommended you to set to the PC mode when connecting to PC; the DTV mode when connecting to DTV.

NOTE

- Vertical frequency: To enable the user to watch the product display, screen image should be changed tens of times every second like a fluorescent lamp. The vertical frequency or refresh rate is the times of image display per second. The unit is Hz.
- Horizontal frequency: The horizontal interval is the time to display one vertical line. When 1 is divided by the horizontal interval, the number of horizontal lines displayed every second can be tabulated as the horizontal frequency. The unit is kHz.

IR CODES

Code (Hexa)	Function	Note
95	ENERGY SAVING (e)	R/C BUTTON
08	POWER (⏻) ON/OFF	R/C BUTTON
0B	INPUT	R/C BUTTON
C4	MONITOR ON	R/C BUTTON (Discrete IR Code)
C5	MONITOR OFF	R/C BUTTON (Discrete IR Code)
43	MENU	R/C BUTTON
40	Up (^)	R/C BUTTON
41	Down (v)	R/C BUTTON
07	Left (<)	R/C BUTTON
06	Right (>)	R/C BUTTON
44	OK (◉)	R/C BUTTON
28	BACK (↶)	R/C BUTTON
5B	EXIT	R/C BUTTON
4D	PSM	R/C BUTTON
02	Volume ◿ (+)	R/C BUTTON
03	Volume ◿ (-)	R/C BUTTON
09	MUTE	R/C BUTTON
E0	BRIGHTNESS ^ (PAGE UP)	R/C BUTTON
E1	BRIGHTNESS v (PAGE Down)	R/C BUTTON
10 to 19	Number Key 0 to 9	R/C BUTTON
72	Red Key (ID ON)	R/C BUTTON
71	Green Key (ID OFF)	R/C BUTTON
63	Yellow Key	R/C BUTTON
61	Blue Key	R/C BUTTON
7B	TILE	R/C BUTTON
5A	AV(CVBS)	Discrete IR Code
BF	Component	Discrete IR Code
D5	RGB	Discrete IR Code
CE	Display Port	Discrete IR Code
C6	DVI-D	Discrete IR Code
E9	HDMI	Discrete IR Code
76	ARC (4:3)	Discrete IR Code
77	ARC (16:9)	Discrete IR Code
AF	ARC (ZOOM,Cinema Zoom 1)	Discrete IR Code
79	ARC (MARK)	R/C BUTTON (Discrete IR Code)
99	Auto Config.	R/C BUTTON (Discrete IR Code)
B1	■	R/C BUTTON
B0	▶	R/C BUTTON
BA	⏸	R/C BUTTON
8F	◀◀	R/C BUTTON
8E	▶▶	R/C BUTTON

ENGLISH

CONTROLLING THE MULTIPLE PRODUCT

- Use this method to connect several products to a single PC. You can control several products at a time by connecting them to a single PC.
- In the Option menu, Set ID must be between 1 and 99 without being duplicated.

Connecting the cable

Connect the RS-232C cable as shown in the picture.

- The RS-232C protocol is used for communication between the PC and product. You can turn the product on/off, select an input source or adjust the OSD menu from your PC.



RS-232C Configurations

7-Wire Configurations (Standard RS-232C cable)



3-Wire Configurations (Not Standard)



Communication Parameter

- Baud Rate : 9600 buad Rate (UART)
- Data Length : 8 bit
- Parity Bit : None
- Stop Bit : 1bit
- Flow Control : None
- Communication Code : ASCII code
- Use a crossed (reverse) cable

Command reference list

		COMMAND		DATA
1	Power	k	a	00H to 01H
2	Aspect Ratio	k	c	01H to 1FH
3	Screen Mute	k	d	00H to 01H
4	Volume Mute	k	e	00H to 01H
5	Volume Control	k	f	00H to 64H
6	Contrast	k	g	00H to 64H
7	Brightness	k	h	00H to 64H
8	Color	k	i	00H to 64H
9	Tint	k	j	00H to 64H
10	Sharpness	k	k	00H to 64H
11	OSD Select	k	l	00H to 01H
12	Remote Lock/ key Lock	k	m	00H to 01H
13	Treble	k	r	00H to 64H
14	Bass	k	s	00H to 64H
15	Audio Balance	k	t	00H to 64H
16	Abnomal state	k	z	FFH
17	White Balance Red Gain	j	m	00H to FEH
18	White Balance Green Gain	j	n	00H to FEH
19	White Balance Blue Gain	j	o	00H to FEH
20	ISM mode	j	p	01H to 08H
21	Energy Saving	j	q	00H to 05H
22	Auto configuration	j	u	01H
23	Remocon Key	m	c	Key Code
24	Fail Over Select	m	i	00H to 02H
25	Fail Over Input Select	m	j	Refer ’25. Fail Over Input Select’
26	4 Hours Off	m	n	00H to 01H
27	Tile Mode Check	d	z	FFH
28	Tile Mode	d	d	00H to 55H
29	Tile H Position	d	e	00H to 14H
30	Tile V Position	d	f	00H to 14H
31	Tile H Size	d	g	00H to 64H
32	Tile V Size	d	h	00H to 64H
33	Tile ID Set	d	i	01H to 19H
34	Natural Mode (In Tile mode)	d	j	00H to 01H
35	Picture mode (PSM)	d	x	00H to 04H
36	Sound mode	d	y	00H to 05H
37	Fan Fault check	d	w	FFH
38	Elapsed time return	d	l	FFH
39	Temperature value	d	n	FFH
40	Lamp fault check	d	p	FFH
41	Speaker	d	v	00H to 01H
42	Sleep Time	f	f	00H to 08H

		COMMAND		DATA
43	Auto Sleep	f	g	00H to 01H
44	Power On Delay	f	h	00H to 64H
45	Language	f	i	00H to 12H
46	DPM Select	f	j	00H to 01H
47	Reset	f	k	00H to 03H
48	Power Indicator	f	o	00H to 01H
49	Serial no.	f	y	FFH
50	S / W Version	f	z	FFH
51	Time 1(Years/ Months/ Days)	f	a	Refer to ‘Time 1’
52	Time 2(Hours/ Minutes/Seconds)	f	x	Refer to ‘Time 2’
53	Off Timer(Repeat mode/ Time)	f	e	Refer to ‘Off Timer’
54	On Timer(Repeat Mode/ Time)	f	d	Refer to ‘On Timer’
55	On Timer Input	f	u	Refer to ‘On Timer Input’
56	H Position	f	q	00H to 64H
57	V Position	f	r	23H to 41H
58	H Size	f	s	00H to 64H
59	Input Select	x	b	20H to D0H
60	Color Temperature	x	u	00H to 64H

- Note : When using the product with a USB DivX player, all commands except for Power (k a), Key (m c), Abnormal state (k z), Fan Fault check (d w), Elapsed time return (d l), Temperature value (d n), Lamp fault Check (d p), Serial no.Check (f y), and S/W Version (f z) are not executed and handled as errors.

Transmission / Receiving protocol

Transmission

[Command1][Command2][ ][Set ID][ ][Data][Cr]

* [Command 1]: First command. (k, j, m, d, f, x)
* [Command 2]: Second command.(a to u)
* [Set ID]: Set up the Set ID number of product.
  range : 01H to 63H. by setting '0', server can control all products.
* In case of operating with more than 2 sets using set ID as '0' at the same time, it should not be checked the ack message. Because all sets will send the ack message, so it's impossible the check the whole ack messages.
* [DATA]: To transmit command data.
  Transmit 'FF' data to read status of command.
* [Cr]: Carriage Return (ASCII code '0 x 0 D')
* [ ]: ASCII code Space (0 x 20)

OK Acknowledgement

[Command2][ ][Set ID][ ][OK][Data][x]

* The Product transmits ACK (acknowledgement) based on this format when receiving normal data. At this time, if the data is data read mode, it indicates present status data. If the data is data write mode, it returns the data of the PC computer.

Error Acknowledgement

[Command2][ ][Set ID][ ][NG][Data][x]

* If there is error, it returns NG

*** Real data mapping**

Hexadecimal Num. (Setting Value)	**Decimal Num.** (Real Value)
0	0
A	10
F	15
10	16
20	32
64	100

01. Power (Command: k a)
To control Power On/Off of the set.

Transmission
[k][a][ ][Set ID][ ][Data][Cr]

Data
00 : Power Off
01 : Power On

Acknowledgement
[a][ ][Set ID][ ][OK][Data][x]

To show the status of Power On/Off.

Transmission
[k][a][ ][Set ID][ ][FF][Cr]

Acknowledgement
[a][ ][Set ID][ ][OK][Data][x]

Data
00 : Power Off
01 : Power On

02. Aspect Ratio (Command: k c)
To adjust the screen format.
You can also adjust the screen format using the ARC (Aspect Ratio Control) button on remote control or in the Screen menu.

Transmission
[k][c][ ][Set ID][ ][Data][Cr]

Data
01 : Normal Screen (4 : 3)
02 : Wide Scran (16 : 9)
04 : Zoom
(AV,Component,HDMI/Display Port DTV)
09 : Just Scan
(Component,HDMI/Display Port DTV)
* When the RGB, DVI-D, HDMI/ Display Port PC mode (1:1)
10 to 1F : Cinema Zoom 1 to 16
(AV, Component, HDMI/Display Port DTV)

Acknowledgement
[c][ ][Set ID][ ][OK][Data][x]

03. Screen Mute (Command: k d)
To select screen mute on / off.

Transmission
[k][d][ ][Set ID][ ][Data][Cr]

Data
00: Screen mute off (Picture on)
01 : Screen mute on (Picture off)

Acknowledgement
[d][ ][Set ID][ ][OK][Data][x]

04. Volume Mute (Command: k e)
To control On/Off of the Volume Mute.

Transmission
[k][e][ ][Set ID][ ][Data][Cr]

Data
00 : Volume Mute On (Volume Off)
01 : Volume Mute Off (Volume On)

Acknowledgement
[e][ ][Set ID][ ][OK][Data][x]

Data
00 : Volume Mute On (Volume Off)
01 : Volume Mute Off (Volume On)

05. Volume Control (Command: k f)
To adjust Volume.

Transmission
[k][f][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H
(Hexadecimal code)

Acknowledgement
[f][ ][Set ID][ ][OK][Data][x]

Data
Min : 00H to Max : 64H

06. Contrast (Command: k g)
To adjust screen contrast.
You can also adjust the contrast in the Picture menu.

Transmission
[k][g][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H

Acknowledgement
[g][ ][Set ID][ ][OK][Data][x]

Data
Min : 00H to Max : 64H
* Refer to 'Real data mapping '.

07. Brightness (Command: k h)
To adjust screen brightness.
You can also adjust the brightness in the Picture menu.

Transmission
[k][h][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H
(Hexadecimal code)
* Refer to 'Real data mapping '.

Acknowledgement
[h][ ][Set ID][ ][OK][Data][x]

* Refer to 'Real data mapping '.

08. Color (Command: k i) (Video Timing only)
To adjust the screen color.
You can also adjust the color in the Picture menu.

Transmission
[k][i][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H
(Hexadecimal code)
* Refer to 'Real data mapping '.

Acknowledgement
[i][ ][Set ID][ ][OK][Data][x]

Data
Min : 00H to Max : 64H

09. Tint (Command: k j)
To adjust the screen tint.
You can also adjust the tint in the Picture menu.

Transmission
[k][j][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H
(Hexadecimal code)
00H : Step R50
64H : Step G50

Acknowledgement
[j][ ][Set ID][ ][OK][Data][x]

Data Min : 00H to Max : 64H
* Tint Real data mapping
0 : Step 0 to Red
64 : Step 100 to Green

10. Sharpness (Command: k k) (Video input only)
To adjust the screen Sharpness.
You can also adjust the sharpness in the Picture menu.

Transmission
[k][k][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H
(Hexadecimal code)
* Refer to 'Real data mapping '.

Acknowledgement
[k][ ][Set ID][ ][OK][Data][x]

Data
Min : 00H to Max : 64H

11. OSD Select (Command: k l)
To control OSD on/off to the set.

Transmission
[k][l][ ][Set ID][ ][Data][Cr]

Data
00: OSD Off
01: OSD On

Acknowledgement
[l][ ][Set ID][ ][OK][Data][x]

Data
00: OSD Off
01: OSD On

12. Remote Lock /Key Lock (Command: k m)
To control Remote Lock on/off to the set.
This function, when controlling RS-232C, locks the remote control and the local keys.

Transmission
[k][m][ ][Set ID][ ][Data][Cr]

Data
00: Off
01: On

Acknowledgement
[m][ ][Set ID][ ][OK][Data][x]

Data
00: Off
01: On

13. Treble (Command: k r)
To adjust treble.

Transmission
[k][r][ ][Set ID][ ][Data][Cr]

Data
00~64: Treble 0~100

Acknowledgement
[r][ ][Set ID][ ][OK/NG][Data][x]

14. Bass (Command: k s)
To adjust bass.

Transmission
[k][s][ ][Set ID][ ][Data][Cr]

Data
00~64: Bass 0~100

Acknowledgement
[s][ ][Set ID][ ][OK/NG][Data][x]

15. Balance (Command: k t)
To adjust the sound balance.

Transmission
[k][t][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H
(Hexadecimal code)
00H : Step L50
64H : Step R50

Acknowledgement
[t][ ][Set ID][ ][OK][Data][x]

Data
Min : 00H to Max : 64H
(Hexadecimal code)
00H : Step 0 to L50
64H : Step 100 to R50
* Balance : L50 to R50

16. Abnormal state (Command: k z)
Used to Read the power off status when Stand-by mode.

Transmission
[k][z][ ][Set ID][ ][Data][Cr]

Data
FF : Read

Acknowledgement
[z][ ][Set ID][ ][OK][Data][x]

Data
00 : Normal (Power on and signal exist)
01 : No signal (Power on)
02 : Turn the monitor off by remote control
03 : Turn the monitor off by sleep time function
04 : Turn the monitor off by RS-232C function
08 : Turn the monitor off by off time function
09 : Turn the monitor off by auto off function

17. White Balance Red Gain (Command: j m)
To adjust white balance red gain.

Transmission
[j][m][ ][Set ID][ ][Data][Cr]

Data
00~FE: Red gain 0~254

Acknowledgement
[z][ ][Set ID][ ][OK/NG][Data][x]

18. White Balance Green Gain (Command: j n)
To adjust white balance green gain.

Transmission
[j][n][ ][Set ID][ ][Data][Cr]

Data
00~FE: Green gain 0~254

Acknowledgement
[n][ ][Set ID][ ][OK/NG][Data][x]

19. White Balance Blue Gain (Command: j o)
To adjust white balance blue gain.

Transmission
[j][o][ ][Set ID][ ][Data][Cr]

Data
00~FE: Blue gain 0~25

Acknowledgement
[o][ ][Set ID][ ][OK/NG][Data][x]

20. ISM mode (Command: j p)
Used to select the afterimage preventing function.

Transmission
[j][p][ ][Set ID][ ][Data][Cr]

Data
01 : Inversion
02 : Orbiter
04 : White Wash
08 : Normal

Acknowledgement
[p][ ][Set ID][ ][OK][Data][x]

21. Energy Saving (Command: j q)
To reduce the power consumption of the Monitor.

Transmission
[j][q][ ][Set ID][ ][Data][Cr]

Data
04: Auto
00: Off
01: Minimum
02: Medium
03: Maximum
05: Screen off

Acknowledgement
[q][ ][Set ID][ ][OK][Data][x]

22. Auto Config. (Command: j u)
To adjust picture position and minimize image shaking. Automatically. NB : Only applies to RGB(PC) mode.

Transmission
[j][u][ ][Set ID][ ][Data][Cr]

Data
01 : To set

Acknowledgement
[u][ ][Set ID][ ][OK][Data][x]

23. Key (Command: m c)
To send IR remote key code.

Transmission
[m][c][ ][Set ID][ ][Data][Cr]

Data
Key code : Refer to 'IR CODES'.

Acknowledgement
[c][ ][Set ID][ ][OK][Data][x]

24. Fail Over Select (Command: m i)
To select Fail Over mode.

Transmission
[m][i][ ][Set ID][ ][Data][Cr]

Data
00: Off
01: Auto
02: Manual

Acknowledgement
[i][ ][Set ID][ ][OK/NG][Data][x]

25. Fail Over Input Select (Command: m j)
To select fail over mode.
* Only available in Fail Over manual mode.

Transmission
[m][j][ ][Set ID][ ][Data1][ ][Data2][ ][Data3]
[ ][Data4][Cr]

Data(Priority 1~4)
60: RGB
70: DVI-D
90: HDMI
C0: Display Port
* Use 0x70 as data for DVI-D input, 0x90 as data for HDMI input, 0xC0 as data for DisplayPort input, regardless their input labels.

Acknowledgement
[j][ ][Set ID][ ][OK/NG][Data1][Data2][Data3][x]

26. 4 Hours Off (Command: m n)
To set the 4 Hours Off function.

Transmission
[m][n][ ][Set ID][ ][Data][Cr]

Data
00: 4 Hours Off Off
01: 4 Hours Off On

Acknowledgement
[n][ ][Set ID][ ][OK/NG][Data][x]

27. Tile Mode Check (Command: d z)
To check Tile Mode status.

Transmission
[d][z][ ][Set ID][ ][Data][Cr]

Data
FF: Check Tile Mode status

Acknowledgement
[z][ ][Set ID][ ][OK/NG][Data1][Data2][Data3][x]

Data1
00: Tile Mode Off
01: Tile Mode On
Data2
00 to 0F: Tile Col Value
Data3
00 to 0F: Tile Row Value

28. Tile Mode (Command: d d)
Change a Tile Mode.

Transmission
[d][d][ ][Set ID][ ][Data][Cr]

Data	Description
00 or 11	Tile mode is off.
12	1 x 2 mode (column x row)
13	1 x 3 mode
14	1 x 4 mode
...	...
55	1 x 2 mode

* The data can not be set to 0X or X0 except 00.

Acknowledgement
[d][ ][Set ID][ ][OK/NG][Data][x]

29. Tile H Position (Command: d e)
To set the Horizontal position.

Transmission
[d][e][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 14H
00H : Step -10(Left)
14H : Step 10(Right)

Acknowledgement
[e][ ][Set ID][ ][OK/NG][Data][x]

30. Tile V Position (Command: d f)
To set the Vertical position.

Transmission
[d][f][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 14H
00H : Step -10(Down)
14H : Step 10(Up)

Acknowledgement
[f][ ][Set ID][ ][OK/NG][Data][x]

31. Tile H Size (Command: d g)
To set the Horizontal size.

Transmission
[d][g][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H
* Refer to 'Real data mapping '.

Acknowledgement
[g][ ][Set ID][ ][OK/NG][Data][x]

32. Tile V Size (Command: d h)
To set the Vertical size.

Transmission
[d][h][ ][Set ID][ ][Data][Cr]

Data
Min : 00H to Max : 64H
* Refer to 'Real data mapping '.

Acknowledgement
[h][ ][Set ID][ ][OK/NG][Data][x]

33. Tile ID Set (Command: d i)
To assign the Tile ID for Tiling function.

Transmission
[d][i][ ][Set ID][ ][Data][Cr]

Data
Min : 01H to Max : 19H
(Hexadecimal code)

Acknowledgement
[i][ ][Set ID][ ][OK/NG][Data][x]

34. Natural Mode (Command: d j)
To assign the Tile Natural mode for Tiling function.

Transmission
[d][j][ ][Set ID][ ][Data][Cr]

Data
00 : Natural Off
01 : Natural On
ff : Read Status

Acknowledgement
[j][ ][Set ID][ ][OK/NG][Data][x]

35. Picture Mode (Command: d x)
To adjust the picture mode.

Transmission
[d][x][ ][Set ID][ ][Data][Cr]

Data Structure

Data(Hex)	Mode
00	Vivid
01	Standard
02	Cinema
03	Sport
04	Game

Acknowledgement
[x][ ][Set ID][ ][OK/NG][Data][x]

36. Sound Mode (Command: d y)
To adjust the Sound mode.

Transmission
[d][y][ ][Set ID][ ][Data][Cr]

Data Structure

Data(Hex)	Mode
01	Standard
02	Music
03	Cinema
04	Sport
05	Game

Acknowledgement
[y][ ][Set ID][ ][OK/NG][Data][x]

37. Fan Fault check (Command: d w)
To check the Fan fault of the Set.

Transmission
[d][w][ ][Set ID][ ][Data][Cr]

* The data is always FF (in Hex).
Data
ff : Read Status

Acknowledgement
[w][ ][Set ID][ ][OK/NG][Data][x]

* Data is the status value of the Fan fault.
Data
00 : Fan fault
01 : Fan Ok
02 : N/A (Not Avaliable)

38. Elapsed time return (Command: d l)
To read the elapsed time.

Transmission
[d][l][ ][Set ID][ ][Data][Cr]

* The data is always FF(in Hex).

Acknowledgement
[l][ ][Set ID][ ][OK/NG][Data][x]

* The data is always FF(in Hex).
(Hexadecimal code)

39. Temperature value (Command: d n)
To read the inside temperature value.

Transmission
[d][n][ ][Set ID][ ][Data][Cr]

* The data is always FF(in Hex).

Acknowledgement
[n][ ][Set ID][ ][OK/NG][Data][x]

* The data is 1 byte long in Hexadecimal.

40. Lamp fault Check (Command: d p)
To check lamp fault.

Transmission
[d][p][ ][Set ID][ ][Data][Cr]

* The data is always FF(in Hex).

Acknowledgement
[p][ ][Set ID][ ][OK/NG][Data][x]

* The data is 1 byte long in Hexadecimal.
Data
00 : Lamp Fault
01 : Lamp Ok
02 : N/A (DPM/Power Off)

41. Speaker (Command: d v)
Turn the speaker on or off.

Transmission
[d][v][ ][Set ID][ ][Data][Cr]

Data
00: Off
01: On

Acknowledgement
[v][ ][Set ID][ ][OK/NG][Data][x]

42. Sleep Time (Command: f f)
Set Sleep Time.

Transmission
[f][f][ ][Set ID][ ][Data][Cr]

Data
00 : Off
01 : 10
02 : 20
03 : 30
04 : 60
05 : 90
06 : 120
07 : 180
08 : 240

Acknowledgement
[f][ ][Set ID][ ][OK/NG][Data][x]

43. Auto Sleep (Command: f g)
Set Auto Sleep.

Transmission
[f][g][ ][Set ID][ ][Data][Cr]

Data
00 : Off
01 : On

Acknowledgement
[g][ ][Set ID][ ][OK/NG][Data][x]

44. Power On Delay (Command: f h)
Set the schedule delay when the power is turned on (Unit: second).

Transmission
[f][h][ ][Set ID][ ][Data][Cr]

Data
00H to 64H (Data value)
* Refer to 'Real data mapping '.

Acknowledgement
[h][ ][Set ID][ ][OK/NG][Data][x]

45. Language (Command: f i)
Set the OSD language.

Transmission
[f][i][ ][Set ID][ ][Data][Cr]

Data
00 : Czech
01 : Danish
02 : German
03 : English
04 : Spanish (EU)
05 : Greek
06 : French
07 : Italian
08 : Dutch
09 : Norwegian
0a : Portuguese(EU)
0b : Portuguese(Brazil)
0c : Russian
0d : Finnish
0e : Swedish
0f : Korean
10 : Simplified Chinese
11 : Japanese
12 : Traditional Chinese

Acknowledgement
[i][ ][Set ID][ ][OK/NG][Data][x]

46. DPM Select (Command: f j)
Set the DPM (Display Power Management) function.

Transmission
[f][j][ ][Set ID][ ][Data][Cr]

Data
00 : Off
01 : On

Acknowledgement
[j][ ][Set ID][ ][OK/NG][Data][x]

47. Reset (Command: f k)
Execute the Picture, Screen and Factory Reset functions.

Transmission
[f][k][ ][Set ID][ ][Data][Cr]

Data
00 : Picture Reset
(Reset the values set in the PICTURE menu.)
01 : Screen Reset
(Reset the values set in under the Screen option.)
02 : Factory Reset
(Reset the values set in the OPTION menu.)
03 : Audio Reset
(Reset the values set in the AUDIO menu.)

Acknowledgement
[k][ ][Set ID][ ][OK/NG][Data][x]

48. Power Indicator (Command: f o)
To set the LED for Power Indicator

Transmission
[f][o][ ][Set ID][ ][Data][Cr]

Data
00 : Off
01 : On

Acknowledgement
[o][ ][Set ID][ ][OK/NG][Data][x]

49. Serial no.Check (Command: f y)
Check the Serial no.

Transmission
[f][y][ ][Set ID][ ][Data][Cr]

Data
FF (to read the serial numbers)

Acknowledgement
[y][ ][Set ID][ ][OK/NG][Data1] to [Data13][x]

* The data format is ASCII Code.

50. S/W Version (Command: f z)
Check the software version.

Transmission
[f][z][ ][Set ID][ ][Data][Cr]

Data
FFH : Read

Acknowledgement
[z][ ][Set ID][ ][OK/NG][Data][x]

51. Time 1(Year/ Month/ Day) (Command: f a)
To set the Time 1(Year/ Month/ Day) values.

Transmission
[f][a][ ][Set ID][ ][Data1][ ][Data2][ ][Data3][Cr]

Data 1
00 to 14: 2010 to 2030
Data 2
01 to 0C: January to December
Data 3
01 to 1F: 1 to 31
* Enter “fa [Set ID] ff” for checking Time 1 values.

Acknowledgement
[a][ ][Set ID][ ][OK/NG][Data1][Data2][Data3][x]

52. Time 2(Hour/ Minute/ Second) (Command: f x)
To set the Time 2(Hour/ Minute/ Second) values.

Transmission
[f][x][ ][Set ID][ ][Data1][ ][Data2][ ][Data3][Cr]

Data1
00 to 17: 00 to 23 hours
Data2
00 to 3B: 00 to 59 minutes
Data3
00 to 3B: 00 to 59 seconds
* Enter “fx [Set ID] ff” for checking Time 2 values.
** This command won’t work if Time 1 has not been set in advance.

Acknowledgement
[x][ ][Set ID][ ][OK/NG][Data1][Data2][Data3][x]

53. Off Timer(Repeat Mode/ Time) (Command: f e)
To set the Off Timer(Repeat mode/ Time) function.

Transmission
[f][e][ ][Set ID][ ][Data1][ ][Data2][ ][Data3][Cr]

Data1
00: Repeat Off
01: Repeat Once
02. Repeat Daily
03: Repeat from Monday to Friday
04: Repeat from Monday to Saturday
05: Repeat from Saturday to Sunday
06. Repeat on Sunday
Data2
00 to 17: 00 to 23 Hours
Data3
00 to 3B: 00 to 59 Minutes
* Enter “fe [Set ID] ff” for checking Off Timer(Repeat mode/ Time) values.
* Check if Time1 and Time2 have been set before setting this function.

Acknowledgement
[e][ ][Set ID][ ][OK/NG][Data1][Data2][Data3][x]

54. On Timer(Repeat Mode/ Time) (Command: f d)
To set the On Timer(Repeat mode/ Time) function.

Transmission
[f][d][ ][Set ID][ ][Data1][ ][Data2][ ][Data3][Cr]

Data1
00: Repeat Off
01: Repeat Once
02. Repeat Daily
03: Repeat from Monday to Friday
04: Repeat from Monday to Saturday
05: Repeat from Saturday to Sunday
06. Repeat on Sunday
Data2
00 to 17: 00 to 23 Hours
Data3
00 to 3B: 00 to 59 Minutes
* Enter “fd [Set ID] ff” for checking On Timer(Repeat mode/ Time) values.
* Check if Time1 and Time2 have been set before setting this function.

Acknowledgement
[d][ ][Set ID][ ][OK/NG][Data1][Data2][Data3][x]

55. On Timer Input (Command: f u)
To set the On Timer Input function.

Transmission
[f][u][ ][Set ID][ ][Data][Cr]

Data
20 : AV
40 : Component
60 : RGB
70 : DVI-D
90 : HDMI
C0 : Display Port
* Check if Time1 and Time2 and On Timer(Repeat Mode/Time) functions have been set before setting this function.

Acknowledgement
[u][ ][Set ID][ ][OK/NG][Data][x]

56. H Position (Command: f q)
To set the Horizontal position.
* Only available for Tile Off mode.

Transmission
[f][q][ ][Set ID][ ][Data][Cr]

Data
00~64: Left 50 ~ Right 50

Acknowledgement
[q][ ][Set ID][ ][OK/NG][Data][x]

57. V Position (Command: f r)
To set the Vertical position.
* Only available for Tile Off mode.

Transmission
[f][r][ ][Set ID][ ][Data][Cr]

Data
23~41: Bottom 15~Top 15

Acknowledgement
[r][ ][Set ID][ ][OK/NG][Data][x]

58. H Size (Command: f s)
To set the Horizontal size.
* Only available for Tile Off mode.

Transmission
[f][s][ ][Set ID][ ][Data][Cr]

Data
00~64: Size -50 ~ +50

Acknowledgement
[s][ ][Set ID][ ][OK/NG][Data][x]

59. Input Select (Command: x b)
To select input source for the Set.

Transmission
[x][b][ ][Set ID][ ][Data][Cr]

Data
20: AV(CVBS)
40: Component
60: RGB(PC)
70: DVI-D
90: HDMI(DTV)
A0: HDMI(PC)
C0: Display Port(DTV)
D0: Display Port(PC)

Acknowledgement
[b][ ][Set ID][ ][OK/NG][Data][x]

60. Color Temperature (Command: x u)
To adjust the screen color temperature.

Transmission
[x][u][ ][Set ID][ ][Data][Cr]

Data
00~64: Warm 50~Cool 50

Acknowledgement
[u][ ][Set ID][ ][OK][Data][x]



To obtain the source code under GPL, LGPL, MPL and other open source licenses, that is contained in this product, please visit http://opensource.lge.com.
In addition to the source code, all referred license terms, warranty disclaimers and copyright notices are available for download.
LG Electronics will also provide open source code to you on CD-ROM for a charge covering the cost of performing such distribution (such as the cost of media, shipping and handling) upon email request to opensource@lge.com.
This offer is valid for three (3) years from the date on which you purchased the product.

Make sure to read the Safety Precautions before using the product.
Keep the Owner's Manual(CD) in an accessible place for future reference.
The model and serial number of the SET is located on the back and one side of the SET.
Record it below should you ever need service.

MODEL _____

SERIAL _____

ENERGY STAR is a set of power-saving guidelines issued by the U.S. Environmental Protection Agency(EPA).



As an ENERGY STAR Partner LGE U. S. A.,Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

Temporary noise is normal when powering ON or OFF this device.