



## OWNER'S MANUAL

# Color Video Camera

Please read this manual carefully before operating your set and retain it for future reference.

#### MODEL

LCB5500-BN

LCB5500-BP



MFL67860049



## CAUTION

RISK OF ELECTRIC SHOCK  
DO NOT OPEN



**CAUTION:** TO REDUCE THE RISK OF ELECTRIC SHOCK  
DO NOT REMOVE COVER (OR BACK)  
NO USER-SERVICEABLE PARTS INSIDE  
REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.



This lightning flash with arrowhead symbol within an equilateral triangle is intended to alert the user to the presence of uninsulated dangerous voltage within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.



The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the product.

**FCC WARNING:** This equipment may generate or use radio frequency energy. Changes or modifications to this equipment may cause harmful interference unless the modifications are expressly approved in the instruction manual. The user could lose the authority to operate this equipment if an unauthorized change or modification is made.

## REGULATORY INFORMATION: FCC Part 15

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment.

This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications.

Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

- A suitable conduit entries, knock-outs or glands shall be provided in the cable entries of this product in the end user.

- Caution: Danger of explosion if battery is incorrectly replaced. Replaced only with the same or equivalent type recommended by the manufacturer. Dispose of used batteries according to the manufacturer's instructions.
- Holes in metal, through which insulated wires pass, shall have smooth well rounded surfaces or shall be provided with brushings.

This Class A digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe A est conforme à la norme NMB-003 du Canada.

**Caution:** This installation should be made by a qualified service person and should conform to all local codes.

**Caution:** To avoid electrical shock, do not open the cabinet. Refer servicing to qualified personnel only.

**Caution:** The apparatus shall not be exposed to water (dripping or splashing) and no objects filled with liquids, such as vases, shall be placed on the apparatus.

To disconnect power from mains, pull out the mains cord plug. When installing the product, ensure that the plug is easily accessible.

**Warning:** Do not install this equipment in a confined space such as a bookcase or similar unit.

**Warning:** Wiring methods shall be in accordance with the National Electric Code, ANSI/NFPA 70.

**Warning:** This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

**Warning:** To reduce a risk of fire or electric shock, do not expose this product to rain or moisture.

## **Disposal of your old appliance**



1. All electrical and electronic products should be disposed of separately from the municipal waste stream via designated collection facilities appointed by the government or the local authorities.
2. The correct disposal of your old appliance will help prevent potential negative consequences for the environment and human health.
3. For more detailed information about disposal of your old appliance, please contact your city office, waste disposal service or the shop where you purchased the product.
4. EEE Compliance with Directive.  
(for Turkey only)



LG Electronics hereby declares that this/these product(s) is/are in compliance with the essential requirements and other relevant provisions of Directive 2004/108/EC and 2011/65/EU.

### **European Standards Centre:**

Krijgsman 1, 1186 DM Amstelveen The Netherlands

- Please note that this is NOT a Customer Service contact point. For Customer Service Information, see Warranty Card or contact the dealer that you purchased this product.

# Important Safety Instructions

---

1. Read these instructions.
2. Keep these instructions.
3. Heed all warnings.
4. Follow all instructions.
5. Do not use this apparatus near water.
6. Clean only with dry cloth.
7. Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.
8. Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.
9. Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
10. Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.
11. Only use attachments/accessories specified by the manufacturer.
12. Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.



13. Unplug this apparatus during lightning storms or when unused for long periods of time.
14. Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.

# Cautions for Safe Operation

---

## Power Supply

This camera must always be operated AC 24 V or DC 12 V.

Certified/ Listed Adaptor which comply with LPS.

## Handling of the unit

Be careful not to spill water or other liquids on the unit. Be cautious not to get combustible or metallic material inside the body. If used with foreign matter inside, the camera is liable to fail or to get cause of fire or electric shock.

- Remove dust or dirt on the surface of the lens with a blower.
- Use a dry soft cloth to clean the body. If it is very dirty, use a cloth dampened with a small quantity of neutral detergent then wipe dry.
- Avoid the use of volatile solvents such as thinners, alcohol, benzene and insecticides. They may damage the surface finish and/or impair the operation of the camera.

## Operating and storage location

Avoid viewing a very bright object (such as light fittings) during an extended period. Avoid operating or storing the unit in the following locations.

- Extremely hot or cold places (operating temperature -10 °C to 50 °C, however, we recommend that the unit be used within a temperature range of 0 °C to 45 °C)
- Damp or dust place
- Places exposed to rain
- Places subject to strong vibration
- Close to generators of powerful electromagnetic radiation such as radio or TV transmitters.

# Contents

---

<b>Features</b> .....	<b>8</b>	White Balance settings .....	28
<b>Part Names and Functions</b> .....	<b>9</b>	Day & Night Setting .....	29
<b>Connections</b> .....	<b>11</b>	Motion Detection Setting.....	30
Precautions .....	11	3D-DNR Setting .....	31
Connection Overview .....	11	Privacy Mask Setting .....	31
Connecting Display device .....	12	Special Menu Settings .....	33
Connecting Power Source.....	12	SYSTEM Setting .....	37
Connecting RS-485 Device.....	13	<b>Specification</b> .....	<b>38</b>
Connecting Alarm Device.....	14		
Connecting Day&Night Switch.....	15		
Mounting the Lens.....	16		
Flange-back Adjustment .....	18		
Mounting the camera .....	19		
<b>Menu Operation</b> .....	<b>20</b>		
OSD Menu control buttons.....	20		
OSD Menu Overview .....	21		
General Operation.....	24		
Exposure Settings.....	24		

# Features

---


This Color Video Camera is designed for installation in a video surveillance system.

This manual contains instructions on how to install and manage the Color Video Camera in your video surveillance system.

Should you require any technical assistance, please contact authorized service center.

- High resolution and high sensitivity with a 6 mm (1/3 Type) Exview HAD II CCD.
- Automatically switch between DC 12 V and AC 24 V.
- Smart motion detector.
- Wide Dynamic Range (WDR)

# Part Names and Functions



## 1 Lens mount cap

The lens mount of the camera is covered using a cap to protect it. Remove the lens cap covering the lens.

## 2 Camera installation bracket

The bracket can be fixed at the top or bottom of the camera.

## 3 Flange-back adjustment lever


## 4 Lens iris output connector (LENS)

This 4- pin connector is used to send the Iris control signal and power supply to an auto-iris type lens.

## 5 Setup menu control buttons

Use these buttons to set the menu options.

# Part Names and Functions



## 6 Power input terminal

Supplies AC 24 V or DC 12 V from an external power source.

## 7 External Device Connectors

- D&N  
Connect the external switch to set the D&N function manually.
- ALARM (Alarm Output Terminal)  
Connect to the alarm input of an external device.
- COM (COMMUNICATION)  
Connect to an external controller of RS-485 format.

## 8 Power indicator

Lights when the camera is powered.

## 9 Video output connector (BNC type)


Supplies analog video signal (composite) to the connected device such as a DVR or monitor.

# Connections

## Precautions

- Be sure to switch off the unit before installation and connection.
- A qualified service person, complying with all applicable codes, should perform all required hardware installation.
- Do not expose the power and connection cable to moisture, which may cause damage to the unit.


## Connection Overview



# Connections

## Connecting Display device


The video signal connection between the camera and the monitor.



## Connecting Power Source

Connect power, using the method listed below:


1. Remove the insulation on the power cable as illustrated. (1)
2. Attach the terminal tips. (2)
3. Connect the power source. (recommended power adapter is AC 24 V/0.5A, DC 12 V/0.5A or above)



# Connections

## Connecting RS-485 Device

Use these ports to connect an external device of RS-485 format.



## RS-485 Protocol

### *Data Communication Format*

- Data Length: 1 Byte (8 Bit)
- Start/Stop Bit: 1 Bit
- Parity Bit: None
- Baud rate: 9 600 bps

### Format

BYTE1	BYTE2	BYTE3
0xE5	0x86	Camera ID
BYTE4	BYTE5	BYTE6
CODE1	CODE2	*C.S.

\*C.S. = Check Sum

- The data of total 6 bytes is transmitted from the external RS-485 device to the camera.
- BYTE 6 : The value of Check Sum from 'BYTE 1 ' to 'BYTE 5 '.
- ex) In case of transmission, 0xC5, 0x5F, 0x02, 0x00, 0x0A"
- C.S. =  $0xC5 + 0x5F + 0x02 + 0x00 + 0x0A = 0x0130$
- therefore, C.S. = 0x30

### Commands


Function	Command
OSD Menu ON/OFF	E5, 86, ID, 41, 02, C.S.

# Connections

LEFT Button	E5, 86, ID, 12, 80, C.S.
Right Button	E5, 86, ID, 12, 90, C.S.
Up Button	E5, 86, ID, 11, 80, C.S.
Down Button	E5, 86, ID, 11, 90, C.S.
Menu Button	E5, 86, ID, 41, 01, C.S.


## Connecting Alarm Device

Alarm terminals are used to connect the alarm (relay) devices such as sensors, door switches, etc. Connect the alarm (relay) device to the alarm (relay) output terminal. Alarm signal outputs at an event occurrence.



### Contact Ratings

- Maximum load current is  $\pm 130$  mA.
- Do not connect any system or device that has over 40 Vp-p bias voltage on the contact terminal.




### Note:

Use a relay unit if the voltage or current of the connected device exceeds the ratings.

# Connections


## Connecting Day&Night Switch

Connect the external D&N switch to the D&N terminal.




### Day function

When you open the external switch, the D&N function is set to Day mode.



### Night function

When you close the external switch, the D&N function is set to night mode.




#### Note:

If you use the external D&N function, you should set the DAY/NIGHT option to EXT on the setup menu.

# Connections

## Mounting the Lens

1. Remove the lens mount cap from the camera.




2. Install the auto-iris lens.

- 2-1. CS mount type lens

Carefully align the lens mount with the camera opening, then turn the lens slowly to install it.

- 2-2. C mount type lens

To allow for flange- back adjustment, install the C-mount adaptor (option) on the lens mount, then carefully align the lens mount with the camera opening and turn the lens slowly to install it.



3. Connect the lens plug to the lens iris output connector (LENS) on the side of the camera.

When using lenses from other makers, the plug shape may not correspond to the terminal on the camera.

In such a case, remove the original plug and using a soldering iron, connect a lens iris plug according to the diagram. (Refer to next page.)


**Note:**

Turn off the camera essentially before the lens connection or replacement.

# Connections

## Lens iris output connector


Pin layout for the lens iris output connector.




No.	DC type lenses
1	Damping -
2	Damping +
3	Drive +
4	Drive -

## Rewire the lens iris plug

1. Cut off the plug of the lens cable, cut off approximately 8 mm of the insulation, and then strip approximately 2 mm of the ends of the cable sheaths.



2. Solder the ends of the cable wires to the ends of the pins, and then attach the cover of the lens iris plug.



# Connections

---


## Flange-back Adjustment

The adjustment is required only when a lens without focus-adjusting mechanism is mounted, or when a lens with adjusting mechanism is mounted and focus that is more accurate is needed.

1. Loosen the flange-back fixing lever.
2. Up and down the flange-back adjusting lever to obtain a focused point while watching the monitor screen.
3. Tighten the flange-back fixing lever.

**Note:**

The object may be out of focus when using a source of near-infrared light than using the visible light.





# Connections

## Mounting the camera

The mounting bracket can be secured on either the top or bottom of the camera. Use the same set of screws to attach the mounting bracket on the camera.

**Note:**


If using a camera mounting bracket, select a location that is strong enough to bear the full weight of the camera and the mounting bracket for long periods, and install the camera and mounting bracket securely.



# Menu Operation

## OSD Menu control buttons

This camera utilizes an on-screen user MENU. To set items on the menu, use the following buttons.



BUTTON	Description
 <b>UP button</b>	Used to move upper direction on the menu screen. Use this button to select an item or adjust the parameters.
 <b>DOWN button</b>	Used to move lower direction on the menu screen. Use this button to select an item or adjust the parameters.
 <b>RIGHT button</b>	Moves the cursor to the right. Used to increment the value selected in the menu. The parameter changes each time this button is pressed.
 <b>LEFT button</b>	Moves the cursor to the left. Used to decrement the value selected in the menu. The parameter changes each time this button is pressed.
 <b>SET button</b>	Executes selections and displays a submenu for an item with the  .

## OSD Menu Overview

# Menu Operation

The following table shows the list of menu items and options. You can adapt the camera to your requirements by setting up the respective items in these menus.

Main Menu	Sub Menu	Contents	
EXPOSURE	ALC / ELC	BACKLIGHT	OFF/WDR/BLC/HSBLC
		BRIGHTNESS	0 to 100
		AGC	OFF/LOW/MIDDLE/HIGH
		SHUTTER	x512, ..., x2, AUTO, OFF, A.FLK, 1/160, ..., 1/120 000
		SENS-UP	OFF / AUTO
		EXIT	RET/ TOP/ END
WHITE BAL	ATW	-	
	AUTO	-	
	AWC ➔ SET KEY	-	
	MANUAL	RED	-100 to 100
		BLUE	-100 to 100
	EXIT	RET/ TOP/ END	

DAY/ NIGHT	AUTO	BURST	ON/OFF
		LEVEL	LOW/ MIDDLE/ HIGH/USER
		DWELL TIME	3 SEC to 60 SEC
	EXT	BURST	ON/OFF
	DAY	-	
	NIGHT	BURST	ON/OFF
MOTION DET	EXIT	RET/ TOP/ END	
	OFF	-	
	AREA SETUP	AREA SELECTION	1 to 8
		STATE	ON / OFF
		POSITION ➡➡	0 to 7
		POSITION ↑↓	0 to 5
		SIZE ➡➡	1 to 8
		SIZE ↑↓	1 to 6
	SENSITIVITY	0 to 100	
	DISPLAY	OUTLINE / MASK1 / MASK2 / OFF	
	ALARM OUT	MESSAGE / OFF	
	3D-DNR	0 to 100	EXIT
		RET/ TOP/ END	

# Menu Operation

PRIVACY MASK	ON	OFF	-	
		RECTANGLE	MASK SELECTION	1 to 8
			DISPLAY	OFF / MOSAIC /COLOR1 to COLOR8
			POSITION 	2 to 98
		CIRCLE	POSITION 	2 to 98
			SIZE 	4 to 100
			SIZE 	4 to 100
			MASK SELECTION	1 to 4
	OFF	RECTANGLE	DISPLAY	OFF / MOSAIC / COLOR1 to COLOR8
			POSITION 	0 to 100
			POSITION 	0 to 100
			SIZE 	1 to 15
		CIRCLE	SIZE 	1 to 15
			RADIUS	1 to 100

PRIVACY MASK	ON	POLYGON	MASK SELECTION	1 to 2
			DISPLAY	OFF / MOSAIC / COLOR1 to COLOR8
		DISPLAY	SHAPE	-
			POSITION	-
	D-ZOOM	EXIT	RET/ TOP/ END	
		OFF	OFF	-
			ZOOM	x 1.0 to x 16.0
			PAN	-100 to 100
	SPECIAL	ON	TIILT	-100 to 100
			D-EFFECT	OFF / MIRROR / V-FLIP / ROTATE
			SHARPNESS	0 to 100
		COLOR	COLOR	0 to 100
			SYNC	INT / LL
		LANGUAGE	USER TITLE	ON / OFF
			LANGUAGE	ENG/CHN/KOR/JAP/FRE/ITA/SPA/POR/DUT/ GER/POL/RUS/TUR/ARA/HEB
		EXIT	RET/ TOP/ END	

# Menu Operation


---

SYSTEM	FACTORY RESET	-	
	COMMUNICATION	CAMERA ID	OFF / 1 to 255
		PROTOCOL	LG / PELCO-D / PELCO-P
		BAUDRATE	2400 bps, 4800 bps, 9600 bps
		SAVE & REBOOT	-
EXIT	RET/ TOP/ END		

# Menu Operation

## General Operation

1. Press [SET] button.  
[CAMERA SETTING] menu appears on the monitor.




2. Use [UP] or [DOWN] button to select an option then press [SET] button.  
Submenu appears on the monitor.
3. Use [UP] or [DOWN] button to select a submenu option.
4. Use [LEFT] or [RIGHT] button to select a value.
  - RET: Return to the previous.
  - TOP: Return to the CAMERA SETTING menu screen.
  - END: Exit the setup menu.

## Exposure Settings

You can set the exposure options using the EXPOSURE menu.

1. Select [EXPOSURE] option on the [CAMERA SETTING] menu.
2. Use [LEFT] or [RIGHT] button to select a mode.
3. Press [SET] button and the [EXPOSURE] menu appears.



# Menu Operation

## Backlight setting

Use Backlight option to view the object clearly in backlight conditions.



1. Select [Backlight] option.
2. Use [LEFT] or [RIGHT] button to select a mode then press [SET].
  - WDR: WDR (Wide dynamic range) feature can be very helpful to cope with very challenging lighting conditions. It is capable of capturing both of the dark part and bright part and combining the differences into a scene to generate a highly realistic image as original scene. Set the WDR limit.
    - > ACE (Adaptive Contrast Enhancement) : This

function is used when you want to display dark areas of WDR brightly.

- BLC: Camera's backlight compensation feature helps alleviate issues of visibility in high contrast areas. Set the BLC limit.
- HSLBC: Use for masking brightness of the specific area to view the subject more clearly. The HSLBC mode is automatically activated regardless of Day and Night mode.
  - > AREA SETTING: Use [LEFT] or [RIGHT] button to select a area then use [UP] or [DOWN] button to select a [ON] or [OFF]. Press [SET] to exit the Area setting menu.
  - > GRAY SCALE: Use [LEFT] or [RIGHT] button to select a gray scale. (GRAY, D.GRAY, BLACK)
  - > USER SCALE: Use [LEFT] or [RIGHT] button to select a bright level. (5 level)
  - > MASK: Use [LEFT] or [RIGHT] button to select [ON] or [OFF]. If you set the [MASK] to [ON], the mask function is activate only when the [HSLBC] is automatically activated in low luminance scene.

# Menu Operation

- OFF: Not used.

## BRIGHTNESS setting

You can increase the brightness of the darkened video. If you set the brightness to lower value, the image is darkened. If you set the brightness to higher value, the image gets bright.



1. Select [BRIGHTNESS] option.
2. Use [LEFT] or [RIGHT] button to set the bright level.

## AGC (Automatic Gain Control) setting

If the images are too dark, change the maximum [AGC] value to make the images brighter. But noise is increase.



1. Select [AGC] option.
2. Use [LEFT] or [RIGHT] button to select a mode.

# Menu Operation

## SHUTTER (Shutter Speed) setting

Select the desired shutter speed for camera exposure. You can change the shutter speed to higher speed to capture fast-moving subjects, though the image becomes darker.



1. Select [SHUTTER] option.
2. Use [LEFT] or [RIGHT] button to set shutter speed.
  - AUTO: Adjust the [LOW LIMIT] and [HIGH LIMIT].
    - > LOW LIMIT: Use [LEFT] or [RIGHT] button to set the [LOW LIMIT].
    - > HIGH LIMIT: Use [LEFT] or [RIGHT] button to set the [HIGH LIMIT].


### **Note:**

- When the SHUTTER is set to AUTO, the picture may become unstable if the camera faces a bright fluorescent light directly. Therefore, take care when installing.
- Set the Shutter OFF when Color Rolling occurs in the indoor scene. Recommend the Shutter Auto in the outdoor scene.
- If you set to one of the SHUTTER options except AUTO and A.FLK on the [SHUTTER] menu, the [BACKLIGHT - WDR] setting is not available and [---] mark is displayed.
- If you set BACKLIGHT mode to WDR, sub menu [SHUTTER LIMIT] of [SHUTTER AUTO] will be blocked and shutter will be fixed. (LCB5500-BN : 1/60, LCB5500-BP : 1/50)

# Menu Operation

## SENS-UP setting

If pictures are not clear due to darkness, this SENS-UP operation would increase the sensitivity of picture.



1. Use [UP] or [DOWN] button to select [SENS-UP] option.
2. Use [LEFT] or [RIGHT] button to select mode.
  - AUTO: Adjust the sensitivity of the picture automatically.
    - > SENS-UP LIMIT: Use [LEFT] or [RIGHT] button to set the SENS-UP limit.
  - OFF: Not used.


## **Note:**

If you set to one of the [SHUTTER] options except [AUTO] on the [SHUTTER] menu, the [SENS-UP] setting is not available and [---] mark is displayed.

# Menu Operation

## White Balance settings

Select the method by which the camera shifts its output colors to compensate for the color of a light source.




- MANUAL: You can set the white balance options manually. Push the [AWC→SET KEY] mode, and then adjust White Balance. You can set the RED and BLUE in the [MANUAL] mode.
  - > RED: Obtains the optimum amount of red gain.
  - > BLUE: Obtains the optimum amount of blue gain.

1. Select [WHITE BAL] option.
2. Use [LEFT] or [RIGHT] button to select a mode then press [SET].
  - ATW (Auto-Tracing White Balance): Use [LEFT] or [RIGHT] button to select the ATW.
  - AUTO : Use [LEFT] or [RIGHT] button to select the [AUTO].
  - AWC→SET KEY: If you select the [AWC→SET KEY] mode, you will be able to set up the White Balance automatically.

# Menu Operation

## Day & Night Setting



1. Select [DAY/NIGHT] option.
2. Use [LEFT] or [RIGHT] button to select mode for Day/Night function.
  - AUTO: You will be able to change the Day/Night mode automatically.

**Note:**  
If you set the AGC to [OFF] on the [EXPOSURE] menu, the AUTO mode of the DAY/NIGHT function is not available and [---] mark is displayed.

> BURST: Use [LEFT] or [RIGHT] button to select [ON] or [OFF].

- > LEVEL: Use [LEFT] or [RIGHT] button to select a level.
- > DWELL TIME: Use [LEFT] or [RIGHT] button to select a dwell time.
- EXT : Switches between color picture and black-and-white picture when an external day/night switching signal is received.
- > BURST: Use [LEFT] or [RIGHT] button to select [ON] or [OFF].
- DAY: Color mode enabled.
- NIGHT: Black-and-white mode enabled.
- > BURST: Use [LEFT] or [RIGHT] button to select [ON] or [OFF].


**Note:**

Select the BURST [ON] or [OFF] when the color noise occurs on the screen in NIGHT Mode after operating the Line-Lock.

# Menu Operation

## Motion Detection Setting

The motion detection detects the moving objects in the scene by monitoring changes in brightness level. You can select the level of sensitivity for motion detection to 8 zone.



1. Select [MOTION DET] option.
2. Use [LEFT] or [RIGHT] button to select a [ON] and press [SET]. The [MOTION DETECTION] menu appears.
3. Select [AREA SETUP] option.
  - Use [LEFT] or [RIGHT] button to select a area (1/8 to 8/8) on the [AREA SELECTION].
  - Use [LEFT] or [RIGHT] button to set up the [ON] or [OFF] on the [STATE].
  - Use [UP] or [DOWN] to select an option then use


[LEFT] or [RIGHT] button to adjust the option.

- POSITION : Moves horizontal position of the mask.
- POSITION : Moves vertical position of the mask.
- SIZE : Enlarge or decrease the horizontal size of the mask.
- SIZE : Enlarge or decrease the vertical size of the mask.

4. Use [SENSITIVITY] option to obtain the optimum detection level.
5. Use [LEFT] or [RIGHT] button to select the [DISPLAY] option.
6. Use [LEFT] or [RIGHT] button to select the [ALARM OUT] option.

# Menu Operation

## 3D-DNR Setting




1. Select [3D-DNR] option.

If pictures are not clear due to brightness, this option would reduce the noise of picture.

2. Use [LEFT] or [RIGHT] button to select a value.

## Privacy Mask Setting

This function is aiming at the protection of personal privacy, selecting a screen part black not to be displayed in the screen. Up to 14 zones can be registered.



1. Select [PRIVACY] option.

2. Use [LEFT] or [RIGHT] button to select a [ON] and press [SET]. The PRIVACY SETUP menu appears.

- RECTANGLE :

- > Use [LEFT] or [RIGHT] button to select a mask (MASK1 to MASK8) on the [MASK SELECTION].
  - > Use [LEFT] or [RIGHT] button to set up the OFF, MOSAIC, COLOR 1 to COLOR 8 on the

# Menu Operation

---

[DISPLAY] option.

- > Use [UP] or [DOWN] to select an option then use [LEFT] or [RIGHT] button to adjust the option.
  - POSITION : Moves horizontal position of the mask.
  - POSITION : Moves vertical position of the mask.
  - SIZE : Enlarge or decrease the horizontal size of the mask.
  - SIZE : Enlarge or decrease the vertical size of the mask.
- CIRCLE :
  - > Use [LEFT] or [RIGHT] button to select a mask (MASK1 to MASK4) on the [MASK SELECTION].
  - > Use [LEFT] or [RIGHT] button to set up the OFF, MOSAIC, COLOR 1 to COLOR 8 on the [DISPLAY] option.
  - > Use [UP] or [DOWN] to select an option then use [LEFT] or [RIGHT] button to adjust the

option.

- POSITION : Moves horizontal position of the mask.
- POSITION : Moves vertical position of the mask.
- SIZE : Enlarge or decrease the horizontal size of the mask.
- SIZE : Enlarge or decrease the vertical size of the mask.
- RADIUS SIZE : You can adjust the RADIUS SIZE (1 to 100).
- POLYGON :
  - > Use [LEFT] or [RIGHT] button to select a mask (MASK1 to MASK2) on the [MASK SELECTION].
  - > Use [LEFT] or [RIGHT] button to set up the OFF, MOSAIC, COLOR 1 to COLOR 8 on the [DISPLAY] option.
  - > Use the [LEFT], [RIGHT], [UP], [DOWN], [SET] button to draw the polygon on the [SHAPE].
  - > Use the [LEFT], [RIGHT], [UP], [DOWN],

# Menu Operation


[SET] button to move the polygon on the [POSITION].

## Note:

- You can adjust the mask color manually except for COLOR 8.
- RED, GREEN, BLUE and TRANSPARENCY adjustments are applied in common from COLOR 1 to COLOR 7, after mask setting.

## Special Menu Settings

This menu lets you adjust and set up D-ZOOM, D-EFFECT, SHARPNESS, COLOR, SYNC, USER TITLE, LANGUAGE function by yourself in the [SPECIAL] menu.



1. Select [SPECIAL] option.
2. Press [SET] button and the [SPECIAL] menu appears.

# Menu Operation

## D-ZOOM (Digital Zoom) Setting

You can select the digital zoom level.



1. Select [D-ZOOM] option on the [SPECIAL] menu.
2. Use [LEFT] or [RIGHT] button to select a [ON] then press [SET] the DIGITAL ZOOM menu appears. When you set to ON, the displayed image can be shaking.
3. Use [UP] or [DOWN] to select a option then use [LEFT] or [RIGHT] button to select a level.
  - ZOOM: Use [LEFT] or [RIGHT] button to enlarge the screen.
  - PAN: Use [LEFT] or [RIGHT] button to move the screen.
  - TILT: Use [LEFT] or [RIGHT] button to move the screen.

## **Note:**

If you set the [D-ZOOM] to [ON], the ZOOM level is set to [x1.0] automatically.

## D-EFFECT (Digital effect) Setting

You can select the digital effect.



1. Select [D-EFFECT] option on the [SPECIAL] menu.
2. Use [LEFT] or [RIGHT] button to select a digital effect.
  - MIRROR: Turn on the mirror effect.
  - ROTATE: Rotate the picture. (180°)
  - V-FLIP: Flip the picture vertically.
  - OFF: Turn off the digital effect.

# Menu Operation

## SHARPNESS Setting

The degree to which the boundary of the two portions is clearly distinguished.



1. Select [SHARPNESS] option on the [SPECIAL] menu.
2. Use [LEFT] or [RIGHT] button to change a adjust the option. If you set the sharpness value to higher, the image outline becomes sharp. If you set to lower value, the image outline becomes dim.

## COLOR Setting

You can switch the displayed picture to gray scale or color.



1. Select [COLOR] option on the [SPECIAL] menu.
2. Use [LEFT] or [RIGHT] button to change a adjust the option.

# Menu Operation

## SYNC Setting



1. Select [SYNC] option on the [SPECIAL] menu.
2. The [SYNC] option is set to [INT] automatically.

### **Note:**

AC24V Adaptor have to use for the [LL] mode setting.

## USER TITLE Setting

You can use the camera identification to assign a number and character to the camera. To disappear the user title, select [OFF].

1. Select [USER TITLE] option on the [SPECIAL] menu.
2. Use [LEFT] or [RIGHT] button to select a [ON] then press [SET]. The USER TITLE menu appears.



3. Use [UP], [DOWN], [LEFT] or [RIGHT] button to select a character or number then press [SET] button.
  - CLR: Clear all entered characters and numbers.
  - POS: Move the USER TITLE position on the screen using the arrow buttons.
  - END: Confirm your selection or exit the setting
  - **1** (Blank): Inserts a space at the cursor position.
  - **◀ / ▶**: Moves cursor to left or right.

# Menu Operation


## LANGUAGE Setting

Select the viewer language for the camera setup menu and OSD information display.



1. Select [LANGUAGE] option on the [SPECIAL] screen.
2. Press [LEFT] or [RIGHT] button to select a language.

## SYSTEM Setting



1. Select the [SYSTEM] menu.
2. Press [SET] button and the [SYSTEM] menu appears.
3. Use [UP] or [DOWN] button to select the option.
  - FACTORY RESET: To reset the camera setting to factory setting, select the [FACTORY RESET] option.
  - COMMUNICATION
    - > CAMERA ID: You can use the camera identification [CAMERA ID] to assign a number to the camera. Use [LEFT] or [RIGHT] to select a CAMERA ID.
    - > PROTOCOL: Select a protocol for RS-485 communication.

# Menu Operation

---

- > BAUD RATE: Set the speed of communication between the camera and the RS-485 unit.
- > SAVE & REBOOT: To confirm the communication settings.

4. Press [SET] button to confirm your selection.

**Note:**

- You need to set up [SAVE & REBOOT] for save [CAMERA ID], [PROTOCOL], [BAUD & RATE] changes.
- The menu screen is move to top menu, after set up [FACTORY RESET].

# Specification

Item	LCB5500-BN	LCB5500-BP
Signal System	NTSC	PAL
Total Pixels number	520 000 Pixels	610 000 Pixels
Effective Pixels number	480 000 Pixels	570 000 Pixels
Image Sensor	6 mm (1/3 Type) Exview HAD II CCD	
ISP		XDI-V
Lens		C / CS Mount
Horizontal Resolution	Color	650 TV Lines
	B / W	700 TV Lines
S/N Ratio		50 dB
Day & Night		ICR (AUTO / DAY / NIGHT / EXT)
Sens-up		OFF / AUTO(x2, ... x512) / MANUAL(x2, ... x512)
Minimum Illumination (F1.2, 30 IRE)	Color	0.2 lx (Sens-up Off), 0.00 3 lx (Sens-up Auto), 0.000 1 lx (Sens-up X512)
	B / W	0.02 lx (Sens-up Off), 0.000 3 lx (Sens-up Auto), 0.000 01 lx (Sens-up X512)
White Balance		ATW / AUTO / AWC → SET KEY / MANUAL
Digital Zoom		X16
IRIS Control		DC
Scanning Frequency (H/V)	15.734 kHz / 59.94 Hz	15.625 kHz / 50 Hz
Sync. System		Internal / Line Lock

# Specification

Auto Gain Control	OFF/ LOW/ MIDDLE/ HIGH	
Exposure	ALC / ELC	
Video Output	1 Vp-p Composite (75 Ω)	
Electronic Shutter	1/60 to 1/120 000	1/50 to 1/120 000
Protocol	RS-485 : LG, Pelco-D, Pelco-P	
Backlight Compensation	OFF/WDR/BLC/HSBLC	
Motion Detection	8 Zones	
Privacy Masking	14 Mask Zones	
3D-DNR	2D + 3D-DNR	
Digital Effect	Off / V-Flip / Mirror / Rotate	
Control Method	RS-485, Coaxial Communication	
Power Source	DC 12V / AC 24V	
Power Consumption	240 mA	
Operating Temperature/ Humidity	-10 °C to 50 °C / 0 % RH to 80 % RH	
Storage Temperature/ Humidity	-20 °C to 60 °C / 0 % RH to 85 % RH	
Dimension (W x H x D)	67.36 mm x 61.50 mm x 133.90 mm	
Weight	362 g	

