



\*LG LED Monitors are LCD Monitors with LED Backlighting.

Please read the safety information carefully before using the product.

LED LCD Monitor (LED Monitor) Model List 27UD68

# **CONTENTS**

### 3 LICENSE

# 4 ASSEMBLING AND PREPARING

- 4 Product Components
- 5 Component and Button Description
- 5 How to Use the Joystick Button
- 6 Input Connector
- 7 Moving and Lifting the Monitor
- 8 Installing the Monitor
- 8 Assembling the stand base
- 9 Detaching the Stand Base
- 10 Using the cable holder
- 10 Installing onto a table
- 11 Adjusting the angle
- 12 Using the Kensington lock
- Installing the wall mount plate
- 13 Installing to a wall

### **14** USING THE MONITOR

- 14 Connecting to a PC
- 14 HDMI connection
- 14 DisplayPort connection
- 15 Connecting to AV Devices
- 15 HDMI connection
- 15 Connecting to External Devices
- 15 Connecting Headphones

### 16 USER SETTINGS

- 17 Customizing settings
- 17 Menu Settings
- 17 - Quick Settings
- 18 - PBP
- 19 - Picture
- 22 -General
- 23 - Reset

# **24** TROUBLESHOOTING

### 26 SPECIFICATIONS

- 26 **27UD68**
- 27 Factory Support Mode (Preset Mode, PC)
- 27 **HDMI**
- 27 DisplayPort
- 28 HDMI Timing (Video)
- 28 Power LED

# **LICENSE**

Each model has different licenses. Visit www.lg.com for more information on the license.



The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



VESA, VESA logo, DisplayPort Compliance Logo and DisplayPort Compliance Logo for dual-mode source are all registered trademarks of the Video Electronics Standards Association.


The following content is only applied to the monitor which is sold in Europe market and which needs to meet the ErP Directive:

- \* This monitor is set to be turned off automatically in 4 hours after you turned on display if there is no adjustment to display.
- \* To make this setting be disabled, change the option to 'Off' in OSD menu of "Automatic Standby".

# ASSEMBLING AND PREPARING

# **Product Components**

Please check whether all the components are included in the box before using the product. If there are missing components, contact the retail store where you purchased the product. Note that the product and components may look different from those shown here.



# -/<u>!</u>\


#### **CAUTION**

- Always use genuine components to ensure safety and product performance.
- The product warranty will not cover damage or injury caused by the use of counterfeit components.
- It is recommend that use the supplied components.
- If you use generic cables not certified by LG, the screen may not display or there may be image noises.



- Note that the components may look different from those shown here.
- Without prior notice, all information and specifications in this manual are subject to change to improve the performance of the product.
- To purchase optional accessories, visit an electronics store or online shopping site or contact the retail store where you purchased the product.

# **Component and Button Description**



# How to Use the Joystick Button

You can easily control the functions of the monitor by pressing the joystick button or moving it left/right with your finger.

### **Basic Functions**


	<b>_</b>	Power on	Press the joystick button once with your finger to turn on the monitor.
		Power off	Press and hold the joystick button once with your finger to turn off the monitor.
	<b>⋖/</b> ▶	Volume Control	You can control the volume by moving the joystick button left/right.



### NOTE -

• The joystick button is located at the bottom of the monitor.

# **Input Connector**



# **Moving and Lifting the Monitor**

When moving or lifting the monitor, follow these instructions to prevent the monitor from being scratched or damaged and to ensure safe transportation regardless of its shape or size.

- It is advisable to place the monitor in the original box or packing material before attempting to move it.
- Before moving or lifting the monitor, disconnect the power cord and all cables.
- Hold the top and bottom of the monitor frame firmly. Do not hold the panel itself.



 When holding the monitor, the screen should face away from you to prevent it being scratched.



- When moving the monitor, avoid any strong shock or vibrations to the product.
- When moving the monitor, keep it upright, never turn the monitor on its side or tilt it sideways.




#### CAUTION

 As far as possible, avoid touching the monitor screen. This may result in damage to the screen or some of the pixels used to create images.




If you use the monitor panel without the stand base, its joystick button may cause the monitor to become unstable and fall, resulting in damage to the monitor or human injury. In addition, this may cause the joystick button to malfunction.



# **Installing the Monitor**

### Assembling the stand base

1 Place the screen face down.







#### **CAUTION**

- To protect the screen from scratches, cover the surface with a soft cloth.
- 2 Check the direction of the stand body (front, back) and then mount the stand body onto the stand hinge.


Use a tool to attach the **stand body** as shown in the figure.



- 3 Attach the Stand Base to Stand Body.
  - 2 Tighten the screw to the right.



4 Attach the screw cover.





### **CAUTION**

Applying excessive force when tightening the screws may cause damage to the monitor. Damage caused in this way will not be covered by the product warranty.



### **CAUTION**

It may hurt your foot off the stand, so be careful.


### **Detaching the Stand Base**

1 Place the screen face down.




### CAUTION -

- To protect the screen from scratches, cover the surface with a soft cloth.
- 7 Turn the screw to the left.
  - 2 Pull out the Stand Base.




3 As shown in the illustration, pull Screw Cover out to separate it from the set.



4 Remove the two screws on the back of **stand body**.

As shown in the illustration, disconnect the **stand body** from the **stand hinge**.





### CAUTION -

- Illustrations in this document represent typical procedures, so they may look different from the actual product.
- Applying excessive force when tightening screws may cause damage to the monitor.
   Damage caused in this way will not be covered by the product warranty.
- Be careful not to hurt your hand on the edges of the screw covers.
- Do not carry the monitor upside down by just holding the base. This may cause the monitor to fall off the stand and could result in personal injury.
- When lifting or moving the monitor, do not touch the monitor screen. The force applied to the monitor screen may cause damage to it.




#### **CAUTION**

It may hurt your foot off the stand, so be careful.

# Using the cable holder


Arrange the cables using the cable holder as shown in the illustration.




### Installing onto a table

1 Lift the monitor and place it on the table in an upright position.

Place at least **100 mm** away from the wall to ensure sufficient ventilation.



2 Connect the power adapter to the monitor and then plug the power cord into the wall outlet.




3 Press the joystick button on the bottom of the monitor to turn on the monitor.



 Unplug the power cord prior to moving or installing the monitor. There is risk of electric shock.

# Adjusting the angle


- 1 Place the monitor in an upright position, mounted on the stand base.
- 2 Adjust the angle of the screen. The angle of the screen can be adjusted forwards or backwards for a comfortable viewing experience.






### **WARNING**

 To avoid injury to the fingers when adjusting the screen, do not hold the lower part of the monitor's frame as illustrated below.



 Be careful not to touch or press the screen area when adjusting the angle of the monitor.




### Using the Kensington lock

The Kensington security system connector is located at the back of the Monitor set.

For more information on installation and usage, refer to the Kensington lock user manual or visit the website at http://www.kensington.com.

Connect the Kensington security system cable between the Monitor set and a table.



# 0

### **NOTE**

 Use of the Kensington lock is optional.
 The accessories can be purchased at your local electronics store.

### Installing the wall mount plate

This monitor supports the specification of the standard wall mount plate or compatible device.


- 1 Place the screen face down. To protect the screen from scratches, cover the surface with a soft cloth.
- 2 Place the wall mount plate onto the monitor and align it with the screw holes.
- 3 Tighten the four screws to fix the plate to the monitor using a screwdriver.



- The wall mount plate is sold separately.
- For more information on installation, refer to the wall mount plate's installation guide.
- Be careful not to use excessive force when mounting the wall mount plate, as this can damage the monitor's screen.

### Installing to a wall

Install the monitor at least 100 mm away from the wall and leave about 100 mm of space at each side of the monitor to ensure sufficient ventilation. Detailed installation instructions can be obtained from your local retail store. Please refer to the manual to install and set up a tilting wall mounting bracket.




To install the monitor to a wall, attach a wall mounting bracket (optional) to the back of the monitor. Make sure that the wall mounting bracket is securely fixed to the monitor and to the wall.

- 1 If you use screw longer than standard, the monitor might be damaged internally.
- 2 If you use improper screw, the product might be damaged and drop from mounted position. In this case, LG Electronics is not responsible for it.

Wall Mount (A x B) Standard screw	100 x 100 M4 x L10
Number of screws	4
Wall Mount Plate (Optional)	LSW 149


Wall Mount (A x B)



# ·/\

#### **CAUTION**

- Unplug the power cord before moving or installing the monitor to avoid electric shocks.
- Installing the monitor on the ceiling or on a slanted wall may result in the monitor falling off, which could lead to injury. Please use the genuine LG wall mounting bracket. For more information, contact your local retail store or a qualified installer.
- Applying excessive force when fastening screws may cause damage to the monitor. Damage caused in this way will not be covered by the product warranty.
- Use the wall mounting bracket and screws that conform to the VESA standard. Damage caused by the use or misuse of inappropriate components will not be covered by the product warranty.
- Screw length from outer surface of back cover should be under 8mm.





- Use the screws specified by the VESA standard.
- The wall mount kit includes the installation guide and all necessary parts.
- The wall mounting bracket is optional. The accessories can be purchased at your local retail store.
- The length of the screw may differ for each wall mounting bracket. Ensure the correct length screw is used.
- For more information, please refer to the user manual for the wall mounting bracket.

# **USING THE MONITOR**

# Connecting to a PC


 This monitor supports the \*Plug and Play feature.

\*Plug and Play: A feature that allows you to add a device to your computer without having to reconfigure anything or install any manual drivers.

### **HDMI** connection

Transmits the digital video and audio signals from your PC and A/V devices to the monitor. Connect your PC and AV device to the monitor with the HDMI cable as illustrated below.

Press the menu button and then select the input option from the input menu.



# 0


#### **NOTE**

- If you use HDMI PC, it can cause compatibility problem.
- Use a certified cable with the HDMI logo attached. If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- · Recommended HDMI cable types
  - High-Speed HDMI®/™ Cable
  - High-Speed HDMI<sup>®</sup>/<sup>™</sup> Cable with Ethernet

### **DisplayPort connection**

Transmits the digital video and audio signals from your PC to the monitor. Connect your PC to the monitor using the DisplayPort cable as illustrated below.

Press the menu button and then select the input option from the input menu.






- There may be no video or audio output depending on the DP version of the PC.
- If you use generic cables not certified by LG, the screen may not display or there may be image noises.

# **Connecting to AV Devices**

#### **HDMI** connection

Transmits the digital video and audio signals from your PC and A/V devices to the monitor. Connect your PC and AV device to the monitor with the HDMI cable as illustrated below.

Press the menu button and then select the input option from the input menu.






#### NOTE

- If you use HDMI PC, it can cause compatibility problem.
- Use a certified cable with the HDMI logo attached. If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- Recommended HDMI cable types
  - High-Speed HDMI<sup>®</sup>/<sup>™</sup> Cable
- High-Speed HDMI®/™ Cable with Ethernet

# **Connecting to External Devices**

### **Connecting Headphones**

Connect peripherals to the monitor via the headphones port. Connect as illustrated.





#### NOTE

- · Peripheral devices are sold separately.
- If you use angled earphones, it may cause a problem with connecting another external device to the monitor. Therefore, it is recommended to use straight earphones.





Angled

Straight

 Depending on the audio settings of the PC and external device, headphones and speaker functions may be limited.

# **USER SETTINGS**

# **Activating the Main Menu**

- 1 Press the joystick button on the bottom of the monitor.
- 2 Move the joystick up/down (▲/▼) and left/right(◄/►) to set the options.
- 3 Press the joystick button once more to exit the main menu.



Button	Menu Status		Description
	Main menu disabled		Enables the main menu.
1	Main mer		Exits the main menu. (Holding down the button to turn off the monitor. You can turn off the monitor this way at any time, including when the OSD is on.)
	•	Main menu disabled	Adjusts the monitor volume level.
		Main menu enabled	Enters the menu features.
	•	Main menu disabled	Adjusts the monitor volume level.
		Main menu enabled	Enters the input feature.
<b>A</b>		Main menu disabled	Enables the main menu.
		Main menu enabled	Enters the game mode feature.
		Main menu disabled	Enables the main menu.
	•	Main menu enabled	Turns off the monitor.

### **Main Menu Features**




Main Menu	Description
Menu	Configures the screen settings.
Game Mode	You can change Picture Mode to a gaming mode.
Input	Sets input mode.
Monitor off	Turns off the monitor.
Exit	Exits the main menu.

# **Customizing settings**

## **Menu Settings**

### -Quick Settings

- 1 To view the **OSD menu**, press the **joystick button** at the bottom of the monitor and then enter the **Menu**.
- 2 Go to Quick Settings > Brightness by moving the joystick.
- 3 Configure the options following the instructions that appear in the bottom right corner.
- 4 To return to the upper menu or set other menu items, move the joystick to ◀ or pressing (◉ / OK) it.
- 5 If you want to exit the OSD menu, move the joystick to ◀ until you exit.



Each option is described below.

Menu > Quick Settings	Description			
Brightness	Adjusts the color contrast and brightness of the screen.			
Contrast	Adjusts the color contrast and brightness of the screen.			
Volume	Adjusts the vo	Adjusts the volume.		
	• Jog joystick button down ( ) in the Volume menu will enable/disable the Mute function.			
Input	Selects the current input mode.			
Ratio	Adjusts the screen ratio.			
	Wide Displays the video in wide-screen, regardless of the video signal input.			
	Original Displays a video according to the input video signal aspect ratio.			
	1:1	1:1 The aspect ratio is not adjusted from the original.		



- The display may look the same for Wide, Original, and 1:1 options at the recommended resolution.
- · The ratio is disabled in the interlaced signal.

### -PBP

- To view the **OSD menu**, press the **joystick button** at the bottom of the monitor and then enter the **Menu**.
- 2 Go to PBP by moving the joystick.
- 3 Configure the options following the instructions that appear in the bottom right corner.
- 4 To return to the upper menu or set other menu items, move the joystick to ◀ or pressing (◉ / OK) it.
- 5 If you want to exit the OSD menu, move the joystick to ◀ until you exit.



Each option is described below.


Menu > PBP	Description						
Sub	Displays the screens of two input modes on			ne monitor.			
		PBP Co	nnection		Sub Screen (Right)		
				HDMI 1	HDMI 2	DisplayPort	
		Screen	HDMI 1	-	-	0	
	(Left)		HDMI 2	-	-	0	
			DisplayPort	0	0	-	
Sound Out	Changes	Changes the audio output in PBP mode.					
Swap	Toggles b	Toggles between the main screen and sub screen in PBP mode.					
Sub Full	Converts the sub screen of PBP mode to the wide screen.						
Ratio	Adjusts the aspect ratio of the main screen or sub screen.						
	Main	Main Wide Displays the video to fit the PBP screen, regardless of the video signal input.					
	Original Displays the video in the aspect ratio of the video signal input on the PE				n the PBP screen.		
	Sub	Wide	Displays the video to fi	t the PBP screen, re	gardless of the video	o signal input.	
		Original Displays the video in the aspect ratio of the video signal input on the PBP screen.				n the PBP screen.	



- When the Sub mode is Off, Sound Out, Swap, Sub Full, and Ratio menus become disabled. The Main/Sub options for Ratio become disabled if there is no signal.
- The optimal resolution for PBP mode is set automatically when PBP mode is set.

### -Picture

- To view the **OSD menu**, press the **joystick button** at the bottom of the monitor and then enter the **Menu**.
- 2 Go to Picture by moving the joystick.
- 3 Configure the options following the instructions that appear in the bottom right corner.
- 4 To return to the upper menu or set other menu items, move the joystick to ◀ or pressing (⑥ / OK) it.
- 5 If you want to exit the OSD menu, move the joystick to ◀ until you exit.



Each option is described below.


Menu > Picture	Description		
Picture Mode	<b>Custom</b> Allows the user to adjust each element. The color mode of the main menu can be adjusted.		
	Reader	Optimizes the screen for viewing documents. You can brighten the screen in the OSD menu.	
	Photo	Optimizes the screen for photos.	
	Cinema	Optimizes the screen for video.	
	sRGB	A standard RGB color space for the monitor and printer.	
	Color Weakness	This mode is for users who cannot distinguish between red and green. It enables users with color weakness to easily distinguish between the two colors.	
	FPS Game 1	This mode is optimized for FPS games.	
	FPS Game 2	It has a higher Black Stabilizer value than FPS Game 1. It is suitable for very dark FPS games.	
	RTS Game	This mode is optimized for RTS Game.	
	Custom (Game)	In this mode, users can customize various elements including game-related options.	
		ure mode is changed in the DP (DisplayPort) input, the screen er or the resolution of your PC screen may be affected.	

Picture Adjust	SUPER RESOLUTION+	High		al clear image		d when a user wants r high quality video or
		Middle	wants	s images betw		ayed when a user modes for comfortable video.
		Low	wants		natural images. It	ayed when a user is effective for slow-
		Off			or everyday viewir in this mode.	ng. SUPER RESOLU-
	Sharpness	Adjusts the	sharp	ness of the so	reen.	
	Black Level	Offset: a monitor of	as a re can dis	play.	video signal, this is	s the darkest color the
		High	Keep	s the current	contrast ratio of th	e screen.
		Low	Lowers the black levels and raises the white levels from the current contrast ratio of the screen.			ne white levels from the
	HDMI ULTRA HD Deep Color	Provides sh TRA HD De		olor.		evice supporting UL-
		4K@60 Hz Support Format <sup>1)</sup>				
		Resolution		Frame rate	Color Depth /	Chroma Sampling
		Resoluti	(Hz)	8 bit	10 bit	
					YC	bCr 4:2:0
		3840 x 2	160	59.94	YC	bCr 4:2:2
		3040 X Z	60.00	60.00	YCbCr 4:4:4	_
					RGB 4:4:4	-
		1) Supporte	ed whe	en HDMI ULTF	RGB 4:4:4 RA HD Deep Color	r is set to On.
			ed whe	en HDMI ULTF		r is set to On.
		• If the	OTE conne	cted device d	RA HD Deep Color	
		• If the Color	OTE conne	cted device d	RA HD Deep Color  pes not support U  t work properly.	LTRA HD Deep
		• If the Color	OTE conne t, the fe	cted device d	RA HD Deep Color  pes not support U  t work properly.	

Game Adjust	Response Time	Sets a response time for displayed pictures based on the speed of the screen.  For a normal environment, it is recommended that you use Middle. For a fast-moving picture, it is recommended that you use high. Setting to High may cause image sticking.			
		High	Sets the response time to High.		
		Middle	Sets the response time to Middle.		
		Low	Sets the response time to Low.		
		Off	Does not use the response time improvement feature.		
	FreeSync	Provides seamless and natural images by synchronizing the vertical frequency of the input signal with that of the output signal.  NOTE  To use the FreeSync feature, a graphic card that supports FreeSync is necessary.  Supported Interface: DisplayPort  For more information, refer to AMD website at http://www.amd.com/FreeSync			
		On	FreeSync function on.		
		Off	FreeSync function off.		
	Black Stabilizer	You can control the black contrast to have better visibility in dark scenes.  Increasing the Black Stabilizer value brightens the low gray level area on the screen. (You can easily distinguish objects on dark game screens.)  Reducing the Black Stabilizer value darkens the low gray level area and increases the dynamic contrast on the screen.			
Color Adjust	Gamma	The higher the gamma value, the darker the image becomes the lower the gamma value, the lighter the image becomes. I not need to adjust the gamma settings, select Off.			
	Color Temp	Manual	Adjusts the color temperature in 500K increments. (Note that 9300K is supported instead of 9500K.)		
		Custom	The user can adjust it to red, green, or blue by customization		
	Red	You can custom	nize the picture color using Red, Green, and Blue colors.		
	Green				
	Blue				
	Six Color	saturation of the Green_Saturat Saturation, Ma low_Saturation	requirements for colors through adjusting the color and e six colors(Red_Hue, Red_Saturation, Green_Hue, tion, Blue_Hue, Blue_Saturation, Cyan_Hue, Cyan_genta_Hue, Magenta_Saturation, Yellow_Hue, Yeln) and saving the settings.		
		*Hue: Adjusts tone of the screen.  *Saturation: Adjusts the saturation of the screen colors. The lower the value, less saturated and bright the colors become. The higher the value, the more saturated and dark the colors become.			
	Reset	Returns the color settings to the default settings.			

### -General

- 1 To view the OSD menu, press the joystick button at the bottom of the monitor and then enter the Menu.
- 2 Go to General by moving the joystick.
- 3 Configure the options following the instructions that appear in the bottom right corner.
- 4 To return to the upper menu or set other menu items, move the joystick to ◀ or pressing (◉ / OK) it.
- 5 If you want to exit the OSD menu, move the joystick to **⋖** until you exit.




Each option is described below.

Menu > General	Description		
Language	Sets the menu s	creen to the desired language.	
SMART ENERGY	High	Saves energy using the high-efficiency SMART ENERGY SAVING feature.	
SAVING	Low	Saves energy using the low-efficiency SMART ENERGY SAVING feature.	
	Off	Disables the SMART ENERGY SAVING feature.	
Power LED	Turns the power LED on the front of the monitor on or off.		
	On	The power LED turns on automatically.	
	Off	The power LED turns off.	
Automatic standby	Feature that automatically turns off the monitor when there is no movement on the screen for a period of time. You can set a timer for the auto-off function. (Off, 4 H, 6 H, and 8 H)		
	NOTE     Be sure to configure this option according to the DisplayPort version supported by your graphics card. Set this option to Disable if your graphics card does not support DisplayPort 1.2.		
Buzzer	This feature lets you set the sound generated from Buzzer when your monitor pow On or Off.		
	On	Enables your monitor`s Buzzer.	
	Off	Disables your monitor's Buzzer.	
OSD Lock	This feature disables the configuration and adjustment of menus.		
	On	Enables OSD Lock.	
	Off	Disables OSD Lock.	
	NOTE     All features are disabled except Brightness, Contrast, Volume, Input, OSD Loc Settings, and the Exit button.		

- The value of energy saving data may differ depending on panel and panel suppliers.
- · If you select the option of SMART ENERGY SAVING is High or Low, monitor luminance become lower or higher depend on source.

### -Reset

- 1 To view the OSD menu, press the joystick button at the bottom of the monitor and then enter the Menu.
- 2 Go to Reset by moving the joystick.
- 3 Configure the options following the instructions that appear in the bottom right corner.
- 4 To return to the upper menu or set other menu items. move the joystick to ◀ or pressing (◉ / OK) it.
- 5 If you want to exit the OSD menu, move the joystick to **◄** until you exit.



Each option is described below.

Menu > Reset	Description	
Do you want to reset your settings?		
Reset	Returns to the default settings.	
Cancel	Cancel the select.	

# **TROUBLESHOOTING**

Nothing is displayed on the screen	Nothing is displayed on the screen.				
Is the monitor's power cord plugged in?	Check if the power cord is correctly plugged into the power outlet.				
Is the power LED on?	Check the power cable connection and press the power button.				
Is the power on and the power LED displaying white?	<ul> <li>Check that the connected input is enabled (Menu &gt; Quick Settings &gt; Input).</li> </ul>				
Is the power LED blinking?	<ul> <li>If the monitor is in sleep mode, move the mouse, or press any key on the keyboard, to switch the display on.</li> <li>Check if the computer is turned on.</li> </ul>				
Is the OUT OF RANGE message being displayed?	<ul> <li>This occurs when signals transferred from the PC (graphics card) are out of the horizontal or vertical frequency range of the monitor. Please see the Product Specification section of this manual to set the appropriate frequency.</li> </ul>				
Is the No Signal message being displayed?	<ul> <li>This is displayed when the signal cable between the PC and the monitor is missing or disconnected. Check the cable and reconnect it.</li> </ul>				

The OSD lock message is being displayed.		
Are some functions not avail-able when you press the Menu button?	The OSD is locked. Go to Menu > General and set OSD Lock to Off.	

The screen retains an image.	
Does image sticking occur even when the monitor is turned off?	<ul> <li>Displaying a still image for a prolonged time may cause damage to the screen, resulting in the retention of the image.</li> <li>To extend the lifetime of the monitor, use a screensaver.</li> </ul>

Screen display is unstable and shaky / Images displayed on the monitor leave shadow trails.		
Did you select the appropriate resolution?	<ul> <li>If the selected resolution is HDMI 1080i 60/50 Hz (interlaced), the screen may be flickering. Change the resolution to 1080P or the recommended resolution.</li> </ul>	



- Vertical frequency In order to display an image, the screen must be refreshed dozens of times per second, like a
  fluorescent lamp. The number of times the screen is refreshed per second is called vertical frequency, or refresh
  rate, and is represented by Hz.
- Horizontal frequency The time it takes to display one horizontal line is called the horizontal cycle. If 1 is divided by the horizontal interval, the result is the number of horizontal lines displayed per second. This is called horizontal frequency and is represented by kHz.



- Check if the graphics card's resolution or frequency is within the range allowed by the monitor and set it to the recommended (optimal) resolution in **Control Panel > Display > settings**.
- Not setting the graphics card to the recommended (optimal) resolution may result in blurred text, a dimmed screen, a truncated display area, or misalignment of the display.
- The setting methods may be different depending on the computer or operating system, and some
  resolutions may not be available depending on the performance of the graphics card. If this is the
  case, contact the manufacturer of the computer or graphics card for assistance.
- Some graphics cards may not support 2560x1080 resolution. If the resolution cannot be displayed, contact the manufacturer of your graphics card.

The display color is abnormal.	
Does the display appear discol-ored (16 colors)?	<ul> <li>Set the color to 24 bit (true color) or higher. In Windows, go to Con-trol Panel &gt; Display &gt; Settings &gt; Color Quality.</li> </ul>
Does the display color appear unstable or monochrome?	<ul> <li>Check if the signal cable is connected properly. Reconnect the cable or reinsert the PC's graphics card.</li> </ul>
Are there spots on the screen?	<ul> <li>When using the monitor, pixilated spots (red, green, blue, white, or black) may appear on the screen. This is normal for an LCD screen. It is not an error, nor is it related to the monitor's performance.</li> </ul>

Do you see an "Unrecognized monitor, Plug&Play (VESA DDC) monitor found" message?		
Have you installed the display driver?	<ul> <li>Be sure to install the display driver from our web site: http://www.lg.com.</li> <li>Make sure to check if the video card supports Plug&amp;Play function.</li> </ul>	

No sound from the headphone port or speaker.		
Are images displayed using DisplayPort or HDMI input without sound?	<ul> <li>Try increasing the volume using the button on the monitor.</li> <li>Set the audio output of the PC to the monitor you are using. On Microsoft Windows, go to Control Panel &gt; Hardware and Sound &gt; Sound &gt; set the monitor as default device.</li> </ul>	

# **SPECIFICATIONS**

### 27UD68

LCD Screen	Туре	TFT (Thin Film Transistor)		
LOD COICCII	Type	LCD (Liquid Crystal Display) Screen		
	Pixel Pitch	0.1554 mm x 0.1554 mm		
Resolution	Maximum Resolution	3840 x 2160 @ 60 Hz		
	Recommended Resolution	3840 x 2160 @ 60 Hz		
Video Signal	Horizontal Frequency	30 kHz to 135 kHz		
	Vertical Frequency	56Hz to 61 Hz		
Input Connector	HDMI IN1, HDMI IN2, DP(I	DisplayPort) IN, H/P(Headphone) OUT		
Power	Voltage	19 V === 2.0 A		
	Power consumption (Typ.)	On Mode : 45.1 W Typ. ( Outgoing condition ) *		
		Sleep Mode ≤ 0.5 W **		
		Off Mode ≤ 0.3 W		
AC/DC adaptor	Type ADS-45SN-19-3 19040G, SHENZHEN HONOR ELECTRONIC production			
	Or type LCAP21C, LIEN CHA	NG ELECTRONIC ENTERPRISE production		
	Or type LCAP26B-E, LIEN CHANG ELECTRONIC ENTERPRISE production			
	Output: 19 V 2.1 A			
Environmental	Operating Condition	Temperature: 0°C to 40°C; Humidity: < 80%		
Conditions	Storing Condition	Temperature: -20°C to 60°C; Humidity: < 85%		
Dimension	Monitor Size (Width x Height x Depth)			
	With Stand	615 mm x 455.7 mm x 186.2 mm		
	Without Stand	615 mm x 365.1 mm x 49.3 mm		
Weight (Without	4.9 kg			
Packaging)				

Product specifications shown above may be changed without prior notice due to upgrade of product functions

The power consumption level can be different by operating condition and monitor setting.

<sup>\*</sup> The On mode power consumption is measured with LGE test standard (Full White pattern , Maximum resolution).

<sup>\*\*</sup> The monitor goes to the Sleep Mode in a couple of minutes(Max 5 minutes).

# Factory Support Mode (Preset Mode, PC) HDMI

Display Modes (Resolution)	Horizontal Frequency(kHz)	Vertical Frequency(Hz)	Polarity(H/V)	Remarks
640 x 480	31.469	59.94	-/-	
800 x 600	37.879	60.317	+/+	
1024 x 768	48.363	60	-/-	
1152 x 864	54.347	60.05	+/+	
1280 x 720	45	60	+/+	
1280 x 1024	63.981	60.02	+/+	
1600 x 900	60	60	+/+	
1920 x 1080	67.5	60	+/-	
1920 x 2160	133.29	60	+/-	Recommended resolution for PBP
3840 x 2160	67.5	30	+/-	
3840 x 2160	135	60	+/-	When HDMI ULTRA HD Deep Color is set to ON.

# **DisplayPort**

Display Modes (Resolution)	Horizontal Frequency(kHz)	Vertical Frequency(Hz)	Polarity(H/V)	Remarks
640 x 480	31.469	59.94	-/-	
800 x 600	37.879	60.317	+/+	
1024 x 768	48.363	60	-/-	
1152 x 864	54.347	60.05	+/+	
1280 x 720	45	60	+/+	
1280 x 1024	63.981	60.02	+/+	
1600 x 900	60	60	+/+	
1920 x 1080	67.5	60	+/-	
1920 x 2160	133.32	60	+/-	Recommended resolution for PBP
3840 x 2160	66.66	30	+/-	
3840 x 2160	133.32	60	+/-	

# **HDMI Timing (Video)**

Factory support mode (Preset Mode)	Horizontal Frequency(kHz)	Vertical Frequency(Hz)	Remarks
480p	31.5	60	
720p	45.0	60	
1080p	67.5	60	
2160p	135	60	When HDMI ULTRA HD Deep Color is set to ON.

# **Power LED**

Mode	LED Color
On Mode	White
Sleep Mode	Flashing White
Off Mode	Off



To obtain the source code under GPL, LGPL, MPL, and other open source licenses, that is contained in this product, please visit http://opensource.lge.com.ln addition to the source code, all referred license terms, warranty disclaimers and copyright notices are available for download.LG Electronics will also provide open source code to you on CD-ROM for a charge covering the cost of performing such distribution (such as the cost of media, shipping, and handling) upon email request to opensource@lge.com. This offer is valid for three (3) years from the date on which you purchased the product.

The model and serial number of the product are located on the back and on one side of the product.

Record them below in case you ever need service.

MODEL	
SERIAL	