



LG

OWNER'S MANUAL

AIR CONDITIONER

Please read this manual carefully before operating your set and retain it for future reference.

CEILING CASSETTE, CEILING CONCEALED DUCT

Original instruction



MFL67870330
Rev.06 120525

Copyright © 2016 - 2025 LG Electronics Inc. All Rights Reserved.



www.la.com



TIPS FOR SAVING ENERGY

Here are some tips that will help you minimize the power consumption when you use the air conditioner. You can use your air conditioner more efficiently by referring to the instructions below:

- Do not cool excessively indoors. This may be harmful for your health and may consume more electricity.
- Block sunlight with blinds or curtains while you are operating the air conditioner.
- Keep doors or windows closed tightly while you are operating the air conditioner.
- Adjust the direction of the air flow vertically or horizontally to circulate indoor air.
- Speed up the fan to cool or warm indoor air quickly, in a short period of time.
- Open windows regularly for ventilation as the indoor air quality may deteriorate if the air conditioner is used for many hours.
- Clean the air filter once every 2 weeks. Dust and impurities collected in the air filter may block the air flow or weaken the cooling / dehumidifying functions.

For your records

Staple your receipt to this page in case you need it to prove the date of purchase or for warranty purposes. Write the model number and the serial number here:

Model number :

Serial number :

You can find them on a label on the side of each unit.

Dealer's name :

Date of purchase :

IMPORTANT SAFETY INSTRUCTIONS

The following symbols are displayed on indoor and outdoor units.

	Read the precautions in this manual carefully before operating the unit.		This appliance is filled with flammable refrigerant (R32)
	This symbol indicates that the Operation Manual should be read carefully.		This symbol indicates that a service personnel should be handling this equipment with reference to the Installation Manual.

READ ALL INSTRUCTIONS BEFORE USING THE APPLIANCE.

Always comply with the following precautions to avoid dangerous situations and ensure peak performance of your product.

⚠ WARNING

It can result in serious injury or death when the directions are ignored.

⚠ CAUTION

It can result in minor injury or product damage when the directions are ignored. This appliance is intended to be used by expert or trained users in shops, in light industry and on farms, or for commercial use by lay persons.

⚠ WARNING

- Always ground the product. There is a risk of electric shock.
- Do not use a defective or underrated circuit breaker. Use the correctly rated breaker and fuse. There is risk of fire or electric shock.
- Do not use a multi consent. Always use this appliance on a dedicated circuit and breaker.
Otherwise it can cause electric shock or fire.
- For electrical work, contact the dealer, seller, a qualified electrician, or an Authorized Service Center. Do not disassemble or repair the product by yourself. There is risk of fire or electric shock.
- Always ground the product as per the wiring diagram. Do not connect the ground wire to gas or water pipes lightening rod or telephone ground wire. There is risk of fire or electric shock.
- Install the panel and the cover of control box securely. There is risk of fire or electric shock due to dust, water etc.

- Use the correctly rated breaker or fuse. There is risk of fire or electric shock.
- Do not modify or extend the power cable. If the power cable or cord has scratches or skin peeled off or deteriorated then it must be replaced. There is risk of fire or electric shock.
- For installation, removal or reinstall, always contact the dealer or an Authorized Service Center. There is risk of fire, electric shock, explosion, or injury.
- Do not install the product on a defective installation stand. Be sure that the installation area does not deteriorate with age. It may cause product to fall.
- Never install the outdoor unit on a moving base or a place from where it can fall down.
The falling outdoor unit can cause damage or injury or even death of a person.
- When the product is soaked (flooded or submerged) in water, contact an Authorized Service Center for repair before using it again. There is risk of fire or electric shock.
- Be sure to check the refrigerant to the used. Please read the label on the product. Incorrect refrigerant used can prevent the normal operation of the unit.
- Don't use a power cord, a plug or a loose socket which is damaged. Otherwise it may cause a fire or electrical shock.
- Do not touch, operate, or repair the product with wet hands. Hold the plug by hand when taking out. There is risk of electric shock or fire.
- Do not place a heater or other heating appliances near the power cable. There is risk of fire and electric shock.
- Do not allow water to run into electric parts. Install the unit away from water sources. There is risk of fire, failure of the product, or electric shock.
- Do not store or use or even allow flammable gas or combustibles near the product. There is risk of fire.
- Indoor/outdoor wiring connections must be secured tightly and the cable should be routed properly so that there is no force pulling the cable from the connection terminals. Improper or loose connections can cause heat generation or fire.

- Safely dispose off the packing materials. Like screws, nails, batteries, broken things etc after installation or svc and then tear away and throw away the plastic packaging bags. Children may play with them and cause injury.
- Make sure to check that the power cable plug is not dirty, loose or broken and then only insert the plug completely. Dirty, loose or broken power plug can cause electric shock or fire.
- In outdoor unit the step-up capacitor supplies high voltage electricity to the electrical components. Be sure to discharge the capacitor completely before conducting the repair work. An charged capacitor can cause electrical shock.
- When installing the unit, use the installation kit provided with the product. Otherwise the unit may fall and cause severe injury.
- Be sure to use only those parts which are listed in the svc parts list. Never attempt to modify the equipment. The use of inappropriate parts can cause an electrical shock, excessive heat generation or fire.
- Do not use the product in a tightly closed space for a long time. Perform ventilation regularly. Oxygen deficiency could occur and hence harm your health.
- Do not open the front grille of the product during operation. (Do not touch the electrostatic filter, if the unit is so equipped.) There is risk of physical injury, electric shock, or product failure.
- If strange sounds, smell or smoke comes from product. Immediately turn the breaker off or disconnect the power supply cable. There is risk of electric shock or fire.
- Ventilate the product room from time to time when operating it together with a stove, or heating element etc. Oxygen deficiency can occur and hence harm your health.
- Turn the main power off and unplug the unit when cleaning or repairing the product. There is risk of electric shock.
- When the product is not to be used for a long time, disconnect the power supply plug or turn off the breaker. There is risk of product damage or failure, or unintended operation.
- Take care to ensure that nobody especially kids could step on or fall onto the outdoor unit. This could result in personal injury and product damage.

- Take care to ensure that power cable could not be pulled out or damaged during operation. There is risk of fire or electric shock.
- Do not place ANYTHING on the power cable. There is risk of fire or electric shock.
- Do not plug or unplug the power supply plug to turn the unit ON/OFF. There is risk of fire or electric shock.
- When flammable gas leaks, turn off the gas and open a window for ventilation before turn the product on. Do not use the telephone or turn switches on or off. There is risk of explosion or fire.
- Do not turn on the breaker or power under condition that front panel, cabinet, top cover, control box cover are removed or opened.
Otherwise, it may cause fire, electric shock, explosion or death.
- Use a vacuum pump or Inert (nitrogen) gas when doing leakage test or air purge. Do not compress air or Oxygen and Do not use Flammable gases.
Otherwise, it may cause fire or explosion. There is the risk of death, injury, fire or explosion.
- The appliance shall be stored in a room without continuously operating ignition sources (for example : open flames, an operating gas appliance or an operating electric heater.)
- Keep any required ventilation openings clear of obstruction.
- The appliance shall be stored in a well-ventilated area where the room size corresponds to the room area as specified for operation. (for R32)
- Ducts connected to an appliance shall not contain an ignition source. (for R32)

⚠ CAUTION

- Two or more people must lift and transport the product. Avoid personal injury.
- Do not install the product where it will be exposed to sea wind (salt spray) directly. It may cause corrosion on the product.
- Install the drain hose to ensure that the condensed water is drained away properly. A bad connection may cause water leakage.

- Keep level even when installing the product. To avoid vibration or noise.
- Do not install the product where the noise or hot air from the outdoor unit could damage or disturb the neighborhoods. It may cause a problem for your neighbors and hence dispute.
- Always check for gas (refrigerant) leakage after installation or repair of product. Low refrigerant levels may cause failure of product.
- Do not use the product for special purposes, such as preserving foods, works of art, etc. It is a consumer air conditioner, not a precision refrigeration system. There is risk of damage or loss of property.
- Do not block the inlet or outlet of air flow. It may cause product failure.
- Use a soft cloth to clean. Do not use harsh detergents, solvents or splashing water etc. There is risk of fire, electric shock, or damage to the plastic parts of the product.
- Do not touch the metal parts of the product when removing the air filter. There is risk of personal injury.
- Do not step on or put anything on the product. (outdoor units) There is risk of personal injury and failure of product.
- Always insert the filter securely after cleaning. Clean the filter every two weeks or more often if necessary. A dirty filter reduces the efficiency.
- Do not insert hands or other objects through the air inlet or outlet while the product is operating. There are sharp and moving parts that could cause personal injury.
- Be cautious when unpacking and installing the product. Sharp edges could cause injury.
- If the refrigerant gas leaks during the repair, do not touch the leaking refrigerant gas. The refrigerant gas can cause frostbite (cold burn)
- Do not tilt the unit when removing or uninstalling it. The condensed water inside can spill.
- Do not mix air or gas other than the specified refrigerant used in the system. If air enters the refrigerant system, an excessively high pressure results, causing equipment damage or injury.

- If the refrigerant gas leaks during the installation, ventilate the area immediately.
Otherwise it can be harmful for your health.
- Dismantling the unit, treatment of the refrigerant oil and eventual parts should be done in accordance with local and national standards.
- Replace all batteries in the remote control with new ones of the same type. Do not mix old and new batteries or different types of batteries. There is risk of fire or product failure.
- Do not recharge or disassemble the batteries. Do not dispose off batteries in a fire. They may burn or explode.
- If the liquid from the batteries gets onto your skin or clothes, wash it well with clean water. Do not use the remote if the batteries have leaked. The chemicals in batteries could cause burns or other health hazards.
- If you eat the liquid from the batteries, brush your teeth and see doctor.
Do not use the remote if the batteries have leaked. The chemicals in batteries could cause burns or other health hazard.
- Do not let the air conditioner run for a long time when the humidity is very high and a door or a window is left open. Moisture may condense and wet or damage furniture.
- Do not expose your skin or kids or plants to the cool or hot air draft. This could harm to your health.
- Do not drink the water drained from the product. It is not sanitary and could cause serious health issues.
- Use a firm stool or ladder when cleaning, maintaining or repairing the product at an height. Be careful and avoid personal injury.
- The air conditioner is not intended for use by young children or invalids without supervision.
- Young children should be supervised to ensure that they do not play with the air conditioner.
- The appliance shall be stored so as to prevent mechanical damage from occurring.

- Any person who is involved with working on or breaking into a refrigerant circuit should hold a current valid certificate from an industry-accredited assessment authority, which authorises their competence to handle refrigerants safely in accordance with an industry recognised assessment specification. (for R32)
- Servicing shall only be performed as recommended by the equipment manufacturer. Maintenance and repair requiring the assistance of other skilled personnel shall be carried out under the supervision of the person competent in the use of flammable refrigerants. (for R32)
- Wear adequate personal protection equipment (PPE) when installing, maintaining or servicing the product.
- This appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved. Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children without supervision.
- This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety. Children should be supervised to ensure that they do not play with the appliance.
- If the supply cord is damaged, it must be replaced by a special cord or assembly available from the manufacturer or its service agent.
- The appliance shall be installed in accordance with national wiring regulations.
- If anyone other than a licensed Professional installs, repairs, or alters LG Electronics Air Conditioning Products, the warranty is voided.
 - All costs associated with repair are then the full responsibility of the owner.
- Do not install the unit in potentially explosive atmospheres.

TABLE OF CONTENTS

2 TIPS FOR SAVING ENERGY

3 IMPORTANT SAFETY INSTRUCTIONS

12 BEFORE USE

- 12 About the system
- 12 Preparing for operation
- 12 Usage
- 12 Cleaning and maintenance
- 12 Service
- 12 Disposal

13 PRODUCT INTRODUCTION

- 13 Name and function of parts (CEILING CASSETTE)
- 13 Name and function of parts (CEILING CONCEALED DUCT)
- 14 Model designation
- 14 Operation Indicator Lamp
- 15 Wired Remote Controller

16 OPERATING INSTRUCTIONS

- 16 Standard Operation - Standard Cooling
- 17 Standard Operation - Power Cooling
- 17 Standard Operation - Heating Mode
- 18 Standard Operation - Dehumidification Mode
- 18 Auto Changeover Mode
- 19 Standard Operation - Fan Mode
- 20 Standard Operation - Auto Operation Mode
- 21 Standard Operation - Airflow Setting
- 22 Standard Operation - Temperature Setting/Room Temperature Check
- 23 Sub Function - Air purification(Optional)
- 24 Sub Function - Comfort Cooling
- 24 Function Setting - Child Lock
- 25 Function Setting - Change Temp
- 26 Function Setting - Elevation Grill(Optional)
- 27 Function Setting - Filter Sign Clear
- 28 Function Setting - Vane Angle Control
- 29 Function Setting - Changing Current Time
- 31 Programming - Simple Reservation
- 32 Programming - Weekly Reservation
- 34 Programming - Sleep Reservation
- 35 Programming - ON Reservation
- 37 Programming - OFF Reservation

39 Programming - Holiday Reservation

40 MAINTENANCE AND SERVICE

- 40 Ceiling Cassette - 1Way (Grille + Panel) / Ceiling Concealed Duct
- 41 Ceiling Cassette - 1Way (With Air Purifier)
- 42 Cleaning the deodorization filter/PM1.0 filter (Optional)
- 44 Cleaning the PM1.0 Sensor
- 45 Purifying filter(Optional)
- 46 Cleaning the deodorization filter/PM1.0 filter (Optional)
- 48 Cleaning the PM1.0 Sensor
- 49 Operation Tips!
- 49 When the air conditioner is not going....
- 50 Troubleshooting Tips! Save time and money!
- 51 Call the service immediately in the following situations

BEFORE USE

About the system

This system of air conditioner can be used for heating/cooling applications.

Preparing for operation

- Contact an installation specialist for installation.
- Use a dedicated circuit.

Usage

- Being exposed to direct airflow for an extended period of time could be hazardous to your health. Do not expose occupants, pets, or plants to direct airflow for extended periods of time.
- Due to the possibility of oxygen deficiency, ventilate the room when used together with stoves or other heating devices.
- Do not use this air conditioner for non-specified special purposes (e.g. preserving precision devices, food, pets, plants, and art objects). Such usage could damage the items.

Cleaning and maintenance

- Do not touch the metal parts of the unit when removing the filter. Injuries can occur when handling sharp metal edges.
- Do not use water to clean inside the air conditioner. Exposure to water can destroy the insulation, leading to possible electric shock.
- When cleaning the unit, first make sure that the power and breaker are turned off. The fan rotates at a very high speed during operation. There is a possibility of injury if the unit's power is accidentally triggered on while cleaning inner parts of the unit.

Service


For repair and maintenance, contact your authorized service dealer.

Disposal

The unit uses hydrofluorocarbon. Contact your dealer when discarding this unit. It is required by law to collect, transport and discard the refrigerant in accordance with the "hydrofluorocarbon collection and destruction" regulations.


PRODUCT INTRODUCTION

Name and function of parts (CEILING CASSETTE)



- 1: Indoor unit
- 2: Outdoor unit
- 3: Remote controller
- 4: Inlet air
- 5: Discharge air
- 6: Refrigerant piping, connection electric wire
- 7: Drain pipe
- 8: Ground wire
Wire to ground outdoor unit to prevent electrical shocks.

Name and function of parts (CEILING CONCEALED DUCT)




- 1: Indoor unit
- 2: Outdoor unit
- 3: Remote controller
- 4: Inlet air
- 5: Discharge air
- 6: Refrigerant piping, connection electric wire
- 7: Drain pipe
- 8: Ground wire
wire to ground outdoor unit to prevent electrical shocks.

Model designation

- Product Name : Air conditioner

- Model Name :




Operation Indicator Lamp



Description	Lamp Color
Cooling mode	Green
Heating mode	Green
Time to clean filter in cooling/heating Mode	Yellowish Green
Time to clean filter when product is not operating	Orange
Hot start or defrost mode before starting heating mode	Green
When reservation set on	Yellowish Green

* The Clean Filter indicator lamp does not light up starting from the corresponding product manufacturing number (after Oct. 2021).

Wired Remote Controller



- 1 OPERATION INDICATION SCREEN
- 2 SET TEMPERATURE Button
- 3 FAN SPEED Button
- 4 ON/OFF Button
- 5 OPERATION MODE SELECTION Button
- 6 WIRELESS REMOTE CONTROLLER RECEIVER
 - Some products don't receive the wireless signals.
- 7 AIR FLOW Button
- 8 SUB FUNCTION Button
- 9 FUNCTION SETTING Button
- 10 VENTILATION Button
- 11 RESERVATION
- 12 UP, DOWN, LEFT, RIGHT Button
 - To check the indoor temperature, press  button.
- 13 ROOM TEMPERATURE Button
- 14 SETTING/CANCEL Button
- 15 ESC Button

* Some functions may not be operated and displayed depending on the product type.


! NOTE

- Display temperature can be different from actual room temperature if the remote controller is installed at the place where sun-rays are falling directly or the place nearby heat source.
- The actual product can be different from above contents depending upon model type.
- When using simultaneous operation system, whenever press remote controller button, system will approximately operate after 1~2 minutes.

OPERATING INSTRUCTIONS

Standard Operation - Standard Cooling

It cools the room by comfortable and clean wind.



1 Press button to turn on the indoor.



2 Press button to select Cooling operation mode.



3 Adjust the desired temperature by pressing buttons.


Press button to check the Room temperature.

When setting the desired temperature higher than room temperature, only ventilation wind is blow out instead of cooling wind.



Standard Operation - Power Cooling

It makes the room cool using pleasant and fresh air quickly.



What is Power Cooling?

- Desired temperature: Po (actually 18 °C)
- Wind flow: power wind
- Wind direction: fix to air-cooling position

* Partial product has no power air-cooling function.

1 Press button to turn on the indoor.



2 Press button to select cooling operation mode.




3 Press button continuously until 'Po' displayed.



} It makes room temperature drop fast by running

Standard Operation - Heating Mode

It supplies warm wind to the indoor.



1 Press button to turn on the indoor.



2 Press button to select Heating mode.



(To check the indoor temperature, press the room temperature button.)

3 Adjust the desired temperature by pressing buttons.




When setting the desired temperature lower than room temperature, there is only ventilation wind.

- Heating drive only operates at the cooling and heating model.
- Heating doesn't operate at cooling exclusive model.

Standard Operation - Dehumidification Mode

It removes humidity while air-cooling weakly.



- 1 Press button to turn on the indoor.
- 2 Press button to select Dehumidification mode. The temperature setting can not be adjusted during operation this mode.
- 3 Press the button to select airflow rate feeble → weak → medium → strong → automatic. (The initial wind powerfulness of humidity removal drive is 'weak'.)


- In rainy season or high humidity climate, it is possible to operate simultaneously dehumidifier and cooling mode to remove humidity effectively.
- The menu item of wind powerfulness might not be partially selected according to the product.

Auto Changeover Mode

- 1 Press button to turn on the indoor.
- 2 Press button to select Auto Changeover Mode.
- 3 The setting temperature as the right side picture can be set in both cooling/ heating model.

Standard Operation - Fan Mode


It blows the air as it is in the indoor, not the cold wind.



- 1 Press  button to turn on the indoor.
- 2 Press  button to select Fan Mode.
- 3 Every time pressing  button, you can select wind flow in order of feeble → weak → medium → strong → automatic.
When running ventilation, compressor of AHU doesn't work.

- Ventilation drive does not release cool wind but general fan
- Because it releases the wind that has no temperature difference from the room, it functions to circulate the inside air.
- The menu item of wind powerfulness might not be partially selected according to the product.

Standard Operation - Auto Operation Mode



1 Press button to turn on the indoor.




2 Press button to select Artificial intelligence Mode.



3 You can adjust the temperature as the picture on the right for cooling and heating model.




4 For the case of cooling exclusive, as the picture on the right, you can adjust the temperature from hot to cold, from "-2" to "2" based on "00".



During operating Auto Operation mode:

- We can use the FAN SPEED button
- We can change manually to other operation mode.

Standard Operation - Airflow Setting



Wind powerfulness : You can simply adjust desired wind powerfulness.

1 Please setup desired wind powerfulness by wind powerfulness button.

- Every time you press wind powerfulness, you can select the wind flow in order of 'feeble → weak → weak medium → medium → medium strong → strong → power → automatic'.
- The menu item might not be partially selected according to product function.




Wind direction : You can simply adjust desired wind direction.

1 Please set desired wind direction by pressing **AIR FLOW** button. You can select wind direction of (comfortable wind → Up/Down and Right/Left → Right/Left → Up/Down) by pressing **AIR FLOW** button. Partial item of wind directions might not be selected according to product function.



* Some functions may not be operated and displayed depending on the product type.

Standard Operation - Temperature Setting/Room Temperature Check



Temperature Setting

1 We can simply adjust the desired temperature.

- Press the buttons to adjust the desired temperature.

: Increase 1 °C or 2 °F per one time pressing

: Decrease 1 °C or 2 °F per one time pressing

• Room temp: Indicate the current room temperature.

• Set temp: Indicate the temperature that user want to set.

* Depend on what kind of controller, the desired temperature can be adjusted at 0.5 °C or 1 °F.

Cooling operation:

- The cooling mode doesn't work if desired temperature is higher than room temperature Please lower the desired temperature.

Heating operation:

- The heating mode doesn't work if desired temperature is lower than room temperature Please increase the desired temperature.

Room Temperature Check

1 Whenever press button, the room temperature will be displayed within 5 seconds.


After 5 seconds, it turns to display the desired temperature.

Because of location of remote controller, the real room temperature and the this displayed value can be different

- 5 °C is proper for the difference between room and outside temperature.

Sub Function - Air purification(Optional)

Only products with humidifying function can use this.



The method to setup cleaning air

1 Repeat pressing **SUB FUNC** button until  icon flash.



2 Press **OK/CLEAR** button to select or cancel the function.

( icon appears or disappears on **SUB FUNCTION** display part up to selection.)



3 After setting, press **ESC** button to exit.




* After setup, it automatically gets out of setup mode if there is no button input for 25 seconds.

* When exiting without pressing set button, the manipulated value is not reflected.

- Cleaning air function is additional function and it might not be indicated or operated at the partial product.
- Cleaning air function is possible only when product is running.
- If you want independent cleaning air drive, please setup cleaning air by pressing additional drive button at ventilation drive.
- * Some functions may not be operated and displayed depending on the product type.

Sub Function - Comfort Cooling

The comfort cooling is the function to automatically control the cooling strength to maintain the pleasant feeling without turning off the product after the indoor temperature reached the desired temperature.



* Some products may not include Comfort cooling function.

- 1 Press **SUB FUNC** button repeatedly until Comfort cooling  icon displayed.



- 2 Turn on/off Comfort cooling function by pressing **OK CLEAR** button.

* The  icon will be displayed in case of setting option and disappear in reverse case.



- 3 Press **ESC** button after setup.


* If no button is selected for about 25 seconds after setup, it exits the setup mode



* If the **OK CLEAR** button is not selected before you exit, the changes will not apply.

Function Setting - Child Lock

It is the function to use preventing children or others from careless using.



- 1 Press **OK CLEAR** button repeatedly until the  is flashing.



- 2 If moving to 'setup' icon area by using   button, 'setup' icon blinks, and child lock function is setup if pressing **OK CLEAR** button at that time.



- 3 When cancelling lock function, if moving to 'cancel' icon by pressing   button and then, pressing **OK CLEAR** button, child lock function is cancelled.


- 4 Press **ESC** button to exit.

* After setup, it automatically gets out of setup mode if there is no button input for 25 seconds.

* When exiting without pressing set button, the manipulated value is not reflected.

Function Setting - Change Temp

Change temperature is the function to setup air-cooling and heating drive automatically changeable according to the temperature at artificial intelligence drive mode.



1 Repeat pressing  button until  icon flash.



2 Press  button to change.

* Converting temp value : 1~7



3 Press  button to complete and active the setting process.




4 Press  button to exit or system will automatically release without any input after 25 seconds.



* When exiting without pressing set button, the manipulated value is not reflected.

Function Setting - Elevation Grill(Optional)

This function is to move the indoor filter up/down for cleaning filter.




- 1 Press button. Repeat pressing button until icon flash. 
- 2 Move to descent using button and press will display descent icon and the up/down grill will descent.
- 3 When up/down grill descents to the desired position, move to stop icon using button and press to stop up/down grill.
- 4 When filter cleaning is finished, fix the filter to the up/down grill, move to ascent icon using button, and press to ascent up/down grill.
- 5 Press to exit.
 - * After setup, it automatically gets out of setup mode if there is no button input for 60 seconds.
 - * When exiting without pressing set button, the manipulated value is not reflected. 

• Elevation grill function only operates in the indoor unit with the elevation grill.

* Some functions may not be operated and displayed depending on the product type.

Function Setting - Filter Sign Clear

This function is to clear the indicator of indoor filter cleaning.



1 Press button repeatedly until the is flashing.



2 When the is flashing, press the to clear this display




- When filter is covered by dust, it will reduce cooling/heating efficiency and accumulate more electric power. Therefore, do clean the filter whenever cleaning time is expired.

* Filter cleaning indication is automatically cancelled without the separate cancellation after certain period of time.

Function Setting - Vane Angle Control


This function is to adjust angle at which airflow is blow out.

* Some functions may not be operated and displayed depending on the product type.



- 1 Repeat pressing  button until  icon flash. 
- 2 Press  button to select active vane : 1 / 2 / 3 / 4 / All / Standard
Select Vane number using   buttons.
※ Vane number : No. 1, 2, 3, 4, all, or standard
 - Selected vane is in operation.
 - Please verify the operating vane.
 - To set the angle of all the vanes, select 'all'.
 - To set as the factory default settings, select 'standard'.
- 3 Select wind angle using  button, and press  button.
 - The boundary of wind angle settings can be changed to 5 levels or 6 levels according to the product.
 - When selecting 'standard' for Vane number, the wind angle does not move.
- 4 Set the wind angles for the remaining vanes as the same as above.
※ There are products with vanes with no. 1 and no. 2 only according to the product types.
- 5 Press  button to exit.
 - ※ After setup, it automatically gets out of setup mode if there is no button input for 60 seconds.
 - ※ When exiting without pressing set button, the manipulated value is not reflected.
- 6 Press  button to complete and active the setting process.
(Airflow direction function will be released whenever setting vane angle) 
- 7 Press  button to exit or system will automatically release without any input after 25 seconds. 

Function Setting - Changing Current Time




1 Please press function setup button. If pressing function setup button repeatedly, it moves to time setup menu. 'Time setup' icon is indicated at that time and date blinks at current time indication area.

Ex) Changing Current Time as 'Monday / AM 10:20'.




2 Press key to adjust the current day.

SUN MON TUE WED THU FRI SAT



3 Press key to move to AM/ PM setting mode (the 'AM/ PM' segment will flash).

12:00




4 Setting AM/ PM value by pressing button.



5 Press button to move to 'Hour' setting mode. (the 'Hour' segment will flash)


12:00



6 Setting Hour value by pressing button.

10:00





7 Press button to move to 'Minute' setting mode. (the 'Minute' segment will flash)



8 Setting Minute value by pressing button.



9 Press button to finish.




10 In the process, press button to release and exit from setting mode.
(In case of exit with incomplete information, it will return to the previous setting)
※ When exiting without pressing set button, the manipulated value is not reflected.



Programming - Simple Reservation

You can set the reservation conveniently in the units of 1 hour from 1 hour to 7 hours.



1 Press button to enter the Programming mode.
(the **SIMPLE** segment flashing)



Ex) Setting Simple Reservation time as '3'.

2 Press button to adjust reservation time.



3 Press button to finish setting.



4 Press button to exit.

- * After setup, it automatically gets out of setup mode if there is no button input for 25 seconds.
- * When exiting without pressing set button, the manipulated value is not reflected.

* When simple reservation setup, product automatically runs or stops after the time that is set.

Programming - Weekly Reservation

You can set the daily reservation in weekly unit.


Weekly reservation keeps operating until before you cancel it once you setup.

- 1 Please move to reservation setup mode by pressing reservation button.
* You can setup two weekly reservations for one day, and up to fourteen reservations for a week.
For example, to setup (Tuesday morning 11:30 turned on ~ afternoon 12:30 turned off), you setup in order below.


- 2 Please move to 'weekly' by repeatedly pressing reservation button. 'Weekly' blinks at this time.




- 3 Please select weekly reservation 1 or weekly reservation 2 by using button.
* You can setup two reservations, weekly reservation 1 and weekly reservation 2, for a day.




- 4 Please move to 'date' setup part by using button. If 'date' indication blinks, please setup date. You can setup date from Monday to Sunday.



- 5 Please move to 'AM/PM' setup part of turning on by using button.



- 6 Please move to 'hour' setup part of turning on by using button.
- It is the part to setup the time at which air-conditioner is turned on.




- 7 Please change time by using button.
- You can setup hour 0~12.

- 8 Please move to 'minute' setup part of turning on by using button.


- 9 If 'minute' indication blinks, please setup 'minute' by using button

10 Please move to 'AM/PM' setup part of turning off by using  button.
 - AM/PM setup is identical with turning on time setup.



11 Please move to 'hour' setup part of turning off by using Right button.
 - It is the part to reserve the time at which air-conditioner is turned off.
 - If 'hour' indication blinks, please setup 'hour'.


* Please setup 'hour' and 'minute' identically with the method to setup turning on time.



12 If finishing weekly reservation setup, please press setup/cancellation button.
 Weekly reservation setup for the day that you set is finished.

13 If you setup with the method identical with above by selecting the day that you'd like to setup, it operates weekly reservation.
 If you setup both turning on reservation time and turning off reservation time identically, it doesn't operate reservation drive.

Weekly reservation explanation



Reservation number

Turning on time

Turning off time

SUN MON TUE WED THU FRI SAT


 Under bar: the indication that there is weekly reservation for corresponding day

* Indoor unit is turned on to desired temperature if it is configured using up/down button during preset of weekly operation time.

- When desired temperature is not set, it is turned on automatically with desired temperature of previous operation.

Programming - Sleep Reservation

Sleep reservation is the function of air-conditioner to run and stop after certain period of time at sleep mode before sleep. When connected to a ventilation product and set the sleep reservation, when it goes to the sleep mode, after the set time has elapsed.



- 1 Press **OK** button to enter the Programming mode.
Ex) Setting Sleep Reservation time as '3'. 
- 2 Repeat pressing **OK** button to enter the SLEEP reservation setting mode.
(**SLEEP** segment flashing) 
- 3 Press **▲ ▼** button to adjust reservation time.
The SLEEP reservation time is from 1 to 7 hours. 
- 4 Press **OK** button to finish setting.
Whenever reservation is done. 
- 5 Press **ESC** button to exit.
※ After setup, it automatically gets out of setup mode if there is no button input for 60 seconds.
※ When exiting without pressing set button, the manipulated value is not reflected.
- If reservation is setup, 'sleep' indication shows up at the lower part of LCD screen.
- 6 If finishing sleep reservation setup, air-conditioner product operates sleep drive and stops after the time that is set.


CAUTION

Please reserve proper time at sleeping. (Too much air-cooling is not good for your health.)

- Because it automatically adjusts desired temperature for comfortable air-cooling at sleep drive, there could be difference between remote controller's desired temperature and air-conditioner body's desired temperature.
- Sleep reservation operates as off reservation for the product whose temperature adjustment isn't controlled by unit of 0.5 °C.

Programming - ON Reservation

Automatically turned On at reserved time that you set.



1 Press button.

Ex) Setting ON Reservation Time as 'AM 10:20'.



2 Repeat pressing button to enter the ON reservation setting mode. (segment flashing)

3 Press button to adjust AM/ PM setting.



4 Press button to Hour setting mode. When the Hour icon flash, please setting time. The setting range is within 1~12.




5 Press button to shift to Minute setting mode. When the Minute icon flash, please setting minute the setting range is within 00~59.



6 Press button to finish setting.





7 Press **ESC** button to exit.


* After setup, it automatically gets out of setup mode if there is no button input for 25 seconds.

* When exiting without pressing set button, the manipulated value is not reflected.

- If reservation is set, 'turned on' indication shows up at the lower part of LCD screen, and air-conditioner product runs at the time that is set.
- If reservation is cancelled, 'turned on' indication disappears.

Programming - OFF Reservation

Automatically turned Off at reserved time that you set.



1 Press  button.


Ex) Setting OFF Reservation Time as 'AM 10:20'.




2 Repeatedly pressing  button to enter the OFF reservation setting mode.
( segment flashing)




3 Press  button to adjust AM/ PM setting.






4 Press  button to shift to Hour setting mode. When the Hour icon flash, please setting time. The setting range is within 1~12.












5 Press  button to shift to Minute setting mode. When the Minute icon flash, please setting minute the setting range is within 00~59.










6 Press  button to finish setting.







7 Press **ESC** button to exit.


* After setup, it automatically gets out of setup mode if there is no button input for 25 seconds.

* When exiting without pressing set button, the manipulated value is not reflected.

- If reservation is set, 'turned off' indication shows up at the lower part of LCD screen, and air-conditioner product runs at the time that is set.
- If reservation is cancelled, 'turned off' indication disappears.

Programming - Holiday Reservation

It automatically stops at reserved day that you set.



1 Please press button.
It enters into reservation setup mode.



2 Please move to 'holiday' by repeatedly pressing .



3 Please move to 'date' that you want to setup holiday by using button.



4 Please appoint or cancel holiday by using or button.
For example, when you setup Monday/Friday to holiday
- 'Monday', 'Friday' letter disappears.



5 Please press button if finishing holiday setup.

* If it comes to appointed holiday, air-conditioner automatically stops. Once you setup holiday appointment, until before you cancel holiday setup, air-conditioner automatically stops within one hour even though you run air-conditioner.

MAINTENANCE AND SERVICE

Ceiling Cassette - 1Way (Grille + Panel) / Ceiling Concealed Duct

⚠ CAUTION

Before performing any maintenance, turn off the main power to the system.

- Never use any of the followings:

Water hotter than 40 °C.

Could cause deformation and/or discoloration.

Volatile substances.

Could damage the surfaces of the air conditioner.



Indoor Unit

Grille, Case and Remote Control



- Turn the system off before cleaning. To clean, wipe with a soft, dry cloth. Do not use bleach or abrasives.

⚠ NOTE

Supply power must be disconnected before cleaning the indoor unit.

Air Filters

The air filters behind the front grille should be checked and cleaned once every 2 weeks or more often if necessary.



TU chassis : 4 EA Rack

⚠ CAUTION

When the air filter is to be removed, do not touch the metal parts of the indoor unit.

It may cause an injury.

- 1 Remove the Air filters.
 - Take hold of the tab and pull slightly forward to remove the filter.
- 2 Clean dirt from the air filter using a vacuum cleaner or washing with water.
 - If dirt is conspicuous, wash with a neutral detergent in lukewarm water.
 - If hot water (40 °C or more) is used, it may be deformed.
- 3 After washing with water, dry well in the shade.
 - Do not expose the air filter to direct sunlight or heat from a fire when drying it.
- 4 Install the air filter.


Ceiling Cassette - 1Way (With Air Purifier)

Cleaning the filter

CAUTION

Before performing any maintenance, turn off the main power to the system.


1 Pull on the handles on both ends of the marked rear side of the front panel, then open the front grille and press down on the two hooks and remove the Pre-filter.



2 Clean with a vacuum cleaner or a soft brush.
 • If the filter is very dirty, wash using water and a neutral detergent.

3 Allow the filter to dry in the shade until completely dry.

4 Install the filter in the reverse order from which it was removed, then close the front grille.
 • When installing the filter, insert the hook in the square hole.



- ① Marker
- ② Pre-filter
- ③ Filter case
- ④ Front intake grille
- ⑤ Handle
- ⑥ Hook
- ⑦ Square hole

WARNING

For safety, turn off the main power switch.

CAUTION




- Make sure that the filter is properly installed in the filter case. (When you insert the filter into the case and push the handle, you will hear a clicking sound when it is secured in place.)
- Be careful not to drop the front grille when removing the filter.
- Do not use volatile liquids or water that is 40 °C or hotter.
- Using the filter when it is not completely dry could cause the product to malfunction.
- Drying the filter near a fire or in direct sunlight may cause damage to the filter.
- When cleaning the filter, be careful not to damage the filter's mesh.

NOTE



- If dust gets in the filter, there could be a drop in cooling capacity.
- Clean around once every two weeks.
- If you have the filter cleaned at an LG Electronics Service Center, a separate fee may be charged. (paid service)
- The number and type of filters provided may differ depending on the model.
- Product shape and components may differ depending on the model.
- The feature may be changed according to the type of model.
- Some functions may not be supported, depending on the model.

Cleaning the deodorization filter/PM1.0 filter (Optional)

- 1 Refer to 'How to Remove the Filter' when removing the filter.
- 2 Grab the handle on the filter case holder and pull in the direction of the arrow to remove the PM1.0 filter.
 - Do not remove the filter case holder and the intake grille.




- 3 As shown in the figure, pull on the handle and remove the deodorization filter.



4 Wash the filter after checking the washing method in 'Filter Information'.

5 After washing, reinstall the deodorization filter and the PM1.0 filter to their original positions, respectively.

- When installing the PM1.0 filter, insert the hook in the square hole.



① PM1.0 filter

② Handle

③ Filter case holder

④ Deodorization filter

⑤ Hook

⑥ Square hole

⚠ WARNING

For safety, turn off the main power switch.

! NOTE

- The feature may be changed according to the type of model.
- Some functions may not be supported, depending on the model.

⚠ CAUTION

- Be careful that the filter case is correctly assembled to the filter holder.
- Be careful not to drop the front grille when removing the filter.
- Do not wash the dust filter with hot water over 40 °C or volatile liquids.
- Do not wash the photocatalytic Deodorization filter in water.
- After cleaning the PM1.0 filter, the buzzer sounds 7 times if the water is not completely dry. Dry the filter thoroughly.
- Drying the filter near a fire or in direct sunlight may cause damage to the filter.
- Wear gloves during installation.

⚠ NOTE

- The quantity and type of filters provided by each model may differ.
- The feature may be changed according to the type of model.
- Some functions may not be supported, depending on the model.


Filter Information

Filter Name	Filter Description
deodorization filter	<ul style="list-style-type: none"> • Dry for 3 hours in sunlight or under fluorescent light. • It is recommended to clean it every six months. (assuming 8 hours of daily use) • Washing the filter with water could damage or deform it.
PM1.0 filter	<ul style="list-style-type: none"> • Clean the filter without disassembling it. • Submerge the PM1.0 filter in water, shaking it several times to clean it. • If the filter is very dirty, soak it for 30 minutes in lukewarm water with mild detergent and rinse thoroughly with clean water. (Do not use acidic detergents such as citric acid.) • It is recommended to clean it every six months. • Dry it thoroughly in the shade for about a day. (If there is any remaining moisture, the buzzer will sound 7 times.) • Drying with a hot air heater, such as a hair dryer or a heater, could damage or deform the filter. • The inside of the filter is sharp, so do not rub or touch it directly.


Cleaning the PM1.0 Sensor

PM1.0 Sensor


1 As shown in the figure below, put your finger in the indicator.




2 Open the front panel and lower the PM1.0 Sensor case as shown in the figure below.




3 Once the PM1.0 Sensor case is lowered all the way, turn the PM1.0 Sensor case to secure it as shown in the figure below.



4 Open the PM1.0 sensor cover on the side of the case.



5 Use a slightly wet cotton swab to wipe dust off the lens, and then use a dry swab to remove the moisture.



6 Close the PM1.0 Sensor case cover, then install the PM1.0 Sensor case in its original position.

WARNING

- For safety, turn off the main power switch.
- Be careful not to drop the product when removing the PM1.0 Sensor corner cover.
- Be careful of falling accidents when cleaning the PM1.0 Sensor.


NOTE

- It is recommended to clean it every six months. (assuming 8 hours of daily use)
- PM1.0 Sensor is only included with Air purification panel.
- The feature may be changed according to the type of model.
- Some functions may not be supported, depending on the model.

Purifying filter(Optional)

Cleaning

The PLASMA filter behind the air filters should be checked and cleaned once every 3 months or more often if necessary.



- 1 After removing the air filters, pull slightly forward to remove the PLASMA filter.
- 2 Dip the PLASMA filter into the water mixed with neutral detergent, for 20~30 minutes.
- 3 Dry the PLASMA filter in the shade for a day (Especially, the humidity must be removed perfectly on this parts).
- 4 Note the cuts of electric discharge lines.
- 5 Re-install the PLASMA filter to the original position.




CAUTION

Don't touch this PLASMA Filter within 10 seconds after opening the inlet grille, it may cause an electric shock.

Replacement


- Recomended use period : About 2 years

- 1 Open front panel and remove air filter.




- 2 Remove PM1.0 filter.

- 3 Insert new PM1.0 filter.




- 4 Reinsert air filter and close front panel.




Cleaning the deodorization filter/PM1.0 filter (Optional)


1 Press the fixing hooks on both sides and open the front grille.



2 Remove PM1.0 filter by pressing the fixing hook.



3 Remove the photocatalyst Deodorization filter by pulling upward.



4 After assembling in reverse order, close the front grille.

⚠ WARNING

For safety, turn off the main power switch.

⚠ CAUTION

- Be careful that the filter case is correctly assembled to the filter holder.
- Be careful not to drop the front grille when removing the filter.
- Do not wash the dust filter with hot water over 40 °C or volatile liquids.
- Do not wash the photocatalytic Deodorization filter in water.
- After cleaning the ultra-fine dust filter, the buzzer sounds 7 times if the water is not completely dry. Dry the filter thoroughly.
- Drying the filter near a fire or in direct sunlight may cause damage to the filter.
- Wear gloves during installation.

⚠ NOTE

- The quantity and type of filters provided by each model may differ.
- The feature may be changed according to the type of model.
- Some functions may not be supported, depending on the model.


Filter Information

Filter Name	Filter Description
Deodorization filter 	<ul style="list-style-type: none"> • Dry for 3 hours in sunlight or under fluorescent light. • It is recommended to clean it every six months. (assuming 8 hours of daily use) • Washing the filter with water could damage or deform it.
PM1.0 filter 	<ul style="list-style-type: none"> • Clean the filter without disassembling it. • Submerge the PM1.0 filter in water, shaking it several times to clean it. • If the filter is very dirty, soak it for 30 minutes in lukewarm water with mild detergent and rinse thoroughly with clean water. (Do not use acidic detergents such as citric acid.) • It is recommended to clean it every six months. • Dry it thoroughly in the shade for about a day. (If there is any remaining moisture, the buzzer will sound 7 times.) • Drying with a hot air heater, such as a hair dryer or a heater, could damage or deform the filter. • The inside of the filter is sharp, so do not rub or touch it directly.


Cleaning the PM1.0 Sensor

PM1.0 Sensor


1 Remove the PM1.0 Sensor corner cover on the front panel.



2 Open the PM1.0 sensor case on the side of the PM1.0 Sensor case and remove the rubber cap.



3 Use a cotton swab to wipe the dirt off the lens, and then use a dry swab to remove the moisture.



Tighten the rubber cap, close the PM1.0 sensor case, and assemble the PM1.0 Sensor corner cover to its original position.

① Rubber cap
② PM 1.0 sensor case

WARNING

- For safety, turn off the main power switch.
- Be careful not to drop the product when removing the PM1.0 Sensor corner cover.
- Be careful of falling accidents when cleaning the PM1.0 sensor.

NOTE

- It is recommended to clean it every six months. (assuming 8 hours of daily use)
- PM1.0 Sensor is only included with Air purification panel.
- The feature may be changed according to the type of model.
- Some functions may not be supported, depending on the model.

Operation Tips!

Do not overcool the room. This is not good for the health and wastes electricity.	Keep blinds or curtains closed. Do not let direct sunshine enter the room when the air conditioner is in operation.	Keep the room temperature uniform. Adjust the vertical and horizontal airflow direction to ensure a uniform temperature in the room.
Make sure that the doors and windows are shut tight. Avoid opening doors and windows as much as possible to keep the cool air in the room.	Clean the air filter regularly. Blockages in the air filter reduce the airflow and lower cooling and dehumidifying effects. Clean at least once every two weeks.	Ventilate the room occasionally. Since windows are kept closed, it is a good idea to open them and ventilate the room now and then.

When the air conditioner is not going....

When air conditioner is not going to be used for a long time.

- 1 Operate the air conditioner at the following settings for 2 to 3 hours.
 - Type of operation: Fan operation mode.
 - This will dry out the internal mechanisms.
- 2 Turn off the breaker.

CAUTION

Turn off the breaker when the air conditioner is not going to be used for a long time.

Dirt may collect and may cause a fire.

- 3 Remove the batteries from the Remote Controller.

Helpful information

The air filters and your electric bill.

If the air filters become clogged with dust, the cooling capacity will drop, and 6 % of the electricity used to operate the air conditioner will be wasted.

When the air conditioner is to be used again.

- 1 Clean the air filter and install it in the indoor unit.
- 2 Check that the air inlet and outlet of the indoor/outdoor unit are not blocked.
- 3 Check that the ground wire is connected correctly. It may be connect to the indoor unit side.

Troubleshooting Tips! Save time and money!

Check the following points before requesting repairs or service.... If the malfunction persist, please contact your dealer.

Case	Explanation
The air conditioner does not operate.	<ul style="list-style-type: none"> Have you made a mistake in timer operation? Has the fuse blown or has the circuit breaker been tripped?
The room has a peculiar odor.	<ul style="list-style-type: none"> Check that this is not a damp smell exuded by the walls, carpet, furniture or cloth items in the room.
It seems that condensation is leaking from the air conditioner.	<ul style="list-style-type: none"> Condensation occurs when the airflow from the air conditioner cools the warm room air.
Air conditioner does not operate for about 3 minutes when restart.	<ul style="list-style-type: none"> This is the protector of the mechanism. Wait about three minutes and operation will begin.
Does not cool or heat effectively.	<ul style="list-style-type: none"> Is the air filter dirty? See air filter cleaning instructions. The room may have been very hot when the room air conditioner was first turned on. Allow time for it to cool down. Has the setting temperature been set incorrectly? Are the indoor unit's air inlet or outlet vents obstructed?
The air conditioner operation is noisy.	<ul style="list-style-type: none"> For a noise that sounds like water flowing. -This is the sound of freon flowing inside the air conditioner unit. For a noise that sounds like the compressed air releasing into atmosphere. -This is the sound of the dehumidifying water being processed inside the air conditioning unit.
Crack sound is heard.	<ul style="list-style-type: none"> This sound is generated by the expansion/contraction of the inlet grille, etc. due to changes of temperature.
Remote control display is faint, or no display at all.	<ul style="list-style-type: none"> Has the circuit breaker been tripped? Are the batteries inserted in the opposite (+) and (-) directions?
The error code is occurred after lightning struck	<ul style="list-style-type: none"> This product has been applied to the over current protection circuit. Error can occur, but it is normal behavior. After few minutes, It will operate normally.
The buzzer sounds. (7 times)	<ul style="list-style-type: none"> Is the suction panel completely closed? Close the suction grille completely. Is the water completely dried after cleaning PM1.0 filter? If moisture remains, let it dry in the shade for about a day. Is PM1.0 filter film torn? Contact the LG Electronics Service Center.

Call the service immediately in the following situations

- Anything abnormal such as burning smell, loud noise etc. happen. Stop the unit and turn the breaker off. Never try to repair by yourself or restart the system in such cases.
- Main power cord is too hot or damaged.
- Error code is generated by self diagnosis.
- Water leaks from indoor unit even if the humidity is low.
- Any switch, breaker (safety, earth) or fuse fails to work properly

User must carry routine checkup & cleaning to avoid unit's poor performance.

In case of special situation, the job must be carried out by service person only.



Manufacturer :
LG Electronics Inc.
84, Wanam-ro, Seongsan-gu, Changwon-si, Gyeongsangnam-do, KOREA

UK Importer :
LG Electronics U.K. Ltd
Velocity 2, Brooklands Drive, Weybridge, KT13 0SL

Eco design requirement

- The information for Eco design is available on the following free access website.
<https://www.lg.com/global/support/cedoc/cedoc>